# Exam, TFY4235 Computational physics

#### Number

### Introduction

SIR, and the more advanced SEIIaR, are mathematical models that aim to capture how pandemics spread throughout a simulation. This paper documents the implementation and results of the simulation of these models in Python, as described in [1].

## **Implementation**

All the different models used in this text follow the same basic form. The goal is to find x(t), given initial conditions  $x(t_0)$ , and a equation of the form

$$f(x(t); args) = \frac{\mathrm{d}x(t)}{\mathrm{d}t}.$$

In the first part, x = (S, I, R), while later  $x = (S_{ij}, E_{ij}, I_{ij}, Ia_{ij}, R_{ij})$  where (ij) are different population groups. This is accomplished using function integrate in utilities.py. It takes as arguments the initial conditions x0, the functions f and step, the list args as well as the time step dt and total time T to simulate. It then creates a discrete approximation of x(t) by taking time steps given by the function step. step is the particular scheme used, for example Runge-Kutta (4,5), while f defines the system.

The equations that give the asymptotic behavior are both of the type x = f(x), and can thus be approximated by recursion, given that they converge. For  $\mathcal{R}_0$  close to one, they converge increasingly slowly, and the program may reach maximum recursion depth. For the parameters in this exercise, however, this was not a problem

### Results

### Deterministic SIR model

The first model is the deterministic SIR model, given by a set of coupled ODEs [1]. In this text, the Runge-Kutta (4, 5) scheme was used, as it is both a simple yet precise scheme. Figure 1 demonstrates that S and R approaches the expected asymptotes, and that I grows exponentially in the beginning.

### References

[1] NTNU, Institutt for Fysikk. Exam, TFY4235 Computational Physics. 2021.




Figure 1: On the left, the fraction of the population that is in each group, over time. The plot on the right shows how the infection spreads exponentially in the beginning