

# lab2\_block1

Shwetha

11/18/2020

## Assignment 2

### 1

Partitioning the data into train , test and validation.

```
bank = read.csv("C:/Users/vcshw/Machine Learning and Stats/Sem1/Machine learning/lab/bank-full.csv", header=TRUE)

bank = bank[,-12]
n = nrow(bank)
set.seed(12345)
id1=sample(1:n, floor(n*0.4))
train=bank[id1,]
d2 = bank[-id1,]
n2 = nrow(d2)
id2=sample(1:n2, floor(n2*0.5))
test=d2[id2,]
validate=d2[-id2,]
```

### 2

Fitting decision tree to training data

```
library(tree)
dt_default = tree(y~.,data = train)
dt_size = tree(y~.,data = train, control = tree.control(nrow(train),minsize = 7000))
dt_dev = tree(y~.,data = train, control = tree.control(nrow(train),mindev = 0.0005))
summary(dt_default)
```

```
##
## Classification tree:
## tree(formula = y ~ ., data = train)
## Variables actually used in tree construction:
## [1] "poutcome" "month" "contact" "housing"
## Number of terminal nodes: 6
## Residual mean deviance: 0.6022 = 10890 / 18080
## Misclassification error rate: 0.1048 = 1896 / 18084
```

```
summary(dt_size)
```

```
##
## Classification tree:
## tree(formula = y ~ ., data = train, control = tree.control(nrow(train),
##   minsize = 7000))
## Variables actually used in tree construction:
## [1] "poutcome" "month"    "contact"
## Number of terminal nodes: 5
## Residual mean deviance: 0.6097 = 11020 / 18080
## Misclassification error rate: 0.1048 = 1896 / 18084
```

```
summary(dt_dev)
```

```
##
## Classification tree:
## tree(formula = y ~ ., data = train, control = tree.control(nrow(train),
##   mindev = 5e-04))
## Variables actually used in tree construction:
## [1] "poutcome" "month"    "contact" "marital" "day"      "campaign"
## [7] "job"      "pdays"   "age"     "balance" "housing"  "education"
## [13] "previous"
## Number of terminal nodes: 122
## Residual mean deviance: 0.5213 = 9363 / 17960
## Misclassification error rate: 0.09362 = 1693 / 18084
```

```
mce_default_train = summary(dt_default)$misclass[1]/summary(dt_default)$misclass[2]
mce_size_train = summary(dt_size)$misclass[1]/summary(dt_size)$misclass[2]
mce_dev_train = summary(dt_dev)$misclass[1]/summary(dt_dev)$misclass[2]
```

```
mce_default_train
```

```
## [1] 0.1048441
```

```
mce_size_train
```

```
## [1] 0.1048441
```

```
mce_dev_train
```

```
## [1] 0.09361867
```

For validation data

```
y_default = predict(dt_default, validate, type = "class")
y_size = predict(dt_size, validate, type = "class")
y_dev = predict(dt_dev, validate, type = "class")

missclass = function(y,y1){
```

```

n = length(y)
return( 1 - sum(diag(table(y,y1)))/n)
}

mce_default_val = missclass(validate$y,y_default)
mce_size_val = missclass(validate$y,y_size)
mce_dev_val = missclass(validate$y,y_dev)
mce_default_val

```

```
## [1] 0.1116927
```

```
mce_size_val
```

```
## [1] 0.1116927
```

```
mce_dev_val
```

```
## [1] 0.112946
```

```
# sensitive on data
```

report the misclassification rates for the training and validation data. Which model is the best one among these three? Report how changing the deviance and node size affected the size of the trees and explain why.


### 3

Selecting optimal tree by training and validation

```

train_score = validate_score = rep(0,52)
for(i in 2:52){
  pruned_tree = prune.tree(dt_dev,best = i)
  pred = predict(pruned_tree, newdata=validate, type="tree")
  train_score[i] = deviance(pruned_tree)
  validate_score[i] = deviance(pred)
}
plot(2:52, train_score[2:52], type="p", col="red", ylim =c(7000,12000))
points(2:52, validate_score[2:52], type="p", col="blue")

```



Optimal amount of leaves = 24

«< which variables seem to be most important for decision making in this tree. Interpret the information provided by the tree structure (not everything but most important findings).

Confusion matrix and missclassification rate for test data.

```
optimal_tree = prune.tree(dt_dev, best = 36)
optimal_pred = predict(optimal_tree, test, type = "class")
confusion_matrix = table(test$y, optimal_pred)
confusion_matrix
```

```
##      optimal_pred
##      no    yes
## no  11868  122
## yes  1347  226
```

```
missclassification_rate = missclass(test$y, optimal_pred)
missclassification_rate
```

```
## [1] 0.1083094
```

```
plot(optimal_tree)
text(optimal_tree)
```



```
##      no yes
## no   0   1
## yes  5   0
```

```
loss_confusion_matrix
```

```
##      loss_fit
##      no   yes
## no 10965 1025
## yes  745  828
```

```
missclass(test$y,loss_fit)
```

```
## [1] 0.1305021
```

Here in the loss function we can see that , penalty for predicting observed yes as no is 5 and no as yes is 1. So on applying loss function , as expected , the missclassification of an observed yes as no is reduced in the confusion matrix here. Previously observed yes predicted as no was 1227 , and now it is 780. However the missclassification error rate has increased.

## 5

Fitting naive bayes model

```
library(e1071)
naive_model = naiveBayes(y~., train)
naive_y = predict(naive_model, test, type = "raw")

pi = seq(0.05,0.95,0.05)
prob_naive_yes = naive_y[,2]
prob_dt_yes = op[,2]
real_y = ifelse(test$y == "yes",1,0) # yes is 1 , no is 0
NAIVE = DT = matrix(0,ncol = 3,nrow = length(pi))

for(i in 1:length(pi)){
  dt_assign = ifelse(prob_dt_yes > pi[i],1,0)
  naive_assign = ifelse(prob_naive_yes > pi[i],1,0)

  cm_dt = table(real_y,dt_assign)
  cm_naive = table(real_y,naive_assign)

  if(all(dim(cm_dt) == c(2,2)) == TRUE){
    tpr_dt = cm_dt[2,2]/sum(cm_dt[2,])
  } else {
    tpr_dt = 0
  }
  if(all(dim(cm_naive) == c(2,2))){
    tpr_naive = cm_naive[2,2]/sum(cm_naive[2,])
  } else {
    tpr_naive = 0
  }
}
```

```

}

if(all(dim(cm_dt) == c(2,2)) == TRUE){
  fpr_dt = cm_dt[1,2]/sum(cm_dt[1,])
}else {
  fpr_dt = 0
}

if(all(dim(cm_dt) == c(2,2)) == TRUE){
  fpr_naive = cm_naive[1,2]/sum(cm_naive[1,])
}else {
  fpr_naive = 0
}

NAIVE[i,] = c(pi[i], tpr_naive, fpr_naive)
DT[i,] = c(pi[i], tpr_dt, fpr_dt)

}

colnames(NAIVE) = c("pi", "TPR", "FPR")
colnames(DT) = c("pi", "TPR", "FPR")

#ROC curve
plot(DT[,3], DT[,2], ylab = "TPR", xlab = "FPR", type = "l", col = "red")
lines(NAIVE[,3], NAIVE[,2], col = "blue")

```

