

ROAD

AIRY
AIRY-D
ALICANTE
ALLER-D
ANLACE
AXION SL
FOX II

MTB

PICCOLO 650B
PICCOLO 650B SL
PICCOLO 29ER
PICCOLO 29ER SL
PYRENEES 650B
PYRENEES 650B AM PRO 150
PYRENEES 29ER
PYRENEES 29ER AM PRO 150

ARTIC

TALLYHO

TRACK

STINGER


TT

SPRINT-2

CX


CCX PRO
CCX PRO D

EDGE DESIGN

[Back to Index](#)


AIRY (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
450	450	400	75°	505	491	100	71°	370	45	964.2	507.2	408	72	371	501
480	480	420.6	74.5°	515	500.1	110	71.5°	370	45	996.3	572.3	408	72	373	513
500	500	440.6	74.5°	525	511.5	115	72°	370	45	972.2	578.1	408	72	381	519.5
520	520	460.6	74°	535	522.9	120	72.5°	370	45	974.6	579.5	408	69	384	522.5
540	540	480.6	73.5°	545	531.7	140	73°	370	45	975.2	580.2	408	69	385	543
560	560	500.6	73.5°	559.6	547.2	155	73°	370	45	990	594.9	408	69	394.5	557.5
580	580	520.6	73°	575	560.9	175	73.5°	370	45	995.1	600	410	69	398	579
600	600	540.6	72.5°	590	574.7	195	73.5°	370	45	1004.2	609	410	69	401.5	598




AIRY- D (Length: mm/ Angle: °)
OLD 135mm/ ROTOR 140mm

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
450	450	400	75°	505	491	95.8	71°	368	45	974.4	507.2	415	72	370.9	500.7
480	480	420.6	74.5°	515	500.1	105.8	71°	368	45	976.4	572.3	415	72	372.8	512.9
500	500	440.6	74.5°	525	511.5	110.8	72°	368	45	981.4	578.1	415	72	381	519.4
520	520	460.6	74°	535	522.9	115.8	72.5°	368	45	974.6	579.5	415	69	384.1	522.5
540	540	480.6	73.5°	545	531.7	135.8	73°	368	45	985.4	580.2	415	69	385.2	543.2
560	560	500.6	73.5°	559.6	547.2	150.8	73°	368	45	1000.1	594.9	415	69	394.5	557.6
580	580	520.6	73°	575	560.9	170.8	73.5°	368	45	1005.2	600	415	69	398.1	578.8
600	600	540.6	72.5°	590	574.7	190.8	73.5°	368	45	1014.3	609	415	69	401.5	598


[Back to Index](#)

SIZE	S	SC	O	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	HD	HB
450	450	75°	505	100	71°	370	45	965.6	570	405	69	367.7	498	46	46
480	480	74.5°	515	110	71.5°	370	45	967.6	572.7	405	69	371.7	510	46	46
500	500	74.5°	525	115	72°	370	45	973.6	578.6	405	69	374	516.5	46	46
520	520	74°	535	120	72.5°	370	45	974.5	579.5	405	69	381	522.5	46	46
540	540	73.5°	545	140	73°	370	45	975.2	580.3	405	69	384	543.2	46	46
560	560	73.5°	560	160	73°	370	45	990	595	405	69	385	558.3	46	46
580	580	73°	575	180	73.5°	370	45	995	600	405	69	395	584	46	46
600	600	72.5°	590	200	73.5°	370	45	1004.2	609	405	69	396.4	602.7	46	46


[Back to Index](#)

ALLER-D (Length: mm/ Angle: °)

SIZE	S	SC	O	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
440	440	74.5°	520	115	71.5°	368	45	974	577.7	406	68	377.8	511.8
470	470	73.6°	540	135	72.5°	368	45	977	580.6	406	68	382.4	534.2
510	510	73°	555	155	73°	368	45	983.2	584.9	408	68	385	555
540	540	73°	570	170	73°	368	45	998.2	599.7	408	68	395.6	569.3
570	570	72.5°	585	190	73.5°	368	45	1007.4	609	408	68	403.5	590.2




SIZE	S	SP	SC	O	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
450	450	400	75°	500	105	70.5°	368	43	963.9	568.3	406	70	365	502
470	470	420	75°	500	110	70.5°	368	43	966.5	570	406	70	365.5	506.2
490	490	450	75°	505	115	71°	368	43	965.4	570	406	70	367.6	512.7
510	510	470	74.5°	517	125	71.5°	368	43	967.1	571.5	406	70	370	524.6
530	530	490	74°	530	135	72°	368	43	967.5	572	406	70	375.4	537
550	550	510	73.5°	548	150	72.5°	368	43	981	585.5	406	70	384.8	551
580	580	540	73.5°	568	170	73°	368	43	996.5	601	406	70	398.3	572




AXION SL (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
470	470	420	75°	500	487.1	100	71.5°	371	43	955.1	560	405	68	366.4	498.6
490	490	440	74°	510	494.8	120	72°	371	43	952.3	557.1	405	68	360.4	521.7
510	510	460	73.5°	530.4	514.3	132.8	72.1°	371	43	967.2	572	405	68	372.2	534.2
540	540	490	73°	548	532.7	145	73.1°	371	43	970.5	575.3	405	68	380.1	549.2
565	565	515	72.5°	569.1	552.4	171.1	73.1°	371	43	986.1	590.7	405	68	388.1	574.2
590	590	540	72°	590.7	572.6	197.3	73.1°	371	43	1004.6	606.2	405	68	396	599.3




SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
450	450	400	75°	510	495.5	100	71°	368	45	970.4	575.8	405	70	376.6	498.7
480	480	430	74.5°	525	510	115	72°	368	45	973	578.4	405	70	381.8	516.3
510	510	460	74°	540	524.7	135	72.5°	368	45	980.2	584.9	405	68	386.5	535
540	540	490	73.5°	555	539.7	155	73°	368	45	985.8	590.4	405	68	390.3	555.9
570	570	520	73°	570	555.4	175	73°	368	45	995.5	600.1	405	68	394.2	575

[Back to Index](#)


ASCETIC (Length: mm/ Angel: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
510	510	465	74°	520	516.1	102	72.5°	365	45	959.7	564.22	405	67	377.74	496.21
530	530	485	74°	535	530.9	120	73°	365	45	970.8	575.27	405	67	387.35	515
550	550	505	73.5°	550	545.1	140	73°	365	45	981.1	585.5	405	67	391.81	534.13
570	570	525	73.5°	565	560.15	160	73°	365	45	996.3	600.6	405	67	401.14	553.25
590	590	545	73°	575	569.31	180	73°	365	45	1003	605.29	407	67	400.01	572.37




PICCOLO 650B (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
16"	412	348	73°	575	556.5	112	69°	485	43	1074	649.5	427	45	395.4	587.3
18"	450	374.5	73°	595	574	120	71°	485	43	1074.5	650	427	45	410	604.9
20"	500	423	73°	620	594	140	71°	485	43	1098	675.5	427	45	429.2	624.2

[Back to Index](#)


PICCOLO 650B SL (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
15.5"	400	347.3	73.5°	570	555.9	101	70°	485	43	1064.4	640.3	428	45	398	581
17.5"	435	381.6	73°	595	570.8	115	70.5°	485	43	1078	654	428	45	410.1	598.1
19"	480	427.1	73°	610	584.2	120	71°	485	43	1089.1	665	428	45	425.7	603.4
20.5"	520	466.9	73°	625	599.1	130	71°	485	43	1104.5	680.3	428	45	437.8	618




PICCOLO 29ER (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
16"	406.5	330.8	73.7°	570.8	567	105	70.7°	506	45	1066.7	635.1	440	65.5	387.3	627.5
18"	458	376.3	73.5°	594	578.5	120	71°	506	45	1084.6	652.8	440	65.5	403.2	643
20"	508	419.5	73.3°	615	590.3	130	72.7°	506	45	1103.9	672	440	65.5	419.3	652.4


[Back to Index](#)

PICCOLO 29ER SL (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
15.5"	395	341	72.5°	580	555	100	69.5°	506	45	1077.4	644.3	440	60	387.1	611.9
17.5"	440	385	72.5°	600	572	105	69.5°	506	45	1097.7	664.5	440	60	405	618
19"	483	431.3	72.5°	620	584.7	120	69.5°	506	45	1117.6	684.3	440	60	419.8	632.1
21"	533	478.2	72.5°	640	606.5	130	69.5°	506	45	1139.3	705.7	440	60	438	640.8


[Back to Index](#)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	Travel	Shock Eye to Eye
16"	415	346	73.8°	570	529.5	100	68°	505	39	1106	671	435	10	556.8	408.4	110	165
18"	440	346	73.8°	600	558	110	68°	505	39	1137	702.5	435	10	566.1	435.6	110	165
20"	470	346	73.8°	625	582.5	120	68°	505	39	1163	728	435	10	574.9	457.9	110	165




PYRENEES 650B AM PRO 150 (Length: mm/ Angle: °)

SIZE	S	SC	O	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	Travel	Shock Eye to Eye
15.5"	400	74°	580	100	68°	540	45	1134.7	694.8	440	5	413.2	591	150	200
17.5"	445	74°	600	110	68°	540	45	1155.5	715.5	440	5	430.2	591	150	200
19"	483	74°	620	120	68.5°	540	45	1171	731	440	5	447.1	602.9	150	200

[Back to Index](#)


PYRENEES 29ER (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	Travel	Shock Eye to Eye
15.5"	395	343.3	73.6°	565	508.5	105	71°	506	46	1079.1	631.7	452	43	386.5	607	110	165
17.5"	449	401	73.6°	598.1	539.5	115	71°	506	46	1112.7	669.4	452	43	416.8	616	110	165
19"	483	343.3	73.6°	617	558	125	71°	506	46	1132	683.4	452	43	432.9	625.5	110	165
21"	533	343.2	73.6°	638	579	131.1	71°	506	46	1153.5	704.9	452	43	451.1	635	110	165




PYRENEES 29ER AM PRO 150 (Length: mm/ Angle: °)

SIZE	S	SC	O	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	Travel	Shock Eye to Eye
15.5"	400	74°	580	100	69°	550	46	1136.2	680	457	25	402.2	620	150	200
17.5"	440	74°	600	110	69°	550	46	1157	701	457	25	419.5	629.3	150	200
19"	480	74°	620	120	69°	550	46	1178	722	457	25	436.8	638.7	150	200
21"	530	74°	640	135	69°	550	46	1198.9	743	457	25	454.2	648	150	200




SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
15"	381	316	67.5°	583	562.1	115	69.5°	468	45	1112	651.6	467	60	401.9	590.3
17"	432	366.4	67.5°	602	576.4	135	70°	468	45	1126.8	666.4	467	60	415.2	611.2
19"	483	416.5	67.5°	622	597	155	70°	468	45	1148	687.5	467	60	429.5	630
21"	533	466	67.5°	640	611.6	175	70°	468	45	1167	706.4	467	60	441.6	648.8


[Back to Index](#)

TALLYHO (Length: mm/ Angle: °)


SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
15"	381	326	73°	538.6	520	110	71°	445	38	1005.1	588.1	420	38	370.8	548.9
17"	432	377	73°	579	554.7	110	71°	445	38	1045.5	628.4	420	38	411.2	548.9
19"	483	428	73°	598	576	110	71°	445	38	1064.5	647.4	420	38	430.2	548.9
21"	533	478	73°	608.3	591.3	125	71°	445	38	1075.3	658.2	420	38	436.1	563.1



SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	HD	HB
490	498	473	75°	516	517	85	72.5°	368	35	932	560	380	60	386.8	471.1	48	57
510	505	477.5	75°	535	536	90	72.5°	368	35	951	579	380	60	404.5	487.1	48	57
540	520	492	75°	557	558	105	72.5°	368	35	974	601.5	380	60	422.6	501.4	48	57
560	539	512	75°	573	574	125	72.5°	368	35	991	618	380	60	433.5	509.3	48	57


[Back to Index](#)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack	HD	HB	ST
450	450	435	75°	490	488	91.5	71°	370	45	945.5	562.5	395	75	372.5	453.5	46	46	75
490	515	500	75°	511	511.5	101.5	72.5°	370	45	945.5	562.8	395	75	378	512	46	46	75
520	525	510	75°	531.5	532	111.5	72.5°	370	45	967	584	395	75	396	521.5	46	46	75
540	542	527	75°	550.5	551	129.5	72.5°	370	45	986.5	603.5	395	75	410	538	46	46	75
560	561	546	75°	569	569.5	148	72.5°	370	45	1006	622.5	395	75	424	556	46	46	75

[Back to Index](#)

CCX PRO (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
480	480	445	75.5°	510	501.4	100	70.5°	400	45	1009.4	590	425	53	378	510
500	500	465	75°	525	516.3	115	70.5°	400	45	1020.8	601.5	425	53	384.5	524
520	520	485	74.5°	535	526.2	125	71°	400	45	1021.1	602.2	425	55	386	537.5
540	540	505	74°	545	536.8	135	71.5°	400	45	1021.7	602.8	425	55	387.5	548.5
560	560	525	73.5°	560	552.2	145	72°	400	45	1026.6	607.6	425	57	393.5	562.5
580	580	545	73°	575	566.8	160	72.5°	400	45	1030.9	612.4	425	57	398	578.5

[Back to Index](#)

CCX PRO D (Length: mm/ Angle: °)

SIZE	S	SP	SC	O	OS	HS	HC	F	OT	WB	FC	RC	G	Reach	Stack
480	480	445	75.5°	510	501.4	100	70.5°	400	45	1009.4	590	425	53	378	510
500	500	465	75°	525	516.3	115	70.5°	400	45	1020.8	601.5	425	53	384.5	524
520	520	485	74.5°	535	526.2	125	71°	400	45	1021.1	602.2	425	55	386	537.5
540	540	505	74°	545	536.8	135	71.5°	400	45	1021.7	602.8	425	55	387.5	548.5
560	560	525	73.5°	560	552.2	145	72°	400	45	1026.6	607.6	425	57	393.5	562.5
580	580	545	73°	575	566.8	160	72.5°	400	45	1030.9	612.4	425	57	398	578.5