
SSMS

SUPERCOATER







www.ssmsengineers.com



SSMSSUPER COATER

SSMSSUPERCOATERis a range of advanced tablet coatings systems which ensure the process of coating more efficient, reliable, flexible, user friendly and controllable. This high quality tablet coating system is designed for small volume to a large scale production size batches. Innovative science based continual developments in the all areas like tablet mixing, spraying systems, drying efficiency control, cleaning system and control system technology will guarantee a highly controlled process & ensuring the delivery of a high quality end product.

FRONT

TECHNICAL SPECIFICATION

MODEL	10"	14"	18"	36"
SUPERCOATER CAPACITY IN KG	0.3-1.3	2-8	5-20	16-64
PANMOTOR(HP)	1	1	1	5
INLETBLOWER(HP)	0.75	0.75	0.75	3
EXHAUSTBLOWER(HP)	1	1	1	5
INLETBLOWER(HP)	825	825	825	1500
EXHAUSTBLOWER(CFM)	1000	1000	1000	2000

MODEL	48"	60"	72"
SUPERCOATERCAPACITYINKG	35-135	71-315	137-607
PANMOTOR(HP)	7.5	10	15
INLETBLOWER(HP)	5	10	15
EXHAUSTBLOWER(HP)	10	15	20
INLETBLOWER(HP)	2500	4500	6000
EXHAUSTBLOWER(CFM)	3500	6000	7500



MANUFACTURED BY:-**SSMS ENGINEERS**

FACTORY ADDRESS

PLOT NO D-4, BHARAT SMALL INDUSTRIAL
ESTATE, B/H PREM

CONDUCTOR, VATVA 382440, AHMEDABAD

Email : ssmsengineers@gmail.com

Ph : +91-99246 88786 / +91 97277 92615

