

34 parameters

WBC, LYM%, MON%, NEU%, EOS%, BAS%, LYM#, MON#, NEU#, EOS#, BAS#, RBC, HGB, HCT,

MCV, MCH, MCHC, RDW_CV, RDW_SD, PLT, MPV, PDW, PCT, P_LCR, P_LCC, RETIC%,

RETIC_ABS, IRF

6 research parameters: ALY#, ALY%, LIC#, LIC%, NRBC#, NRBC%

2 histograms for RBC and PLT

2 scatter grams: 5-part differential scatter gram

Eosinophils and Neutrophils scatter gram

Two 3-D stereograms

Principles of operation

WBC 5-part: flow cytometry(FCM) + 4 angles laser light scatter

WBC analysis: optical and impedance measurements

RBC/PLT analysis: impedance method

HGB test: cyanide-free reagent colorimetry

RETIC test: flow cytometry (FCM) + laser light scatter + chemical dye method

Reagent

Diluent, detergent, lyse, sheath, RETIC staining solution

Sampling modes

Auto loader 20 μ L, manual mode 20 μ L, pre-diluted mode 20 μ L

Aperture diameter

WBC 100 μ m, RBC/PLT 68 μ m

Throughput

Auto & manual mode: up to 60 samples per hour, support STAT

Sampling device

Auto loader with 50 (10 \times 5 racks) sample storage capacity

Built-in bar code reader

Data storage

Up to 200,000 sample results with all grams

Alarms

Error messages

Display

PC display with windows system, 17-inch color TFT display

LIS

Support, with HL7 protocol

Power

AC 100–240V, 50/60Hz, 300VA

Dimension & Weight

580 mm (L) \times 750 mm (W) \times 550 mm (H), about 73 kg

URIT Since 1984
Global Diagnostics Supplier



URIT-5380

5-Part-Diff Hematology Analyzer

34 Parameters including RETIC_ABS, RETIC%, IRF

Flow Cytometry (FCM) + Multi Angle Scatter Separation (MASS)

Hourly throughput up to 60 samples

Resistant RBC mode

Multi-language software available (Tailor-Made)



URIT Medical Electronic Co., Ltd.

Head Office

Add.: No. D-07 Information Industry
District, High-tech Zone, Guilin, Guangxi, 541004, P.R. China
Tel: +86-773-2288586 Fax: +86-773-2288560
E-mail: export@uritest.com service@uritest.com
<http://www.urit.com>

Shenzhen Office

Add.: Room EJ, 24th Floor, New Baohui Building, Nanhai Road,
Nanshan District, Shenzhen, P.R. China
Tel: +86-755-26413721
Rev :201901-2 (20190128)




Guilin, China



Laser Scatter

- Reticulocyte test: RETIC_ABS, RETIC%, IRF
- 34 parameters, 2 histograms, 2 scatter grams and two 3D stereograms
- Hourly throughput up to 60 samples
- Auto loader with 50 sample storage capacity
- The combination of WIC and WOC for WBC counting
- Impedance method for RBC and PLT counting
- Cyanide free reagent for hemoglobin counting
- On board storage capacity of 200,000 samples with all grams
- Built-in bar code reader
- LIS and HIS available with HL7 protocol



2D+3D Grams

- Two 2D histograms: RBC and PLT
- Two 2D scattergrams: 5-part differential Eosinophil and Neutrophil
- Two 3D multi angle vision grams



Sheath Flow Regulation

- Chemical dye free technology
- Only sheath reagent for WBC 5-Diff



Data Management

- On board storage capacity of 200,000 samples with all grams
- Professional data statistics query system



Sample Aspiration Device

- Flexible sample aspiration blood collection tubes including: standard tube, capillary tube, disposable plastic tube and micro tube



Operation Interface

- Simple operate with user friendly illustrated icons
- Handy tool tips
- Unique URIT operation interface like all URIT hematology series



Electronic and Mechanical Components

- Individual quality control management
- Military level
- 20 years field-proven



Quality Control Solution

- URIT original QC reagent with multi method as L-J, X, X-R, X-B, etc.
- Third party QC solution available

