

TCP, HTTP	1
TCP #1: Sockets	1
TCP #2: Throughput	4
HTTP #3: Requests	4
DNS, Recap	7
DNS reconnaissance #1 (dig)	7

TCP, HTTP

TCP #1: Sockets

Using ChatGPT...

`sudo ss -tlnp | grep LISTEN`

MA Hi chat, can you write a sudo linux command that lists all TCP sockets in a listen state on an IPv4 address and showing the program thats using it?

Certainly! You can use the `netstat` or `ss` command to list all TCP sockets in a listen state on an IPv4 address and display the associated program. Here's a `sudo` command using `ss` to achieve this:

```
bash Copy code
```

```
sudo ss -tlnp | grep 'LISTEN'
```

Let me break down the command:

- `sudo`: Runs the command with superuser privileges, which may be necessary to view information about all sockets and their associated programs.
- `ss`: A command-line utility to investigate sockets. In this case, we're using it to list TCP sockets.
- `-tlnp`: This set of options instructs `ss` to display TCP sockets (`-t`), show only listening sockets (`-l`), and display numeric addresses and port numbers (`-n`). The `-p` option is used to show the associated process.
- `|`: This is a pipe operator that passes the output of the `ss` command to the next command.
- `grep LISTEN`: Filters the output to only display lines that contain the word 'LISTEN'. This helps you focus on listening sockets.

When you run this command, you'll see a list of listening TCP sockets, along with the associated programs or processes using them.

```
marvleon@course-vm:~$ sudo ss -tlnp | grep 'LISTEN'
LISTEN 0      4096      127.0.0.1:34523      0.0.0.0:*      users: (("containerd",pid=474,fd=10))
LISTEN 0      128       0.0.0.0:22          0.0.0.0:*      users: (("sshd",pid=807,fd=3))
LISTEN 0      4096     127.0.0.53%lo:53      0.0.0.0:*      users: (("systemd-resolve",pid=387,fd=14))
LISTEN 0      128       [::]:22            [::]:*      users: (("sshd",pid=807,fd=4))
LISTEN 0      2         [::1]:3350         [::]:*      users: (("xrdp-sesman",pid=613,fd=7))
LISTEN 0      2         *:3389             *:*         users: (("xrdp",pid=699,fd=11))
marvleon@course-vm:~$
```

List a service that can be contacted from any interface on the machine.

sshd

List a service that can only be contacted by local processes.

containerd

```
marvleon — ssh marvleon@linux.cs.pdx.edu — 89x54
marvleon@ada:~$ ss -tulnp | grep LISTEN
tcp LISTEN 0 511 127.0.0.1:39507 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6100 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6101 0.0.0.0:*
tcp LISTEN 0 511 127.0.0.1:39221 0.0.0.0:*
tcp LISTEN 0 4096 127.0.0.53:53 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6102 0.0.0.0:*
tcp LISTEN 0 128 0.0.0.0:22 0.0.0.0:*
tcp LISTEN 0 511 127.0.0.1:44343 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6103 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:631 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6104 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6105 0.0.0.0:*
tcp LISTEN 0 100 127.0.0.1:25 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6106 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6107 0.0.0.0:*
tcp LISTEN 0 511 127.0.0.1:45211 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6108 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6109 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6110 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6111 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6112 0.0.0.0:*
tcp LISTEN 0 5 127.0.0.1:5984 0.0.0.0:*
tcp LISTEN 0 511 127.0.0.1:39361 0.0.0.0:*
tcp LISTEN 0 128 127.0.0.1:6113 0.0.0.0:*
tcp LISTEN 0 5 127.0.0.1:5953 0.0.0.0:*
tcp LISTEN 0 4096 *:113 *:
tcp LISTEN 0 128 [::]:6100 [::]:*
tcp LISTEN 0 50 *:1716 *:
tcp LISTEN 0 128 [::]:6101 [::]:*
tcp LISTEN 0 50 *:1717 *:
tcp LISTEN 0 128 [::]:6102 [::]:*
tcp LISTEN 0 128 [::]:22 [::]:*
tcp LISTEN 0 128 [::]:6103 [::]:*
tcp LISTEN 0 128 [::]:631 [::]:*
tcp LISTEN 0 128 [::]:6104 [::]:*
tcp LISTEN 0 128 [::]:6105 [::]:*
tcp LISTEN 0 100 [::]:25 [::]:*
tcp LISTEN 0 128 [::]:6106 [::]:*
tcp LISTEN 0 128 [::]:6107 [::]:*
tcp LISTEN 0 128 [::]:6108 [::]:*
tcp LISTEN 0 128 [::]:6109 [::]:*
tcp LISTEN 0 128 [::]:6110 [::]:*
tcp LISTEN 0 128 [::]:6111 [::]:*
tcp LISTEN 0 128 [::]:6112 [::]:*
tcp LISTEN 0 5 [::]:5984 [::]:*
tcp LISTEN 0 128 [::]:6113 [::]:*
tcp LISTEN 0 5 [::]:5953 [::]:*
marvleon@ada:~$
```

List the services that this machine provides for external access

ssh (port 22), auth (port 113), audio file server (port 1716), fj-hdnet (port 1717)

Using chatGPT...

Sudo lsof -iTCP -sTCP:LISTEN

```
marvleon@course-vm:~$ sudo lsof | wc -l
4514
marvleon@course-vm:~$ sudo lsof -iTCP -sTCP:LISTEN
COMMAND  PID  USER  FD  TYPE  DEVICE  SIZE/OFF  NODE  NAME
systemd-r 387 systemd-resolve 14u IPv4 16737 0t0 TCP localhost:domain (LISTEN)
container 474 root 10u IPv4 18843 0t0 TCP localhost:34523 (LISTEN)
xrdp-sesm 613 root 7u IPv6 17371 0t0 TCP ip6-localhost:3350 (LISTEN)
xrdp 699 xrdp 11u IPv6 18812 0t0 TCP *:ms-wbt-server (LISTEN)
sshd 807 root 3u IPv4 18826 0t0 TCP *:ssh (LISTEN)
sshd 807 root 4u IPv6 18828 0t0 TCP *:ssh (LISTEN)
marvleon@course-vm:~$
```

TCP #2: Throughput

```
marvleon@vm-us-west1-b:~$ iperf -c 10.142.0.2 -p 80
-----
Client connecting to 10.142.0.2, TCP port 80
TCP window size: 85.0 KByte (default)
-----
[  1] local 10.138.0.3 port 33694 connected with 10.142.0.2 port 80
[ ID] Interval           Transfer     Bandwidth
[  1] 0.0000-10.0777 sec   426 MBytes  355 Mbits/sec
marvleon@vm-us-west1-b:~$ iperf -c 10.132.0.2 -p 80
-----
Client connecting to 10.132.0.2, TCP port 80
TCP window size: 85.0 KByte (default)
-----
[  1] local 10.138.0.3 port 44572 connected with 10.132.0.2 port 80
[ ID] Interval           Transfer     Bandwidth
[  1] 0.0000-10.2548 sec   189 MBytes  154 Mbits/sec
marvleon@vm-us-west1-b:~$ iperf -c 10.152.0.2 -p 80
-----
Client connecting to 10.152.0.2, TCP port 80
TCP window size: 85.0 KByte (default)
-----
[  1] local 10.138.0.3 port 56098 connected with 10.152.0.2 port 80
[ ID] Interval           Transfer     Bandwidth
[  1] 0.0000-10.2040 sec   170 MBytes  140 Mbits/sec
marvleon@vm-us-west1-b:~$
```

Explain the relative differences (or lack thereof) in your results

US-east (10.142.0.2) has the most available bandwidth (355 Mbits/sec) likely because it's the closest to the US-west. EU-west (10.132.0.2) had less bandwidth (154 Mbits/sec) because it's much farther away but the difference compared to AUS-SE (10.152.0.2) is only 14 Mbits/sec. This is likely because US-west is somewhat in between Australia and Europe.

HTTP #3: Requests

Name	Status	Protocol	Type	Initiator	Size
Odin: marvleon google.com	307	http/1.1	docume...	Other	(disk ca...
www.google.com	200	h3	document	google.com/	52.3 kB
google.com	200	h2	docume...	google.com/	(disk ca...

http://google.com/


















- *307 Internal Redirect from disk cache*
- This means the browser internally redirected the request, probably because of the site's security policy which prevents the request from going out over HTTP. The resource was retrieved from the browser's local disk cache and not fetched over the network.

https://www.google.com/

- *200 OK*
- This means the client's request was successfully received, understood and processed by the server.

https://google.com/

- *200 Moved permanently (from disk cache)*
- *This means that request was successful but it was served from the browser's local disk cache.*

Name	X	Headers	Preview	Response	Initiator	Timing
 google.com	Odin: marvleon					
 www.google.com						
 google.com						
 m=cdos,hsm,jsa,mb4ZUb,d,csi,cEt90b,SNUUn3,qdd...						
 googlelogo_light_color_272x92dp.png						
 swg-gshield-logo-rgb-64px.png						
 data:image/png;base...						
 rs=AA2YrTvixsfv1A3Mw-06Md8Ysk0A4FqoTA						
 rs=AA2YrTspfdc2CFY9fQlqvAUeVsoR6jxShA						
 desktop_searchbox_sprites318_hr.webp						
 gen_204?s=webhp&t=aft&atyp=csi&ei=ndskZa3CG...						
 cb=gapi.loaded_0						
 m=lvPZ6d?xjs=s1						
 rs=ACT90oE9ucNpNcib4rPP2h2LT8Hy2Qwb0A						
 search?q&cp=0&client=gws-wiz&xssi=t&gs_pcr=2...						
 client_204?atyp=i&biw=200&bih=1040&dpr=2&ei=n...						
 m=sv6q,svde,svdz,svm6,MkHvGd?xis=s3						
▼ General						
Request URL:		https://www.google.com/				
Request Method:		GET				
Status Code:		200 OK				
Remote Address:		[2607:f8b0:400a:806::2004]:443				
Referrer Policy:		strict-origin-when-cross-origin				
▼ Response Headers						
Accept-Ch:		Sec-CH-UA-Arch				
Accept-Ch:		Sec-CH-UA-Bitness				
Accept-Ch:		Sec-CH-UA-Full-Version				
Accept-Ch:		Sec-CH-UA-Full-Version-List				
Accept-Ch:		Sec-CH-UA-Model				
Accept-Ch:		Sec-CH-UA-Platform				
Accept-Ch:		Sec-CH-UA-Platform-Version				
Accept-Ch:		Sec-CH-UA-WoW64				
Alt-Svc:		h3=":443"; ma=2592000,h3-29=":443"; ma=2592000				

What URL does the first redirection send the browser to?

- Location: <https://google.com/>

What URL does the second redirection send the browser to?

- Location <https://www.google.com/>

Take a screenshot of when cookies are set via Set-Cookie:

Set-Cookie:	Odin: marvleon	1P_JAR=2023-10-10-05; expires=Thu, 09-Nov-2023 05:16:37 GMT; path=/; domain=.google.com; Secure; SameSite=none
-------------	----------------	--

Request Cookies

☐ show filtered out request cookies

Odin: marvleon

Name	Value	D...	Path	Ex...	Size	Http...	Se...	Sa...	Pa...	P...
AEC	Ackid1ScNTBRdfMCd5dMf1q5...	/	20...	61	✓	✓	Lax		Me...
OGPC	19037049-1:	/	20...	15					Me...
NID	511=d3f4kKJD2NASKm6kljQN...	/	20...	187	✓	✓	None		Me...
1P_JAR	2023-10-10-05	/	20...	19		✓	None		Me...

Response Cookies

Name	Value	D...	Path	Ex...	Size	Http...	Se...	Sa...	Pa...	P...
1P_JAR	2023-10-10-05	/	20...	110		✓	none	htt...	Me...

Take a screenshot of when cookies are attached via Cookie:

Cookie:

Odin: marvleon

AEC=Ackid1ScNTBRdfMCd5dMf1q5CPjTsun7u_H8AJeEINZrd4k-JH_4XYH8ig; OGPC=19037049-1;; NID=511=d3f4kKJD2NASKm6kljQN2DtWt3r5Z476FbNIJFg_JgoNTZPSebtoa92ZFngVjBNJkyXlxRXC3Luk9HzZOVoBMh1yC-UKNYmXWxmMgBHONylmzcc2K_NLboln2cM2lm3mBVpUlpk4Up53al7Vc-Eu-0OVWxrOZVnT3ztROnAjbxsrb8tcdmFZ; 1P_JAR=2023-10-10-05

Request Cookies

☐ show filtered out request cookies

Odin: marvleon

Name	Value	D	P...	E..	S..	H.	S..	S.	P..	P
AEC	Ackid1ScNTBR...	...	/	2...	61	✓	✓	L...		M.
OGPC	19037049-1:	...	/	2...	15					M.
NID	511=d3f4kKJD2...	...	/	2...	1...	✓	✓	N..		M.
1P_JAR	2023-10-10-05	...	/	2...	19		✓	N..		M.

Name	X	Headers	Payload	Preview	Response	Initiator	Timing	Cookies
<input type="checkbox"/> search?q=Portla&cp=6&client=gws-wiz&xssi=t&gs_pcr...	1				}			
<input type="checkbox"/> search?q=Portland&cp=7&client=gws-wiz&xssi=t&gs_p...	-				}			
<input type="checkbox"/> search?q=Portland&cp=8&client=gws-wiz&xssi=t&gs...	2				[[{"portland state university",46,[512,433,131],{"lm":[],"zh":"Portland State University","zi":"Public univer			
<input type="checkbox"/> search?q=Portland%20&cp=9&client=gws-wiz&xssi=t...								
<input type="checkbox"/> search?q=Portland%20S&cp=10&client=gws-wiz&xssi...								
<input type="checkbox"/> search?q=Portland%20St&cp=11&client=gws-wiz&xss...								
<input type="checkbox"/> search?q=Portland%20Sta&cp=12&client=gws-wiz&xs...								
<input type="checkbox"/> search?q=Portland%20Stat&cp=13&client=gws-wiz&x...								
<input type="checkbox"/> search?q=Portland%20State&cp=14&client=gws-wiz&...								

Odin: marvleon

DNS, Recap

DNS reconnaissance #1 (dig)