

Package ‘udwqTools’

January 16, 2019

Title A Collection of R Tools for Utah Division of Water Quality

Version 0.0.0.9000

Authors Jake Vander Laan, Utah Division of Water Quality, jvander@utah.gov [aut, cre]

Description This package is intended to house R tools developed and for use by UDWQ staff as well as support the UDWQ irTools package.

Depends R (>= 3.5.1)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Roxygen list(markdown = TRUE)

R topics documented:

assignUses	1
bu_poly	2
calcTSI	2
facToNum	3
readECHO_ec	3
readECHO_fac	4
readWQP	5
ul_trophic	6
Index	7

assignUses	<i>Assign Utah beneficial use classes to sites</i>
------------	--

Description

This function assigns beneficial use classes to water quality portal type site objects (or data with site information attached).

Usage

```
assignUses(x, lat = "LatitudeMeasure", long = "LongitudeMeasure",  
  flatten = FALSE)
```

Arguments

x	Input dataset. Must include latitude & longitude columns.
lat	Name of latitude column. Default matches WQP objects.
long	Name of longitude column. Default matches WQP objects.
flatten	Logical. If FALSE (default), maintain use categorys as single comma separated column. If TRUE, use column and data are flattened by expanded use column.

Examples

```
# Read a couple of sites from Mantua Reservoir
sites=readWQP(type="sites", siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"))
sites_uses=assignUses(sites)
sites_uses_flat=assignUses(sites, flatten=TRUE)
```

bu_poly	<i>Utah's beneficial use polygon shapes</i>
---------	---

Description

Polygons containing beneficial use designations and water body type information. Used to assign uses or standards to site locations.

Usage

```
bu_poly
```

Format

An sf type polygon shapefile

calcTSI	<i>Calculate TSI values from input data</i>
---------	---

Description

This function calculates TSI values according to Utah's IR methods from input data containing values for of chlorophyll, total phosphorus, and secchi disk depth. Note that inputs for these parameters must be specified in units of ug/L, mg/L, and meters, respectively.

Usage

```
calcTSI(x, in_format = "wide", chl_ugL = "chl", TP_mgL = "TP",
        SD_m = "SD")
```

Arguments

x	Input dataset
in_format	One of "wide" or "flat" to specify data input format. Note that only wide format inputs are currently supported.
chl_ugL	Name of chlorophyll-a variable in ug/L
TP_mgL	Name of total phosphorus variable in mg/L
SD_m	Name of secchi disk depth variable in m

Examples

```
data(ul_trophic)
head(ul_trophic)
tsi=calcTSI(ul_trophic,chl_ugL="ChlA",TP_mgL="Phosphate.phosphorus.Total",SD_m="Depth.Secchi.disk.depth")
head(tsi)
plot(TSIchl~ChlA,tsi)
```

 facToNum

Convert factors to numeric equivalents

Description

Converts input object to number if class=="factor". If class != "factor", input object is returned un-altered.

Usage

```
facToNum(x)
```

Arguments

x	Input vector object
---	---------------------

 readECHO_ec

Read effluent chart data from EPA ECHO webservice

Description

This function extracts effluent chart data from EPA ECHO for multiple stations & combinations of parameters. All arguments are optional except p_id. At least one p_id must be specified.

Usage

```
readECHO_ec(..., print = TRUE)
```

Arguments

...	additional arguments to be passed to ECHO query path. See https://echo.epa.gov/tools/web-services/effluent-charts#!/Effluent_Charts/get_eff_rest_services_download_effluent_chart optional arguments for effluent chart data reads. Note that arguments for output are ignored.
print	Logical. If TRUE (default), print summary table of facilities & parameters returned.
p_id	Permitted facility ID. Either a single text value (in quotes) or a vector of text values.
parameter_code	Parameter code. Either a single text value (in quotes) or a vector of text values.
start_date	Query start date in "mm/dd/yyyy" format.
end_date	Query end date in "mm/dd/yyyy" format.

Value

A flat data frame of EPA ECHO effluent chart data

Examples

```
#Extract effluent chart data for facility UT0025241, all outfalls
UT0025241_ec=readECHO_ec(type="ec",p_id="UT0025241")
head(UT0025241_ec)

# Extract effluent total phosphorus data from outfall 001 for facility UT0025241
UT0025241_tp_001=readECHO_ec(p_id="UT0025241", parameter_code="00665", outfall="001")
UT0025241_tp_001_effluent=UT0025241_tp_001[UT0025241_tp_001$monitoring_location_desc=="Effluent Gross",]
head(UT0025241_tp_001_effluent)

# Extract flow through facility from UT0021717
UT0021717_flow=readECHO_ec(p_id="UT0021717", parameter_code="50050")

# Extract flow & TP from UT0025241 & UT0021717
tp_flow=readECHO_ec(p_id=c("UT0025241","UT0021717"), parameter_code=c("50050","00665"))
```

readECHO_fac

Read facility information from EPA ECHO webservices

Description

This function extracts facility information from EPA ECHO based on argument inputs.

Usage

```
readECHO_fac(type = "", ...)
```

Arguments

...	Additional arguments to be passed to ECHO query path. See https://echo.epa.gov/tools/web-services/facility-search-water#!/Facility_Information/get_cwa_rest_services_get_facility_info for optional arguments for facilities. Note that arguments for output are ignored.
-----	--

Value

A data frame of EPA ECHO facility information

Examples

```
# Read facility locations in Utah
ut_fac=readECHO_fac(p_st="ut", p_act="y")
head(ut_fac)
# Read facility locations for two permit IDs
two_fac=readECHO_fac(p_pid=c("UT0021717", "UT0025241"))
two_fac
```

readWQP	<i>Read EPA Water Quality Portal Data</i>
---------	---

Description

This function extracts water quality data from EPA's Water Quality Portal based on user argument inputs. Note that connections to the WQP occasionally time out during download. This function tries to download requested files up to 10 times before exiting. All arguments except type are optional, but at least one should be provided to limit download size and prevent errors connecting to WQP. Note that some, but not all, special characters in characteristic names have been accounted for. If in doubt, use the WQP web interface to determine the appropriate syntax for odd characteristic names.

Usage

```
readWQP(type = "result", ..., print = TRUE)
```

Arguments

type	Data type to read. One of "result", "narrowresult", "sites", "activity", or "dequantlim".
...	additional arguments to be passed to WQP query path. See https://www.waterqualitydata.us/portal/ for optional arguments.
print	Logical. Print summary table of sites & characteristics (only for result or narrowresult types).
startDateHi	Query start date in 'mm-dd-yyyy' format.
startDateLo	Query end date in 'mm-dd-yyyy' format.

Value

A data frame of WQP data

Examples

```
# Read some data from Mantua Reservoir (2016-2018)
nr=readWQP(type="narrowresult", siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"),
  startDateLo="01-01-2016", startDateHi="12-31-2018")

# Read just Arsenic, Cadmium, and DO, all dates
nr=readWQP(type="narrowresult",
  siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"),
  characteristicName=c("Arsenic", "Cadmium", "Dissolved oxygen (DO)"))

# Read all Total dissolved solids statewide (2016-2018) (& note statecode for Utah)
tds_sw=readWQP(type="result",
  statecode="US:49",
  characteristicName="Total dissolved solids",
  startDateLo="01-01-2016", startDateHi="12-31-2018",
  print=F)

# Read sites in Utah
sites=readWQP(type="sites", statecode="US:49")
plot(LatitudeMeasure~LongitudeMeasure, sites[sites$LatitudeMeasure>0 & sites$LongitudeMeasure<0,])
```

ul_trophic

Utah Lake trophic data

Description

Utah Lake trophic data

Usage

```
data(ul_trophic)
```

Format

A data.frame with 729 rows and 15 columns

Index

*Topic **datasets**

bu_poly, [2](#)

ul_trophic, [6](#)

assignUses, [1](#)

bu_poly, [2](#)

calcTSI, [2](#)

facToNum, [3](#)

readECHO_ec, [3](#)

readECHO_fac, [4](#)

readWQP, [5](#)

ul_trophic, [6](#)