

# Package ‘wqTools’

November 18, 2019

**Title** A Collection of R Tools for Utah Division of Water Quality

**Version** 0.0.0.9000

**Authors**

Jake Vander Laan, Utah Division of Water Quality, [jvander@utah.gov](mailto:jvander@utah.gov) [aut, cre], Elise Hinman, Utah Division of Water Quality, [ehinman@utah.gov](mailto:ehinman@utah.gov) [aut]

**Description** This package is intended to house R tools developed and for use by UDWQ staff as well as support the UDWQ irTools package.

**Depends** R (≥ 3.5.0)

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.1

**Roxygen** list(markdown = TRUE)

**Imports** data.table,

dplyr,  
glue,  
leaflet,  
RColorBrewer,  
akima,  
jsonlite,  
leaflet.extras,  
lubridate,  
mapedit,  
plyr,  
rLakeAnalyzer,  
reshape2,  
sf,  
tidyr,  
lwgeom

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

## R topics documented:

|                                      |                   |
|--------------------------------------|-------------------|
| <a href="#">assignAUs</a> . . . . .  | <a href="#">2</a> |
| <a href="#">assignHUCs</a> . . . . . | <a href="#">3</a> |

|                          |           |
|--------------------------|-----------|
| assignUses . . . . .     | 3         |
| au_poly . . . . .        | 4         |
| buildLDC . . . . .       | 4         |
| buildMap . . . . .       | 5         |
| bu_poly . . . . .        | 6         |
| calcTSI . . . . .        | 6         |
| convertUnits . . . . .   | 7         |
| downloadWQP . . . . .    | 8         |
| facToNum . . . . .       | 9         |
| huc12_poly . . . . .     | 9         |
| huc8_12_poly . . . . .   | 9         |
| huc8_poly . . . . .      | 10        |
| profileHeatMap . . . . . | 10        |
| profilePlot . . . . .    | 11        |
| readAWQMS . . . . .      | 12        |
| readECHO_ec . . . . .    | 13        |
| readECHO_fac . . . . .   | 14        |
| readWQP . . . . .        | 14        |
| readWQPbySite . . . . .  | 16        |
| ss_poly . . . . .        | 17        |
| ul_trophic . . . . .     | 17        |
| ut_poly . . . . .        | 18        |
| wmu_poly . . . . .       | 18        |
| wqpDD . . . . .          | 18        |
| <b>Index</b>             | <b>19</b> |

---

## assignAUs

*Assign Utah assessment units to sites*

---

### Description

This function assigns assessment units to water quality portal type site objects (or data with site information attached). This can be done before or after assigning beneficial uses.

### Usage

```
assignAUs(data, lat = "LatitudeMeasure", long = "LongitudeMeasure")
```

### Arguments

|             |   |
|-------------|---|
| <b>data</b> | Input dataset. Must include latitude & longitude columns. |
| <b>lat</b>  | Name of latitude column. Default matches WQP objects.     |
| <b>long</b> | Name of longitude column. Default matches WQP objects.    |

### Value

Returns the input data frame with assessment unit information appended.

**Examples**

```
# Read a couple of sites from Mantua Reservoir
sites=readWQP(type="sites", siteid=c("UTAHDWQ_WQX-4900440","UTAHDWQ_WQX-4900470"))
sites_AUS=assignUses(sites)
```

---

**assignHUCs**
*Assign HUC 8 & 12 values to sites*


---

**Description**

This function assigns HUC 8 & 12 values to water quality portal type site objects (or data with site information attached).

**Usage**

```
assignHUCs(data, lat = "LatitudeMeasure", long = "LongitudeMeasure")
```

**Arguments**

|             |   |
|-------------|---|
| <b>data</b> | Input dataset. Must include latitude & longitude columns. |
| <b>lat</b>  | Name of latitude column. Default matches WQP objects.     |
| <b>long</b> | Name of longitude column. Default matches WQP objects.    |

**Value**

Returns the input data frame with HUC 8 & 12 information appended.

**Examples**

```
# Read a couple of sites from Mantua Reservoir
sites=readWQP(type="sites", siteid=c("UTAHDWQ_WQX-4900440","UTAHDWQ_WQX-4900470"))
sites_HUCs=assignHUCs(sites)
```

---

**assignUses**
*Assign Utah beneficial use classes to sites*


---

**Description**

This function assigns beneficial use classes to water quality portal type site objects (or data with site information attached).

**Usage**

```
assignUses(data, lat = "LatitudeMeasure", long = "LongitudeMeasure",
  flatten = FALSE)
```

**Arguments**

|                      |  |
|----------------------|--|
| <code>data</code>    | Input dataset. Must include latitude & longitude columns.  |
| <code>lat</code>     | Name of latitude column. Default matches WQP objects.  |
| <code>long</code>    | Name of longitude column. Default matches WQP objects.   |
| <code>flatten</code> | Logical. If FALSE (default), maintain use categorys as single comma separated column. If TRUE, use column and data are flattened by expanded use column. |

**Examples**

```
# Read a couple of sites from Mantua Reservoir
sites=readWQP(type="sites", siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"))
sites_uses=assignUses(sites)
sites_uses_flat=assignUses(sites, flatten=TRUE)
```

---

|                      |  |
|----------------------|--|
| <code>au_poly</code> | <i>Utah's IR-specific assessment unit polygons</i> |
|----------------------|--|

---

**Description**

Polygons containing assessment unit designations.

**Usage**

```
au_poly
```

**Format**

An sf type polygon shapefile

---

|                       |   |
|-----------------------|---|
| <code>buildLDC</code> | <i>Calculate parameter loading capacity</i> |
|-----------------------|---|

---

**Description**

Uses flow, parameter concentration, and standard values to determine observed loading and loading capacity

**Usage**

```
buildLDC(x, flow, date, value, location, parameter, crit, loading_units,
  mos = 0.1, cf, plot_it = TRUE)
```

**Arguments**

|                            |   |
|----------------------------|---|
| <code>x</code>             | A data frame containing columns indicating flow and parameter concentration for given dates (required for plotting: location and parameter name). Note that flow data for which no parameter values exist are still used to construct LDC plot. |
| <code>flow</code>          | String. Column name containing flow data.   |
| <code>date</code>          | String. Column name containing date data.   |
| <code>value</code>         | String. Column name containing parameter concentration data.  |
| <code>location</code>      | String. Column name containing location name(s).  |
| <code>parameter</code>     | String. Column name containing parameter name.  |
| <code>crit</code>          | Numeric. Represents the standard criterion (in same concentration units as parameter) against which observed loadings are compared.   |
| <code>loading_units</code> | String. Indicates the loading units (amount/time) to be plotted on the y-axis of the LDC (if <code>plot_it = TRUE</code> ).   |
| <code>mos</code>           | Numeric. A decimal representing the percent margin of safety to apply to the loading capacity for management decisions.   |
| <code>cf</code>            | Numeric. A value representing the correction factor linking flow and parameter concentration to desired unit (load per time).   |
| <code>plot_it</code>       | Logical. If <code>TRUE</code> , plots observed capacity and loading capacity in one figure in a load duration curve framework.  |

**Value**

A data frame containing original columns supplied to function plus observed loading, loading capacity, loading capacity plus margin of safety, season, and flow percentile.

---

|                       |   |
|-----------------------|---|
| <code>buildMap</code> | <i>Build a site map of WQP sites or ECHO facilities</i> |
|-----------------------|---|

---

**Description**

Build a map of sample sites, facilities, or both. Map includes sites, beneficial use and assessment unit polygons, and satellite and topo baselayers. This is designed to work with column names as extracted from WQP or AWQMS & ECHO via `udwqTools` functions `readWQP()`, `readAWQMS()` and `readECHO_fac()`. Map will launch in default browser (or R-Studio's browser if using R-Studio). Site and assessment unit features are searchable by identifier and name via the search button on the left side of the map. The most recently turned on layer is "on top" of the map. Only features on top will show their pop-up on click.

**Usage**

```
buildMap(fac, sites, au_poly, bu_poly, ss_poly, huc12_poly, huc8_poly,
  search = c("sites", "aus"), plot_polys = TRUE, dragging = T, ...)
```

**Arguments**

|            |   |
|------------|---|
| fac        | Facility locations queried via readECHO_fac.  |
| sites      | Site locations queried via readWQP(type="sites"). May also be a data file with WQP site information merged to it.   |
| au_poly    | Optional. Polygon file to be mapped as assessment units. Useful for mapping a subset of specific assessment units. If missing, the default state wide AU polygon is used. |
| bu_poly    | Optional. Polygon file to be mapped as beneficial uses. Useful for mapping a subset of beneficial uses. If missing, the default state wide uses polygon is used.          |
| ss_poly    | Optional. Polygon file to be mapped as site specific standards. Useful for mapping a subset of ss polygons. If missing, the default state wide ss polygon is used.        |
| huc12_poly | Optional. Polygon file to be mapped as huc12 polygons. Useful for mapping a subset of polygons. If missing, the default state wide huc 12 polygon is used.                |
| huc8_poly  | Optional. Polygon file to be mapped as huc8 polygons. Useful for mapping a subset of polygons. If missing, the default state wide huc 8 polygon is used.                  |
| search     | Vector of objects to be made searchable. One or both of "sites" and "aus". Defaults to c("sites", "aus"). Any other inputs are ignored.                                   |

**Examples**

```
# Read sites & facility locations
jr_sites=readWQP(type="sites",
siteid=c("UTAHDWQ_WQX-4994100", "UTAHDWQ_WQX-4994120", "UTAHDWQ_WQX-4991860",
"UTAHDWQ_WQX-4994190", "UTAHDWQ_WQX-4994172", "UTAHDWQ_WQX-4994090",
"UTAHDWQ_WQX-4992890", "UTAHDWQ_WQX-4992880", "UTAHDWQ_WQX-4992480",
"UTAHDWQ_WQX-4992055", "UTAHDWQ_WQX-4991940", "UTAHDWQ_WQX-4991880"))
jr_fac=readECHO_fac(p_pid=c("UT0024392", "UT0024384", "UT0025852", "UT0021725"))
#Build some maps
map1=buildMap(sites=jr_sites, fac=jr_fac) #define new object for use later
map1 #call generated map object to launch in browser
buildMap(sites=jr_sites) #just sites, launch w/o generating map object in workspace
buildMap(fac=jr_fac) #just facilities
buildMap() #Build an empty map w/ just AU, BU, and SS std polys
#html maps can be saved via htmlwidgets package saveWidget(map1, file="your/path/map1.html")
```

---

bu\_poly

*Utah's beneficial use polygon shapes*


---

**Description**

Polygons containing beneficial use designations and water body type information. Used to assign uses or standards to site locations.

**Usage**

```
bu_poly
```

**Format**

An sf type polygon shapefile

---

calcTSI

*Calculate TSI values from input data*

---

**Description**

This function calculates TSI values according to Utah's IR methods from input data containing values for of chlorophyll, total phosphorus, and secchi disk depth. Note that inputs for these parameters must be specified in units of ug/L, mg/L, and meters, respectively.

**Usage**

```
calcTSI(x, in_format = "flat", chl_ugL = "Chlorophyll a",
        TP_mgL = "Phosphate-phosphorus", SD_m = "Depth, Secchi disk depth",
        value_var = "ResultMeasureValue", param_var = "CharacteristicName")
```

**Arguments**

|           |  |
|-----------|--|
| x         | Input dataset  |
| in_format | One of "wide" or "flat" to specify data input format. Note that only wide format inputs are currently supported. |
| chl_ugL   | Name of chlorophyll-a variable in ug/L   |
| TP_mgL    | Name of total phosphorus variable in mg/L  |
| SD_m      | Name of secchi disk depth variable in m  |

**Examples**

```
data(ul_trophic)
head(ul_trophic)
tsi=calcTSI(ul_trophic,chl_ugL="ChlA",TP_mgL="Phosphate.phosphorus.Total",SD_m="Depth.Secchi.disk.depth")
head(tsi)
plot(TSIchl~ChlA,tsi)
```

---

convertUnits

*Convert data to target units*

---

**Description**

This converts flat data to target units as defined in the dataset. It creates three new columns in your dataset: 1. The converted unit value, 3. the conversion factor used, & 4. a recommended acceptance/rejection based on pairs of input & target units. All original columns are retained.

**Usage**

```
convertUnits(x, input_units, target_units = "target_unit", value_var,
            conv_val_col = "converted_value")
```

**Arguments**

|                           |   |
|---------------------------|---|
| <code>x</code>            | Input dataset.  |
| <code>value_var</code>    | Column name of <code>x</code> containing result values (in quotes).   |
| <code>conv_val_col</code> | Name of new values column for converted values (in quotes).           |
| <code>input_unit</code>   | Column name of <code>x</code> with units to convert from (in quotes). |
| <code>target_unit</code>  | Column name of <code>x</code> with units to convert to (in quotes).   |

**Examples**

```
# Make example data
value=c(abs(rnorm(5,1, 0.1)), rnorm(5, 1000, 100), rnorm(5, 20, 1))
raw_units=c(rep('mg/l',5), rep('ug/L', 5), rep('deg C',5))
preferred_units=c(rep('mg/L', 10), rep('deg C',5))
data=data.frame(value,raw_units,preferred_units)
data

# Unit conversion
conv_data=convertUnits(data, input_units='raw_units', target_units='preferred_units', value_var='value', con
conv_data
```

---

|                          |  |
|--------------------------|--|
| <code>downloadWQP</code> | <i>Download water quality, station, and other data from USEPA Water Quality Portal</i> |
|--------------------------|--|

---

**Description**

Download data from EPA's Water Quality Portal (WQP) as .csv files to `outfile_path` folder.

**Usage**

```
downloadWQP(outfile_path = getwd(), retrieve = c("narrowresult",
  "activity", "sites", "detquantlim"),
  siteType = c("Aggregate surface-water-use",
  "Lake, Reservoir, Impoundment", "Spring", "Stream"),
  statecode = "US:49", zip = FALSE, unzip = FALSE, ...)
```

**Arguments**

|                           |   |
|---------------------------|---|
| <code>outfile_path</code> | Path for file outputs. Defaults to current working directory.   |
| <code>retrieve</code>     | Vector of data type names to retrieve from WQP. One or more of: "result", "narrowresult", "activity", "sites", "detquantlim". Defaults to query narrowresult, activity, sites, and detquantlim. |
| <code>zip</code>          | Logical. If FALSE (default) files are downloaded straight as csv. If TRUE, files are downloaded as zipped folders (helps prevent server time-outs, recommend for large downloads).              |
| <code>...</code>          | Other arguments to be passed to <code>readWQP</code> when generating a query URL.   |
| <code>start_date</code>   | Query start date. "mm/dd/yyyy" format.  |
| <code>end_date</code>     | Query end date. "mm/dd/yyyy" format.  |
| <code>zip</code>          | Logical. If FALSE (default) files downloaded as zip folders are not automatically unzipped. If TRUE, the function will unzip all downloaded zip files. Only used if <code>zip==TRUE</code> .    |



**Value**

Exports .csv files for all selected data types during selected date period in specified output path.

**Examples**

```
# Read 2018 download narrow result & sites
downloadWQP(outfile_path='C:\\Your\\Folder\\Path', start_date="01/01/2018", end_date="12/31/2018", retrieve=
```

---

|          |   |
|----------|---|
| facToNum | <i>Convert factors to numeric equivalents</i> |
|----------|---|

---

**Description**

Converts input object to number if class=="factor". If class!="factor", input object is returned un-altered.

**Usage**

```
facToNum(x)
```

**Arguments**

x                      Input vector object

---

|            |  |
|------------|--|
| huc12_poly | <i>HUC 12 polygons for the state of Utah</i> |
|------------|--|

---

**Description**

HUC 12 polygons for the state of Utah.

**Usage**

```
huc12_poly
```

**Format**

An sf type polygon shapefile

---

|              |  |
|--------------|--|
| huc8_12_poly | <i>Unioned HUC 8 &amp; 12 polygons for the state of Utah</i> |
|--------------|--|

---

**Description**

Unioned HUC 8 & 12 polygons for the state of Utah.

**Usage**

huc8\_12\_poly

**Format**

An sf type polygon shapefile

---

|           |   |
|-----------|---|
| huc8_poly | <i>HUC 8 polygons for the state of Utah</i> |
|-----------|---|

---

**Description**

HUC 8 polygons for the state of Utah.

**Usage**

huc8\_poly

**Format**

An sf type polygon shapefile

---

|                |                              |
|----------------|------------------------------|
| profileHeatMap | <i>Profile heat map plot</i> |
|----------------|------------------------------|

---

**Description**

Plots a lake profile heatmap for a single site and parameter.

**Usage**

```
profileHeatMap(data, parameter, depth = "Depth_m", param_units,
  depth_units = "m", date = "ActivityStartDate", show_dates = TRUE,
  min_date = min(data[, date], na.rm = T), max_date = max(data[, date],
  na.rm = T), param_lab = "pH", criteria)
```

**Arguments**

|             |  |
|-------------|--|
| data        | Lake profile data (wide format)  |
| parameter   | Column name for parameter to be used as z-values.  |
| depth       | Column name for depth column.  |
| param_units | Character. Parameter units. Used to plot build label.  |
| depth_units | Character. Depth units. Used to plot build label.  |
| date        | Date column name. Must be in 'YYYY-mm-dd' format.  |
| show_dates  | Logical. If TRUE (default), show individual profile dates on plot x-axis.  |
| min_date    | Minimum plot date. 'YYYY-mm-dd' format.  |
| max_date    | Maximum plot date. 'YYYY-mm-dd' format.  |
| param_lab   | Character. Label to be used for parameter name. Used to build plot label.  |
| criteria    | Vector of criteria values to be used as contours on heatmap plot. If not specified, contours from 0-30 at increments of 5 are drawn. |

---

|             |  |
|-------------|--|
| profilePlot | <i>Plot an individual lake profile</i> |
|-------------|--|

---

**Description**

Plots an individual lake profile provided in long data format. If provided, dashed lines representing water quality criteria are also plotted. Default arguments are set to take data from the water quality portal, however, they may be updated as needed to reflect different data sources.

**Usage**

```
profilePlot(data, parameter = "CharacteristicName",
  units = "ResultMeasure.MeasureUnitCode",
  depth = "Depth, data-logger (ported)", do = "Dissolved oxygen (DO)",
  temp = "Temperature, water", pH = "pH",
  value_var = "ResultMeasureValue", line_no = "DataLoggerLine",
  do_crit, temp_crit, pH_crit)
```

**Arguments**

|           |  |
|-----------|--|
| data      | Lake profile data (long format)                          |
| parameter | Column name containing parameter names.                  |
| units     | Column name containing data units.                       |
| depth     | Name of depth variable in input data.                    |
| do        | Name of dissolved oxygen variable in input data.         |
| temp      | Name of temperature variable in input data.              |
| pH        | Name of pH variable in input data.                       |
| value_var | Column name of value variable.                           |
| line_no   | Column name containing line number.                      |
| do_crit   | Optional. Dissolved oxygen criterion to display on plot. |
| temp_crit | Optional. Temperature criterion to display on plot.      |
| pH_crit   | Optional. Vector of two pH criteria to display on plot.  |

## Examples

```
# Read in some profile data
nr=readWQP(type="narrowresult", siteid="UTAHDWQ_WQX-4938550", print=F)
act=readWQP(type="activity", siteid="UTAHDWQ_WQX-4938550", print=F)
nr_act=merge(nr, act, all.x=T)
profiles=nr_act[!is.na(nr_act$DataLoggerLine),] #Subset to profile data
table(droplevels(profiles$ActivityIdentifier)) #Find activity IDs associated w/ profiles
profilePlot(subset(profiles,ActivityIdentifier=="UTAHDWQ_WQX-BORFG051909-4938550-0519-Pr-F"))
profilePlot(subset(profiles,ActivityIdentifier=="UTAHDWQ_WQX-LC082807-210255-PR3855083007"), do_crit=4, tem
```

---

|           |                                      |
|-----------|--------------------------------------|
| readAWQMS | <i>Read AWQMS Water Quality Data</i> |
|-----------|--------------------------------------|

---

## Description

This function extracts water quality data from AWQMS based on user argument inputs. All arguments except type are optional, but at least one must be provided to limit download size and prevent errors connecting to AWQMS. Note that some, but not all, special characters have been accounted for (e.g. spaces, fore-slashes, and commas in characteristic names and site types).

## Usage

```
readAWQMS(type = "results", unnest_results = TRUE, ...)
```

## Arguments

|                |  |
|----------------|--|
| type           | Data type to read. One of "projects", "sites", "metrics", "results", "continuous_results", "indexes", or "beach_actions".  |
| unnest_results | If TRUE (default) and type=="results", the result data frame is unnested from the query return object.   |
| ...            | additional arguments to be passed to AWQMS query path. See <a dd="" format.<="" href="http://awqms.org/node/2-%3Cimg alt='AWQMS logo' data-bbox='328 598 345 612'/%3E AWQMS Tutorials - Web Services for optional arguments.&lt;/a&gt;&lt;/td&gt;&lt;/tr&gt; &lt;tr&gt; &lt;td&gt;start_date&lt;/td&gt;&lt;td&gt;Query start date in " mm="" td="" yyyy"=""></a> |
| end_date       | Query end date in "mm/dd/yyyy" format.   |

## Value

A data frame of AWQMS data

## Examples

```
# Read a couple of sites
sites=readAWQMS(type='sites', MonitoringLocationIdentifiersCsv=c("4900440","4900470"))
# Make a map of those sites & assign assessment units & uses
buildMap(sites=sites)
sites_aus=assignAUs(sites)
sites_aus_uses=assignUses(sites_aus)
sites_aus_uses

# Read all results from those sites (2016-2018)
results=readAWQMS(type='results', MonitoringLocationIdentifiersCsv=c("4900440","4900470"), start_date="01/0
```

```
# Read a subset of those results (just two parameters, 2016-2018)
results2=readAWQMS(type='results', MonitoringLocationIdentifiersCsv=c("4900440","4900470"), Characteristic=

# Read Utah DWQ projects
projects=readAWQMS(type="projects", OrganizationIdentifiersCsv="UTAHDWQ_WQX")
# Read state-wide TDS
ut_tds=readAWQMS(type='results', start_date="01/01/2016", end_date="12/31/2018", StateCode="UT", Characteris
```

readECHO\_ec

*Read effluent chart data from EPA ECHO webservice*

## Description

This function extracts effluent chart data from EPA ECHO for multiple stations & combinations of parameters. All arguments are optional except p.id. At least one p.id must be specified.

## Usage

```
readECHO_ec(..., print = TRUE,
  stringsAsFactors = default.stringsAsFactors())
```

## Arguments

|                  |   |
|------------------|---|
| ...              | additional arguments to be passed to ECHO query path. See <a href="https://echo.epa.gov/tools/webservices/effluent-charts#!/Effluent_Charts/get_eff_rest_services_download_effluent_chart">https://echo.epa.gov/tools/webservices/effluent-charts#!/Effluent_Charts/get_eff_rest_services_download_effluent_chart</a> optional arguments for effluent chart data reads. Note that arguments for output are ignored. |
| print            | Logical. If TRUE (default), print summary table of facilities & parameters returned.  |
| stringsAsFactors | Logical. Passed to read.csv. See ?read.csv for more information.  |
| p.id             | Permitted facility ID. Either a single text value (in quotes) or a vector of text values.   |
| parameter_code   | Parameter code. Either a single text value (in quotes) or a vector of text values.  |
| start_date       | Query start date in "mm/dd/yyyy" format.  |
| end_date         | Query end date in "mm/dd/yyyy" format.  |

## Value

A flat data frame of EPA ECHO effluent chart data

## Examples

```
#Extract effluent chart data for facility UT0025241, all outfalls
UT0025241_ec=readECHO_ec(p_id="UT0025241", start_date="01/01/2010", end_date="01/15/2019")
head(UT0025241_ec)

# Extract effluent total phosphorus data from outfall 001 for facility UT0025241
```

```

UT0025241_tp_001=readECHO_ec(p_id="UT0025241", parameter_code="00665", outfall="001")
UT0025241_tp_001_effluent=UT0025241_tp_001[UT0025241_tp_001$monitoring_location_desc=="Effluent Gross",]
head(UT0025241_tp_001_effluent)

# Extract flow through facility from UT0021717
UT0021717_flow=readECHO_ec(p_id="UT0021717", parameter_code="50050")

# Extract flow & TP from UT0025241 & UT0021717
tp_flow=readECHO_ec(p_id=c("UT0025241","UT0021717"), parameter_code=c("50050","00665"))

```

---

readECHO\_fac

*Read facility information from EPA ECHO webservice*


---

## Description

This function extracts facility information from EPA ECHO based on argument inputs.

## Usage

```
readECHO_fac(...)
```

## Arguments

... Additional arguments to be passed to ECHO query path. See [https://echo.epa.gov/tools/webservices/facility-search-water#!/Facility\\_Information/get\\_cwa\\_rest\\_services\\_get\\_facility\\_info](https://echo.epa.gov/tools/webservices/facility-search-water#!/Facility_Information/get_cwa_rest_services_get_facility_info) for optional arguments for facilities. Note that arguments for output are ignored.

## Value

A data frame of EPA ECHO facility information

## Examples

```

# Read facility locations in Utah
ut_fac=readECHO_fac(p_st="ut", p_act="y")
head(ut_fac)
# Read facility locations for two permit IDs
two_fac=readECHO_fac(p_pid=c("UT0021717","UT0025241"))
two_fac

```

---

readWQP

*Read EPA Water Quality Portal Data*


---

## Description

This function extracts water quality data from EPA's Water Quality Portal based on user argument inputs. Note that connections to the WQP occasionally time out during download. This function tries to download requested files up to 10 times before exiting. All arguments except `type` are optional, but at least one should be provided to limit download size and prevent errors connecting to WQP. Note that some, but not all, special characters in characteristic names have been accounted for. If in doubt, use the WQP web interface to determine the appropriate syntax for odd characteristic names. This function coerces non-numeric values in `ResultMeasureValue` column (for `result` & `narrowresult` type queries). This may generate NA values with a warning for special characters.

## Usage

```
readWQP(type = "result", ..., print = FALSE, coerce_num = FALSE,
        url_only = FALSE, auid = NULL, huc12 = NULL, huc8 = NULL,
        clip_geom = TRUE)
```

## Arguments

|                         |  |
|-------------------------|--|
| <code>type</code>       | Data type to read. One of "result", "narrowresult", "sites", "activity", or "detquantlim".   |
| <code>...</code>        | additional arguments to be passed to WQP query path. See <a href="https://www.waterqualitydata.us">https://www.waterqualitydata.us</a> for optional arguments.   |
| <code>print</code>      | Logical. Print summary table of sites & characteristics (only for <code>result</code> or <code>narrowresult</code> types).   |
| <code>coerce_num</code> | Logical. If TRUE the <code>ResultMeasureValue</code> column in <code>result</code> and <code>narrowresult</code> type reads is coerced to numeric values. This will generate NAs in the <code>ResultMeasureValue</code> column for non-numeric values. Defaults to FALSE.  |
| <code>url_only</code>   | Logical. If FALSE (default) read and return data. If TRUE, return just the query url.  |
| <code>auid</code>       | Optional. A vector of Utah DWQ assessment unit identifiers for which to query data. Note that <code>siteid</code> , <code>huc8</code> , and <code>huc12</code> arguments are ignored if <code>auid</code> is specified.  |
| <code>huc12</code>      | Optional. A vector of <code>huc12</code> digit codes for which to query data. Note that <code>siteid</code> & <code>huc8</code> arguments are ignored if <code>huc12</code> is specified.  |
| <code>huc8</code>       | Optional. A vector of <code>huc8</code> digit codes for which to query data. Note that the <code>siteid</code> argument is ignored if <code>huc8</code> is specified.  |
| <code>clip_geom</code>  | If <code>auid</code> , <code>huc12</code> , or <code>huc8</code> is specified, should data be subset to the polygon geometries? If TRUE (default) data are subset to polygon geometries. If FALSE, the bounding box of the selected polygons is used to query data (sites outside the polygons may be returned). Ignored if <code>auid</code> , <code>huc8</code> , and <code>huc12</code> are all NULL. |
| <code>start_date</code> | Query start date in "mm/dd/yyyy" format.   |
| <code>end_date</code>   | Query end date in "mm/dd/yyyy" format.   |

## Value

A data frame of WQP data

## Examples

```
# Read some data from Mantua Reservoir (2016-2018)
nr=readWQP(type="narrowresult", siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"),
  start_date="01/01/2016", end_date="12/31/2018")

# Read just Arsenic, Cadmium, and DO, all dates
nr=readWQP(type="narrowresult",
  siteid=c("UTAHDWQ_WQX-4900440", "UTAHDWQ_WQX-4900470"),
  characteristicName=c("Arsenic", "Cadmium", "Dissolved oxygen (DO)"))

# Read all Total dissolved solids statewide (2016-2018) (& note statecode for Utah)
tds_sw=readWQP(type="result",
  statecode="US:49",
  characteristicName="Total dissolved solids",
  start_date="01/01/2016", end_date="12/31/2018",
  print=F)

# Read data by assessment unit identifiers
utah_lake_nr=readWQP(type="narrowresult",
  auid=c('UT-L-16020201-004_01', 'UT-L-16020201-004_02'),
  start_date="01/01/2016", end_date="12/31/2018",
  siteType=c("Lake, Reservoir, Impoundment", "Stream"),
  print=F)
utah_lake_sites=readWQP(type="sites",
  auid=c('UT-L-16020201-004_01', 'UT-L-16020201-004_02'),
  siteType=c("Lake, Reservoir, Impoundment", "Stream"),
  print=F)
buildMap(sites=utah_lake_sites)

# Read sites by HUC 12
huc12_sites=readWQP(type="sites",
  huc12=c('160202010900'),
  siteType=c("Lake, Reservoir, Impoundment", "Stream"),
  print=F)
buildMap(sites=huc12_sites)

# Read DWQ's sites
sites=readWQP(type="sites", statecode="US:49", organization="UTAHDWQ_WQX", siteType=c("Lake, Reservoir, Impoundment", "Stream"),
  plot(LatitudeMeasure~LongitudeMeasure, sites[sites$LatitudeMeasure>0 & sites$LongitudeMeasure<0,])
```

---

readWQPbySite

*Read WQP data by selecting sites in an interactive map*


---

## Description

This function allows the user to read WQP data by selecting desired sites in an interactive map and specifying desired types of data and output. When map is launched, either click (mode="click") or draw polygons (mode="draw") around desired sites, then click "Done" button at bottom right of map. If edit==TRUE, an edit dialog will open in R console. Update "keep" column to anything other than "Y" to reject selected sites, then close dialog to proceed.



**Usage**

```
readWQPbySite(sites, map, mode = "click", types = c("sites",
  "narrowresult", "activity"), merge = T, edit = T,
  sitetypes = c("Canal Drainage", "Canal Irrigation", "Canal Transport",
  "Lake", "Lake, Reservoir, Impoundment", "Reservoir", "River/Stream",
  "River/Stream Intermittent", "River/Stream Perennial", "Seep", "Spring",
  "Stream", "Stream: Canal", "Stream: Ditch", "Wetland",
  "Wetland Undifferentiated"), ...)
```

**Arguments**

|                  |   |
|------------------|---|
| <b>sites</b>     | Optional. A sites object containing lat/long columns named "Latitude-Measure" & "LongitudeMeasure". If no sites object is provided, a Utah state-wide query of WQP will be generated for you.                                   |
| <b>map</b>       | Optional. A map object to use as a background for site selection. If no map object is provided, a basic map will be generated for you.  |
| <b>mode</b>      | Mode for map selection. One of "click" or "draw". Click allows site selection by clicking on individual sites. Draw allows site selection by polygons.  |
| <b>types</b>     | Vector of data types to read from WQP for selected sites. See ?wqTools::readWQP for options.  |
| <b>merge</b>     | Logical. If TRUE (default), merge all selected data types to single data frame. Merges are performed as left joins in order they are provided. If FALSE, return list of individual data objects.                                |
| <b>edit</b>      | Logical. If TRUE (default) open editor in R console to edit selected sites. To drop sites from the query, update the "keep" column to anything other than "Y", then close edit dialog.  |
| <b>sitetypes</b> | Vector of site types to be included in query (only used if sites argument is not provided).   |
| <b>...</b>       | Other arguments to be passed to readWQP (e.g. start_date, end_date, characteristicName, etc.). See ?wqTools::readWQP for more info. This is passed to both the sites query (if sites are not provided) and the results queries. |

**Examples**

```
wqp_data=readWQPbySite(start_date="01/01/2016", end_date="12/31/2018")
```

---

ss\_poly

*Utah's site-specific standard polygon shapes*


---

**Description**

Polygons containing site-specific standard designations and information.

**Usage**

```
ss_poly
```

**Format**

An sf type polygon shapefile

---

|            |                               |
|------------|-------------------------------|
| ul_trophic | <i>Utah Lake trophic data</i> |
|------------|-------------------------------|

---

**Description**

Utah Lake trophic data

**Usage**

data(ul\_trophic)

**Format**

A data.frame with 729 rows and 15 columns

---

|         |   |
|---------|---|
| ut_poly | <i>Utah state boundary, excluding tribal jurisdictions (unofficial)</i> |
|---------|---|

---

**Description**

Polygon showing unofficial boundaries of the State of Utah, excluding tribal jurisdictions. This is an unofficial representation used to screen sites for the integrated report only.

**Usage**

ut\_poly

**Format**

An sf type polygon shapefile

---

|          |  |
|----------|--|
| wmu_poly | <i>Utah DWQ watershed management unit polygons</i> |
|----------|--|

---

**Description**

Utah DWQ watershed management unit polygons.

**Usage**

wmu\_poly

**Format**

An sf type polygon shapefile

---

|       |  |
|-------|--|
| wqpDD | <i>Run the Water Quality Portal Data Dashboard Runs the Water Quality Portal Data Dashboard app embedded in UT WQ tools package.</i> |
|-------|--|

---

**Description**

Run the Water Quality Portal Data Dashboard Runs the Water Quality Portal Data Dashboard app embedded in UT WQ tools package.

**Usage**

wqpDD()

# Index

## \*Topic **datasets**

- au\_poly, [4](#)
- bu\_poly, [6](#)
- huc12\_poly, [9](#)
- huc8\_12\_poly, [9](#)
- huc8\_poly, [10](#)
- ss\_poly, [17](#)
- ul\_trophic, [17](#)
- ut\_poly, [18](#)
- wmu\_poly, [18](#)

- assignAUs, [2](#)
- assignHUCs, [3](#)
- assignUses, [3](#)
- au\_poly, [4](#)

- bu\_poly, [6](#)
- buildLDC, [4](#)
- buildMap, [5](#)

- calcTSI, [6](#)
- convertUnits, [7](#)

- downloadWQP, [8](#)

- facToNum, [9](#)

- huc12\_poly, [9](#)
- huc8\_12\_poly, [9](#)
- huc8\_poly, [10](#)

- profileHeatMap, [10](#)
- profilePlot, [11](#)

- readAWQMS, [12](#)
- readECHO\_ec, [13](#)
- readECHO\_fac, [14](#)
- readWQP, [14](#)
- readWQPbySite, [16](#)

- ss\_poly, [17](#)

- ul\_trophic, [17](#)
- ut\_poly, [18](#)

- wmu\_poly, [18](#)
- wqpDD, [18](#)