Sequence diagram — AI assistance (2/2): the public space finder

Visitor
Front end · React
SpaceFinderChat
Back end · NestJS
SpaceFinder Controller
«service» SpaceFinder Service
«service» OpenAiService
«repository» PrismaService
Data
PostgreSQL
External
«external» LLM provider (OpenAI-compatible)

1 "An office in Msheireb for 8 people, around 15,000 a month"
2 POST /public/space-finder (messages), no token
3 find(messages)

1. understand: the model reads the request

opt [API key configured]
4 chatJson(messages, "type, min_capacity, max_monthly_budget, area, keywords")
5 POST /chat/completions
6 JSON criteria
7 criteria, or null
8 keep known types and positive numbers only

2. search: a database query, no model

9 space.findMany(PUBLIC filter AND criteria)
10 SELECT spaces

opt [no match]
11 findMany again without budget and capacity, then also without the area
12 relaxed = true

3. reply: the model describes only the rows found

alt [matches, and API key configured]
13 chat(listings as data, "at most three sentences")
14 POST /chat/completions
15 text
16 reply (cut to 700 characters)

[no key, or the call fails]
17 "I found N available spaces"

4. answer

18 reply, criteria, matches, relaxed
19 201 Created
20 reply and listing cards (open on the map)

PUBLIC filter: is_published, status AVAILABLE, map coordinates set.
The model never selects data: an injected prompt can change what it says, never what it can read. Throttled: 12 requests/min.