

# Docker Notes

Your Name

Date:



# Contents

|          |                                                    |           |
|----------|----------------------------------------------------|-----------|
| <b>1</b> | <b>Notes info introduction</b>                     | <b>5</b>  |
| <b>2</b> | <b>Geting Started with Docker</b>                  | <b>7</b>  |
| 2.1      | Base CLI Command . . . . .                         | 7         |
| <b>3</b> | <b>Image Creation, Management and Registry</b>     | <b>9</b>  |
| <b>4</b> | <b>Networking</b>                                  | <b>11</b> |
| <b>5</b> | <b>Orchestration</b>                               | <b>13</b> |
| <b>6</b> | <b>Orchestration using Kubernetes</b>              | <b>15</b> |
| <b>7</b> | <b>Installation and Configuration of Docker EE</b> | <b>17</b> |
| <b>8</b> | <b>Security</b>                                    | <b>19</b> |
| <b>9</b> | <b>Storage and Volumes</b>                         | <b>21</b> |



# Chapter 1

## Notes info introduction

**Purpose of notes** These are a set of notes on Docker.



## Chapter 2

# Getting Started with Docker

## 2.1 Base CLI Command

### 2.1.1 Docker Image commands

```
docker image build
docker image history
docker image inspect
docker image pull
```

### 2.1.2 Docker Container Commands

```
docker container create
docker container exec
docker container logs
docker container run
```

Can use man pages via CLI. See `docker container --help` See `docker container create --help`

Consider old syntax vs new syntax

```
docker run <image>
docker ps
docker logs <ps>
#-----New syntax
docker container run
docker container ls
docker container logs <id>
```

`docker ps` is the same as `docker container ls`

## 2.2 Images vs Containers

A Docker image is a standalone, read-only package that includes everything needed to run a software application: the code, runtime, system tools, libraries and settings.

- App Runtime

- Libraries
- Config and Env Vars
- Dependencies

Docker containers are running instances of images. See docker hub for more

Can launch multiple containers from a Single Docker Image Can launch multiple containers from different docker Images

### 2.2.1 Attached vs Detached modes

In most cases you will be running containers in detached modes, however there some specific use cases where you might want to run it in attached mode as well.

When you use the docker container run `image:` without any extra flags, Docker starts the container in Attached Mode. In this mode, your terminal's local standard input, output and error streams are "attached" to the container.

Note: If you press Ctrl + C in the terminal, you send a SIGINT signal to the container's primary process, which usually stops the container entirely.

To run a container in the background, you use the `-d` or `--detach` flag. This detached mode is the standard for any long-running service, for example web server containers or database containers. Ideally, you would like it to be running all of the time so you would use it with detached mode.

```
docker container run nginx
docker container run --detach nginx
docker container run -d nginx
```

Generally in most cases, you will be using the detached mode in the production environments.

### 2.2.2 Basic Container Management Commands

When you have container running you can perform multiple operations on the container.

#### Managing the state of a container

```
docker container start <name>
docker container stop <name>
docker container restart <name>
```

#### Monitoring Performance

Example: A container can be consuming a certain level of memory and CPU

```
docker container stats <name>
```

This command can be useful in identifying which container is using the most CPU.

```
docker container inspect <name>
```

This command will get detailed information related to the container.



```
docker container rm <name>
docker container rm <name> --force
#--- use for exited containers
docker container ls -a
docker container rm <name1> <name2>
```

This will remove a container. If the container is running you can use force remove.

### 2.2.3 Basic Container Lifecycle

A docker container lives as long as its main process runs. If the process stops, the container stops. If the process is running the container will continue to run.

Short-lived containers - Use for scripts, batch jobs and one time commands.

Long Running Containers - Run a continuous process User for Web Servers, APIs, Database etc.

In production environments you will most likely use long-running containers.

### Default Container Command

In Docker, the default container command is the instruction that tells the container process which process to run immediately upon starting. You can override the default container command if required.

### 2.2.4 Docker Container exec

`docker exec` lets you run a command inside an already running container.

```
docker container exec nginx ls -l
```

### 2.2.5 docker container exec - important of -i and -t flags

For simple commands that just print the output, you don't need any flags. The command runs, prints its result to your terminal and exits. No interaction is needed.

In most cases however you would want to go inside the container, so you will require a shell. In such cases, you will require an additional set of flags that need to be added here.

If you want to connect inside a container using a shell like `bash`, `sh` (similar to SSH), the default approach will not work. `Bash` will close immediately. This is because it is an interactive shell that detects there is no input stream (STDIN) to read from. Without an active input stream or a terminal, it assumes its job is done and exists immediately.

### 2.2.6 The -i flag (interactive)

By default, Docker runs commands in non-interactive mode and does not keep the input stream (STDIN) open. using `-i` keeps STDIN attached to the container process, which is necessary for any interactive process.

```
docker container exec -i nginx bash
```

### 2.2.7 The -t Flag (TTY)

This will give you a full-fledged experience. Overview: the hyphen t flag allocates a pseudo terminal. If you just use the -t flag, the standard input get closed so that the keystrokes have no path to reach the process inside the container.

```
docker container exec -t nginx bash # This is very similar to SSH into a Linux server
```

Using the -it option, users can get a full interactive shell. You can type, navigate and explore.

```
docker container exec -it nginx bash
docker container exec -i -t nginx bash #Equivalent
exit # Return to the host system.
```

Using this command, you can run everything inside the container environment.

Note: Not every container comes with a shell, however the majority of them do. Note: Navigate Linux/OS file directory to see which binaries are available.

## 2.3 Basics of Ports

When data arrives at your computer or a server, the operating system needs to know which program should receive it. Ports help figure out which application should receive incoming data. An application can listen on a specific port number (port binding)

When incoming data comes, this data will also have the port number. The server will forward the data to the application with the matching port number. Ports are numbers from 0 to 65,535 and only one process can bind to a specific port on the same IP address at a time.

It is the responsibility of the incoming data to provide the port number so that the operating system can correctly map and send the data to the appropriate program over here.

```
netstat -ntlp # for linux. See what applications are bound to which ports.
```

## 2.4 Publishing Ports in Docker

When a container has been started, it is assigned a unique IP address within its configured Docker network. The application running inside the container may listen on a specific port.

Containers connected to the same network can communicate with each other using the container's IP address and the application's listening port.

Note: The internal Docker network IP addresses are not directly accessible from the host system (In Windows and Mac OS). On linux hosts, the Docker bridge network is directly reachable from the host via container IP.

```
curl 172.17.0.2:80 # This will work on Linux not on windows or mac OS
```

### 2.4.1 Ports Concept

When we talk about ports in Docker, we are always talking about two different locations.

- Host Port (outside) - The port you type into your browser (e.g. localhost:8080)
- Container Port (inside) - The port the actual application is configured to use (e.g. 80)

## 2.4.2 Connecting to Container Application

To allow a container to accept incoming connections from the host or the outside world, you must bind (map) it to a host port. Once this is done the users can send a request to the IP address of the server followed by the port number.

```
docker container run -d --name nginx -p 8080:80 nginx
curl 172.17.0.2:8080 # this should work after the above command
```

## 2.5 Docker Restart Policy

by default, Docker containers will not start when they exit or when the docker daemon is restarted. Sometimes the server restarts and we want all the containers to automatically be started again.

Docker provides restart policies to control whether your containers start automatically when they exit, or when Docker restarts.

### 2.5.1 Restart policies

You can specify the restart policy by using the `--restart` flag with the docker run command.

- `no` - The default. Docker will not restart the container under any circumstances
- `on-failure` - Restarts only if the container exits with a non-zero exit code
- `unless-stopped` - Always restarts except when you manually stop the container. If manually stopped, it won't restart even after a daemon restart.
- `always` - Always restarts regardless of exit code, including after a daemon restart — even if the container was manually stopped before the daemon went down.

In production environments we want the containers to start back up again should the server restart.

### 2.5.2 Choosing the right policy

| Policy                      | Restarts on crash? | Restarts on success exit? | Restarts after daemon restart |                           |
|-----------------------------|--------------------|---------------------------|-------------------------------|---------------------------|
| <code>no</code>             | No                 | No                        | No                            | Development               |
| <code>always</code>         | Yes                | Yes                       | Yes                           | Critical services         |
| <code>on-failure</code>     | yes                | no                        | Only if it was running        | Batch processing          |
| <code>unless-stopped</code> | Yes                | Yes                       | Only if no manually stopped   | Databases, message queues |

Table 2.1: Your table caption



## **Chapter 3**

# **Creation, Management and Registry**



## **Chapter 4**

# **Networking**





## **Chapter 5**

# **Orchestration**



## **Chapter 6**

# **Orchestration using Kubernetes**



## **Chapter 7**

# **Installation and Configuration of Docker EE**



# **Chapter 8**

## **Security**





## **Chapter 9**

# **Storage and Volumes**