

Pointers and Dynamic Memory Allocation

Constructors Clarifications

- Multiple constructors, only one is invoked

main()

```
#include "Animal.hpp"
```

```
int main()  
{
```

```
    Animal nameless; //calls default constructor
```

```
    Animal tiger("tiger"); //calls parameterized const. w/ default args
```

```
    Animal shark("shark", false, true); //calls parameterized constructor  
                                         //with all arguments
```

```
    //more code here . . .
```

```
}; //end main
```

```
class Animal  
{  
public:  
    Animal(); //default constructor  
    Animal(std::string name, bool domestic = false,  
           bool predator = false); //parameterized constructor  
    // more code here  
}; // end Animal
```

Constructors Clarifications

- Multiple constructors, only one is invoked
- Initialize ALL data members in parameterized constructor, not only those with arguments
- Explicitly call Base class constructor only if needs argument values or if there is no default to be called

Constructors Clarifications

- Multiple constructors, only one is invoked
- Initialize ALL data members in parameterized constructor, not only those with arguments
- Explicitly call Base class constructor only if needs argument values or if there is no default to be called

```

class Fish
{
public:
    Fish(); //default constructor

    Fish(std::string name, bool domestic = false,
          bool predator = false); //parameterized
    constructor

    // more code here

}; // end Fish

```

Fish.cpp

```
#include "Fish.hpp"
```

```
//default constructor
```

```
Fish::Fish(): venomous_(0){}
```

Base class (Animal)
constructor always called
first. It will initialize derived
data members.

```
//parameterized constructor
```

```
Fish::Fish(std::string name, bool domestic, bool predator):
    Animal(name, domestic, predator), venomous_(0){}
```

```
//more code here . . .
```

Base class parameterized
constructor needs access to
argument values and must be
called explicitly.

Pointer Variables

A typed variable whose value is the address of another variable of same type

```

int x = 5;
int y = 8;
int *p, *q = nullptr; //declares two int pointers

```

Make sure you do this if not assigning a value!

• • •

Program Stack

Type	Name	Address	Data
...
int	x	0x12345670	5
int	y	0x12345674	8
int pointer	p	0x12345678	nullptr
int pointer	q	0x1234567C	nullptr
...


```

int x = 5;
int y = 8;
int *p, *q = nullptr; //declares two int pointers

```

Make sure you do this if not assigning a value!

```

. . .
p = &x; // sets p to the address of x
q = &y; // sets q address of y

```

Program Stack

Type	Name	Address	Data
...
int	x	0x12345670	5
int	y	0x12345674	8
int pointer	p	0x12345678	0x12345670
int pointer	q	0x1234567C	0x12345674
...

```
int x = 5;
int y = 8;
int *p, *q = nullptr; //declares two int pointers
```

Make sure you do this if not assigning a value!

```
. . .
p = &x; // sets p to the address of x
q = &y; // sets q address of y
```

We won't do much of this

Program Stack

Type	Name	Address	Data
...
int	x	0x12345670	5
int	y	0x12345674	8
int pointer	p	0x12345678	0x12345670
int pointer	q	0x1234567C	0x12345674
...

Recall Dynamic Variables

What if I cannot statically allocate data? (e.g. will be reading from input at runtime)

Recall Dynamic Variables

What if I cannot statically allocate data? (e.g. will be reading from input at runtime)

Allocate dynamically with **new**

Dynamic Variables

Created at runtime in the memory **heap**
using operator **new**

Nameless typed variables accessed through pointers

```
// create a nameless variable of type dataType on the  
//application heap and stores its address in p  
dataType *p = new dataType;
```

Program Stack

Type	Name	Address	Data
...
dataType ptr	p	0x12345678	0x100436f20
...

Heap

Type	Address	Data
...
dataType	0x100436f20	
...

Accessing members

```
dataType some_object;  
dataType *p = new dataType;  
// initialize and do stuff with instantiated objects
```

• • •

```
string my_string = some_object.getName();  
string another_string = p->getName();
```

To access member functions
in place of . operator

Deallocating Memory

```
delete p;  
p = nullptr;
```


Deletes **the object**
pointed to by p

Must do this!!!


Avoid Memory Leaks (1)

Occurs when object is created in free store but program no longer has access to it

```
dataType *my_ptr = new dataType;  
dataType *your_ptr = new dataType;  
// do stuff with my_ptr and your_ptr
```




```
your_ptr = my_ptr;
```



Avoid Memory Leaks (2)

Occurs when object is created in free store but program no longer has access to it

```
void leakyFunction(){
  dataType *my_ptr = new dataType;
  dataType *your_ptr = new dataType;
  // do stuff with my_ptr and your_ptr
}
```




Avoid Memory Leaks (2)

Occurs when object is created in free store but program no longer has access to it


```
void leakyFunctionFixed(){  
    dataType *my_ptr = new dataType;  
    dataType *your_ptr = new dataType;  
    // do stuff with my_ptr and your_ptr  
    delete my_ptr;  
    my_ptr = nullptr;  
    delete your_ptr;  
    your_ptr = nullptr;  
}
```

Left scope of local
pointer variables
but deleted dynamic
objects first




Avoid Dangling Pointers

Pointer variable that no longer references a valid object




```
delete my_ptr;
```



Fix

```
delete my_ptr;  
my_ptr = nullptr;
```


Must do this!!!



Avoid Dangling Pointers

Pointer variable that no longer references a valid object


```
delete my_ptr;  
my_ptr = nullptr;
```



Avoid Dangling Pointers

Pointer variable that no longer references a valid object

```
delete my_ptr;  
my_ptr = nullptr;
```




```
delete your_ptr; // ERROR!!!! No object to delete
```

Avoid Dangling Pointers


Pointer variable that no longer references a valid object

```
delete my_ptr;  
my_ptr = nullptr;
```



Fix

```
delete my_ptr;  
my_ptr = nullptr;  
your_ptr = nullptr;
```



Must set all pointers to nullptr!!!

What is wrong with the following code?

```
void someFunction()  
{  
    int* p = new int[5];  
    int* q = new int[10];  
  
    p[2] = 9;  
    q[2] = p[2]+5;  
    p[0] = 8;  
    q[7] = 15;  
  
    std::cout<< p[2] << " " << q[2] << std::endl;  
    q = p;  
    std::cout<< p[0] << " " << q[7] << std::endl;  
}
```

What is wrong with the following code?

```
void someFunction()  
{  
    int* p = new int[5];  
    int* q = new int[10];
```

```
    p[2] = 9;  
    q[2] = p[2]+5;  
    p[0] = 8;  
    q[7] = 15;
```

MEMORY LEAK:
int[10] lost on heap

SEGMENTATION FAULT
int[5] index out of range

```
    std::cout<< p[2] << " " << q[2] << std::endl;  
    q = p;  
    std::cout<< p[0] << " " << q[7] << std::endl;
```

```
}
```

MEMORY LEAK:
Did not delete int[5]
before exiting function

Next let's try a different
implementation for Bag