neo4j / **neo4j**

Watch 238   Star 1,885   Fork 730

DocumentingTestBase now uses all planners

Merged **pontusmelke** merged 2 commits into `neo4j:2.3` from `Mats-SX:2.3-doctest-all-planners` Apr 23, 2015

Conversation 10	Commits 2	Files changed 23	+220 −202

Mats-SX commented Apr 21, 2015   Collaborator

No description provided.

Mats-SX added `docs` `2.3` `cypher` labels Apr 21, 2015

davidegrohmann commented on an outdated diff Apr 21, 2015   Show outdated diff

davidegrohmann commented on an outdated diff Apr 22, 2015   Show outdated diff

davidegrohmann commented on the diff Apr 22, 2015

...c/test/scala/org/neo4j/cypher/docgen/DeleteTest.scala   View full changes

```
                  ((6 lines not shown))
38   38             AsciiDocSimpleStyle.withAutomaticRelationshipTypeColors()
39   39
40   40       def section = "Delete"
41   41
42   42       @Test def delete_single_node() {
     43  +       val createLabeledNode = (db: GraphDatabaseAPI) => db.inTx {
     44  +         db.createNode(DynamicLabel.label("Useless"))
     45  +       } : Unit
```

davidegrohmann added a note Apr 22, 2015   Collaborator

What is `: Unit` here used for?

Mats-SX added a note Apr 22, 2015   Collaborator

It specifies the return value of the anonymous function. Without it, the return value is inferred to be `Node` (because that's what db.createNode() returns). I thought it was more clean than to write `val createLabeledNode: (GraphDatabaseAPI) => Unit = (db: GraphDatabaseAPI) => db.inTx { db.createNode(DynamicLabel.label("Useless")) }`

Add a line note

davidegrohmann commented on the diff Apr 22, 2015

...ala/org/neo4j/cypher/docgen/DocumentingTestBase.scala   View full changes

Labels

`2.3`
`cypher`
`docs`

Milestone

No milestone

Assignee

No one assigned

3 participants

```
            ((38 lines not shown))
300  304
301        -      } catch {
302        -        case e: CypherException if expectedException.nonEmpty =>
     305   +  private def executeWithAllPlannersAndAssert(query: String, assertions: In
     306   +                                             expectedException: Option[Cla
     307   +                                             expectedCaught: CypherExcepti
     308   +                                             prepareFunction: => Unit) = {
     309   +    val params = Option(parameters).getOrElse(Map.empty)
     310   +
     311   +    // COST planner is default. Can't specify it without getting exception
     312   +    val planners = Seq("", "CYPHER PLANNER=rule ")
```

davidegrohmann added a note Apr 22, 2015   `Collaborator`

IDP?

Mats-SX added a note Apr 22, 2015   `Collaborator`

Hm, didn't consider using both DP/IDP. Which one is default if nothing is specified by the query?

davidegrohmann added a note Apr 23, 2015   `Collaborator`

Nevermind, we run only COST and RULE in other tests as well. This is fine.

Add a line note

Mats-SX added some commits Apr 21, 2015

- RewindableExecutionResult no longer loses information about used plan… ⋯   `d3bcb93`
- DocumentingTestBase now uses both cost and rule planners. ⋯   `da6acca`

pontusmelke merged commit **6a9d568** into `neo4j:2.3` Apr 23, 2015   **View details**
1 check passed

Mats-SX deleted the `Mats-SX:2.3-doctest-all-planners` branch Apr 24, 2015

Sign up for free **to join this conversation on GitHub**. Already have an account? **Sign in to comment**