Ten. Million. Questions. Let's celebrate all we've done together.

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free.

Take the 2-minute tour

In Neo4j, is there a way to read relationship name dynamically using loadcsv?



..

1

I have created nodes using LOAD CSV method using Cypher. The next part is creating relationships with the nodes. For that I have CSV in the following format

fromStopName, from, route, toStopName, to
Swargate, 1, route1_1, Swargate Corner, 2
Swargate Corner, 2, route1_1, Hirabaug, 3
Hirabaug, 3, route1_1, Maruti, 4
Maruti, 4, route1_1, Mandai, 5

Now I would like to have "route" name as relationship between nodes. So, I am using the following LOAD CSV command in CYPHER

USING PERIODIC COMMIT
LOAD CSV WITH HEADERS FROM "file:C:\\\busroutes.csv" AS row
MATCH(f {name:row.fromStopName}),(t {name:row.toStopName}) CREATE f - [:row.route]->

But looks like, I cannot do that. Instead, if I name relationship statically and then assign property from csv route field, it works.

USING PERIODIC COMMIT
LOAD CSV WITH HEADERS FROM "file:C:\\\busroutes.csv" AS row
MATCH(f {name:row.fromStopName}),(t {name:row.toStopName}) CREATE f - [:CONNECTS {ro

I am wondering if this is disabled to enforce good practice of having "pure" verb kind of relationships and avoiding creating multiplicity of same relationship. like "connected by 1_1" "connected by 1_2".

Or I am just not finding the right link or not using correct syntax. Appreciate help!

neo4j cypher

share improve this question

edited Mar 29 at 8:09

Michael Hunger

25.2k • 2 • 21 • 41

asked Mar 29 at 7:18

Kognizant
394 • 1 • 11

active

oldest

votes

add a comment

1 Answer

Right now you can't as this is structural information.



Either use neo4j-import tool for that.Or use one CSV file per type and spell out the rel-type.



Or even filter the CSV and do multi-pass:



e.g.

USING PERIODIC COMMIT
LOAD CSV WITH HEADERS FROM "file:C:\\\busroutes.csv" AS row
with row where row.route = "route1_1"
MATCH(f {name:row.fromStopName}),(t {name:row.toStopName})
CREATE (f)-[:route1_1]->(t)

There is also a trick using fake conditionals but you still have to spell them out.

active 4 months ago

viewed 35 times

asked 4 months ago

Blog

Why Stack Overflow is a Good Workplace for Women

Related

- Neo4j: Conditions on Relationships with Depth
- 1 Neo4j: query for all paths with specified relationships
- 1 neo4j LOAD CSV with Tabs
- How to create unique nodes and relationships by csv file imported in neo4j?
- Neo4J Grandchild Relationships Linked to Nodes
- o neo4j Cypher Create relationship using proprieties
- Programmatically creating relationships between words in Neo4j using Cypher
- 1 Loading relationships from CSV data into neo4j db
- How can I optimise a Neo4j MERGE query on a node with many relationships?
- 1 Neo4j-Cypher create conditional relationship

Hot Network Questions

- Carrying a handgun in other countries with a US concealed carry permit
- Can a Glaive be stowed in a Ruby Scabbard?
- Lunch with the CEO
- Why are carpenter's pencils flat?
- If static methods can't be overriden, how its working here (For Java)?
- What is aliasing and what causes it?
- ∆ Two definitions of Green's function
- Is Let us = Let's?
- Scraping High-Res image tiles from the MoMA website



add a comment

Your Answer



Post as a guest

Name	
Email	
required, but never shown	

Sign up or log in

Sign up using Google

Sign up using Facebook

Sign up using Stack Exchange

Post Your Answer

By posting your answer, you agree to the privacy policy and terms of service.

Not the answer you're looking for? Browse other questions tagged neo4j cypher or ask your own question.

a question feed

tour help blog chat data legal privacy policy work here advertising info mobile contact us feedback CULTURE / **TECHNOLOGY** LIFE / ARTS SCIENCE OTHER RECREATION Stack Overflow Programmers Database Administrators Photography English Language & Stack Apps Usage Server Fault Cross Validated (stats) Meta Stack Exchange Super User Ask Different (Apple) SharePoint Stack Overflow Careers Web Applications WordPress Movies & TV User Experience Development Travel **Physics** Ask Ubuntu Geographic Information Mathematica Salesforce Arqade (gaming) Game Development Electrical Engineering ExpressionEngine® Bicvcles Biology Personal Finance & Role-playing Games more (5) more (13) more (21) Academia more (9)

Name for a device purposefully put together from faulty parts

Using siunitx, \ohm results in an italic Omega

Prove the theorem on analytic geometry in the picture.

Legacy application unreachable code

Suggested alternatives for that horrible new noun 'nice-to-have'?

What's the philosophy behind delaying writing data to disk

I added more water to my ciabatta dough by accident

Was クリスマスケーキ used metaphorically about women?

Why do we still use keys to start cars? why not passwords?

Remove a language from the "Preferred language order"

more hot questions