


```
((21 lines not shown))
          M
                    +import java.util.NoSuchElementException
                   +import org.mockito.Mockito._
                   +import org.mockito.invocation.InvocationOnMock
                   +import org.mockito.stubbing.Answer
                   +import org.neo4j.cypher.internal.commons.CypherFunSuite
               28
                   +import org.neo4j.cypher.internal.compiler.v2_3.PlannerName
               29
                   +import org.neo4j.cypher.internal.compiler.v2_3.executionplan.InternalExecut
               30
                    +import org.neo4j.graphdb.Result.{ResultRow, ResultVisitor}
                    +import org.neo4j.graphdb.{Node, Relationship, ResourceIterator}
                   +import org.neo4j.kernel.impl.query.{QueryExecutionMonitor, QuerySession}
                   +import scala.collection.mutable.ListBuffer
                    +/**
       pontusmelke added a note Mar 27, 2015
                                                                                    Collaborator
       we usually remove these generated comments
      Add a line note
pontusmelke commented on the diff Mar 27, 2015
      ...ty/kernel/src/main/java/org/neo4j/graphdb/Result.java
                                                                                 View full changes
          M
                   ((8 lines not shown))
              195 +
                        st This is an alternative to using the iterator form of Result. Using
                          st creation perspective.
              196
                        * @param visitor the ResultVisitor instance that will see the results
              198 +
              199 +
              200
                        void accept( ResultVisitor visitor );
              201 +
              202 +
              203
                         * Describes a row of a result. The contents of this object is only sta
                         * {@linkplain ResultVisitor#visit(ResultRow) visit} call. The data it
              205
                         * {@linkplain ResultVisitor#visit(ResultRow) the visit method}. Instar
              206 +
                         st for later, or shared with other threads, rather the content should k
              207
                       interface ResultRow
              209 +
                             // TODO: Figure out type coercion around primitives
              210
       pontusmelke added a note Mar 27, 2015
                                                                                    Collaborator
       Are we figuring this out now or later?
      Add a line note
pontusmelke commented on the diff Mar 30, 2015
      \verb|.../scala/org/neo4j/cypher/ExtendedExecutionResult.scala|\\
                                                                                 View full changes
          M
                  ((7 lines not shown))
               24
        24
                    trait ExtendedExecutionResult extends ExecutionResult {
               26
                     def planDescriptionRequested: Boolean
        26
                     def executionType: QueryExecutionType
                      def notifications: Iterable[Notification]
               28
               29 +
                   + def accept(visitor: ResultVisitor): Unit = {
               30
       pontusmelke added a note Mar 30, 2015
                                                                                    Collaborator
       I think that this should be pushed even further down. Having this implementation in
```

PipeExecutionResult and ExplainExecutionResult instead.



Inc.

Terms Privacy Security Contact

W

Status API Training Shop Blog About Help