

Questions

Tags

Users

Badges

Inaneworod

Ask Question

Ten. Million. Questions. Let's celebrate all we've done together.

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free.

Take the 2-minute tour

asked 4 months ago

spring data neo4j Failed to mark transaction as rollback only



Blog

Why Stack Overflow is a Good Workplace for Women

Related

- Spring Data Neo4j -@RelationshipType issues
- indexing a collection spring data neo4i
- Spring Data Neo4j
 Transaction does not work
 with Neo4j server
- neo4j 2.0.0 with spring data neo4j
- 2 Neo4j and spring-dataneo4j - importing large datasets
- Neo4j database not persisting using Spring Data Neo4j
- 1 Change property data type in Neo4j using spring-dataneo4i
- Failed to mark transaction as rollback only in Spring Data Neo4j
- 1 Intermittent EntityNotFoundException with Spring Data Neo4j
- O Spring Data Neo4j neo4jTemplate.fetch() only returns one value

Hot Network Questions

- As a professional photographer, how can one handle a wedding photographer being rude or demanding in a way that will compromise overall image quality?
- Make subscript size smaller (always)
- What is a device purposefully put together from faulty parts
- The Programming Language Quiz
- Need to convert date format in apex
- Aerofoil that gives reasonably good lift for both flow directions: forward and backward
- Did a Kamikaze ever impact the hull of a ship, as opposed to the deck?

Work on work you love. From home.





i use repository to query, but i throw exception, i use spring-data-neo4j-3.2.2

org.neo4j.graphdb.TransactionFailureException: Failed to mark transaction as rollb at org.neo4i.kernel.TopLevelTransaction.failure(TopLevelTransaction.iava:86) ~[neo $\verb|at org.neo4j.cypher.internal.spi.v2_1. Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.close)| | Transaction Bound Query Context.close (Transaction Bound Query Context.$ at org.neo4j.cypher.internal.compiler.v2_1.spi.DelegatingQueryContext.close(Delega at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext.or at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext\$\$a at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext\$\$a at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext\$\$ at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext.or at org.neo4j.cypher.internal.compiler.v2_1.spi.ExceptionTranslatingQueryContext.cl at org.neo4j.cypher.internal.compiler.v2_1.spi.DelegatingQueryContext.close(Delega at org.neo4j.cypher.internal.compiler.v2_1.executionplan.ExecutionWorkflowBuilder\$ at org.neo4j.cypher.internal.compiler.v2_1.executionplan.ExecutionWorkflowBuilder\$ at org.neo4j.cypher.internal.compiler.v2_1.TaskCloser\$\$anonfun\$1.apply(TaskCloser. at org.neo4j.cypher.internal.compiler.v2_1.TaskCloser\$\$anonfun\$1.apply(TaskCloser. at scala.collection.TraversableLike\$\$anonfun\$flatMap\$1.apply(TraversableLike.scala at scala.collection.TraversableLike\$\$anonfun\$flatMap\$1.apply(TraversableLike.scala at scala.collection.immutable.List.foreach(List.scala:318) ~[scala-library-2.10.4. at scala.collection.TraversableLike\$class.flatMap(TraversableLike.scala:251) ~[sca at scala.collection.AbstractTraversable.flatMap(Traversable.scala:105) ~[scala-lib at org.neo4j.cypher.internal.compiler.v2_1.TaskCloser.close(TaskCloser.scala:40) ^ at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator\$\$anonfun\$close\$1.apply\$ at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator\$\$anonfun\$close\$1.apply(at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator\$\$anonfun\$close\$1.apply($at org.neo4j.cypher.internal.compiler.v2_1. Closing Iterator \$\$ an onfun\$ translate Exception for the state of the state$ at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.decoratedCypherExceptio at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.translateException(Clos at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.close(ClosingIterator.s at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator\$\$anonfun\$failIfThrows\$1 at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.decoratedCypherExceptio

```
at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.failIfThrows(ClosingIte at org.neo4j.cypher.internal.compiler.v2_1.ClosingIterator.hasNext(ClosingIterator at org.neo4j.cypher.internal.compiler.v2_1.PipeExecutionResult.hasNext(PipeExecuti at scala.collection.Iterator$$anon$11.hasNext(Iterator.scala:327) ~[scala-library-at scala.collection.convert.Wrappers$IteratorWrapper.hasNext(Wrappers.scala:29) ~[at org.neo4j.cypher.internal.compiler.v2_1.PipeExecutionResult$$anon$1.hasNext(Pip at org.neo4j.helpers.collection.IteratorWrapper.hasNext(IteratorWrapper.java:42) ~
```

my repository

} my controller

```
@RequestMapping(value = "/movies", method = RequestMethod.GET, headers = "Accept=te
public String findMovies(Model model, @RequestParam("q") String query) {
    if (query != null && !query.isEmpty()) {
        //Page<Movie> movies = movieRepository.findByTitleLike(query, new PageRe
        Iterable<Movie> movies = movieRepository.findByTitleLike(query);
        log.debug("==== query result ======" + movies);
        model.addAttribute("movies", IteratorUtil.asCollection(movies));
    } else {
        model.addAttribute("movies", Collections.emptyList());
    }
    model.addAttribute("query", query);
    //addUser(model);
    return "/movies/list";
}
```

my movie entity

```
@NodeEntity
public class Movie {
  @GraphId
Long nodeId;

@Indexed(indexType = IndexType.FULLTEXT, indexName = "id")
String id;

@Indexed(indexType = IndexType.FULLTEXT, indexName = "search")
String title;
```

where is wrong?would i need service to calling repository, it ry and use @Transactional, but it does not work well too.thank for help , if you have some idea, please tell me!

```
09:49:36.895 [http-nio-8080-exec-2] DEBUG o.s.web.servlet.DispatcherServlet - 09:49:36.901 [http-nio-8080-exec-2] DEBUG o.s.w.s.m.a.DefaultAnnotationHandlerMappin 09:49:36.904 [http-nio-8080-exec-2] DEBUG o.s.web.servlet.DispatcherServlet - Last-M 09:49:36.927 [http-nio-8080-exec-2] DEBUG o.s.w.b.a.s.HandlerMethodInvoker - Invokin 09:49:36.938 [http-nio-8080-exec-2] DEBUG o.s.t.jta.JtaTransactionManager - Creating 09:49:36.942 [http-nio-8080-exec-2] DEBUG o.s.d.n.s.q.CypherQueryEngineImpl - Execut 09:49:37.006 [http-nio-8080-exec-2] DEBUG o.s.t.jta.JtaTransactionManager - Initiati 09:49:37.007 [http-nio-8080-exec-2] DEBUG o.s.w.s.m.a.AnnotationMethodHandlerExcepti 09:49:37.039 [http-nio-8080-exec-2] DEBUG o.s.w.s.m.a.ResponseStatusExceptionResolve 09:49:37.039 [http-nio-8080-exec-2] DEBUG o.s.w.s.m.s.DefaultHandlerExceptionResolve 09:49:37.047 [http-nio-8080-exec-2] DEBUG o.s.web.servlet.DispatcherServlet - Could
```

this is my log when i calling movies?q=sky,(i have three movies sky,sky1,sky2,i want to search sky it shows all three),i add a log.debug after calling cypher i found when excute cypher,it retunrn org.springframework.data.neo4j.conversion.QueryResultBuilder@10c2631,is it problem here?

neo4j spring-data-neo4j

share improve this question edited Apr 8 at 2:03

asked Apr 7 at 6:15
yang
45 • 8

- Does developing on ARM Processors from different vendors differ much?
- What are the advantages and disadvantages of an oblique wing over a swing wing
- Has any Star Trek character appeared in all three division uniform colors?
- How does java.util.EnumSet<E>
- Can a Glaive be stowed in a Ruby Scabbard?
- Preventing a Print expression from generating a new cell each time it executed
- Compact way of writing (a + b == c or a + c == b or b + c == a)
- Important formulas in Combinatorics
- Approximation of Borel sets by a countable collection of majorants
- Could a communication satellite that fails to reach GEO be repurposed?
- How to deal with people looking at their mobile phone during my presentation?
- Why are my tomatoes cracking and what can I do?
- Where did the nickname of 'Bones' for McCoy come from?
- What does OWA stand for?
- How do I remove Candy Crush Saga from Windows 10?
- My 4.5 yrs old son has no dominant hand
- Using Emergency Fund to Sell Upside-down Car

Have you tried wrapping the request in a transaction, it'll be required for reading the movies? Also I think that you will have to build the regex and pass it in to the repository method (rather than build it on the fly) so the query becomes WHERE movie.title =~ {0} and the argument is "(?i).*" + query + ".*" . – JohnMark13 Apr 7 at 12:02 *

Ewww....OP may or may not be doing something wrong here, but if you can make an internal kernel class throw a NullPointerException, you're probably also dealing with a bug in neo4j, right? – FrobberOfBits Apr 7 at 15:09

can you provide the omitted frames from the stacktrace? – Michael Hunger Apr 7 at 21:34

thanks for answering my question,@JohnMark13@FrobberOfBits @ Michael Hunger,i am new learner of neo4j,this is my first example.i had add some log info ,i think something may wrong when running cypher,but what shoud i do? – yang Apr 8 at 2:09


i think i have solve my problem.i change Iterable<Movie> to List<Movie>,it works well,but i dont konw why.By the way,my cypher have a little problem,when i search sky2,it return all(sky,sky1,sky2),it is not my need^~^ – yang Apr 8 at 3:53

Know someone who can answer? Share a link to this question via email, Google+, Twitter, or Facebook.

Your Answer



Sign up or log in



Post as a guest


Email required, but never shown	Name			
required, but never shown	Email			
	required, but ne	ever show	n	

Post Your Answer

By posting your answer, you agree to the privacy policy and terms of service.

Browse other questions tagged <code>neo4j</code> <code>spring-data-neo4j</code> or ask your own question.

a question feed



Web Applications Ask Ubuntu Webmasters Game Development TeX - LaTeX	WordPress Development Geographic Information Systems Electrical Engineering Android Enthusiasts Information Security	User Experience Mathematica Salesforce ExpressionEngine® Answers more (13)	Movies & TV Seasoned Advice (cooking) Home Improvement Personal Finance & Money Academia more (9)	Travel Christianity Arqade (gaming) Bicycles Role-playing Games more (21)	Physics MathOverflow Chemistry Biology more (5)	Stack Overflow Careers
---	--	--	---	---	---	------------------------

site design / logo © 2015 Stack Exchange Inc; user contributions licensed under cc by-sa 3.0 with attribution required