Tags

Users

Badges

l Inanswered


Ask Question

Ten. Million. Questions. Let's celebrate all we've done together.

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free.

Take the 2-minute tour

# Neo4j - How to build proper multi-dimensional query for my graph





I have a simple social-networking like graph w/ users, friends, comments, likes etc. Users can "own" items, comment on "items", like "items". I am trying to write a cypher query that returns "items" along w/ extra information to display them in my stream.



I have tried using **optional match** and **collect** and stuff, but there is always some part of the result that doesn't work.

### Specifically, for a given user(say user1), I want to return "items" that:

- 1. a specific user + his friends own
- 2. show number of likes,
- 3. also show number of comments.
- 4. Know if the item is already owned by me (so I can hide "own" button in the UI)
- 5. If the item is owned by friends, I want to show name, image of up to 2 friends (but not more than 2 friends if, say, 5 friends own that item)

You can copy-paste below to get the graph

```
// 3 users
CREATE (u1:USER{name:"USER1", image: "image1"})
CREATE (u2:USER{name:"USER2", image: "image2"})
CREATE (u3:USER{name:"USER3", image: "image3"})
//3 items
CREATE (i1:ITEM{name:"ITEM1"})
CREATE (i2:ITEM{name:"ITEM2"})
CREATE (i3:ITEM{name:"ITEM3"})
// OWNERSHIP ..
//user1 owns 2 items
CREATE (u1)-[:OWNS]->(i1)
CREATE (u1)-[:OWNS]->(i2)
// user2 owns i2 and i3
CREATE (u2)-[:0WNS]->(i2)
CREATE (u2)-[:0WNS]->(i3)
// user3 also owns i2 and i3 (so i2 is owned by u1, u2 and u3; and i3 is owned by
CREATE (u3)-[:0WNS]->(i2)
CREATE (u3)-[:0WNS]->(i3)
// FRIENDSHIP..
// user1 is friend of both user2 and user3
CREATE (u1)-[:FRIEND_OF]->(u2)
```

asked 4 months ago

viewed 59 times

active 4 months ago

Blog

Why Stack Overflow is a Good Workplace for Women

### Related

- Describing a Cypher Query for multi-level relationship in Neo4j?
- O Cypher Query to get connected nodes from two relations
- Detecting cycles in neo4j property graph using cypher
- node degree query on Neo4j with huge graph ( million nodes and links)
- neo4j cypher : how to query a linked list
- Neo4j Cypher query for finding neighbourhood graph
- Neo4j time dependent graph model
- Construct NEO4J Cypher Graph Query to show intermediate nodes in path
- Neo4j slow cypher query big graph with hierarchies
- 1 Querying the Neo4j

# Hot Network Questions

- Proving that all integers are even or odd
- Would allowing shorter passwords sometimes be more secure?
- Dullness vs. going overboard: Should I be calling people 'enfants terribles' in an academic paper?
- My 4.5 yrs old son has no dominant hand
- Is there a single-word antoym for "Opportunity"?
- When does the designer pay for a reprint
- Did Arnold Rimmer kill the Red Dwarf crew?
- Should you always minimize cognitive load

```
CREATE (u1)-[:FRIEND_OF]->(u3)

// COMMENTS ..

//user1 has commented on all those items he owns
CREATE (u1i1:COMMENT{text:"user1 comment on item1"})

graph neo4j cypher

share improve this question

asked Apr 1 at 2:26

Raja Rao
1,124 * 9 * 16
```

add a comment

#### 2 Answers

Let's build your query up step by step:



Specifically, for a given user(say user1), I want to return "items" that: a specific user + his friends own



MATCH (u:USER {name: "USER1"})-[:FRIEND\_OF\*0..1]-(friend:USER)-[:OWNS]-(i:ITEM)
WITH u,i,
 // Know if the item is already owned by me (so I can hide "own" button in the U
 sum(size((u)-[:OWNS]->(i))) > 0 as user\_owns,
 // If the item is owned by friends, I want to show name, image of up to 2 frien
 collect({name:friend.name, image:friend.image})[0..2] as friends

RETURN u,i, user\_owns, friends
// show number of likes,
 sum(size(()-[:LIKED]->(i))) as like,
// also show number of comments,
 sum(size(()-[:COMMENT\_FOR]->(i))) as comments

Actually because it is such a good question, I sat down and created a GraphGist documenting each step here.

share improve this answer

answered Apr 1 at 10:49

Michael Hunger
25.2k • 2 • 21 • 41

Thanks Michael! That GraphGist is really cool and very helpful! I wasn't even aware of it. Learning a lot b/w your's and stephan's answers. – Raja Rao Apr 1 at 15:20

add a comment

# LightningChart The FASTEST Rendering Charts for WPF and WinForms True DirectX Acceleration in 2D and 3D



Fairly easy. First you need to have a variable path length match from 0..1 on FRIEND\_0F returning either yourself. Follow to all items being owned by those.

3

Use OPTIONAL MATCH for likes and comments since there might or might not exist any.

Since there are potentially multiple paths to a single item, you need to count the distinct likes and comments.

To check if you already own the item, check the endpoint of the variable path match from above if its name is yours.

For getting up to two images of the friends owning the item filter the list for your friends and return the image property. Last step is to slice the collection for the first two elements using subscript operator.

```
MATCH (:USER { name:'USER1' })-[:FRIEND_0F*0..1]->(me_or_friend)-[:0WNS]->(item)

OPTIONAL MATCH (item)<-[:LIKED]-()

OPTIONAL MATCH (item)<-[c:COMMENT_FOR]-()

WITH item, count(distinct l) AS likes, count(distinct c) AS comments,

collect(DISTINCT me_or_friend) AS me_or_friends

RETURN item, likes, comments,
```

- Remove a language from the "Preferred language order"
- The Hiding Rules Contradict
  Themselves. What Can I Make Of
  This?
- How to use Piano pedals without using the foot?
- How do I know when my sauce is reduced enough?
- Manager sounds upset every time I inform him of a (minor) obstacle
- How do I remove Candy Crush Saga from Windows 10?
- What are the advantages and disadvantages of an oblique wing over a swing wing
- Why do tenured professors still publish in pay-walled venues?
- & Antonym of Overlap?

votes

active

oldest

- Password strength of random words and brainflaver
- Can you open source firmware to closed hardware?
- Prove the theorem on analytic geometry in the picture.
- Em `cond` with less redundancy
- Suggested alternatives for that horrible new noun 'nice-to-have'?
- → Why moving fan seems transparent?
- What is aliasing and what causes it?

### **Final comment:**

On SO we appreciate if you show in your question what you've already tried yourself to solve the problem. Question like "solve that problem for me" are not that much welcome.

share improve this answer

edited Apr 1 at 8:18

answered Apr 1 at 8:07

Stefan Armbruster

23.1k • 2 • 28 • 51

Thanks @stefan for this. Sorry, I forgot to add the query I was using. The 1st 3 lines were the same as yours but I wasn't using "with" and also didnt know abt the subscript at all... so impossible to solve –

Raja Rao


Apr 1 at 15:15 

add a comment

### Your Answer



## Sign up or log in



## Post as a guest


| Name                      |   |
|---------------------------|---|
|                           | ] |
| Email                     |   |
| required, but never shown | ] |

Post Your Answer

By posting your answer, you agree to the privacy policy and terms of service.

Not the answer you're looking for? Browse other questions tagged graph neo4j cypher or ask your own question.

a question feed



Information Security more (13) Money Role-playing Games more (5) more (21) more (9)