

Ten. Million. Questions. Let's celebrate [all we've done together](#).

Stack Overflow is a question and answer site for professional and enthusiast programmers. It's 100% free.

Take the 2-minute tour

Auto increment property with py2neo (Neo4j)?



I'm using flask with py2neo for my Rest service , I have a user node with the label "User".

2 how to autoincrement id for the "User" label , in neo4j using py2neo?

python neo4j auto-increment py2neo

share improve this question

add a comment

asked Apr 7 at 12:30

Sidali Hallak
299 ● 3 ● 8

1 Answer

active oldest votes

You don't, and you probably shouldn't. Neo4j already provides an internal `id` field that is an auto-incrementing integer. It isn't a property of the node, but is accessible via the `id()` function, like this:

```
MATCH (n:Person)
RETURN id(n);
```

So whenever you create any node, this already happens automatically for free by neo4j, and isn't done by py2neo.

If you need a different type of identifier for your code, I'd recommend something that's plausibly globally unique, like a [UUID](#) which is very easy to do in python, rather than an auto-incrementing integer.

The trouble with auto-incrementing numbers as IDs is that since they have a pattern to them (auto-incrementing) people come to rely on the value of the identifier, or come to rely on expectations of how the ID will be assigned. This is almost always a bad idea in databases. The sole purpose of the identifier is to be unique from everything else. It doesn't mean anything, and in some cases isn't even guaranteed not to change. Avoid embedding any reliance on any particular value or assignment scheme into your code.

That's why I like UUIDs, is because their assignment scheme is essentially arbitrary, and they clearly don't mean anything -- so they don't tempt designers to do anything clever with them. :)

share improve this answer

answered Apr 7 at 12:45

FrobberOfBits
8,397 ● 7 ● 29

Can I get some clarification: I've read elsewhere online that we shouldn't be relying on Neo4j's internal ID it keeps for nodes and should instead use our own id, but then you mention here that we shouldn't be using our own id. Thanks! – [Lamoni](#) Apr 30 at 15:28

@Lamoni this answer doesn't say you shouldn't use your own ID. Using your own ID is a good idea. Embedding meaning in that ID is a bad idea. (Hence UUIDs, which have no meaning, all they are is unique) – [FrobberOfBits](#) Apr 30 at 17:16

ahh thank you for the clarification, my bad on misunderstanding. Thanks! – [Lamoni](#) May 1 at 10:44

add a comment

asked 4 months ago

viewed 46 times

active 4 months ago

Blog

Why Stack Overflow is a Good Workplace for Women

Related

- 0 [py2neo: create relation with properties using batch](#)
- 2 [Working with indexes in neo4j and py2neo](#)
- 1 [py2neo not enforcing uniqueness constraints in Neo4j database](#)
- 1 [Py2neo Neo4j Batch submit error](#)
- 0 [How to create label on py2neo object using Object-Graph-Mapping before saved in Neo4j database](#)
- 1 [Difficulty with py2neo, neo4j and AJAX](#)
- 0 [Create many nodes in Neo4j using Py2neo](#)
- 1 [Can't delete neo4j nodes with a relationship using py2neo](#)
- 2 [py2neo \(Neo4j\) : py2neo.packages.httpstrea m.http.SocketError: Operation not permitted](#)
- 0 [Neo4j Python py2neo authorization error](#)

Hot Network Questions

- Aerofoil that gives reasonably good lift for both flow directions: forward and backward
- As a professional photographer, how can one handle a wedding photographer being rude or demanding in a way that will compromise overall image quality?
- An "outside the box" sequence
- Is it possible to automate tests for in progress sprint
- Select polygons one by one and export them using arcpy
- Can you open source firmware to closed hardware?

Your Answer

