stackoverfloooooooow

Questions | Tags | Users | Badges | Unanswered | Ask Question

spring data neo4j not lookup node

asked   4 months ago
viewed   23 times

▲

0

▼

★

1

I set some value to my neo4jdb,an i can see them in web-browser,so my db have nodes.but when i look up them,it returns null.what is wrong?my spring data neo4j version is 3.2.2.thanks for help,i have in disturbing with this four a long time

Related

1 Selecting multiple nodes with Spring Data Neo4j @Query

2 Spring Data Neo4j does not recognize externally inserted nodes

1 Neo4j: Inserting 7k nodes is slow (Spring Data Neo4j / SpringRestGraphDatabase)

1 neo4j 2.0.0 with spring data neo4j

0 Spring Data Neo4j : find all nodes with a list of propertyvalues

2 Neo4j and spring-data-neo4j - importing large datasets

0 Neo4j database not persisting using Spring Data Neo4j

1 Spring Data Neo4j Create duplicate nodes with underscore

3 How to add labels to nodes using spring data neo4j?

0 I use lookup to get value from Neo4jDB,but it return null

```
package com.oberon.fm.neo4j.service;

import org.neo4j.graphdb.GraphDatabaseService;
import org.neo4j.graphdb.Transaction;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.data.neo4j.support.Neo4jTemplate;
import org.springframework.data.neo4j.template.Neo4jOperations;

import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;
import com.oberon.fm.domain.Movie;
import com.oberon.fm.domain.User;

@Service
public class DatabasePopulator {
@Autowired
Neo4jOperations operation;
@Autowired
Neo4jTemplate template;
private final static Logger log = LoggerFactory
        .getLogger(DatabasePopulator.class);

@Transactional
public void populateWithSomeTestData() {
    System.out.println("==== Populating ====");
    GraphDatabaseService graphDb = template.getGraphDatabaseService();
    Transaction tx = graphDb.beginTx();
    try {
```

Hot Network Questions

🔶 Can a Glaive be stowed in a Ruby Scabbard?

```
        User user = new User("micha", "Micha", "password",
                User.Roles.ROLE_USER);
        User me = template.save(user);
        User yang = template.save(new User("yang", "Yang", "password",
                User.Roles.ROLE_USER));
        User ollie = template.save(new User("ollie", "Olliver", "password",
                User.Roles.ROLE_USER));
        me.addFriend(ollie);
```

} error info

```
2null
3null
java.lang.NullPointerException
at com.oberon.fm.neo4j.service.DatabasePopulator.loginCheck(DatabasePopulator.java
at com.oberon.fm.neo4j.service.DatabasePopulator$$FastClassBySpringCGLIB$$c9138765
at org.springframework.cglib.proxy.MethodProxy.invoke(MethodProxy.java:204)
at org.springframework.aop.framework.CglibAopProxy$DynamicAdvisedInterceptor.inter
at com.oberon.fm.neo4j.service.DatabasePopulator$$EnhancerBySpringCGLIB$$27698688.
at com.oberon.fm.controller.AuthController.loginCheck(AuthController.java:41)
at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.ja
at java.lang.reflect.Method.invoke(Method.java:483)
at org.springframework.web.bind.annotation.support.HandlerMethodInvoker.invokeHand
at org.springframework.web.servlet.mvc.annotation.AnnotationMethodHandlerAdapter.i
at org.springframework.web.servlet.mvc.annotation.AnnotationMethodHandlerAdapter.h
at org.springframework.web.servlet.DispatcherServlet.doDispatch(DispatcherServlet.
at org.springframework.web.servlet.DispatcherServlet.doService(DispatcherServlet.j
at org.springframework.web.servlet.FrameworkServlet.processRequest(FrameworkServle
at org.springframework.web.servlet.FrameworkServlet.doPost(FrameworkServlet.java:8
at javax.servlet.http.HttpServlet.service(HttpServlet.java:644)
at org.springframework.web.servlet.FrameworkServlet.service(FrameworkServlet.java:
at javax.servlet.http.HttpServlet.service(HttpServlet.java:725)
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFil
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain
at org.apache.tomcat.websocket.server.WsFilter.doFilter(WsFilter.java:52)
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFil
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain
at org.springframework.web.filter.CharacterEncodingFilter.doFilterInternal(Charact
at org.springframework.web.filter.OncePerRequestFilter.doFilter(OncePerRequestFilt
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFil
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain
at org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:
at org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:
at org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.ja
at org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:142)
at org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:79)
```

neo4j   spring-data-neo4j

share improve this question

asked Mar 27 at 5:44

yang
45 ● 8

add a comment

Know someone who can answer? Share a link to this question via email, Google+, Twitter, or Facebook.

Your Answer

B *I* 🔗 66 {} 🖼 ≣ ≣ ≣ ≣ ↶ ↷

Browse other questions tagged neo4j   spring-data-neo4j or ask your own question.

🔊 question feed