

## Vault :

Ansible allow keeping sensitive data such as passwords or key in encrypted files with the help of vaults...these yaml files can only be accessed via password

```
[ansible@ip-172-31-17-137 ~]$ ansible-vault create akshat.yml
```

It will ask you to put some password...whatever pass you want to put ..put it there and when you type it will not be visible

```
---
- hosts: demo
  user: ansible
  become: yes
  connection: ssh
~
~
~
```

---

```
- hosts: demo
  user: ansible
  become: yes
  connection: ssh
```

```
[ansible@ip-172-31-17-137 ~]$ ls
akshat.yml  index.html  target.yml
[ansible@ip-172-31-17-137 ~]$
```

```
...yaml
$ vi akshat.yaml
```

```
$ANSIBLE_VAULT;1.1;AES256
38363465393432303834353736363232363462643835363838316261326636383534303463663533
6134643164363736313731306133363437633730316164380a626232326463346165386133643036
61626438316439613063623831656635336563393233633534613363646332376239663464393933
3836646434323466660a663535363130366665323438333731363566373365333761623461333961
65393236663062323435663835353036333430626563616161613333343138636266623566663761
66623964313533343637653830623937363535613735303962313630346264643637363437306362
6236306533346132356561623561383562303266633616134636434313435623636326331376239
65303232396665373165
~
~
~
```

Encrypted file will open in front of us

But lets say I want to edit this yaml file...how can I edit this file?

```
ansible-vault edit akshat.yaml
```

It will ask for pass ..put the pass

```
--
- hosts: demo
  user: ansible
  become: yes
  connection: ssh
~
~
```

### to change the pass of the vault

```
ansible-vault rekey akshat.yml
```

```
[ansible@ip-172-31-17-137 ~]$ ansible-vault rekey akshat.yml
Vault password:
New Vault password:
Confirm New Vault password:
Rekey successful
```

### execute the yaml file in vault

```
Rekey successful
[ansible@ip-172-31-17-137 ~]$ ansible-playbook akshat.yml
ERROR! Attempting to decrypt but no vault secrets found
[ansible@ip-172-31-17-137 ~]$
```

```
ansible-playbook akshat.yml --ask-vault-pass
```

```
[ansible@ip-172-31-17-137 ~]$ ansible-playbook akshat.yml --ask-vault-pass
Vault password:

PLAY [demo] *****

TASK [Gathering Facts] *****
[WARNING]: Platform linux on host 172.31.20.198 is using the discovered Python interpreter at /usr/bin/python3.6.8;
Python interpreter could change this. See https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html
for more information.
ok: [172.31.20.198]
[WARNING]: Platform linux on host 172.31.24.204 is using the discovered Python interpreter at /usr/bin/python3.6.8;
Python interpreter could change this. See https://docs.ansible.com/ansible/2.9/reference_appendices/interpreter_discovery.html
for more information.
ok: [172.31.24.204]
```

---

---

This is how the vault works

