

mysterious_data_sol

November 19, 2021


```
[ ]: %matplotlib inline
import matplotlib
import numpy as np
import matplotlib.pyplot as plt
```

```
[ ]: # Load the data matrix
A = np.loadtxt('mysterious_data__.txt')
n,d = A.shape
print(f'The matrix A contains {n} points in dimension {d}')
```

The matrix A contains 3000 points in dimension 1000

Each row of A corresponds to a datapoint.

```
[ ]: Ac = A - A.mean(0)
AAT = Ac.T @ Ac
sp, vec = np.linalg.eigh(AAT,)
plt.plot(sp[::-1][:10])
plt.yscale('log')
```




```
[ ]: f = Ac @ vec[:, -2:]  
f.shape
```

```
[ ]: (3000, 2)
```

```
[ ]: plt.scatter(f[:, 1], - f[:, 0])
```

```
[ ]: <matplotlib.collections.PathCollection at 0x7f9ef6a34c90>
```



1 How was the data created?

```
[ ]: from matplotlib import image  
import matplotlib.pyplot as plt  
import numpy as np  
# load image as pixel array  
  
image = image.imread('images.jpg').sum(-1)  
image = 1 - image / image.max()  
image_ = image > 0.85  
plt.imshow(image_)  
  
## get points
```

```

xs, ys = np.where(image > 0.85)
plt.figure()
ax = plt.subplot(111)
ax.scatter(ys, -xs, s=0.2)
ax.set_aspect('equal')
n_points = xs.shape[0]


## hide point in higher dimension - with smaller random noise
dim = 1000
image_hd = 0.01 * np.random.randn(n_points, dim)
image_hd[:, 0] += 1e4 * xs
image_hd[:, 1] += 1e4 * ys


data = image_hd

## change basis using an orthogonal matrix
from scipy.stats import ortho_group # Requires version 0.18 of scipy

P = ortho_group.rvs(dim=dim)
data = image_hd @ P


```






```
[ ]: A = data
n,d = A.shape
print(f'The matrix A contains {n} points in dimension {d}')
Ac = A - A.mean(0)
AAT = Ac.T @ Ac
sp, vec = np.linalg.eigh(AAT,)
plt.plot(sp[:-1][:10])
plt.yscale('log')
```

The matrix A contains 7391 points in dimension 1000



```
[ ]: f = Ac @ vec[:, -2:]
plt.scatter(- f[:, 1], f[:, 0])
```

```
[ ]: <matplotlib.collections.PathCollection at 0x7fe721264d10>
```



[]:

[]: