



TECHNISCHE
UNIVERSITÄT
DARMSTADT



Personalized Transaction Kernels for Recommendation using MCTS

**Maryam Tavakol, Tobias Joppen,
Ulf Brefeld, and Johannes Fürnkranz**

Kassel, 25.09.2019

Outline

- ▶ Introduction and motivation
- ▶ Personalized transaction kernels
- ▶ Informed sampling strategies
- ▶ Empirical study
- ▶ Summary and Conclusions

Recommender Systems

- A user views the following item:



Goal: recommend an item(s) that is relevant to the user

Task: capture/understand the interests of users

Traditional Approaches

Collaborative filtering (Resnick et al., 1994): based on collecting information from many users


Traditional Approaches

Collaborative filtering (Resnick et al., 1994): based on collecting information from many users




Traditional Approaches

Collaborative filtering (Resnick et al., 1994): based on collecting information from many users




Traditional Approaches

Collaborative filtering (Resnick et al., 1994): based on collecting information from many users



Traditional Approaches

Collaborative filtering (Resnick et al., 1994): based on collecting information from many users



Shortcomings

Shortcomings

- Operates with explicit feedback



Shortcomings

- Operates with explicit feedback
- Computationally expensive for large-scale problems



Shortcomings

- Operates with explicit feedback
- Computationally expensive for large-scale problems
- Does not cope with data sparsity



Shortcomings

- Operates with explicit feedback
- Computationally expensive for large-scale problems
- Does not cope with data sparsity
- Fails in cold-start problem



Filling the Gap

- Explicit feedback → **preference-based feedback**
 - Computational complexity:
 - Users (personalization) → **efficient multi-task learning**
 - Items (online recommendation) → **informed search**
 - Data sparsity
 - Cold-start problem
-
- The diagram consists of two purple arrows originating from the words 'Data sparsity' and 'Cold-start problem' in the list above. Both arrows point towards the word 'contextual model' located at the bottom right of the slide.

Qualitative Feedback

A user views the following item:



Qualitative Feedback

A user views the following item:



recommended items:



Qualitative Feedback

A user views the following item:



recommended items:



Qualitative Feedback

A user views the following item:



recommended items:



Qualitative Feedback

A user views the following item:



recommended items:



Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback


Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback

contextual model: tensor product


Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback




Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback




Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback



Main Contributions

- An **efficient** preference model is proposed for recommendation with qualitative feedback




Outline

- ▶ Introduction and motivation
- ▶ Personalized transaction kernels
- ▶ Informed sampling strategies
- ▶ Empirical study
- ▶ Summary and Conclusions

The Preference Model

The Preference Model


user




context




The Preference Model



The Preference Model




The Preference Model



using standard SVM method:
(Joachims, 2002)

$$\mathbf{w}^\top (\phi(\mathbf{x}_i|u, \mathbf{s}_t) - \phi(\mathbf{x}_j|u, \mathbf{s}_t)) \geq 0$$

The Preference Model



using standard SVM method:
(Joachims, 2002)

$$\mathbf{w}^\top \left(\phi(\mathbf{x}_i | u, \mathbf{s}_t) - \phi(\mathbf{x}_j | u, \mathbf{s}_t) \right) \geq 0$$


kernel function

Tensor Kernels

■ context:  ,  , \$\$\$, ♂ , 

■ item:  ,  , \$, ♀ , 

■ context \otimes item:  ,  , ... ,  \$,  ♀ ,  

Tensor Kernels

- context:  ,  , \$\$\$, ♂ , 
- item:  ,  , \$, ♀ , 
- context \otimes item:  ,  , ... ,  \$,  ♀ ,  
- Now assume the existence of m data sources:

Tensor Kernels

- context:  ,  , \$\$\$, ♂ , 
- item:  ,  , \$, ♀ , 
- context \otimes item:  ,  ,  , ...,  \$,  ♀ ,  
- Now assume the existence of m data sources:

$$\left\langle \{\mathbf{x}^1 \otimes \dots \otimes \mathbf{x}^m\}, \{\mathbf{z}^1 \otimes \dots \otimes \mathbf{z}^m\} \right\rangle = \prod_{k=1}^m \langle \mathbf{x}^k, \mathbf{z}^k \rangle$$

Personalized Kernels

- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space

Personalized Kernels

- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space



\otimes context \otimes item



\otimes context \otimes item

Personalized Kernels


- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space




\otimes context \otimes item



\otimes context \otimes item




:




Personalized Kernels

- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space




Personalized Kernels

- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space



Personalized Kernels

- Using different hashing functions for users:
 - every user has her own specific representation
 - but in a joint feature space



The interaction between random subspaces is negligible with high probability
(Weinberger, 2009)

Preference-based Transaction Kernels

- A **collective** term for all users is added for **cold-start** scenarios

Preference-based Transaction Kernels

- A **collective** term for all users is added for **cold-start** scenarios

$$k^{pc} := \underbrace{\text{hash}(\text{user} \otimes \text{context} \otimes \text{item})}_{\text{personalized kernel}} + \underbrace{\text{hash}(\text{context} \otimes \text{item})}_{\text{collective kernel}}$$

Preference-based Transaction Kernels

- A **collective** term for all users is added for **cold-start** scenarios

$$k^{pc} := \underbrace{\text{hash}(\text{user} \otimes \text{context} \otimes \text{item})}_{\text{personalized kernel}} + \underbrace{\text{hash}(\text{context} \otimes \text{item})}_{\text{collective kernel}}$$

shared for all users 

Preference-based Transaction Kernels

- A **collective** term for all users is added for **cold-start** scenarios

$$k^{pc} := \underbrace{\text{hash}(\text{user} \otimes \text{context} \otimes \text{item})}_{\text{personalized kernel}} + \underbrace{\text{hash}(\text{context} \otimes \text{item})}_{\text{collective kernel}}$$

shared for all users 

$$k(\mathbf{x}_i \succ \mathbf{x}'_i, \mathbf{x}_j \succ \mathbf{x}'_j) =$$

$$k^{pc}(\mathbf{x}_i, \mathbf{x}_j) - k^{pc}(\mathbf{x}_i, \mathbf{x}'_j) - k^{pc}(\mathbf{x}'_i, \mathbf{x}_j) + k^{pc}(\mathbf{x}'_i, \mathbf{x}'_j)$$

Outline

- ▶ Introduction and motivation
- ▶ Personalized transaction kernels
- ▶ Informed sampling strategies
- ▶ Empirical study
- ▶ Summary and Conclusions

Online Recommendation

- How to find the *best* product to recommend?
- Given the preference model:
 - enumerate over all available items
 - compute their utility for a given user and context
 - return the item(s) that maximizes the utility

Online Recommendation

- How to find the *best* product to recommend?
- Given the preference model:
 - enumerate over all available items
 - compute their utility for a given user and context
 - return the item(s) that maximizes the utility




Informed Sampling

- Smarten the search to approximate the (near-) optimal product
 - using Monte Carlo Tree Search (MCTS) (Browne et al., 2012)


Informed Sampling

- Smarten the search to approximate the (near-) optimal product
- using Monte Carlo Tree Search (MCTS) (Browne et al., 2012)




Informed Sampling

- Smarten the search to approximate the (near-) optimal product
 - using Monte Carlo Tree Search (MCTS) (Browne et al., 2012)



MCTS in Feature Space

- Leaf nodes specify a complete item with all categorical features



each layer selects an attribute

MCTS Modifications

- Utilize the preference information over features

MCTS Modifications

- Utilize the preference information over features
- Find the best product (leaf node), instead of the best action in the root node

MCTS Modifications

- Utilize the preference information over features
- Find the best product (leaf node), instead of the best action in the root node
- Keep a list of best n products found while searching

MCTS Modifications

- Utilize the preference information over features
- Find the best product (leaf node), instead of the best action in the root node
- Keep a list of best n products found while searching
- Avoid redundant evaluation of the same product
 - Remove leaf nodes that have been tested from the tree

Outline


- ▶ Introduction and motivation
- ▶ Personalized transaction kernels
- ▶ Informed sampling strategies
- ▶ Empirical study
- ▶ Summary and Conclusions

Empirical Study

- Pairwise preference data from Zalando (www.zalando.com)
- About 680k users and 16k products
- More than 3.5 million total transactions
- **Attributes:** category, sub-category, color, gender, brand
- **Baseline:** JRank(Basilico, Hofmann, 2004) (preference model), random subset exhaustion and greedy stochastic search (search)
- **Evaluation measure:** AUC (preference model), utility (search)


Results—Preference Model

Overall performance for 10-fold cross validation




- ▶ highly accurate performance of personalized & combined model

Results—Preference Model



- ▶ more data per user: more robust personalization
- ▶ but for most users, **collective kernel** has an important role



Results—Informed Sampling



- MCTS outperforms the baselines in much smaller search spaces

Results—Informed Sampling



Example tests for a given product, four different users



- ▶ the choice of λ is important in the performance

Results—Informed Sampling

User 4 is a new user without training data



- ▶ MCTS finds the optimal product with a lower number of samples

Outline

- ▶ Introduction and motivation
- ▶ Personalized transaction kernels
- ▶ Informed sampling strategies
- ▶ Empirical study
- ▶ Summary and Conclusions

Summary and Conclusions

Summary and Conclusions

- ▶ Preference-based learning to model personalized interests of users in contextual settings

Summary and Conclusions

- ▶ Preference-based learning to model personalized interests of users in contextual settings
- ▶ Transaction kernels combine **tensor products** with **hashing functions** to capture individual as well as collective user preferences

Summary and Conclusions

- ▶ Preference-based learning to model personalized interests of users in contextual settings
- ▶ Transaction kernels combine **tensor products** with **hashing functions** to capture individual as well as collective user preferences
- ▶ A variant of MCTS method efficiently retrieves near-optimal items for online recommendation

Summary and Conclusions

- ▶ Preference-based learning to model personalized interests of users in contextual settings
- ▶ Transaction kernels combine **tensor products** with **hashing functions** to capture individual as well as collective user preferences
- ▶ A variant of MCTS method efficiently retrieves near-optimal items for online recommendation
- ▶ The model shows effective and efficient performance in real-world scenarios

Thanks for Your Attention!


maryamtavakol.com
maryam.tavakol@tu-dortmund.de

■ References

- P. Resnick, N. Iacovou, M. Suchak, P. Bergstrom, and J. Riedl. *GroupLens: an open architecture for collaborative filtering of netnews*. In Proceedings of the 1994 ACM Conference on Computer Supported Cooperative Work, pp. 175–186. ACM, 1994
- T. Joachims, *Optimizing search engines using clickthrough data*. In Proceedings of the 8th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. pp. 133–142. ACM (2002)
- K. Weinberger, A. Dasgupta, J. Langford, A. Smola, J. Attenberg, *Feature hashing for large scale multitask learning*. In Proceedings of the 26th International Conference on Machine Learning (ICML-09). pp. 1113–1120. ACM (2009)
- C. B. Browne, E. Powley, D. Whitehouse, S. M. Lucas, P. I. Cowling, P. Rohlfshagen, S. Tavener, D. Perez, S. Samothrakis, S. Colton, *A survey of Monte Carlo tree search methods*. IEEE Transactions on Computational Intelligence and AI in Games 4(1), 1–43 (2012)
- J. Basilico, T. Hofmann, *Unifying collaborative and content-based filtering*. In Proceedings of the 21st International Conference on Machine Learning (ICML-04). p. 9. ACM (2004)

Results—Preference Model

The effect of the size of hashing function



- ▶ The more bits are used, the better the personalization model