

Combining Axiom Injection and Knowledge Base Completion for Efficient Natural Language Inference

Masashi Yoshikawa◆, Koji Mineshima★, Hiroshi Noji♥, Daisuke Bekki★

◆Nara Institute of Science and Technology

★Ochanomizu University


♥Artificial Intelligence Research Center, AIST

AAAI-33 2019/XX/XX

Today's Talk


- Goal:
 - Developing **Accurate & Efficient** RTE system based on higher-order logic
 - Proof Assistant Coq: Automated higher-order theorem proving $\forall x.\mathbf{hike}(x) \rightarrow \mathbf{walk}(x)$
 - Issue: How to deal the massive amount of knowledge (axioms) ?? $\forall x.\mathbf{walk}(x) \rightarrow \neg\mathbf{ride}(x)$
 \vdots
 - **Extending knowledge base & efficient reasoning** lie in a strained relation
- We solve the issue by combining logic-based RTE system with **knowledge base completion!**
- We develop a **Coq plugin** for the further efficiency

Background: ccg2lambda_(Mineshima+, 2015)



Premise	
$\frac{\frac{A}{NP/N} \quad \frac{\text{man}}{N}}{\lambda F. \lambda G. \exists x. F(x) \wedge G(x)} > \frac{\text{hikes}}{S \setminus NP}$	
$\frac{NP}{\lambda G. \exists x. \text{man}(x) \wedge G(x)} < \frac{S \setminus NP}{\lambda Q. Q(\lambda x. \exists e. \text{hike}(e) \wedge \text{subj}(e, x))}$	
$\frac{\exists x. \text{man}(x) \wedge \exists e. \text{hike}(e) \wedge \text{subj}(e, x)}{S}$	

Hypothesis	
$\frac{\frac{A}{NP/N} \quad \frac{\text{man}}{N}}{\lambda F. \lambda G. \exists x. F(x) \wedge G(x)} > \frac{\text{walks}}{S \setminus NP}$	
$\frac{NP}{\lambda G. \exists x. \text{man}(x) \wedge G(x)} < \frac{S \setminus NP}{\lambda Q. Q(\lambda x. \exists e. \text{walk}(e) \wedge \text{subj}(e, x))}$	
$\frac{\exists x. \text{man}(x) \wedge \exists e. \text{walk}(e) \wedge \text{subj}(e, x)}{S}$	



- **1st Issue:** Tensed relation between extending knowledge and efficient reasoning
- **2nd ssue:** Needs to exit a Coq proving session to run abduction

Knowledge Base Completion

- Wordnet
 - 0.1 million nodes, 0.5 million edges
- Freebase
 - 2 billion edges
- Knowledge base is not complete



- Not all true facts (relations) are annotated


→ Infer missing knowledge using ML

(hike, hypernym, walk)

(walk, antonym, ride)

(hike, hypernym, go)

...



Knowledge Base Completion

- Design a function f to evaluate a triplet (s, r, o) is true or false
 - Simple models with the efficiency in mind (e.g. use of diagonal matrices)
 - Higher-order relations (e.g. transitivity) are modeled with loss function (Bouchard+, 2015)
 - Achieves high scores on WordNet benchmark datasets(WN18, more than 94% in Hits@1)
- TransE (Bordes+, 2013)

$$f(s, r, o) = ||\mathbf{e}_s + \mathbf{e}_r - \mathbf{e}_o||_2^2, \mathbf{e}_i \in \mathbb{R}^n$$

Very simple
additive model

- ComplEx (Trouillon+, 2016)

$$f(s, r, o) = \sigma(\text{Re}(\langle \mathbf{e}_s, \mathbf{e}_r, \overline{\mathbf{e}_o} \rangle)), \mathbf{e}_s, \mathbf{e}_r, \mathbf{e}_o \in \mathbb{C}^n$$

Models
anti-symmetry
in complex vector
space

Proposed: Axiom Injection using Knowledge Base Completion

- We replace abduction method based on search on KBs (Martínez-Gómez+, 2017)
- Instead, our method uses a KBC function f
 - Convert triplets whose scores are above a predefined threshold
 - Conversion is defined in terms of relations r :

Relation r	Generated Axiom	Example
synonym, hypernym, derivationally-related	$\forall x.(s(x) \rightarrow o(x))$	$(\text{make}, r, \text{build}) \rightsquigarrow \forall e.(\text{make}(e) \rightarrow \text{build}(e))$
antonym	$\forall x.(s(x) \rightarrow \neg o(x))$	$(\text{parent}, r, \text{child}) \rightsquigarrow \forall x.(\text{parent}(x) \rightarrow \neg \text{child}(x))$
hyponym	$\forall x.(o(x) \rightarrow s(x))$	$(\text{talk}, r, \text{advise}) \rightsquigarrow \forall e.(\text{advise}(e) \rightarrow \text{talk}(e))$

Proposed: Axiom Injection using Knowledge Base Completion


- **Very Fast:** traversal on KB \rightarrow matrix operation of $O(n)$
 - Large gap in computing transitive closure (hypernym \rightarrow hypernym $\rightarrow \dots$)
- **Scalable:** Adding new triplets with low cost
 - KB Graph: The time of a traversal is increased as # of entities does...
 - If s, r, and o exist already, no increase of # of parameters!
 - In the experiment, we add knowledge from VerbOcean(Chklovski+, 2004)
- **Latent knowledge** obtained in KBC model is also available (e.g. (hike, antonym, ride))

ccg2lambda (Mineshima+, 2015)




Premise	
$\frac{\frac{A}{NP/N} \quad \frac{\text{man}}{N}}{\lambda F. \lambda G. \exists x. F(x) \wedge G(x)} > \frac{\text{hikes}}{S \setminus NP}$	
$\frac{NP}{\lambda G. \exists x. \text{man}(x) \wedge G(x)} < \frac{\lambda Q. Q(\lambda x. \exists e. \text{hike}(e) \wedge \text{subj}(e, x))}{S}$	
$\exists x. \text{man}(x) \wedge \exists e. \text{hike}(e) \wedge \text{subj}(e, x)$	

Hypothesis	
$\frac{\frac{A}{NP/N} \quad \frac{\text{man}}{N}}{\lambda F. \lambda G. \exists x. F(x) \wedge G(x)} > \frac{\text{walks}}{S \setminus NP}$	
$\frac{NP}{\lambda G. \exists x. \text{man}(x) \wedge G(x)} < \frac{\lambda Q. Q(\lambda x. \exists e. \text{walk}(e) \wedge \text{subj}(e, x))}{S}$	
$\exists x. \text{man}(x) \wedge \exists e. \text{walk}(e) \wedge \text{subj}(e, x)$	




- ✓ **1st Issue:** Tensed relation between extending knowledge and efficient reasoning
- ➔ **2nd Issue:** Needs to exit a Coq proving session to run abduction

Even Faster Reasoning with our Coq plugin (abduction)



Even Faster Reasoning with our Coq plugin (abduction)




		Premise	
A	man		
NP/N	N		
$\lambda F.\lambda G.\exists x.F(x) \wedge G(x)$	$\lambda x.\text{man}(x)$		
NP		$S \setminus NP$	
$\lambda G.\exists x.\text{man}(x) \wedge G(x)$		$\lambda Q.Q(\lambda x.\exists e.\text{hike}(e) \wedge \text{subj}(e, x))$	
S			
$\exists x.\text{man}(x) \wedge \exists e.\text{hike}(e) \wedge \text{subj}(e, x)$			

		Hypothesis	
A	man		
NP/N	N		
$\lambda F.\lambda G.\exists x.F(x) \wedge G(x)$	$\lambda x.\text{man}(x)$		
NP		$S \setminus NP$	
$\lambda G.\exists x.\text{man}(x) \wedge G(x)$		$\lambda Q.Q(\lambda x.\exists e.\text{walk}(e) \wedge \text{subj}(e, x))$	
S			
$\exists x.\text{man}(x) \wedge \exists e.\text{walk}(e) \wedge \text{subj}(e, x)$			

- No need to quit Coq
- Python server
- DL libraries (and use of GPUs...)
- The mechanism can be extended for other problems of theorem proving
- e.g. premise selection (Alemi+, 2016)



• **1st Issue:** Tensed relation between extending knowledge and efficient reasoning




• **2nd Issue:** Needs to exit a Coq proving session to run abduction

Experiments

- We evaluate our model on SICK(Marelli+, 2014) dataset
 - Metrics: accuracy and processing time of an RTE problem
 - (macro average of 5 runs on trial set, timeout 100 sec.)
- We use ComplEx (Trouillon+ 2016) as our KBC model.
- Logistic loss: $\sum_{((s,r,o),t) \in \mathcal{D}} t \log f(s,r,o) + (1-t) \log(1-f(s,r,o))$
- In this work, we create training data as well
 - by extracting triplets from WordNet: (syno-, ant-, hypo-, hyper- nyms ..)
 - VerbOcean(Chklovski+, 2004): relations among verbs

Experimental Results on SICK

	Accuracy	Speed (Sec. / Problem)
no abduction	77.30	3.79
search-based (WordNet)	83.55	9.12
search-based (+VerbOcean)	83.68	9.42
KBC-based (WordNet)	83.55	4.03
KBC-based (+VerbOcean)	83.45	3.84



- Baseline: axiom injection based on search on KBs (Martínez-Gómez+, 2017)
- **Accuracy**: comparable / slightly lower compared to baseline
- **Processing Speed**: greatly improve; come close to "no abduction" case
- **Augmentation with VerbOcean**: further improvement in speed

Analyzing Latent Knowledge on More Challenging LexSICK dataset

- We construct a new RTE problems to evaluate latent knowledge of KBC model in terms of RTE.
- 60 problems of combination of syntactic & lexical phenomena

P: Someone is dropping the meat in a pan.

-> **H:** The meat is being thrown into a pan.

P: The man is singing and playing the guitar.

-> **H:** The guitar is being performed by a man.

Summary:

- A KBC-based injection method of lexical knowledge to logic-based RTE systems
 - Efficient, Scalable, Provides latent knowledge
 - `abduction` tactic enables even faster reasoning

- Future work

- Phrase-level lexical axioms $\forall x.(\mathbf{have}(x) \wedge \mathbf{fun}(x)) \rightarrow \mathbf{enjoy}(x)$

- Compositionally compute their vectors from word's ones

- Lexical axioms from multiword expressions

$$\forall x.\mathbf{make_up_one's_mind}(x) \rightarrow \mathbf{determine}(x)$$