



Analog Outputs

A1 Off

Frequency: 1 Hz

Amplitude: 1.00 V

Waveform: ☒ Sine ☐ Triangle

Mode: ☒ Unipolar ☐ Bipolar

A2 Off

Frequency: 1 Hz

Amplitude: 1.00 V

Waveform: ☒ Sine ☐ Triangle

Mode: ☒ Unipolar ☐ Bipolar

Pulse Outputs

P1 Off

Frequency: 1 Hz

Duty: 50%

P2 Off

Frequency: 1 Hz

Duty: 50%

Horizontal Control

☒ Y vs T

☐ X vs Y

X: Ch1

Y: Ch1

Time Scale: 500 ms/div

Trigger

Trigger Off

☒ Rising Edge

☐ Falling Edge

☐ Channel 1

☐ Channel 2

☐ Channel 3

☐ Channel 4

Run Control

☒ Continuous

☐ Single

☐ Stop

Power

Power is On

USB Power: 0.50 W

Channel 1

Ch1 On

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

Channel 2

Ch2 Off

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

Channel 3

Ch3 Off

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

Channel 4

Ch4 Off

Sensitivity: 2.0 V/div

Range: +5V, 0, -5V

v0.8.2