TCP Allusion™

LED Lamps with Smooth Warm Dimming

Product Specifications



Introducing TCP's Allusion "incandescent-like" LED smooth warm dimming technology. LEDs with a unique dimming profile that replicates true incandescent/halogen dimming.

Reasons to choose the Alllusion LED Lamps from TCP

- Dimming Range (CCT):
  - A19 – 2700K to 2000K
  - B11 – 2400K to 1900K
  - BR30 – 3000K to 2000K
  - PAR30 – 3000K to 2000K
  - PAR38 – 3000K to 2000K
  - 5"/6" Downlight – 3000K to 1800K
- Energy efficient: Up to 85% more efficient than incandescent/halogen replacements
- Long life: 25,000 hours
- Similar look and feel as incandescent alternative
- Approved for damp locations

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Decorative Lighting
- Chandeliers
- Recessed Downlights
- Track Lights
- Dimmable 6" & 5" Downlight applications

Specifications:

Voltage	120 VAC
Input Line Frequency	50/60HZ
Lamp Life (Rated)	25,000 hours
Minimum Starting Temp	-30°C
Maximum Operating Temp	40°C
CRI	80
Beam Angle	25° (PAR30, PAR38)
Base	E12, E26
Warranty	5 Years

Suitable for use in totally enclosed fixtures

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

c UL us LISTED RoHS COMPLIANT 5 YEAR WARRANTY

LED Lamps with Smooth Warm Dimming

Specifications:


A19


B10


BR30


PAR30


PAR38


5″/6″ Recessed Downlight

ITEM #	DESCRIPTION	VOLTAGE	WATTS	REPLACEMENT WATTS	LUMENS	LPW	BEAM ANGLE	CCT	CRI	R9	MOL (inches)	DIA (inches)
TCP Allusion LED Lamps												
LED9A19DA	9W A19 A-Lamp	120	9	60	650	72.2	OMNI	2700K to 2000K	80	>0	4.6	2.4
LED5E12B11DA	5W B11 Candelabra Blunt Tip	120	5	25	300	60.0	OMNI	2400K to 1900K	80	>0	3.8	1.4
LED5E12B11DAF	5W B11 Candelabra Blunt Tip Frost	120	5	25	300	60.0	OMNI	2400K to 1900K	80	>0	3.8	1.4
LED10BR30DA	10W BR30	120	10	65	675	67.5	OMNI	3000K to 2000K	80	>0	5.4	3.8
LED15P30DA	15W PAR30	120	15	100	950	63.3t	25°	3000K to 2000K	80	>0	5.2	4.8
LED15P38DA	15W PAR38	120	15	100	975	65.0	25°	3000K to 2000K	80	>0	5.2	4.8
LED10DR56DA	11W 5″/6″ Recessed Downlight	120	11	65	1100	100.0		3000K to 1800K	80	>0	3.0	7.5

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com
©TCP MAY 2025/WF103409

c UL us LISTED
RoHS COMPLIANT
5 YEAR WARRANTY