

# California Quality LED Lamps

## Product Specifications

TCP's California Quality High CRI LED line offers exceptional color consistency and rendering while meeting all requirements for Title 24 JA8-2019-E.

## Reasons to choose the California Quality LED Lamps from TCP

- Excellent color consistency and CRI enhance colors of focal point while maintaining uniformity throughout lighting installation
- Uses up to 80% less energy than halogen alternatives, providing instant energy savings
- Long lasting - minimizing replacement and maintenance costs
- Smooth, uniform dimming
- PAR style lamps can be used in wet locations
- Shatter resistant - lowering the risk of injury and breakage
- Meets California Title 24 JA8-2019-E
- Damp location rated - PARs wet location rated

## Ideal Applications

- Track and Display Lights
- Sconces
- General Lighting
- Table and Floor Lamps
- Ceiling Fixture and Sconces
- Recessed Downlights
- Protected Outdoor Fixtures

## Specifications

Voltage .....120V/12V
Input Line Frequency..... 50/60Hz
Lamp Life (Rated) ..... 15,000 / 25,000 / 35,000 hours
Minimum Starting Temp .....-22°C/-8°F
Maximum Operating Temp.....45°C/113°F
CRI..... ≥ 90

Beam Angle .....Omnidirectional, 360°, 110°, 40°, 25°
Base .....E12, E26, GU5.3, GU10, GU24
Warranty.....3 Years (Filaments)
.....5 Years (A/BR/R20/MR16/PAR/Downlights)
Suitable for use in totally enclosed fixtures

**TCP®**
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

DAMP LOCATION

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day

5 YEAR WARRANTY
*Based on 12 hours use per day

# TCP California Quality LED Lamps

## Specifications

### A Lamps


6W A19


10W A19


13W A19


17W A21


17/10/6 W A21 3 Way

### R20 Lamp


7W R20

### MR16 Lamps


7W GU10 MR16



6.5W GU5.3 MR16

### BR Lamps


8W BR30


16W BR30


13.5W BR40

### PAR Lamps


13W PAR38


10W PAR30


7W PAR20


7W PAR16

### Downlights


4" Downlights

### Filaments


9W A19


4.5W B11


4.5W G16


4.5W G25


5W T10


4.2W ST19

**TCP**®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

DAMP LOCATION

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day*

5 YEAR WARRANTY
*Based on 12 hours use per day*

# TCP California Quality LED Lamps

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | CCT | HOURS | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **A Lamps – Dimmable • 25,000 Hours** | | | | | | | | | | | | | | |
| L40A19D2527KCQ | A19 40W 27K DIM CQ | 6 | 40 | 475 | OMNI | 2700K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | E26 | 12 |
| L40A19D2530KCQ | A19 40W 30K DIM CQ | 6 | 40 | 475 | OMNI | 3000K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | E26 | 12 |
| L40A19D2535KCQ | A19 40W 35K DIM CQ | 6 | 40 | 475 | OMNI | 3500K | 25,000 | 90 | 4.0 | 2.2 | Y | Y | E26 | 12 |
| L40A19D2541KCQ | A19 40W 41K DIM CQ | 6 | N/A | 525 | OMNI | 4100K | 25,000 | 90 | 4.0 | 2.2 | Y | N/A | E26 | 12 |
| L40A19D2550KCQ | A19 40W 50K DIM CQ | 6 | N/A | 525 | OMNI | 5000K | 25,000 | 90 | 4.0 | 2.2 | Y | N/A | E26 | 12 |
| L60A19D2527KCQ | A19 60W 27K DIM CQ | 10 | 60 | 800 | OMNI | 2700K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | E26 | 12 |
| L60A19D2530KCQ | A19 60W 30K DIM CQ | 10 | 60 | 800 | OMNI | 3000K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | E26 | 12 |
| L60A19D2535KCQ | A19 60W 35K DIM CQ | 10 | 60 | 800 | OMNI | 3500K | 25,000 | 90 | 4.3 | 2.4 | Y | Y | E26 | 12 |
| L60A19D2541KCQ | A19 60W 41K DIM CQ | 10 | N/A | 800 | OMNI | 4100K | 25,000 | 90 | 4.3 | 2.4 | Y | N/A | E26 | 12 |
| L60A19D2550KCQ | A19 60W 50K DIM CQ | 10 | N/A | 800 | OMNI | 5000K | 25,000 | 90 | 4.3 | 2.4 | Y | N/A | E26 | 12 |
| L75A19D2527KCQ | A19 75W 27K DIM CQ | 13 | 75 | 1100 | OMNI | 2700K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | E26 | 12 |
| L75A19D2530KCQ | A19 75W 30K DIM ECQ | 13 | 75 | 1100 | OMNI | 3000K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | E26 | 12 |
| L75A19D2535KCQ | A19 75W 35K DIM ECQ | 13 | 75 | 1100 | OMNI | 3500K | 25,000 | 90 | 4.4 | 2.5 | Y | Y | E26 | 12 |
| L75A19D2541KCQ | A19 75W 41K DIM CQ | 13 | N/A | 1100 | OMNI | 4100K | 25,000 | 90 | 4.4 | 2.5 | Y | N/A | E26 | 12 |
| L75A19D2550KCQ | A19 75W 50K DIM CQ | 13 | N/A | 1100 | OMNI | 5000K | 25,000 | 90 | 4.4 | 2.5 | Y | N/A | E26 | 12 |
| L100A21D2527KCQ | A21 100W 27K DIM CQ | 17 | 100 | 1600 | OMNI | 2700K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | E26 | 12 |
| L100A21D2530KCQ | A21 100W 30K DIM CQ | 17 | 100 | 1625 | OMNI | 3000K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | E26 | 12 |
| L100A21D2535KCQ | A21 100W 35K DIM CQ | 17 | 100 | 1625 | OMNI | 3500K | 25,000 | 90 | 5.2 | 2.8 | Y | Y | E26 | 12 |
| L100A21D2541KCQ | A21 100W 41K DIM CQ | 17 | N/A | 1675 | OMNI | 4100K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| L100A21D2550KCQ | A21 100W 50K DIM CQ | 17 | N/A | 1675 | OMNI | 5000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| L100A213W2527KCQ | A21 3 WAY 100/60/40W 27K CQ | 17/10/6 | 100/60/40 | 1650/800/450 | OMNI | 2700K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| L100A213W2530KCQ | A21 3 WAY 100/60/40W 30K CQ | 17/10/6 | 100/60/40 | 1650/800/450 | OMNI | 3000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| L100A213W2541KCQ | A21 3 WAY 100/60/40W 41K CQ | 17/10/6 | N/A | 1700/800/450 | OMNI | 4100K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| L100A213W2550KCQ | A21 3 WAY 100/60/40W 50K CQ | 17/10/6 | N/A | 1700/800/450 | OMNI | 5000K | 25,000 | 90 | 5.2 | 2.8 | Y | N/A | E26 | 12 |
| **R20 Lamps – Dimmable • 25,000 Hours** | | | | | | | | | | | | | | |
| L50R20D2527KCQ | R20 50W 27K DIM CQ | 7 | 50 | 525 | 110° | 2700K | 25,000 | 90 | 3.8 | 2.5 | Y | Y | E26 | 12 |
| L50R20D2530KCQ | R20 50W 30K DIM CQ | 7 | 50 | 525 | 110° | 3000K | 25,000 | 90 | 3.8 | 2.5 | Y | Y | E26 | 12 |
| **MR16 Lamps – Dimmable • 25,000 Hours** | | | | | | | | | | | | | | |
| L50MR16GUD2527KFLCQ | MR16 50W 27K GU10 DIM 40° CQ | 7 | 50 | 500 | 40° | 2700K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU10 | 12 |
| L50MR16GUD2530KFLCQ | MR16 50W 30K GU10 DIM 40° CQ | 7 | 50 | 500 | 40° | 3000K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU10 | 12 |
| **MR16 Lamps – Dimmable 25,000 Hours 12V** | | | | | | | | | | | | | | |
| L50MR16D2527KFLCQ | MR16 50W 27K GU5.3 DIM 40° CQ | 6.5 | 50 | 430 | 40° | 2700K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU5.3 | 12 |
| L50MR16D2530KFLCQ | MR16 50W 30K GU5.3 DIM 40° CQ | 6.5 | 50 | 470 | 40° | 3000K | 25,000 | 90 | 2.3 | 2.0 | Y | N | GU5.3 | 12 |

**TCP®**
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

DAMP LOCATION

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day

5 YEAR WARRANTY
*Based on 12 hours use per day

# TCP California Quality LED Lamps

## Specifications

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | CCT | HOURS | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **BR Lamps – Dimmable • 25,000 Hours** | | | | | | | | | | | | | | |
| L65BR30D2527KCQ | BR30 65W 27K DIM CQ | 8 | 65 | 650 | 110° | 2700K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 |
| L65BR30D2530KCQ | BR30 65W 30K DIM CQ | 8 | 65 | 650 | 110° | 3000K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 |
| L65BR30D2541KCQ | BR30 65W 41K DIM CQ | 8 | N/A | 650 | 110° | 4100K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 |
| L65BR30D2550KCQ | BR30 65W 50K DIM CQ | 8 | N/A | 700 | 110° | 5000K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 |
| L100BR30D2527KCQ | BR30 100W 27K DIM CQ | 16 | 100 | 1500 | 110° | 2700K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 |
| L100BR30D2530KCQ | BR30 100W 30K DIM CQ | 16 | 100 | 1550 | 110° | 3000K | 25,000 | 90 | 5.4 | 3.8 | Y | Y | E26 | 12 |
| L100BR30D2541KCQ | BR30 100W 41K DIM CQ | 16 | N/A | 1600 | 110° | 4100K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 |
| L100BR30D2550KCQ | BR30 100W 50K DIM CQ | 16 | N/A | 1600 | 110° | 5000K | 25,000 | 90 | 5.4 | 3.8 | Y | N/A | E26 | 12 |
| L85BR40D2527KCQ | BR40 85W 27K DIM CQ | 13.5 | 85 | 1065 | 110° | 2700K | 25,000 | 90 | 6.1 | 5.0 | Y | Y | E26 | 12 |
| L85BR40D2530KCQ | BR40 85W 30K DIM CQ | 13.5 | 85 | 1065 | 110° | 3000K | 25,000 | 90 | 6.1 | 5.0 | Y | Y | E26 | 12 |
| L85BR40D2541KCQ | BR40 85W 41K DIM CQ | 13.5 | N/A | 1065 | 110° | 4100K | 25,000 | 90 | 6.1 | 5.0 | Y | N/A | E26 | 12 |
| L85BR40D2550KCQ | BR40 85W 50K DIM CQ | 13.5 | N/A | 1065 | 110° | 5000K | 25,000 | 90 | 6.1 | 5.0 | Y | N/A | E26 | 12 |
| **PAR Lamps – Dimmable • 25,000 Hours** | | | | | | | | | | | | | | |
| L90P38D2527KFLCQ | PAR38 90W 27K DIM 40° CQ | 13 | 90 | 950 | 40° | 2700K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 |
| L90P38D2530KFLCQ | PAR38 90W 30K DIM 40° CQ | 13 | 90 | 1000 | 40° | 3000K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 |
| L90P38D2527KNFLCQ | PAR38 90W 27K DIM 25° CQ | 13 | 90 | 950 | 25° | 2700K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 |
| L90P38D2530KNFLCQ | PAR38 90W 30K DIM 25° CQ | 13 | 90 | 1000 | 25° | 3000K | 25,000 | 90 | 5.3 | 4.8 | Y | Y | E26 | 12 |
| L75P30D2527KNFLCQ | P30 75W 27K DIM 25° CQ | 10 | 75 | 750 | 25° | 2700K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L75P30D2530KNFLCQ | P30 75W 30K DIM 25° CQ | 10 | 75 | 750 | 25° | 3000K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L75P30D2535KNFLCQ | P30 75W 35K DIM 25° CQ | 10 | 75 | 750 | 25° | 3500K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L75P30D2527KFLCQ | P30 75W 27K DIM 40° CQ | 10 | 75 | 750 | 40° | 2700K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L75P30D2530KFLCQ | P30 75W 30K DIM 40° CQ | 10 | 75 | 750 | 40° | 3000K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L75P30D2535KFLCQ | P30 75W 35K DIM 40° CQ | 10 | 75 | 750 | 40° | 3500K | 25,000 | 90 | 4.6 | 3.8 | Y | Y | E26 | 12 |
| L50P20D2527KNFLCQ | P20 50W 27K DIM 25° CQ | 7 | 50 | 550 | 25° | 2700K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 |
| L50P20D2530KNFLCQ | P20 50W 30K DIM 25° CQ | 7 | 50 | 550 | 25° | 3000K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 |
| L50P20D2527KFLCQ | P20 50W 27K DIM 40° CQ | 7 | 50 | 600 | 40° | 2700K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 |
| L50P20D2530KFLCQ | P20 50W 30K DIM 40° CQ | 7 | 50 | 600 | 40° | 3000K | 25,000 | 90 | 3.5 | 2.5 | Y | Y | E26 | 12 |
| L50P16D2527KFLCQ | P16 50W 27K DIM 40° CQ | 7 | 50 | 500 | 40° | 2700K | 25,000 | 90 | 3.5 | 2.0 | Y | Y | E26 | 12 |
| L50P16D2530KFLCQ | P16 50W 30K DIM 40° CQ | 7 | 50 | 500 | 40° | 3000K | 25,000 | 90 | 3.5 | 2.0 | Y | Y | E26 | 12 |

**TCP®**
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

DAMP LOCATION

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day

5 YEAR WARRANTY
*Based on 12 hours use per day

# TCP California Quality LED Lamps

## Specifications

| ITEM # | DESCRIPTION | WATTS | REPLACEMENT WATTS | LUMENS | BEAM ANGLE | COLOR | HOURS | CRI | MOL (inches) | DIA (inches) | TITLE 20 | JA8 | BASE | CASE QTY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Downlights – Dimmable • 35,000 Hours** | | | | | | | | | | | | | | |
| L75DR4D3527KCQ | Downlight 4" 27K DIM CQ | 9.5 | 75 | 750 | 110° | 2700K | 35,000 | 90 | 3.0 | 5.0 | Y | Y | E26 | 12 |
| L75DR4D3530KCQ | Downlight 4" 30K DIM CQ | 9.5 | 75 | 750 | 110° | 3000K | 35,000 | 90 | 3.0 | 5.0 | Y | Y | E26 | 12 |
| L75DR4D3541KCQ | Downlight 4" 41K DIM CQ | 9.5 | N/A | 750 | 110° | 4100K | 35,000 | 90 | 3.0 | 5.0 | Y | N/A | E26 | 12 |
| **Filament Lamps – Dimmable • 15,000 Hours** | | | | | | | | | | | | | | |
| LFF60A19D1527KCQ | LED 9W GLASS A19 DIM 27K CQ | 9 | 60 | 810 | OMNI | 2700K | 15,000 | 90 | 4.3 | 2.4 | Y | N | E26 | 12 |
| LFF60A19D1530KCQ | LED 9W GLASS A19 DIM 30K CQ | 9 | 60 | 810 | OMNI | 3000K | 15,000 | 90 | 4.3 | 2.4 | Y | N | E26 | 12 |
| FB11D4027ECCQ | LED FIL 4.5W B11 CL E12 27K CQ | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 3.8 | 1.4 | Y | N | E12 | 12 |
| FG16D4027EFCQ | LED FIL 4.5W G16 FR E12 27K CQ | 4.5 | 40 | 360 | 360° | 2700K | 15,000 | 90 | 3.4 | 2.0 | Y | N | E12 | 12 |
| FG16D4027ECCQ | LED FIL 4.5W G16 CL E12 27K CQ | 4.5 | 40 | 360 | 360° | 2700K | 15,000 | 90 | 3.4 | 2.0 | Y | N | E12 | 12 |
| FG25D4027FCQ | LED FIL 4.5W G25 FR E26 27K CQ | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 4.5 | 3.2 | Y | N | E26 | 12 |
| FG25D4027CCQ | LED FIL 4.5W G25 CL E26 27K CQ | 4.5 | 40 | 350 | 360° | 2700K | 15,000 | 90 | 4.5 | 3.2 | Y | N | E26 | 12 |
| FT1005D4027CCQ | LED FIL 5W T10 CL E26 27K CQ | 5 | 40 | 450 | 360° | 2700K | 15,000 | 90 | 5.3 | 1.2 | Y | N | E26 | 12 |
| FST19D4027CCQ | LED FIL 4.2W ST19 CL E26 27K CQ | 4.2 | 40 | 340 | 360° | 2700K | 15,000 | 90 | 5.4 | 2.5 | Y | N | E26 | 12 |

## Dimmer Compatibility

| E26 SUGGESTED DIMMER COMPATIBILITY | |
|---|---|
| MANUFACTURER | MODEL NUMBER |
| Leviton | R50-IPL06-10M |
| | R61-06674-P0I |
| Lutron | CTCL-153PDH-WH |
| | TGCL-153PH-WH |
| | DVWCL-153PH-WH |

| MR16 SUGGESTED DIMMER COMPATIBILITY | |
|---|---|
| MANUFACTURER | MODEL NUMBER |
| Leviton | Sureslide 6615P |
| Lutron | Diva DVLV-600P |
| | Divs DVELV-300P |
| | Skylark SLEV-300P |
| | Skylark SLV-600P |
| | Nova NELV-450 |
| | Nova NTELV-600 |
| | MALV-600 |
| | VERTI VTELV-600M |
| Cooper | DAL06P - All load dimmer |
| | SAL06P |

**TCP®**
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com
©TCP JUL 2025/WF312450

DAMP LOCATION

c UL us LISTED

RoHS COMPLIANT

3 YEAR WARRANTY
*Based on 12 hours use per day

5 YEAR WARRANTY
*Based on 12 hours use per day

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

| | |
|---|---|
| Sales: | Catalog Number: |
| Date: | Type: |
| Model: | Notes: |
| Project: | |
| Rep: | |

TCP® we know light.™

For more information on the quality and care TCP can deliver, call us at 800.324.1496 or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516