

# Product Discovery, Requirements, and Technical Design Specification

## CorbitChat Mobile Application for Jira Data Center

Proposed version: 1.0 | Default language: Persian | Target platforms: Android and iOS

Prepared for product analysis, design, development, and QA teams

**Architecture decision:** The mobile application should be a native or cross-platform client for Jira Data Center and the CorbitChat plugin. Jira remains the system of record, while the mobile experience is delivered through a dedicated Mobile API inside the existing Jira plugin. This allows chat, projects, boards, issues, comments, replies, dashboards, and push notifications to work with real Jira permissions and the existing CorbitChat data model.

## Table of Contents

- 1. Product Goal and Scope
- 2. Current Plugin Capabilities and Reusable Assets
- 3. Proposed System Architecture
- 4. Product Modules and Functional Requirements
- 5. Mobile UX Design and Screen Model
- 6. API, Data, Security, and Authentication
- 7. Push Notifications and Event Model
- 8. Non-Functional Requirements
- 9. Delivery Phases and Acceptance Criteria
- 10. Official References and UI Reference Appendix

## 1. Product Goal and Scope

The goal is to build a bilingual mobile application for Jira Data Center users. The application must provide enterprise chat, project access, board access, issue tracking, comments, replies, personal dashboards, notifications, and key Jira data in a mobile-first experience. It should not be a simple WebView wrapper around Jira. It should be fast, touch-friendly, readable, bilingual, and optimized for Persian/RTL as the default experience while also supporting English/LTR.

**Product principle:** Jira remains the primary system for records and permissions. The mobile app only displays data the current user is allowed to access, and every write operation must go through Jira permissions or CorbitChat plugin services.

## 1.1 Target Users

| User role                   | Primary mobile need                                     | Key scenarios                                                                                  |
|-----------------------------|---------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Regular user / team member  | View tasks, messages, comments, and notifications       | See today's tasks, reply to comments, chat with colleagues, receive mention push notifications |
| Project manager             | Track boards, members, overdue work, and project status | View project board, filter overdue tasks, open project chat, review team workload              |
| Executive / manager         | Use a summary dashboard and monitor activity            | View projects, open issue counts, important notifications, and recent project reports          |
| Jira / plugin administrator | Control configuration, access, and system health        | Manage push settings, field display rules, version status, and diagnostics                     |

## 1.2 Version 1.0 Scope

- Secure login to Jira Data Center and optional support for one or more Jira instances if required by the organization.
- Personal dashboard with unread messages, today's tasks, overdue tasks, follow-up tasks, and active colleagues.
- Full chat experience: direct chat, group chat, project chat, Jira Assistant, replies, reactions, attachments, voice messages, read receipts, and mentions.
- Project list and project detail pages with project metadata, members, boards, issues, and project chat.
- Scrum/Kanban board access with a mobile-friendly board mode, columns, cards, filters, and issue drill-down.
- Complete issue detail view including summary, description, status, assignee, reporter, priority, due dates, custom fields, attachments, comments, replies, worklogs, and selected history/activity.
- Native Jira comments, comment replies, automatic parent-author mentions, reply attachments, and compatibility with the Jira web UI.
- Server-driven field formatting and color rules without requiring a mobile app release for every display rule change.
- Push notifications for messages, mentions, assignments, status changes, replies, overdue tasks, and Jira Assistant events.
- Bilingual Persian/English support with Persian as the default language, full RTL support, and a language switch in settings.

## 1.3 Out of Scope for Version 1.0

- Replacing the full Jira desktop UI or implementing all Jira administration features in the mobile app.
- Editing every complex custom field type in the first release. Full field visibility is mandatory, but full field editing can be delivered incrementally.
- Complete offline-first support for write operations. Version 1.0 should include read caching and draft preservation for messages and comments.
- Rebuilding Jira's workflow rule engine. The mobile app should consume permitted Jira transitions and operations.

## 2. Current Plugin Capabilities and Reusable Assets

According to the current CorbitChat architecture document, CorbitChat is a P2 plugin for Jira Data Center 9.x. It uses Active Objects, Spring-wired services, REST modules, chat services, Web Push, Board Gallery, Jira Assistant, and native Jira comment reply enhancements. This means a large part of the required product logic already exists inside Jira and should be reused rather than reimplemented from scratch.

| Existing asset                                             | Mobile reuse                                        | Required change                                                                        |
|------------------------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------------------------------|
| Conversation / Message / Attachment / Reaction / ReadState | Yes, core mobile chat model                         | Add mobile-oriented DTOs, pagination/cursors, and mobile-friendly endpoints            |
| Project Chat                                               | Yes, official chat inside each Jira project         | Expose as a project tab and support notification deep links                            |
| Jira Assistant                                             | Yes, Jira activity center inside chat               | Add mobile event types and quick actions such as mark as seen                          |
| Board Gallery                                              | Yes, board and project entry point                  | Convert desktop card grid logic into API and mobile UI                                 |
| Comment Reply                                              | Yes, but desktop DOM logic is not reusable directly | Move shared reply behavior into REST/services; mobile must not manipulate Jira web DOM |
| Browser Web Push                                           | Not sufficient for native mobile                    | Add FCM/APNs or a push relay for Android and iOS                                       |
| Admin settings and Access Policy                           | Yes                                                 | Extend for mobile settings, device tokens, and field formatting rules                  |

## 3. Proposed System Architecture

**Main recommendation:** The best architecture is a Mobile BFF inside the existing Jira plugin. The mobile app talks to dedicated plugin endpoints, and the plugin uses Jira Java API, Jira REST, Active Objects, and existing CorbitChat services.

With this model, the mobile app behaves as a first-class Jira integration without being forced to consume raw Jira endpoints directly. The Mobile API returns small, paginated, permission-aware, cacheable, UI-ready payloads.

### 3.1 Main Components

| Layer      | Responsibility                                           | Recommended technology                                                       |
|------------|----------------------------------------------------------|------------------------------------------------------------------------------|
| Mobile App | UI, cache, push registration, secure storage, deep links | Flutter or React Native; Flutter is recommended for stable RTL and custom UI |

|                          |                                                            |                                                                           |
|--------------------------|------------------------------------------------------------|---------------------------------------------------------------------------|
| Mobile API inside plugin | Mobile REST APIs, DTOs, permission checks, aggregation     | Jira P2 REST module: /rest/corbit-mobile/1.0/*                            |
| CorbitChat Services      | Chat, messages, groups, projects, attachments, read states | Existing plugin services                                                  |
| Jira Integration Layer   | Issues, projects, boards, comments, worklogs, transitions  | Jira Java API for P2 app logic and Jira REST/Agile REST where appropriate |
| Persistence              | Chat, push tokens, settings, formatting rules, sessions    | Active Objects + PluginSettings                                           |
| Push Provider            | Mobile push delivery                                       | FCM for Android and APNs or Firebase Messaging for iOS                    |

### 3.2 Why a Dedicated Mobile API Instead of Direct Jira REST Consumption

| Option                        | Benefits                                                                                     | Risks / weaknesses                                                                                              | Conclusion                                     |
|-------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Direct Jira REST from mobile  | Fast initial start, fewer plugin changes                                                     | Complex auth, large payloads, scattered endpoints, difficult push handling, risk of exposing unnecessary fields | Acceptable only for a small PoC                |
| Mobile API inside plugin      | Secure, permission-aware, controllable, cache-friendly, and aligned with existing chat logic | Requires backend development inside the plugin                                                                  | Recommended approach                           |
| Separate backend outside Jira | Greater scale and independent control                                                        | Contradicts the current requirement that Jira acts as backend; adds deployment and trust complexity             | Only consider if push/scale demands require it |

### 3.3 Recommended Data Flow

- After login, the mobile app calls /mobile/bootstrap to load the user profile, language settings, unread counts, feature flags, and device capabilities.
- The dashboard is loaded through one aggregated endpoint to avoid many expensive startup calls to Jira.
- Issue lists use cursor/page pagination and field projection; issue detail uses controlled expansion.
- Chat uses the existing Conversation/Message model, but responses are normalized for mobile.
- Push notifications should carry only a safe event identifier and summary; the app loads full details from the Mobile API after opening.

## 4. Product Modules and Functional Requirements

### 4.1 Login, Server Selection, and User Profile

- Login screen with Jira URL, organization-approved authentication method, language, and connection test.

- Secure token/session storage in iOS Keychain and Android Keystore.
- Profile view with display name, avatar, presence, accessible projects, and last sync time.
- Full logout and device token revocation from the plugin side.

## 4.2 User Dashboard

The dashboard should be the operational first screen of the app. It can be inspired by the reference screenshots, but it should have its own CorbitChat/Jira-centered design.

| Card / section        | Data                                                                         | Behavior                                   |
|-----------------------|------------------------------------------------------------------------------|--------------------------------------------|
| New messages          | Unread direct/group/project/bot conversations                                | Tap opens chat list or Jira Assistant      |
| Today's tasks         | JQL: assignee=currentUser AND due=today or organization-specific date fields | Tap opens filtered issue list              |
| Overdue tasks         | due < now and statusCategory != Done                                         | Warning color and sort by overdue duration |
| Follow-up tasks       | Watching, mentioned, assigned, recently updated                              | Show quick actions                         |
| Colleagues            | Active members in shared projects and recent chats                           | Start chat or view profile                 |
| Recent reports/events | Assistant events and activity feed                                           | Mark seen and deep link to issue           |

## 4.3 Chat

- Conversation list with All, Personal, Groups, Projects, and Assistant tabs.
- Conversation/user search, direct chat creation, group creation, and member management with Access Policy enforcement.
- Message rendering with Persian/English text, emoji, reactions, replies, edit/delete, forward, pinned messages, and read receipts.
- Attachments including images, files, audio, and voice messages; preview and download must enforce permissions.
- Mention typeahead and [~username] token support for Jira compatibility.
- Project Chat as the official conversation for each project, accessible from project pages, boards, and issue screens.

## 4.4 Projects

- List accessible projects with avatar, key, name, lead, open issue count, and unread project chat count.
- Project detail page with Overview, Board, Issues, Chat, Members, and Activity tabs.
- Project overview with high-level status, overdue items, assigned-to-me items, recently updated issues, and board links.
- Project members with avatar, presence, role, and shortcut to direct chat.

## 4.5 Project Board

The mobile board should not simply shrink the desktop board. It should provide two modes: a column-based Kanban/Scrum mode for larger screens and a List by Status mode for daily mobile use.

| Capability      | Description                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------------------|
| Board Directory | List boards accessible to the current user with search and Scrum/Kanban filtering.                                       |
| Board View      | Horizontally scrollable columns, count per column, quick filters, and pull-to-refresh.                                   |
| List View       | Group issues by status for small screens; faster and more readable than full columns.                                    |
| Sprint Support  | Show active/future/closed sprints and filter issues by sprint.                                                           |
| Card Fields     | Summary, key, status, assignee avatars, priority, due date, attachment/comment count, and server-defined colored fields. |
| Quick Actions   | Open issue, perform allowed status transition, assign to me, quick comment, and open project chat.                       |

## 4.6 Complete Issue Detail

The issue detail screen is the most important non-chat screen. The user must be able to see the complete task information, not only summary and status. The display should be field-driven so organization-specific custom fields can appear without app changes.

| Section            | Content                                                   | Behavior                                                        |
|--------------------|-----------------------------------------------------------|-----------------------------------------------------------------|
| Header             | Issue key, summary, issue type, priority, status, project | Colored status and transition menu if allowed                   |
| People             | Assignee, reporter, watchers, participants                | Tap for profile/chat                                            |
| Dates              | Created, updated, due, resolution, sprint dates           | Persian or Gregorian date formatting based on language/settings |
| Description        | Rendered Jira body                                        | Secure HTML/wiki-rendered display with links and images         |
| Fields             | All visible system/custom fields                          | Grouping, search in fields, colored display rules               |
| Comments           | Comments, reply badges, attachments, mentions             | Send comment/reply and auto-mention parent author               |
| Attachments        | Files and images                                          | Preview/download/upload if permitted                            |
| Worklog            | Worklog list and time entry if allowed                    | Phase 1 display, Phase 2 create/edit                            |
| History / Activity | Status, assignee, field, and comment changes              | Filter important activity                                       |

## 4.7 Issue Comments and Replies

- Comments must be created as native Jira comments so Jira's own notifications and audit behavior remain active.

- Replies must preserve the parent comment context, automatically mention the parent author, and store a recognizable quote/preview contract in the comment body or metadata.
- If the current plugin stores replies through Jira wiki quote syntax, the mobile app should follow the same contract so desktop and mobile understand each other.
- After a reply is posted, Jira Assistant should generate the corresponding event and push notification for the mentioned user.

## 4.8 Field Formatting and Color Rules

Field display rules must not be hard-coded in the mobile app. The plugin should expose a Field Display Rules API that defines how each field should be formatted, colored, badged, or iconized.

| Rule type       | Example                    | Mobile display              |
|-----------------|----------------------------|-----------------------------|
| Value mapping   | Priority = Highest         | Red badge with warning icon |
| Status category | Done / In Progress / To Do | Standard status colors      |
| Date threshold  | dueDate < now              | Red overdue indicator       |
| Numeric range   | progress >= 80             | Green progress bar          |
| Text pattern    | field contains VIP         | Special label               |
| User field      | assignee = currentUser     | Subtle highlight on card    |

## 5. Mobile UX Design and Screen Model

### 5.1 UI Principles

- Persian and RTL are the default; English and LTR are supported through language settings.
- Use bottom navigation for primary screens: Dashboard, Chat, Projects, Tasks, More.
- Use a drawer or More menu for Settings, Colleagues, Notifications, About, and Logout.
- Use short operational cards on the dashboard; avoid heavy text on the first screen.
- Issue cards should be dense but readable: key, two-line summary, status, assignee, due date, and badges.
- For boards, List View should be the default mobile view, while Board Columns should be an alternate mode.
- Every screen must include loading, empty, error, no-permission, and retry states.

### 5.2 Screen Map

| Screen         | Input                              | Main output/action                          |
|----------------|------------------------------------|---------------------------------------------|
| Login / Server | Jira URL and authentication method | Connect, receive bootstrap, register device |
| Dashboard      | Bootstrap + dashboard summary      | Open task list, chat, project, issue        |
| Chats          | Conversation list                  | Open conversation, create chat/group        |
| Conversation   | conversationId                     | Send message, reply, attach, react          |
| Projects       | Project list                       | Open project detail                         |

|                |                    |                                                |
|----------------|--------------------|------------------------------------------------|
| Project Detail | projectKey         | Overview, Board, Issues, Chat, Members         |
| Board          | boardId/projectKey | Show cards, filter, open issue                 |
| Issue List     | JQL/filter context | Sort, filter, open issue                       |
| Issue Detail   | issueKey           | Comment/reply, transition, attachment, worklog |
| Notifications  | Event feed         | Mark seen, deep link                           |
| Settings       | User preferences   | Language, notifications, cache, logout         |

## 6. API, Data, Security, and Authentication

### 6.1 Recommended Authentication Options

For an enterprise deployment, three authentication paths are possible. The final decision must depend on the organization's security policy, whether Jira is accessible from mobile networks/VPN, and the capabilities enabled in the Jira Data Center instance.

| Method                         | Description                                                                 | Benefit                                               | Risk / note                                             |
|--------------------------------|-----------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------|
| PAT                            | The user creates a Personal Access Token and stores it in the app           | Simple and officially supported for REST integrations | Weaker UX; users must manage tokens                     |
| OAuth 2.0 / enterprise SSO     | Login through the official identity flow and revocable tokens               | Best enterprise option if enabled                     | Requires careful Jira/IdP configuration                 |
| Mobile Session Token in plugin | After secure login, the plugin issues short-lived access and refresh tokens | Better UX and full plugin-side control                | Requires strong security design, audit, and revoke flow |

**Execution recommendation:** For an internal MVP, start with PAT if accepted by the organization. For a mature product, implement Mobile Session Tokens inside the plugin or use OAuth/SSO. In every case, all endpoints must resolve the current user and execute operations through Jira permissions.

### 6.2 Proposed Mobile API Endpoints

| Group     | Proposed endpoint                     | Description                                                      |
|-----------|---------------------------------------|------------------------------------------------------------------|
| Bootstrap | GET /rest/corbit-mobile/1.0/bootstrap | Profile, language, feature flags, unread counts, mobile settings |
| Dashboard | GET /mobile/dashboard                 | Dashboard cards, counts, recent activity, colleagues             |
| Projects  | GET /mobile/projects                  | Accessible projects with status summary                          |



|              |                                                 |                                                                 |
|--------------|-------------------------------------------------|-----------------------------------------------------------------|
| Project      | GET /mobile/projects/{key}                      | Project details, boards, members, summary                       |
| Boards       | GET /mobile/boards                              | Accessible board list with filters                              |
| Board Issues | GET /mobile/boards/{id}/issues                  | Paginated issue cards for board/column/sprint                   |
| Issues       | POST /mobile/issues/search                      | Controlled JQL search, filters, sort, projection                |
| Issue Detail | GET /mobile/issues/{key}                        | All fields, rendered fields, comments, attachments, transitions |
| Comments     | POST /mobile/issues/{key}/comments              | Create native Jira comment                                      |
| Reply        | POST /mobile/issues/{key}/comments/{id}/replies | Reply with automatic mention and desktop-compatible contract    |
| Transitions  | GET/POST /mobile/issues/{key}/transitions       | Show and execute allowed transitions                            |
| Worklog      | GET/POST /mobile/issues/{key}/worklogs          | Show/create worklogs if permitted                               |
| Chat         | GET/POST /mobile/conversations/*                | Mobile wrapper around existing CorbitChat REST                  |
| Push         | POST /mobile/devices                            | Register device token and platform                              |
| Formatting   | GET /mobile/field-display-rules                 | Field color and formatting rules                                |

## 6.3 Additional Active Objects Data Model

| Entity              | Purpose                                           | Key fields                                                           |
|---------------------|---------------------------------------------------|----------------------------------------------------------------------|
| JimMobileDevice     | Register devices and push tokens                  | userKey, platform, deviceId, pushTokenHash, enabled, lastSeenAt      |
| JimMobileSession    | Manage sessions/tokens if this option is selected | userKey, tokenHash, refreshHash, expiresAt, revokedAt, deviceId      |
| JimMobilePreference | Language and notification preferences             | userKey, language, quietHours, notificationLevel                     |
| JimFieldDisplayRule | Field color and formatting rules                  | fieldId, conditionType, conditionValue, color, icon, label, priority |
| JimMobileSyncCursor | Lightweight sync for dashboard/chat/activity      | userKey, scope, cursorValue, updatedAt                               |
| JimMobileAudit      | Audit sensitive mobile operations                 | userKey, action, entityType, entityId, ip, createdAt                 |

## 6.4 Security and Permissions

- No mobile endpoint may return data based only on an identifier. The user and permission context must always be checked.
- Issue/project/board operations must use native Jira permissions such as Browse Project and Edit Issue.
- Chat operations must use JimAccessPolicyService, membership checks, and existing conversation permissions.

- Tokens and device tokens must be stored as hashes or encrypted values; raw tokens must never be written to logs.
- All communication must use HTTPS. Certificate pinning is optional but recommended for sensitive organizations.
- Push payloads should be minimal: title, event type, safe identifier, and no sensitive field content.
- All write operations, including comment, reply, transition, upload, send message, and mark read, should have minimal audit records.
- Rate limiting and abuse protection are required for login, message sending, file upload, and search.

## 7. Push Notifications and Event Model

The current browser Web Push implementation is sufficient for Jira web pages but not for a native mobile app. Native mobile push must be added separately. The practical recommendation is Firebase Cloud Messaging for Android and iOS, or APNs directly for iOS if the team prefers. The Jira plugin should act as the push sender unless the organization requires a separate push relay due to network restrictions.

| Event                   | Recipient                                     | Deep link                                    |
|-------------------------|-----------------------------------------------|----------------------------------------------|
| Direct message          | Other participant                             | corbitchat://conversation/{id}               |
| Group/project mention   | Mentioned users                               | corbitchat://conversation/{id}?message={mid} |
| Jira Assistant mention  | User mentioned in Jira comment                | corbitchat://issue/{key}?comment={id}        |
| Assignment              | New assignee                                  | corbitchat://issue/{key}                     |
| Important status change | Watcher/assignee or policy-defined recipients | corbitchat://issue/{key}                     |
| Comment reply           | Parent comment author and mentioned users     | corbitchat://issue/{key}?comment={id}        |
| Overdue task reminder   | Assignee                                      | corbitchat://issues?filter=overdue           |

### 7.1 Notification Preferences

- Enable/disable notifications for direct chats, groups, projects, Assistant, assignments, and reminders.
- Quiet hours and mute settings for conversations or projects.
- Notification detail level: full text, sender/issue key only, or generic notification.
- Global badge count and per-tab badge count.

## 8. Non-Functional Requirements

| Area        | Requirement                                                                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Performance | Dashboard should load in under 2 seconds on a normal internal network; issue detail should load in under 3 seconds with pagination for comments/activity. |
| Scalability | Endpoints must use pagination, field projection, and caching; heavy JQL queries without limits must be prevented.                                         |

|                 |                                                                                                                                            |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Jira DC Cluster | AO writes, push sending, and scheduled reminders must be cluster-safe; duplicate push events must be prevented through locks/fingerprints. |
| Reliability     | Controlled retry for push and network failures; clear error states in the app.                                                             |
| Localization    | fa-IR default, en-US support, dynamic RTL/LTR, Persian/Gregorian date formatting based on settings.                                        |
| Accessibility   | Good contrast, readable typography, minimum 44px touch targets, and text scaling support.                                                  |
| Observability   | Structured logs and metrics for API latency, push success/failure, active devices, and error rate.                                         |
| Compatibility   | Recommended baseline: Android 10+ and iOS 14+, adjustable based on organizational requirements.                                            |

## 9. Delivery Phases and Acceptance Criteria

| Phase                          | Output                                                                              | Acceptance criteria                                                                              |
|--------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Phase 0 - Technical Spike      | Jira connection, login, bootstrap, one issue list, one conversation                 | Prove authentication, permissions, Android/iOS builds, and connection to a real Jira DC instance |
| Phase 1 - MVP Core             | Dashboard, chats, projects, read-only issue detail, basic push                      | User can send/receive messages, view projects/tasks, and receive push notifications              |
| Phase 2 - Jira Actions         | Comment/reply, transitions, attachments, worklog display, field rules               | Native comments are created, reply with mention works, colored fields are displayed              |
| Phase 3 - Board & Productivity | Mobile board, filters, sprint support, advanced dashboard, notification preferences | Project manager can track board status and overdue work from mobile                              |
| Phase 4 - Hardening            | Security, audit, cluster behavior, performance, admin mobile settings               | Load, security, network interruption, and multi-node Jira DC tests pass                          |

### 9.1 Technical Definition of Done

- Every mobile endpoint has positive and negative permission tests.
- Every API has standard pagination/limit handling and a consistent error contract.
- No sensitive data is sent to logs, push payloads, or crash reports.
- Every screen implements loading, empty, error, no-permission, and retry states.
- RTL Persian and LTR English are tested across all main screens.
- Push is tested on Android and iOS in foreground, background, and terminated states.
- Comment/reply works correctly in Jira web UI and generates Jira Assistant events.
- API documentation and release notes are updated with each delivery phase.

## 10. Official Technical References

This specification is based on the current CorbitChat architecture document and official Atlassian documentation for Jira Data Center REST APIs, Jira integrations, REST structure, authentication, webhooks, boards, issues, and search APIs.

- Jira Data Center REST API reference: <https://developer.atlassian.com/server/jira/platform/rest/v11002/>
- Jira Data Center platform REST API reference 9.14: <https://docs.atlassian.com/software/jira/docs/api/REST/9.14.0/>
- Integrating with Jira Data Center: <https://developer.atlassian.com/server/jira/platform/integrating-with-jira-server/>
- About Jira Server REST APIs: <https://developer.atlassian.com/server/jira/platform/about-the-jira-server-rest-apis/>
- Using Personal Access Tokens for Atlassian Data Center: <https://confluence.atlassian.com/enterprise/using-personal-access-tokens-1026032365.html>

## Appendix A - UX Reference Screenshots

The following screenshots are used as inspiration for information structure, dashboard, menu, board, and chat behavior. The final product design should maintain an independent CorbitChat identity and respect Jira Data Center constraints; it should not copy this UI directly.

|                                                                                                                                  |                                                                                                                         |
|----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <p><b>Current Jira / CorbitChat chat</b></p>  | <p><b>Mobile project board</b></p>  |
| <p><b>User dashboard</b></p>                                                                                                     | <p><b>Project group and activity</b></p>                                                                                |



Side menu



Project task list



## Appendix B - Risks and Open Decisions

| Risk / decision                 | Impact                                               | Recommendation                                                            |
|---------------------------------|------------------------------------------------------|---------------------------------------------------------------------------|
| Authentication method selection | Direct impact on security, UX, and delivery timeline | Spike at the start of Phase 0 using the real organizational Jira instance |
| Mobile access to Jira           | If Jira is internal-only, login and push             | Decide between VPN/MDM or secure                                          |

|                          |                                               |                                                                           |
|--------------------------|-----------------------------------------------|---------------------------------------------------------------------------|
|                          | become more complex                           | reverse proxy                                                             |
| Complex custom fields    | Full display is easier than full editing      | Version 1.0 should display all fields and introduce editing incrementally |
| Push in a closed network | FCM/APNs require outbound internet access     | Consider Push Relay or MDM notification if restricted                     |
| Jira DC cluster          | Duplicate events/push notifications may occur | Use fingerprinting, cluster locks, and AO-based deduplication             |