Service Delivery Calculator API – Service Standards

USPS Web Tools™

Application Programming Interface

User Guide

Version 3.13 (03/25/2025)



Table of Contents

1.0	Intro	oduction to Web Tools	
		Before you get started:	
		GetLocations API	
2.	1	Overview	3
		API Signature Table	3
2.2	2	Request Descriptions	3
	2.2.1	Sample Request	7
2.3	3	Response Descriptions	7
	2.3.1	Sample Response	16

1.0 Introduction to Web Tools

See the <u>Developers Guide</u> to learn the administrative process for gaining access to the Web Tools APIs as well as the basic mechanism for calling the APIs and processing the results. The Developer's Guide also contains information on testing and troubleshooting.

Note: The Request Parameter sections present the XML input tags for generating live requests along with the restrictions on the values allowed. An error message will be returned if an incorrect value is entered. Also, be aware of the maximum character amounts allowed for some tags. If the user enters more than those amounts, an error will not be generated. The Web Tool will simply pass in the characters up to the maximum amount allowed and disregard the rest. This is important since the resulting value could prevent a correct response.

When building the XML request, pay attention to the order and case for tags. An error message will be returned if an incorrect value is entered. Remember that all data and attribute values in this document are for illustration purposes and are to be replaced by your actual values. For instance, a line of sample code may be:

<DestinationZIP>12345</DestinationZIP>

In this instance, you will replace "12345" with the destination zip code for your request.

1.1 Before you get started:

For information on registering and getting started with Web Tools, please refer to the Step-By-Step guide found on the Web Tools <u>Technical Documentation Page</u>.

2.0 SDCGetLocations API

2.1 Overview

The SDCGetLocations Web Tools API allows customers to get estimates on delivery standards between 3- or 5-digit Zip Codes for Priority Mail Express, Priority Mail, First Class Mail, Marketing Mail, Periodicals, and Package Services. The data returned by the API is intended for display only. The content or sequence of the string data returned in the API response may change.

2.1.1 API Signature Table

Scheme	Host	Path	API	XML
https://	secure.shippingapis.com	/shippingapi.dll?	API=SDCGetLocations	&XML=(see below)

Note: GET HTTP requests have length restrictions, whereas POST HTTP requests do not. Please take this under consideration when determining the request-response method that you choose.

2.2 Request Descriptions

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRequest	Required	API=SDCGetLocations	(Alias)	
SDCGetLocationsRequest / USERID		This attribute specifies your Web Tools user ID. See the <u>Developer's Guide</u> for information on obtaining your USERID.	NMTOKEN	
		For Example: USERID="XXXXXXX"		

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRequest / PASSWORD		This attribute specifies your Web Tools password. See the <u>Developer's Guide</u> for information on your Password. For Example: PASSWORD="XXXXXXXX"	NMTOKEN	

SDCGetLocationsRequest Required / MailClass		lass for commitment data. For ilClass>0 <mailclass></mailclass>	String	minOccurs="1" maxOccurs="1" Enumerations=
	Mail Class Value	Description		• 0 • 000
	0	All Mail Classes (1-digit)		• 9000
	000	All Mail Classes (1-digit) All Mail Classes (3-digit)		• 9000
	9000	All HAZMAT Mail Classes		• 9001
	3000	(4-digit)		• 2
	1	Priority Mail Express		• 9002
	9001	Priority Mail Express		• 201
		HAZMAT		• 201 • 202
	2	Priority Mail		• 202 • 203
	9002	Priority Mail HAZMAT		• 204
	201	Priority Mail 1-Day		• 9204 • 9204
		(Deprecated)		• 205
	202	Priority Mail 2-Day]	• 9205
		(Deprecated)		• 206
	203	Priority Mail 3-Day]	• 9206 • 9206
		(Deprecated)		• 3
	204	Priority Mail Military		• 301
	9204	Priority Mail Military		• 301
		HAZMAT		• 303
	205	Priority Mail DPO		• 303
	9205	Priority Mail DPO HAZMAT		• 304
	206	Priority Mail Offshore		• 9304
	9206	Priority Mail Offshore		• 4
		HAZMAT		• 401
	3	USPS Ground Advantage		• 402
	004	(up to 15.999 oz)		• 403
	301	First-Class Mail Letters		• 404
	302	First-Class Mail Flats		• 5
	303	First-Class Mail Cards		• 501
	304	USPS Ground Advantage		• 502
	9304	(up to 15.999 oz) USPS Ground Advantage		• 6
	9304	(up to 15.999 oz)		• 602
		HAZMAT		• 603 • 604
	4	Standard Mail		• 605
	401	Standard Mail Letters		• 7
	402	Standard Mail Flats		• 9007
	403	Standard Mail Marketing Parcels		• 9
	404	Standard Mail Simple		• 9009
		Samples		
	5	Periodicals		
	501	Periodicals	1	
	502	Parcel Shaped Periodicals	1	
	6	Package Services	1	
	6	USPS Ground Advantage,	1	
		LIVES, Offshore		
	602	Standard Post]	
	603	Media Mail		

Tag Name	Occurs	Description		Туре	Validation
		604 605 7 9007 9	Library Mail Bound Printed Matter Parcel Select Parcel Select HAZMAT USPS Ground Advantage (1 to 70lbs) USPS Ground Advantage (1 to 70lbs) HAZMAT		
SDCGetLocationsRequest / OriginZIP	Required	characters. For example:	be valid. May be 3, 5, or 9	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRequest / DestinationZIP	Required	code. For example:	be a valid 5-character zip P>54324	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRequest / AcceptDate	Optional	date may be up Defaults to sys Enter the date For example:	will be mailed. Acceptance p to 30 days in advance. stem date. in format: dd-mmm-yyyy.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRequest / AcceptTime	Optional	facility. Default returned when request will be Enter the time For example:	will be accepted at a postal as to system time. Default value no value is included in the current time CT. in format: HHMM	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRequest / NonEMDetail	Optional	mail classes w For example:	onal detail for Non-Expedited hen 'True.' Default='False' il>True	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRequest / NonEMOriginType	Optional	shipments: Valid Values: "1" = Local Ma "2" = Destination For example:	icator for non-Expedited il on Entered Mail nType>1	String	minOccurs="0" maxOccurs="1" Enumeration • 1 • 2

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRequest / NonEMDestType	Optional	Destination type indicator for non-Expedited shipments: Valid Values: "1" = PO-Addressee - Street "2" = PO-Addressee - PO Box "3" = Hold for pickup For example: <nonemdesttype>1</nonemdesttype>	String	minOccurs="0" maxOccurs="1" Enumeration • 1 • 2 • 3
SDCGetLocationsRequest / Weight	Optional	Item weight. For future use.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRequest / SortationLevel	Optional	Value "PST" used to indicate presort service standards for First-Class Mail. For example: <sortationlevel>PST</sortationlevel>	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRequest	Required once		(Alias)	

2.2.1 Sample Request

Request: SDCGetLocations:

- <SDCGetLocationsRequest USERID="XXXXXXXXX" PASSWORD="">
- <MailClass>0</MailClass>
- <OriginZIP>63123</OriginZIP>
- <DestinationZIP>20770</DestinationZIP>
- <AcceptDate>5/26/2021</AcceptDate>
- <AcceptTime>0900</AcceptTime>
- <NonEMDetail>True</NonEMDetail>
- <NonEMOriginType>1</NonEMOriginType>
- <NonEMDestType>1</NonEMDestType>
- <SortationLevel> </SortationLevel>
- </SDCGetLocationsRequest>

2.3 Response Descriptions

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e	Required		(Alias)	
SDCGetLocationsRespons e / Release	Required	Release version	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / CallerID	Required	Caller ID	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / MailClass	Required	MailClass from request	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / OriginZIP	Required	OriginZIP from request	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / OriginCity	Required	Origin City	String	minOccurs="0" maxOccurs="1"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / OriginState	Required	Origin State	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / DestZIP	Required	DestinationZIP from request	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / DestCity	Required	Destination City	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / DestState	Required	Destination State	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / AcceptDate	Required	Acceptance date at postal facility	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / AcceptTime	Required	Acceptance time at postal facility	String	minOccurs="1" maxOccurs="1"
SDCGetLocationsRespons e / Weight	Optional	Weight from request	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / SortationLevel	Optional	SortationLevel from request	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited	Optional	Groups Priority Mail Express Mail and Priority Mail Commitments and Scheduled Delivery Dates. Appears where applicable: SDCGetLocationsRequest [MailClass='0' or MailClass='1']	(Group)	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / EAD	Optional	Effective Acceptance Date	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment	Optional, repeatin g up to unbound ed times	Groups Priority Mail Express commitment information	(Group)	minOccurs="0" maxOccurs="unboun ded"
SDCGetLocationsRespons e / Expedited / Commitment / MailClass	Optional	Mail Class indicator for Priority Mail Express. Value = "1"	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / CommitmentName	Optional	Commitment Name Valid Values: 1-Day 2-Day 3-Day DPO Military Note: If a scenario exceeds a 3-day commitment then no value will be returned in the response field	String	minOccurs="0" maxOccurs="1" Enumeration= • 1-Day • 2-Day • 3-Day • DPO • Military
SDCGetLocationsRespons e / Expedited / Commitment / CommitmentTime	Optional	Commitment Time. Value will only be returned for Priority Mail Express.	String	minOccurs="0" maxOccurs="1" Enumeration= • 1800

Tag Name	Occurs	Description		Туре	Validation	
SDCGetLocationsRespons e / Expedited /	Optional	Commitment Sequence Valid Values:		String	minOccurs="0" maxOccurs="1"	
Commitment /		Seq #	Service Standard			
CommitmentSeq		A0118	1-Day at 6:00 PM			
		B0118	1-Day at 6:00 PM			
		A0218	2-Day at 6:00 PM			
		B0218	2-Day at 6:00 PM			
SDCGetLocationsRespons e / Expedited / Commitment / Location	Optional, repeatin g up to unbound ed times	Groups dro	p off location information	(Group)	minOccurs="0" maxOccurs="unboun ded"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / SDD	Optional	Scheduled Delivery Date		String	minOccurs="0" maxOccurs="1"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / COT	Optional	Cut-off Time		String	minOccurs="0" maxOccurs="1"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / FacType	Optional	Facility Type		String	minOccurs="0" maxOccurs="1" Enumeration= • POST OFFICE • PRIORITY MAIL EXPRESS COLLECTION BOX • AIR MAIL FACILITY	
SDCGetLocationsRespons e / Expedited / Commitment / Location / Street	Optional	Facility Stre	eet	String	minOccurs="0" maxOccurs="1"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / City	Optional	Facility City		String	minOccurs="0" maxOccurs="1"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / State	Optional	Facility State		String	minOccurs="0" maxOccurs="1"	
SDCGetLocationsRespons e / Expedited / Commitment / Location / ZIP	Optional	Facility Zip	Code	String	minOccurs="0" maxOccurs="1"	

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / Expedited / Commitment / Location / IsGuaranteed	Optional	Indicates if Guarantee is offered for Priority Mail Express. Valid Values "1" = Guaranteed "2" = No Guarantee "3" = Temporary No Guarantee	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment	Optional, repeatin g up to unbound ed times	Groups Priority Mail commitment information	(Group)	minOccurs="0" maxOccurs="unboun ded"
SDCGetLocationsRespons e / Expedited / Commitment / MailClass	Optional	Mail Class indicator for Priority Mail. Value = "2"	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / CommitmentName	Optional	Commitment Name	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / CommitmentTime	Optional	Commitment Time	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / CommitmentSeq	Optional	Commitment Sequence Valid Values:	String	minOccurs="0" maxOccurs="1"
Communicacy		Seq # Service Standard		
		C0100 1-Day Street		
		C0200 2-Day Street		
		C0300 3-Day Street		
		D0100 1-Day PO Box		
		D0200 2-Day PO Box		
		D0300 3-Day PO Box		
		E0100 1-Day HFPU		
		E0200 2-Day HFPU		
		E0300 3-Day HFPU		
SDCGetLocationsRespons e / Expedited / Commitment / Location	Optional, repeatin g up to unbound ed times	Groups drop off location information	(Group)	minOccurs="0" maxOccurs="unboun ded"
SDCGetLocationsRespons e / Expedited / Commitment / Location / SDD	Optional	Scheduled Delivery Date	String	minOccurs="0" maxOccurs="1"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / Expedited / Commitment / Location / COT	Optional	Cut-off Time	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / FacType	Optional	Facility Type. Valid Values: "POST OFFICE" "PRIORITY MAIL EXPRESS COLLECTION BOX" "AIR MAIL FACILITY"	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / Street	Optional	Facility Street	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / City	Optional	Facility City	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / State	Optional	Facility State	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / ZIP	Optional	Facility Zip Code	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / Expedited / Commitment / Location / IsGuaranteed	Optional	Indicates if Guarantee is offered. Valid Values "1" = Guaranteed "2" = No Guarantee "3" = Temporary No Guarantee	String	minOccurs="0" maxOccurs="1" Enumeration= 1 2 3
SDCGetLocationsRespons e / Expedited / Commitment / ExpeditedMessage	Optional	Holds a message code value for the customer explaining their delivery date when certain conditions are met: Valid Message Codes "1" = Over 200 Results "1001" = Destination Type not valid for APO/FPO/DPO Zip	String	minOccurs="0" maxOccurs="1" Enumeration= • 1 • 1001
SDCGetLocationsRespons e / Expedited / Commitment / ExpeditedTransMsg	Optional, repeatin g up to unbound ed times	Groups Priority Mail Express transportation messaging	(Group)	minOccurs="0" maxOccurs="unboun ded"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / Expedited / Commitment / ExpeditedTransMsg / MsgCode	Optional	Priority Mail Express transportation messaging code Valid Message Codes "TM100" = This is a Military/Embassy specific ZIP Code for an APO/FPO/DPO(Air/Army Post Office, Fleet Post Office or Diplomatic Post Office) "TM103" = Your shipment may be delayed due to transportation issues.	String	minOccurs="0" maxOccurs="1" Enumeration= • TM100 • TM103
SDCGetLocationsRespons e / Expedited / Commitment / ExpeditedTransMsg /Msg	Optional	Priority Mail Express transportation messaging text. For example: <msg>Your shipment may be delayed due to transportation issues.</msg>	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited	Optional	Groups Non-Expedited Mail Class elements (appears where applicable: SDCGetLocationsRequest[MailClas s=0]) *Note: If this is a Hold for Pickup section then all elements from SDCGetLocationsResponse/NonEx pedited/EAD through SDCGetLocationsResponse/NonEx pedited/NonExpeditedExceptions/ NonExpeditedWTMsg will not be returned.	(Group)	minOccurs="0" maxOccurs="unboun ded"
SDCGetLocationsRespons e / NonExpedited / MailClass	Optional	Mail Class.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / NonExpeditedDestType	Optional	Destination Type. Valid Values "1" PO-Addressee - Street "2" PO-Addressee - PO Box "3" HFPU	String	minOccurs="0" maxOccurs="1" Enumeration= • 1 • 2 • 3
SDCGetLocationsRespons e / NonExpedited / EAD	Optional	Effective Acceptance Date.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / SvcStdDays	Optional	Service Standard Days.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / SchedDlvryDate	Optional	Scheduled Delivery Date.	String	minOccurs="0" maxOccurs="1"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / NonExpedited / HFPU	Optional, repeatin g up to one time	Groups Hold for Pickup information. If not present, then a HFPU Service Standard is not available.	(Group)	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / EAD	Optional	Effective Acceptance Date.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / COT	Optional	Cut-off Time.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard	Optional, repeatin g up to one time	Groups Hold for Pickup Service Standard Elements.	(Group)	minOccurs="0" maxOccurs="2"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / SvcStdMsg	Optional	Service Standard Message.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / SvcStdDays	Optional	Service Standard Days.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location	Optional, repeatin g up to 40 times	Groups Hold for Pickup Location information.	(Group)	minOccurs="0" maxOccurs="40"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / SchedDlvryDate	Optional	Scheduled Delivery Date.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / NonDeliveryDays	Optional	Non-Delivery Days.	String	minOccurs="0" maxOccurs="40"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / RAUName	Optional	RAU Name.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / Street	Optional	RAU Street Address.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / ZIP	Optional	Facility Zip Code.	String	minOccurs="0" maxOccurs="1"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes	Optional	Groups Close times by day of the week for Hold for Pickup location.	(Group)	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / M	Optional	Close Time for Monday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / Tu	Optional	Close Time for Tuesday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / W	Optional	Close Time for Wednesday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / Th	Optional	Close Time for Thursday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / F	Optional	Close Time for Friday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / Sa	Optional	Close Time for Saturday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / Su	Optional	Close Time for Sunday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / CloseTimes / H	Optional	Close Time for Holiday.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / NonExpeditedExceptions	Optional	Groups Hold for Pickup Location Exception Elements.	(Group)	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / NonExpeditedExceptions / NonExpeditedMsg	Optional	Additional exception messaging. Valid Message Codes "00133" = SDD Cannot be Calculated.	String	minOccurs="0" maxOccurs="unboun ded" Enumeration= • 00133

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / City	Optional	RAU City.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / ServiceStandard / Location / State	Optional	RAU State.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / HFPUGlobalExcept	Optional	Groups Hold for Pickup Exception Elements.	(Group)	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / HFPUGlobalExcept / PostCOT	Optional	Indicates if the mailpiece arrived after the Cut-Off Time.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / HFPUGlobalExcept / OverMaxResults	Optional	Indicates if more than the number of returned Hold for Pickup locations was found.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / HFPUGlobalExcept / NoHFPULocInd	Optional	Indicates if there were no locations found in the RAU that support Hold for Pickup	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPU / HFPUGlobalExcept / NonExpeditedWTMsg	Optional	Additional exception messaging. Valid Message Codes O0133 SDD Cannot be Calculated O0135 SSD lists OD Pair but is missing the Service Standard	String	minOccurs="0" maxOccurs="unboun ded" Enumeration= • 00133 • 00135
SDCGetLocationsRespons e / NonExpedited / HFPUGlobalExcept / NonExpeditedTransMsg	Optional, repeatin g up to unbound ed times	Groups Non-Expedited Mail transportation messaging.	(Group)	minOccurs="0" maxOccurs="unboun ded"
SDCGetLocationsRespons e / NonExpedited / HFPUGlobalExcept / NonExpeditedTransMsg / MsgCode	Optional	Non-Expedited Mail transportation messaging code.	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e / NonExpedited / HFPUGlobalExcept / NonExpeditedTransMsg /	Optional, repeatin g up to unbound ed times	Non-Expedited transportation messaging text.	String	minOccurs="0" maxOccurs="unboun ded"

Tag Name	Occurs	Description	Туре	Validation
SDCGetLocationsRespons e / NonExpedited / NonExpeditedExceptions / NonExpeditedTransMsg/ MsgCode	Optional	Groups Non-Expedited transportation messaging. Valid Message Code "TM103" = Your shipment may be delayed due to transportation issues.	(Group)	minOccurs="0" maxOccurs="1" Enumeration • TM103
SDCGetLocationsRespons e / NonExpedited / NonExpeditedExceptions / NonExpeditedTransMsg / Msg	Optional	Non-Expedited transportation messaging code. For example: <msg>Your shipment may be delayed due to transportation issues.</msg>	String	minOccurs="0" maxOccurs="1"
SDCGetLocationsRespons e	Required		(Alias)	

2.3.1 Sample Response

Response: SDCGetLocations:

- <SDCGetLocationsResponse>
- <Release>2.0</Release>
- <CallerID>4</CallerID>
- <SourceID>004</SourceID>
- <MailClass>0</MailClass>
- <OriginZIP>63123</OriginZIP>
- <OriginCity>SAINT LOUIS</OriginCity>
- <OriginState>MO</OriginState>
- <DestZIP>20770</DestZIP>
- <DestCity>GREENBELT</DestCity>
- <DestState>MD</DestState>
- <AcceptDate>2021-05-26</AcceptDate>
- <AcceptTime>0900</AcceptTime>
- <NonExpeditedOriginType>1</NonExpeditedOriginType>
- <Expedited>
- <EAD>2021-05-26</EAD>
- <Commitment>
- <MailClass>1</MailClass>
- <CommitmentName>1-Day</CommitmentName>
- <CommitmentTime>1800</CommitmentTime>
- <CommitmentSeq>A0118</CommitmentSeq>
- <Location>
- <SDD>2021-05-27</SDD>
- <COT>1730</COT>
- <FacType>POST OFFICE</FacType>
- <Street>55 GRASSO PLZ</Street>
- <City>SAINT LOUIS</City>
- <State>MO</State>
- <ZIP>63123</ZIP>
- <lsGuaranteed>1</lsGuaranteed>
- </Location>
- </Commitment>
- <Commitment>
- <MailClass>2</MailClass>

</SDCGetLocationsResponse>

<CommitmentName>2-Day</CommitmentName> <CommitmentTime/> <CommitmentSeq>C0200</CommitmentSeq> <Location> <SDD>2021-05-28</SDD> <COT>1730</COT> <FacType>POST OFFICE</FacType> <Street>55 GRASSO PLZ</Street> <City>SAINT LOUIS</City> <State>MO</State> <ZIP>63123</ZIP> <IsGuaranteed>2</IsGuaranteed> </Location> </Commitment> </Expedited> <NonExpedited> <MailClass>3</MailClass> <NonExpeditedDestType>1</NonExpeditedDestType> <EAD>2021-05-26</EAD> <COT>1730</COT> <SvcStdMsg>3 Days</SvcStdMsg> <SvcStdDays>3</SvcStdDays> <SchedDlvryDate>2021-05-29</SchedDlvryDate> </NonExpedited> <NonExpedited> <MailClass>4</MailClass> <NonExpeditedDestType>1</NonExpeditedDestType> <EAD>2021-05-26</EAD> <COT>1730</COT> <SvcStdMsg>7 Days</SvcStdMsg> <SvcStdDays>7</SvcStdDays> <SchedDlvryDate>2021-06-03</SchedDlvryDate> </NonExpedited> <NonExpedited> <MailClass>5</MailClass> <NonExpeditedDestType>1</NonExpeditedDestType> <EAD>2021-05-26</EAD> <COT>1730</COT> <SvcStdMsg>4 Days</SvcStdMsg> <SvcStdDays>4</SvcStdDays> <SchedDlvryDate>2021-06-01</SchedDlvryDate> </NonExpedited> <NonExpedited> <MailClass>6</MailClass> <NonExpeditedDestType>1</NonExpeditedDestType> <EAD>2021-05-26</EAD> <COT>1730</COT> <SvcStdMsg>6 Days</SvcStdMsg> <SvcStdDays>6</SvcStdDays> <SchedDlvryDate>2021-06-02</SchedDlvryDate> </NonExpedited>