

ProtoObject
Object
Collection
SequenceableCollection
ArrayedCollection
ByteArray
CompiledCode
CompiledMethod

ProtoObject
Object
Collection
SequenceableCollection
ArrayedCollection
ByteArray
CompiledCode
CompiledMethod

MicMicrodownSharedPool class >> #initialize

1. Microdown

This notebook is a learning step to understand **Microdown** ,
the markup language used in Pharo.
We start with a look at the *special symbols* that trigger different formattings:

"MicMicrodownSharedPool class, protocol class initialization"

initialize
"self initialize"

AnchorMarkup := '@'.
AnnotatedParagraphMarkup := '!!!'.
CodeblockMarkup := '```.
CommentedLineMarkup := '%'.
EnvironmentClosingBlockMarkup := '!>'.
EnvironmentOpeningBlockMarkup := '<!!'.
HeaderMarkup := '#'.
HorizontalLineMarkup := '***'.
MathClosingBlockMarkup := '\$\$'.
MathOpeningBlockMarkup := '\$\$'.
MetaDataClosingBlockMarkup := '}'.
MetaDataOpeningBlockMarkup := '{'.
OrderedListSemiMarkup := '. '.
PreformattedMarkup := '> '.
TableCellMarkup := '|'.
UnorderedListMarkup := '- '.
UnorderedListPlusMarkup := '+ '.
UnorderedListStarMarkup := '* '.

ArgumentListDelimiter := '&'.
ArgumentListEqualsDelimiter := '='.
ArgumentListOfFigureStartDelimiter := '?'.
ArgumentListStartDelimiter := '|'.

AnchorReferenceCloserMarkup := '@*'.
AnchorReferenceOpenerMarkup := '*@'.

AnnotationCloserMarkup := '!}'.
AnnotationOpenerMarkup := '{!'.

BoldMarkup := '**'.
FigureNameOpenerMarkup := '!['.
ItalicMarkup := '_'.
LinkNameCloserMarkup := ']'.
LinkNameOpenerMarkup := '['.
MathMarkup := '\$'.
MonospaceMarkup := '`'.
RawCloserMarkup := '}}'.
RawOpenerMarkup := '{{'.
StrikeMarkup := '~'.
URLCloserMarkup := ')'.
URLOpenerMarkup := '('.

Delimiters := {
AnchorReferenceCloserMarkup.
AnchorReferenceOpenerMarkup.
AnnotationCloserMarkup.
AnnotationOpenerMarkup.
BoldMarkup.
FigureNameOpenerMarkup.
ItalicMarkup.
LinkNameCloserMarkup.
LinkNameOpenerMarkup.
MathMarkup.
MonospaceMarkup.
RawCloserMarkup.
RawOpenerMarkup.
StrikeMarkup.
URLCloserMarkup.
URLOpenerMarkup } asSet