This notebook introduces basic objects that populate a Smalltalk image.
In particular, we write in the Pharo dialect, which adheres to the following principles:

ProfStef pharoZenValues

1	'Easy to understand, easy to learn from, easy to change.'
2	'Objects all the way down.'
3	'Examples to learn from.'
4	'Fully dynamic and malleable.'
5	'Beauty in the code, beauty in the comments.'
6	'Simplicity is the ultimate elegance.'
7	'Better a set of small polymorphic classes than a large ugly one.'
8	'Classes structure our vocabulary.'
9	'Messages are our vocabulary.'
10	'Polymorphism is our esperanto.'
11	'Abstraction and composition are our friends.'
12	'Tests are important but can be changed.'
13	'Explicit is better than implicit.'
14	'Magic only at the right place.'
15	'One step at a time.'
16	'There is no unimportant fix.'
17	'Learning from mistakes.'
18	'Perfection can kill movement.'
19	'Quality is an emerging property.'
20	'Simple processes to support progress.'
21	'Communication is key.'
22	'A system with robust abstractions that a single person can understand.'

For instance, let's create a very simple object,

o := Object new

where o is a reference to it. Wait for a moment and look at the little labels above each boxes.
They shows the *class* of the object represented in the box, so let's inspect it

o class

that is what's called the *Smalltalk object model* . Moreover, observe how such a
class has been obtained, through the message class defined as follows:

ProtoObject >> #class

And in turn, have a look at what a *primitive* is:

#whatIsAPrimitive implementors

hash	6142976
identityHash	6142976
asStringPangoText	an Object

#Object

name	
class	
superclass	
methodsCount	471
instanceCount	138
category	#'Kernel-Objects'

```
ProtoObject << #Object
    layout: FixedLayout;
    traits: {};
    slots: {};
    sharedVariables: { #DependentsFields };
    sharedPools: {};
    tag: 'Objects';
    package: 'Kernel'
```

asFluidDefinitionShape

'Object class'

name	
class	
superclass	
methodsCount	33
instanceCount	1
category	#'Kernel-Objects'

```
ProtoObject class << Object class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

#ProtoObject

name	
class	
superclass	nil
methodsCount	53
instanceCount	1
category	#'Kernel-Objects'

```
nil << #ProtoObject
    layout: FixedLayout;
    traits: {};
    slots: {};
    sharedVariables: {};
    sharedPools: {};
    tag: 'Objects';
    package: 'Kernel'
```

asFluidDefinitionShape

'ProtoObject class'

name	
class	
superclass	
methodsCount	1
instanceCount	1
category	#'Kernel-Objects'

```
Class class << ProtoObject class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

#Metaclass

name	
class	
superclass	
methodsCount	73
instanceCount	8778
category	#'Kernel-Classes'

```
ClassDescription << #Metaclass
    layout: FixedLayout;
    traits: {};
    slots: { #thisClass };
    sharedVariables: {};
    sharedPools: {};
    tag: 'Classes';
    package: 'Kernel'
```

asFluidDefinitionShape

'Metaclass class'

name	
class	
superclass	
methodsCount	1
instanceCount	1
category	#'Kernel-Classes'

```
ClassDescription class << Metaclass class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

#ClassDescription

name	
class	
superclass	
methodsCount	198
instanceCount	0
category	#'Kernel-Classes'

```
Behavior << #ClassDescription
    layout: FixedLayout;
    traits: {};
    slots: { #organization . #commentSourcePointer };
    sharedVariables: {};
    sharedPools: {};
    tag: 'Classes';
    package: 'Kernel'
```

asFluidDefinitionShape

'ClassDescription class'

name	
class	
superclass	
methodsCount	0
instanceCount	1
category	#'Kernel-Classes'

```
Behavior class << ClassDescription class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

#Behavior

name	
class	
superclass	
methodsCount	277
instanceCount	0
category	#'Kernel-Classes'

```
Object << #Behavior
    traits: {};
    slots: { #superclass . #methodDict . #format . #layout };
    sharedVariables: { #ClassProperties . #ObsoleteSubclasses };
    sharedPools: {};
    tag: 'Classes';
    package: 'Kernel'
```

asFluidDefinitionShape

'Behavior class'

name	
class	
superclass	
methodsCount	4
instanceCount	1
category	#'Kernel-Classes'

```
Object class << Behavior class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

#Class

name	
class	
superclass	
methodsCount	226
instanceCount	0
category	#'Kernel-Classes'

```
ClassDescription << #Class
    layout: FixedLayout;
    traits: {};
    slots: { #subclasses . #name . #classPool . #sharedPools . #environment . #category };
    sharedVariables: {};
    sharedPools: {};
    tag: 'Classes';
    package: 'Kernel'
```

asFluidDefinitionShape

'Class class'

name	
class	
superclass	
methodsCount	10
instanceCount	1
category	#'Kernel-Classes'

```
ClassDescription class << Class class
    traits: {};
    slots: {}
```

asFluidDefinitionShape

'ProtoObject, protocol *class membership*'

```
class
    "Primitive. Answer the object which is the receiver's class. Essential. See
    Object documentation whatIsAPrimitive."

    <primitive: 111>
    self primitiveFailed
```

array	
firstIndex	1
lastIndex	1
hash	203874011
identityHash	1029350656
asStringPangoText	an OrderedCollection(Object class>>#whatIsAPrimitive)

1	
2	nil
3	nil
4	nil
5	nil
6	nil
7	nil
8	nil
9	nil
10	nil

'Object class, protocol *documentation*'

```
whatIsAPrimitive
    "Some messages in the system are responded to primitively. A primitive
    response is performed directly by the interpreter rather than by evaluating
    expressions in a method. The methods for these messages indicate the
    presence of a primitive response by including <primitive: n> or
    <primitive: 79 error: ec>before the first expression in the method.

    In the second case, ec is a special temporary variable that holds an error code.
    In the VM primitive, failure is indicated by a variable called primFailCode being
    non-zero. On activating a method with a failing primitive, if the index is in
    bounds of the    primitiveFailCodes array in the VMspecialObjectsArray then the
    failure code substitutes the symbol in the    primitiveFailCodes array, otherwise
    it supplies the integer value.

    Primitives exist for several reasons. Certain basic or 'primitive'
    operations cannot be performed in any other way. Smalltalk without
    primitives can move values from one variable to another, but cannot add two
    SmallIntegers together. Many methods for arithmetic and comparison
    between numbers are primitives. Some primitives allow Smalltalk to
    communicate with I/O devices such as the disk, the display, and the keyboard.
    Some primitives exist only to make the system run faster; each does the same
    thing as a certain Smalltalk method, and its implementation as a primitive is
    optional.

    When the Smalltalk interpreter begins to execute a method which specifies a
    primitive response, it tries to perform the primitive action and to return a
    result. If the routine in the interpreter for this primitive is successful,
    it will return a value and the expressions in the method will not be evaluated.
    If the primitive routine is not successful, the primitive 'fails', and the
    Smalltalk expressions in the method are executed instead. These
    expressions are evaluated as though the primitive routine had not been
    called.

    The Smalltalk code that is evaluated when a primitive fails usually
    anticipates why that primitive might fail. If the primitive is optional, the
    expressions in the method do exactly what the primitive would have done (See
    Number @). If the primitive only works on certain classes of arguments, the
    Smalltalk code tries to coerce the argument or appeals to a superclass to find
    a more general way of doing the operation (see SmallInteger +). If the
    primitive is never supposed to fail, the expressions signal an error (see
    SmallInteger asFloat).

    Each method that specifies a primitive has a comment in it. If the primitive is
    optional, the comment will say 'Optional'. An optional primitive that is not
    implemented always fails, and the Smalltalk expressions do the work
    instead.

    If a primitive is not optional, the comment will say, 'Essential'. Some
    methods will have the comment, 'No lookup'. See Object
    howToModifyPrimitives for an explanation of special selectors which are
    not looked up.

    For the primitives for +, -, *, and bitShift: in SmallInteger, and truncated
    in Float, the primitive constructs and returns a 16-bit
    LargePositiveInteger when the result warrants it. Returning 16-bit
    LargePositiveIntegers from these primitives instead of failing is
    optional in the same sense that the LargePositiveInteger arithmetic
    primitives are optional. The comments in the SmallInteger primitives say,
    'Fails if result is not a SmallInteger', even though the implementor has the
    option to construct a LargePositiveInteger. For further information on
    primitives, see the 'Primitive Methods' part of the chapter on the formal
    specification of the interpreter in the Smalltalk book."

    self error: 'comment only'
```