

Jumeau numérique dans l'environnement: Microclimat urbain

Hanna CHETOUANE, Narmimane ZAOUACHE

October 7, 2025

UFR of Mathematics and Informatics - University of Strasbourg

Comment les jumeaux numériques aident-ils à comprendre les effets des aménagements urbains sur le micro-climat ?


Plan

- L'écologie et le climat sont devenus des enjeux majeurs, surtout dans les villes où se développent des îlots de chaleur
- Solutions: Végétalisation, choix de matériaux adaptés et aménagements urbains repensés
- Les collectivités locales doivent ainsi prendre des décisions sur les stratégies d'aménagement à adopter et en évaluer l'impact environnemental et sanitaire

→ Simuler et prédire ces effets de ces choix sur le microclimat urbain et la santé publique ⇒ **Jumeau numérique**


Qu'est-ce qu'un jumeau numérique ?

- Réplique virtuelle et dynamique d'un système réel, qui, couplé à des outils de simulation, permet d'analyser et prédire son comportement dans différentes conditions
- S'appuie sur des données réelles (météorologiques et urbaines) issues de capteurs, d'observations ou de modèles physiques



Défi actuel en France: projet JNFT porté par l'IGN, le Cerema et l'Inria, qui vise à créer un jumeau numérique multithématique couvrant le territoire français

Fonctionnement d'un jumeau numérique



Physique:

- Données (météo, propriétés des matériaux, composition de l'air)
- Micro-climat




Numérique:

- Paramètres
- Maquette 3D maillée

Modèles physiques:

- Phénomènes physiques continus: PDEs (Navier-Stokes, chaleur, transport, diffusion)
- Interaction entre bâtiments, vent, végétation: Fluid-Structure Interaction (NS + Elasticity)
- Écoulement d'air et échanges thermiques: Computational Fluid Dynamics (NS + Heat; Transport; transfert radiatif)



Utilisation ROM: Réduction de l'ordre des modèles physiques pour accélérer les simulations

- **Offline:** Préparation du modèle


- Réduction de la dimension en capturant l'essentiel du système: Proper Orthogonal Decomposition (POD), Reduced Basis Method (RBM)
- Hyper-réduction: Réduit temps de calcul des termes non-linéaires (DEIM: Discrete Empirical Interpolation Method, gappy POD: gappy Proper Orthogonal Decomposition)

- **Online:** Simulation du modèle réduit pour tester différents scénarios rapidement



Data-Driven Models: basé sur les données, prédiction rapide


- Régression: prédit des phénomènes (température, qualité de l'air, vent) à partir de variables (matériaux, végétation...)
- Gaussian Process: prédit et donne l'incertitude pour des zones avec peu de données
- Réseaux de Neurones: capture les relations complexes et non-linéaires entre les variables
- Modèles d'ensembles: amélioration de la précision et de la robustesse des prédictions, en combinant plusieurs modèles



Data assimilation: Combinaison des modèles physiques et des données pour corriger les simulations, obtenir un maximum de précision et rendre ces simulations exploitables

- VAR: ajuste le modèle physique pour que les simulations collent aux observations (sur un ou plusieurs pas de temps)
- Filtre de Kalman: Mise à jour des prédictions en temps réel pour un suivi dynamique
- PBDW, GEIM: reconstruction du système avec peu de données, pour une vue d'ensemble
- Capteurs virtuels: estimation de variables où il n'y a pas de mesures, voir l'effet de nouveaux aménagements

Architecture Pipeline -



The digital twin architecture is divided into two main phases:

Offline: model construction, calibration, and reduction.

Online: real-time assimilation and decision support.

This structure ensures continuous synchronization between the physical and virtual environments.

Methods – Part 1: Physical and Reduced Models

1. Physical and Numerical Modeling

- Based on fundamental equations (CFD, thermal transfer, radiation).
- Represents airflow, heat diffusion, and the effect of urban materials.
- Provides detailed simulations but is computationally expensive.

2. Reduced Order Model (ROM / Surrogate Model)

- Built from the results of the high-fidelity physical model.
- Techniques: POD (Proper Orthogonal Decomposition), Reduced Basis Method (RBM), Hyper-reduction (DEIM).
- Enables calculations 100 to 1000 times faster while preserving accuracy.

Methods – Part 2: Data-driven and Data Assimilation

3. Data-driven Approaches (Machine Learning)

- Use sensor data to complement or correct physical models.
- Methods: regression models, neural networks (Neural-ODE), Gaussian Processes.
- Useful in areas with limited or missing physical data.

4. Data Assimilation

- Continuously adjusts the model parameters using real-time measurements.
- Common methods: EnKF (Ensemble Kalman Filter), 4D-VAR, PBDW/GEIM.
- Keeps the digital twin consistent with the real environment in real time.

Data & Instrumentation — Data Budget (Urban Microclimate)

Goal: quantify sensor data rates and daily volumes to size network & storage for real-time operation.

Sensor	#	Freq (Hz)	sample	Throughput (kB/s)	Vol/day (GB)	Comments
Air thermometer (T)	20	1.00	8	0.16	0.014	Ambient temperature
Hygrometer (RH)	10	1.00	8	0.08	0.007	Relative humidity
Anemometer (3-axis)	5	1.00	12	0.06	0.005	Wind speed & direction
Pyranometer (solar)	5	0.20	16	0.016	0.0014	Global irradiance
Thermal camera*	2	0.033	500,000	33.0	2.85	H.264, store temperature maps

Formulas:

Throughput (kB/s) Volume/day (GB)

$$\text{Throughput(kB/s)} : = \frac{\# \times \text{sample} \times \text{Freq}}{1000}$$

$$\text{Volume/day(GB)} : = \frac{\text{Throughput (kB/s)} \times 86\,400}{10^6}$$

Protocols/latency (summary): LoRaWAN for low-rate sensors (2–5 s latency);
Wi-Fi/4G for cameras (< 0.5 s).

Privacy: camera streams anonymized on edge; only thermal maps stored.

V&V & UQ — Verification, Validation & Uncertainty Quantification

Goal

Goal: ensure accuracy, reliability, and safety of decisions in the urban microclimate digital twin.

Step	Purpose	Methods / Indicators
1 Verification	Check model implementation and numerical stability.	Compare the Reduced Order Model (ROM) with the full CFD model. Ensure no numerical or stability errors.
2 Validation	Evaluate how well the model matches real-world data.	Compare predictions with sensor measurements (T° , wind, humidity). Metrics: MAE , RMSE , R^2 .
3 Uncertainty Quantification (UQ)	Estimate the confidence level of model predictions.	Methods: Monte Carlo, sensitivity analysis, Bayesian estimation. Example: $T = 32 \pm 1.5^\circ\text{C}$.
4 Veto / Alert Mechanism	Prevent wrong or unsafe decisions when uncertainty is too high.	If variance or RMSE > threshold \rightarrow trigger alert or model recalibration.

Outcome: a validated, uncertainty-aware model ensuring trustworthy real-time decisions.

Transfer & Deployment — CI/CD, Edge vs Cloud, Observability, Risks

Goal

ensure a smooth transition from R&D to real-time operation of the urban microclimate digital twin.

Aspect	Description	Tools / Key Points
CI/CD (Continuous Integration & Deployment)	Automate the update cycle for models and data.	GitHub Actions, Docker, unit tests for ROM/data, dashboard updates.
Containers & Orchestration	Ensure portability and scalability of digital twin services.	Docker / Kubernetes: deployment of ROM model, APIs, dashboards.
Edge vs Cloud Computing	Balance local computing (edge) and centralized storage (cloud).	Edge: low latency (cameras, sensors). Cloud: heavy computations (assimilation, ROM training).
Observability & Monitoring	Track performance, errors, and model drifts.	Logs, metrics, and alerts through Grafana / Prometheus.
Costs & Risks (CAPEX/OPEX)	Optimize hardware resources and minimize downtime.	CAPEX: servers / sensors. OPEX: maintenance, energy, network. Risk: failure, model drift.

Outcome: a reliable, automated, and maintainable digital twin for long-term operation.

Perspectives & Limitations — Toward a Sustainable Digital Twin

- **Scalability:** adapt the model to larger urban areas (optimized ROM, cloud computation).
- **Robustness:** handle sensor failures or noisy data (redundancy, adaptive models).
- **Bias:** avoid overfitting to one district (multi-scenario validation).
- **Privacy:** ensure GDPR compliance and anonymization of visual data.
- **Ethics:** promote transparency, explainable AI, and citizen involvement.

Thank you for your attention!

Any questions?

University of Strasbourg – 2025

Bibliographie