

```

repeat task.wait() until game:IsLoaded()
task.wait(0.5)

pcall(function()
    game:GetService("StarterGui"):SetCore("SendNotification", {
        Title = "نظام التشغيل",
        Text = "جاري تحميل واجهة Invictus V14...",
        Duration = 3
    })
end)

local success, Rayfield = pcall(function()
    return loadstring(game:HttpGet('https://sirius.menu/rayfield'))()
end)

if not success or type(Rayfield) ~= "table" then
    success, Rayfield = pcall(function()
        return
        loadstring(game:HttpGet('https://raw.githubusercontent.com/sirius-xyz/Rayfield/main/source.lua'))()
    end)
end

if not success or type(Rayfield) ~= "table" then
    return
end

-- =====
-- استدعاء الخدمات الأساسية
-- =====
local Players = game:GetService("Players")
local RunService = game:GetService("RunService")
local ReplicatedStorage = game:GetService("ReplicatedStorage")
local HttpService = game:GetService("HttpService")
local UserInputService = game:GetService("UserInputService")
local CoreGui = game:GetService("CoreGui")
local lp = Players.LocalPlayer

-- =====
-- إعدادات البيانات والمواقع المحفوظة [ 1 ]
-- =====
local DATA_FILE = "khurafi_delta_data_v11.json"
local SAVE = {safe1 = "", safe2 = "", safe3 = "", safe4 = "", safe5 = ""}
local SavedWaypoints = {}
local SelectedWaypointName = nil

local function loadData()

```

```

pcall(function()
    if readfile and isfile and isfile(DATA_FILE) then
        local data = HttpService:JSONDecode(readfile(DATA_FILE))
        if data and type(data) == "table" then
            SAVE.safe1 = data.safe1 or ""
            SAVE.safe2 = data.safe2 or ""
            SAVE.safe3 = data.safe3 or ""
            SAVE.safe4 = data.safe4 or ""
            SAVE.safe5 = data.safe5 or ""

            if data.waypoints and type(data.waypoints) == "table"
then
                SavedWaypoints = {}
                for wpName, cfData in pairs(data.waypoints) do
                    if type(cfData) == "table" then
                        SavedWaypoints[wpName] =
CFrame.new(unpack(cfData))
                    end
                end
            end
        end
    end
end)
end

local function saveData()
    pcall(function()
        if writefile then
            local waypointsData = {}
            for wpName, cf in pairs(SavedWaypoints) do
                waypointsData[wpName] = {cf:GetComponents()}
            end
            local dataToSave = {
                safe1 = SAVE.safe1, safe2 = SAVE.safe2,
                safe3 = SAVE.safe3, safe4 = SAVE.safe4,
                safe5 = SAVE.safe5, waypoints = waypointsData
            }
            writefile(DATA_FILE, HttpService:JSONEncode(dataToSave))
        end
    end)
end

loadData()

local function isSafe(name)
    local lowerName = name:lower()
    local boxes = {SAVE.safe1, SAVE.safe2, SAVE.safe3, SAVE.safe4,
SAVE.safe5}
    for _, boxText in ipairs(boxes) do

```

```

        if boxText and boxText ~= "" then
            for s in boxText:gmatch("%S+") do
                if lowerName:find(s:lower(), 1, true) then return true
            end
        end
    end
end
return false
end

local function getPlayerNames(includeAll)
    local names = {}
    if includeAll then table.insert(names, "All") end
    for _, p in ipairs(Players:GetPlayers()) do
        if p ~= lp then table.insert(names, p.Name) end
    end
    return names
end

local function getPlayerNamesForTargets()
    local names = {"لا أحد"}
    for _, p in ipairs(Players:GetPlayers()) do
        if p ~= lp then table.insert(names, p.Name) end
    end
    return names
end

local function getWaypointNames()
    local names = {}
    for name, _ in pairs(SavedWaypoints) do table.insert(names, name) end
    if #names == 0 then table.insert(names, "لا يوجد مواقع محفوظة") end
    return names
end

-- =====
-- [ 2 ] إعدادات الأورا والسحب وحماية الإمساك
-- =====
local HitR = nil
local function findHitRemote()
    local function search(obj)
        for _, child in pairs(obj:GetChildren()) do
            if (child:IsA("RemoteFunction") or child:IsA("RemoteEvent"))
            and child.Name == "Hit" then return child end
            local found = search(child)
            if found then return found end
        end
    end
    return nil
end
end

```

```

HitR = search(ReplicatedStorage)
if not HitR then
    local combat = ReplicatedStorage:FindFirstChild("Packages")
    if combat then combat = combat:FindFirstChild("Knit") end
    if combat then combat = combat:FindFirstChild("Services") end
    if combat then combat = combat:FindFirstChild("CombatService")
end
    if combat then
        local rf = combat:FindFirstChild("RF")
        if rf then HitR = rf:FindFirstChild("Hit") end
    end
end
end
findHitRemote()

local GrabRF = ReplicatedStorage:FindFirstChild("OldPackages") and
ReplicatedStorage.OldPackages.Knit.Services.CombatService.RF.Grab

local AuraEnabled = false
local rangeVal = 50
local apsVal = 15
local AuraTargetSelected = "All"
local lastHitTick = 0

local AutoGrab = false
local AutoTargetEnabled = false
local SpecificTargetEnabled = false

local ChosenTargetName1 = ""
local ChosenTargetName2 = ""
local ChosenTargetName3 = ""

local TargetDropdown1, TargetDropdown2, TargetDropdown3

local TriggerDistance = 15
local grabRepeatVal = 3
local TpSelectedPlayer = ""

local AutoLookEnabled = false
local AutoMagnetEnabled = false

-- =====
-- منطق حماية الإمساك والانتقام التلقائي المعدل (Anti-Grab Auto Reset & Revenge)
-- =====
local AntiGrabEnabled = false

local function executeAutoReset(reason)
    if not AntiGrabEnabled then return end

```

```

local char = lp.Character
local hum = char and char:FindFirstChild("Humanoid")
if hum and hum.Health > 0 then
    pcall(function()
        Rayfield:Notify({
            Title = "حماية الإمساك 🛡️",
            Content = "...تم كشف الإمساك! جاري إعادة الترسيب التلقائي",
            Duration = 2
        })
    end)

    local neck = char:FindFirstChild("Head") and
char.Head:FindFirstChild("Neck")
    if neck then neck:Destroy() end
    hum.Health = 0
end
end

local function getPlayerFromPart(part)
    local current = part
    while current and current ~= game do
        local plr = Players:GetPlayerFromCharacter(current)
        if plr then return plr end
        current = current.Parent
    end
    return nil
end

local function setupAntiGrab(char)
    if not char then return end

    char.DescendantAdded:Connect(function(child)
        if not AntiGrabEnabled then return end

        task.wait(0.1)

        if child:IsA("Weld") or child:IsA("WeldConstraint") or
child:IsA("Motor6D") then
            local part0 = child.Part0
            local part1 = child.Part1

            if part0 and part1 then
                local isPart0Me = part0:IsDescendantOf(char)
                local isPart1Me = part1:IsDescendantOf(char)

                local attackerPart = nil

```

```

-- تحديد جزء المهاجم بغض النظر عن اتجاه الالتصاق
if isPart0Me and not isPart1Me then
    attackerPart = part1
elseif not isPart0Me and isPart1Me then
    attackerPart = part0
end

if attackerPart then
    local attackerPlayer =
getPlayerFromPart(attackerPart)

    -- ☒ التعديل هنا: التأكد من أن المهاجم لاعب آخر وليس سكرتير
الطيران الخاص بك

    if attackerPlayer and attackerPlayer ~= lp then
        local attackerName = attackerPlayer.Name

        if ChosenTargetName1 == "" or ChosenTargetName1
== attackerName then
            ChosenTargetName1 = attackerName
            pcall(function()
TargetDropdown1:Set({attackerName}) end)
            elseif ChosenTargetName2 == "" or
ChosenTargetName2 == attackerName then
                ChosenTargetName2 = attackerName
                pcall(function()
TargetDropdown2:Set({attackerName}) end)
            else
                ChosenTargetName3 = attackerName
                pcall(function()
TargetDropdown3:Set({attackerName}) end)
            end

            SpecificTargetEnabled = true

            pcall(function()
                Rayfield:Notify({
                    Title = "نظام الانتقام 🎯",
                    Content = "تم تحديد" .. attackerName ..
"كهدف!",
                    Duration = 3
                })
            end)

            executeAutoReset("تم الإمساك بك بواسطة" ..
attackerName)
        end
    end
end

```

```

else
    local name = child.Name:lower()
    if name:find("grabbed") or name:find("stunned") then
        executeAutoReset("تأثير الإمساك: " .. child.Name)
    end
end
end)

local hum = char:WaitForChild("Humanoid", 3)
if hum then
    hum.StateChanged:Connect(function(_, newState)
        if not AntiGrabEnabled then return end
        -- ☒ لتفادي (PlatformStanding) التعديل هنا: تم تعطيل القتل عند الطيران
التعارض
        -- if newState == Enum.HumanoidStateType.PlatformStanding
then
        --     executeAutoReset("تم تقييد حركتك" (PlatformStanding))
        -- end
    end)
end
end

if lp.Character then setupAntiGrab(lp.Character) end
lp.CharacterAdded:Connect(setupAntiGrab)

local function removeLookGyro()
    if lp.Character and lp.Character:FindFirstChild("HumanoidRootPart")
then
        local bg =
lp.Character.HumanoidRootPart:FindFirstChild("AutoLookGyro")
        if bg then bg:Destroy() end
    end
end

local function isTarget(name)
    if AuraTargetSelected == "All" or AuraTargetSelected == "" then
return true end
    return name:lower() == AuraTargetSelected:lower()
end

local function doHit(hum, pos)
    if not hum or not hum.Parent then return end
    if HitR then
        if HitR:IsA("RemoteEvent") then HitR:FireServer(hum,
Vector3.new(pos.X, pos.Y, pos.Z))
        elseif HitR:IsA("RemoteFunction") then HitR:InvokeServer(hum,
Vector3.new(pos.X, pos.Y, pos.Z)) end
    end
end

```

```

end

-- =====
-- [ 3 ] المطور والإشعارات ESP إعدادات التأثيرات وال
-- =====
local BWNameActive = false; local currentNameMode = "NONE"; local
rnHue = 0; local bwLastUpdate = 0
local rnSpeed = 0.7; local rnUpdateRate = 0.02; local policeToggle =
false
local rainbowNameRemote = ReplicatedStorage:WaitForChild("Remotes",
10)
rainbowNameRemote = rainbowNameRemote and
rainbowNameRemote:FindFirstChild("SetRPNameColor")

local EspEnabled = false; local EspBoxes = true; local EspNames = true

local function getEspColor(playerName)
    if isSafe(playerName) then return Color3.fromRGB(0, 255, 100) end
    local isAuraTarget = (AuraTargetSelected ~= "All" and
AuraTargetSelected ~= "" and playerName == AuraTargetSelected)
    local isGrabTarget = (SpecificTargetEnabled and (playerName ==
ChosenTargetName1 or playerName == ChosenTargetName2 or playerName ==
ChosenTargetName3))
    if isAuraTarget or isGrabTarget then return Color3.fromRGB(255, 50,
50) end
    return Color3.fromRGB(255, 255, 255)
end

local function removeEsp(char)
    if not char then return end
    if char:FindFirstChild("ESP_Highlight") then
char.ESP_Highlight:Destroy() end
    if char:FindFirstChild("ESP_Billboard") then
char.ESP_Billboard:Destroy() end
end

local function applyEsp(player)
    if player == lp or not player.Character then return end
    local char = player.Character
    removeEsp(char)
    if not EspEnabled then return end

    local targetColor = getEspColor(player.Name)

    if EspBoxes and not char:FindFirstChild("ESP_Highlight") then
        local highlight = Instance.new("Highlight")
        highlight.Name = "ESP_Highlight"
        highlight.Adornee = char
    end
end

```



```

        highlight.FillColor = targetColor
        highlight.OutlineColor = Color3.fromRGB(255, 255, 255)
        highlight.FillTransparency = 0.5
        highlight.OutlineTransparency = 0
        highlight.DepthMode = Enum.HighlightDepthMode.AlwaysOnTop
        highlight.Parent = char
    end

    local head = char:FindFirstChild("Head") or
char:WaitForChild("Head", 3)
    if head and EspNames and not char:FindFirstChild("ESP_Billboard")
then
        local billboard = Instance.new("BillboardGui")
        billboard.Name = "ESP_Billboard"
        billboard.Adornee = head
        billboard.Size = UDim2.new(0, 150, 0, 45)
        billboard.StudsOffset = Vector3.new(0, 2.8, 0)
        billboard.AlwaysOnTop = true

        local textLabel = Instance.new("TextLabel")
        textLabel.Size = UDim2.new(1, 0, 1, 0)
        textLabel.BackgroundTransparency = 1
        textLabel.TextColor3 = targetColor
        textLabel.TextStrokeTransparency = 0.4
        textLabel.Font = Enum.Font.SourceSansBold
        textLabel.TextSize = 12
        textLabel.Parent = billboard
        billboard.Parent = char

        task.spawn(function()
            while EspEnabled and player and player.Parent and char and
char.Parent and head and head.Parent do
                if not char:FindFirstChild("ESP_Billboard") or (EspBoxes
and not char:FindFirstChild("ESP_Highlight")) then
                    applyEsp(player)
                    break
                end

                local myChar = lp.Character
                if myChar and myChar:FindFirstChild("HumanoidRootPart")
and char:FindFirstChild("HumanoidRootPart") then
                    local dist =
math.floor((myChar.HumanoidRootPart.Position -
char.HumanoidRootPart.Position).Magnitude)
                    textLabel.Text = "@" .. player.Name .. "\n[" ..
tostring(dist) .. " Studs]"
                    end
                    task.wait(0.4)
                end
            end
        end)
    end

```

```

        end
    end)
end
end

local function refreshAllEsp()
    for _, p in ipairs(Players:GetPlayers()) do
        if p ~= lp and p.Character then
            if EspEnabled then applyEsp(p) else removeEsp(p.Character)
        end
    end
end
end

local function trackPlayerEsp(plr)
    if plr == lp then return end

    if plr.Character then
        task.spawn(function()
            task.wait(0.5)
            if EspEnabled then applyEsp(plr) end
        end)
    end

    plr.CharacterAdded:Connect(function()
        task.wait(0.5)
        if EspEnabled then applyEsp(plr) end
    end)
end

local function checkPlayerNotification(plr, eventType)
    local isSafePlayer = isSafe(plr.Name)
    local isTargetPlayer = (AuraTargetSelected ~= "All" and
        AuraTargetSelected ~= "" and plr.Name == AuraTargetSelected)
        or (SpecificTargetEnabled and (plr.Name ==
        ChosenTargetName1 or plr.Name == ChosenTargetName2 or plr.Name ==
        ChosenTargetName3))

    if isSafePlayer or isTargetPlayer then
        local statusTag = isSafePlayer and "● [SAFE]" or "● [TARGET]"
        local actionText = (eventType == "join") and "دخل السيرفر" or "غادر السيرفر"
        local title = statusTag .. " " .. actionText
        local content = "@" .. plr.Name .. " (" .. (plr.DisplayName or "") .. ")"

        pcall(function()
            Rayfield:Notify({

```

```

        Title = title,
        Content = content,
        Duration = 4
    })
end)
end
end

for _, p in ipairs(Players:GetPlayers()) do
    trackPlayerEsp(p)
end

Players.PlayerAdded:Connect(function(plr)
    trackPlayerEsp(plr)
    checkPlayerNotification(plr, "join")
end)

Players.PlayerRemoving:Connect(function(plr)
    checkPlayerNotification(plr, "leave")
end)

task.spawn(function()
    while task.wait(2) do
        if EspEnabled then
            for _, p in ipairs(Players:GetPlayers()) do
                if p ~= lp and p.Character then
                    local hasHighlight =
p.Character:FindFirstChild("ESP_Highlight")
                    local hasBillboard =
p.Character:FindFirstChild("ESP_Billboard")

                    if (EspBoxes and not hasHighlight) or (EspNames and
not hasBillboard) then
                        applyEsp(p)
                    end
                end
            end
        end
    end
end)

-- Floating UI
local IsInvisible = false; local invisParts = {}
local InvisGui = Instance.new("ScreenGui"); InvisGui.Name =
"FloatingInvisUI"; InvisGui.ResetOnSpawn = false
InvisGui.IgnoreGuiInset = true
local successGui = pcall(function() InvisGui.Parent = CoreGui end)
if not successGui then InvisGui.Parent = lp:WaitForChild("PlayerGui")

```

```

end
InvisGui.Enabled = false

local FloatBtn = Instance.new("TextButton")
FloatBtn.Size = UDim2.new(0, 100, 0, 45)
FloatBtn.AnchorPoint = Vector2.new(1, 0)
FloatBtn.Position = UDim2.new(1, -120, 0, 5)
FloatBtn.BackgroundColor3 = Color3.fromRGB(220, 60, 60)
FloatBtn.Text = "تخفی: ❌"
FloatBtn.TextColor3 = Color3.fromRGB(255, 255, 255)
FloatBtn.Font = Enum.Font.SourceSansBold
FloatBtn.TextSize = 18
FloatBtn.Active = true
FloatBtn.Draggable = false
FloatBtn.Parent = InvisGui
local UICorner = Instance.new("UICorner"); UICorner.CornerRadius =
UDim.new(0, 8); UICorner.Parent = FloatBtn

local function updateInvisParts()
    invisParts = {}
    if lp.Character then
        for _, obj in pairs(lp.Character:GetDescendants()) do
            if (obj:IsA("BasePart") or obj:IsA("Decal")) and obj.Name ~=
"HumanoidRootPart" then
                if obj.Transparency < 1 then table.insert(invisParts,
{obj = obj, origTrans = obj.Transparency}) end
            end
        end
    end
end

end
end

FloatBtn.MouseButton1Click:Connect(function()
    IsInvisible = not IsInvisible
    if IsInvisible then
        FloatBtn.BackgroundColor3 = Color3.fromRGB(60, 220, 60);
FloatBtn.Text = "تخفی: ✅"
        updateInvisParts()
        for _, item in pairs(invisParts) do if item.obj and
item.obj.Parent then item.obj.Transparency = 0.5 end end
    else
        FloatBtn.BackgroundColor3 = Color3.fromRGB(220, 60, 60);
FloatBtn.Text = "تخفی: ❌"
        for _, item in pairs(invisParts) do if item.obj and
item.obj.Parent then item.obj.Transparency = item.origTrans end end
    end
end)

local IsHoldingMagnet = false

```

```

local MagnetGui = Instance.new("ScreenGui"); MagnetGui.Name =
"FloatingMagnetUI"; MagnetGui.ResetOnSpawn = false
MagnetGui.IgnoreGuiInset = true
local successMagGui = pcall(function() MagnetGui.Parent = CoreGui end)
if not successMagGui then MagnetGui.Parent =
lp:WaitForChild("PlayerGui") end
MagnetGui.Enabled = false

local HoldMagBtn = Instance.new("TextButton")
HoldMagBtn.Size = UDim2.new(0, 100, 0, 45)
HoldMagBtn.AnchorPoint = Vector2.new(1, 0)
HoldMagBtn.Position = UDim2.new(1, -10, 0, 5)
HoldMagBtn.BackgroundColor3 = Color3.fromRGB(60, 100, 220)
HoldMagBtn.Text = "مغناطيس"
HoldMagBtn.TextColor3 = Color3.fromRGB(255, 255, 255)
HoldMagBtn.Font = Enum.Font.SourceSansBold
HoldMagBtn.TextSize = 18
HoldMagBtn.Active = true
HoldMagBtn.Draggable = false
HoldMagBtn.Parent = MagnetGui
local MagUICorner = Instance.new("UICorner"); MagUICorner.CornerRadius
= UDim.new(0, 8); MagUICorner.Parent = HoldMagBtn

HoldMagBtn.MouseButton1Down:Connect(function()
    IsHoldingMagnet = true
    HoldMagBtn.BackgroundColor3 = Color3.fromRGB(60, 220, 60)
end)
HoldMagBtn.MouseButton1Up:Connect(function()
    IsHoldingMagnet = false
    HoldMagBtn.BackgroundColor3 = Color3.fromRGB(60, 100, 220)
end)
HoldMagBtn.MouseLeave:Connect(function()
    IsHoldingMagnet = false
    HoldMagBtn.BackgroundColor3 = Color3.fromRGB(60, 100, 220)
end)

lp.CharacterAdded:Connect(function()
    IsInvisible = false; FloatBtn.BackgroundColor3 = Color3.fromRGB(220,
60, 60); FloatBtn.Text = "تخفي: ✖"
    IsHoldingMagnet = false; HoldMagBtn.BackgroundColor3 =
Color3.fromRGB(60, 100, 220)
    removeLookGyro()
end)

local isInfJump = false; local isSpeedEnabled = false; local
currentWalkSpeed = 35
UserInputService.JumpRequest:Connect(function()
    if isInfJump and lp.Character then

```

```

        local humanoid = lp.Character:FindFirstChildOfClass("Humanoid")
        if humanoid then
humanoid:ChangeState(Enum.HumanoidStateType.Jumping) end
        end
end)

-- =====
-- [ 4 ] بناء واجهة Rayfield
-- =====
local Window = Rayfield:CreateWindow({
Name = "الأنفكتوس العراقي",
LoadingTitle = "Aura, Grab, ESP & More",
LoadingSubtitle = "by KHURAFI",
Theme = "Default",
DisableRayfieldPrompts = false,
DisableBuildWarnings = true,
ConfigurationSaving = {
    Enabled = true,
    FolderName = "KHURAFI_Data",
    FileName = "AuraDeltaSettings"
},
KeySystem = false
})

local MainTab = Window:CreateTab("Aura", 4483345998)
local GrabTab = Window:CreateTab("4483345998", "الإمساك")
local PlayerTab = Window:CreateTab("4483345998", "اللاعب")
local WaypointsTab = Window:CreateTab("4483345998", "المواقع")
local EspTab = Window:CreateTab("ESP", 4483345998)
local NameTab = Window:CreateTab("4483345998", "الاسم")
local SettingsTab = Window:CreateTab("4483345998", "الإعدادات")

-- Aura
MainTab:CreateToggle({ Name = "تفعيل الأورا (STATUS)", CurrentValue =
false, Flag = "AuraToggle", Callback = function(Value) AuraEnabled =
Value end })
MainTab:CreateSlider({ Name = "نطاق الضرر", Range = {5, 100}, Increment
= 1, Suffix = "Studs", CurrentValue = 50, Flag = "RangeSlider",
Callback = function(Value) rangeVal = Value end })
MainTab:CreateSlider({ Name = "سرعة الضرب", Range = {1, 60}, Increment
= 1, Suffix = "Hit/s", CurrentValue = 15, Flag = "APSSlider", Callback
= function(Value) apsVal = Value end })
local AuraTargetDropdown = MainTab:CreateDropdown({ Name = "الهدف",
Options = getPlayerNames(true), CurrentOption = {"All"},
MultipleOptions = false, Flag = "AuraTargetDropdown", Callback =
function(Options) if Options[1] then AuraTargetSelected = Options[1];
refreshAllEsp() end end })
MainTab:CreateButton({ Name = "تحديث الأهداف", Callback = function()

```

```
AuraTargetDropdown:Refresh(getPlayerNames(true)) end }}
```

-- الإمساك

```
GrabTab:CreateSection("حماية الإمساك والانتقام (Anti-Grab & Revenge)")
GrabTab:CreateToggle({ Name = "الهروب وتحديد المهاجم كهدف تلقائي", CurrentValue
= false, Flag = "AntiGrabToggle", Callback = function(Value)
AntiGrabEnabled = Value end })
```

```
GrabTab:CreateSection("إعدادات السحب العام")
GrabTab:CreateToggle({ Name = "سحب مستمر (الكل)", CurrentValue = false,
Flag = "AutoGrabToggle", Callback = function(Value) AutoGrab = Value
end })
GrabTab:CreateToggle({ Name = "استهداف تلقائي (أي شخص يقترب)",
CurrentValue = false, Flag = "AutoTargetToggle", Callback =
function(Value) AutoTargetEnabled = Value end })
```

```
GrabTab:CreateSection("إعدادات السحب المحدد (الذكية)")
TargetDropdown1 = GrabTab:CreateDropdown({ Name = "اختر اللاعب الأول 1",
Options = getPlayerNamesForTargets(), CurrentOption = {"لا أحد"},
MultipleOptions = false, Flag = "SpecificTargetDropdown1", Callback =
function(Options) if Options[1] then ChosenTargetName1 = (Options[1]
== "لا أحد") and "" or Options[1]; refreshAllEsp() end end })
TargetDropdown2 = GrabTab:CreateDropdown({ Name = "اختر اللاعب الثاني 2",
Options = getPlayerNamesForTargets(), CurrentOption = {"لا أحد"},
MultipleOptions = false, Flag = "SpecificTargetDropdown2", Callback =
function(Options) if Options[1] then ChosenTargetName2 = (Options[1]
== "لا أحد") and "" or Options[1]; refreshAllEsp() end end })
TargetDropdown3 = GrabTab:CreateDropdown({ Name = "اختر اللاعب الثالث 3",
Options = getPlayerNamesForTargets(), CurrentOption = {"لا أحد"},
MultipleOptions = false, Flag = "SpecificTargetDropdown3", Callback =
function(Options) if Options[1] then ChosenTargetName3 = (Options[1]
== "لا أحد") and "" or Options[1]; refreshAllEsp() end end })
```

```
GrabTab:CreateToggle({ Name = "تفعيل السحب المحدد", CurrentValue = false,
Flag = "SpecificTargetToggle", Callback = function(Value)
SpecificTargetEnabled = Value; refreshAllEsp() end })
```

```
GrabTab:CreateSlider({ Name = "نطاق تفعيل السحب (المسافة)", Range = {5,
100}, Increment = 1, Suffix = "Studs", CurrentValue = 15, Flag =
"TriggerDistanceSlider", Callback = function(Value) TriggerDistance =
Value end })
GrabTab:CreateSlider({ Name = "عدد تكرار أمر السحب", Range = {1, 15},
Increment = 1, Suffix = "مرة", CurrentValue = 3, Flag =
"GrabRepeatSlider", Callback = function(Value) grabRepeatVal = Value
end })
```

```
GrabTab:CreateSection("المغناطيس والتوجيه")
GrabTab:CreateToggle({ Name = "توجيه تلقائي (النظر للهدف 🎯)", CurrentValue =
```

```

false, Flag = "AutoLookToggle", Callback = function(Value)
AutoLookEnabled = Value; if not Value then removeLookGyro() end end })
GrabTab:CreateToggle({ Name = "مغناطيس تلقائي (لا يعمل بالقتال)",
CurrentValue = false, Flag = "AutoMagnetToggle", Callback =
function(Value) AutoMagnetEnabled = Value end })
GrabTab:CreateToggle({ Name = "إظهار زر المغناطيس العائم (للوضع القتالي)",
CurrentValue = false, Flag = "HoldMagnetToggle", Callback =
function(Value) MagnetGui.Enabled = Value; if not Value then
IsHoldingMagnet = false end end })

```

```

GrabTab:CreateSection("الانتقال السريع إلى لاعب")
local TpDropdown = GrabTab:CreateDropdown({ Name = "انتقال إلى لاعب",
Options = getPlayerNames(false), CurrentOption = {""}, MultipleOptions
= false, Flag = "TpDropdown", Callback = function(Options)
TpSelectedPlayer = Options[1] end })
GrabTab:CreateButton({ Name = "انتقال (Teleport)", Callback = function()
if TpSelectedPlayer ~= "" then local targetPlr =
Players:FindFirstChild(TpSelectedPlayer) local myChar = lp.Character
if targetPlr and targetPlr.Character and
targetPlr.Character:FindFirstChild("HumanoidRootPart") and myChar and
myChar:FindFirstChild("HumanoidRootPart") then
myChar.HumanoidRootPart.CFrame =
targetPlr.Character.HumanoidRootPart.CFrame * CFrame.new(0, 0, 0.8)
end end end })
GrabTab:CreateButton({ Name = "تحديث قوائم اللاعبين", Callback = function()
local n = getPlayerNamesForTargets() TargetDropdown1:Refresh(n);
TargetDropdown2:Refresh(n); TargetDropdown3:Refresh(n);
TpDropdown:Refresh(getPlayerNames(false)) end })

```

```

-- Player
PlayerTab:CreateToggle({ Name = "إظهار زر التخفي العائم", CurrentValue =
false, Flag = "InvisSystemToggle", Callback = function(Value)
InvisGui.Enabled = Value; if not Value and IsInvisible then
IsInvisible = false; FloatBtn.BackgroundColor3 = Color3.fromRGB(220,
60, 60); FloatBtn.Text = "تخفي: ✖"; for _, item in pairs(invisParts)
do if item.obj and item.obj.Parent then item.obj.Transparency =
item.origTrans end end end end })
PlayerTab:CreateToggle({ Name = "تثبيت السرعة", CurrentValue = false, Flag
= "SpeedToggle", Callback = function(Value) isSpeedEnabled = Value; if
not Value and lp.Character then local hum =
lp.Character:FindFirstChildOfClass("Humanoid") if hum then
hum.WalkSpeed = 16 end end end })
PlayerTab:CreateSlider({ Name = "قيمة السرعة", Range = {16, 150},
Increment = 1, Suffix = "WS", CurrentValue = 35, Flag = "SpeedSlider",
Callback = function(Value) currentWalkSpeed = Value end })
PlayerTab:CreateToggle({ Name = "قفز لانهائي", CurrentValue = false, Flag
= "InfJumpToggle", Callback = function(Value) isInfJump = Value end })

```



```

-- Waypoints
WaypointsTab:CreateSection("إدارة الأماكن المحفوظة")
local NewWaypointName = ""
WaypointsTab:CreateInput({ Name = "اسم المكان", PlaceholderText = "اكتب اسم المكان...", RemoveTextAfterFocusLost = false, Callback = function(Text) NewWaypointName = Text end })
local WaypointDropdown
WaypointsTab:CreateButton({ Name = "حفظ الموقع الحالي", Callback = function() if NewWaypointName ~= "" and lp.Character and lp.Character:FindFirstChild("HumanoidRootPart") then SavedWaypoints[NewWaypointName] = lp.Character.HumanoidRootPart.CFrame; saveData(); Rayfield:Notify({Title = "تم الحفظ", Content = NewWaypointName, Duration = 2}); if WaypointDropdown then WaypointDropdown:Refresh(getWaypointNames()) end else Rayfield:Notify({Title = "خطأ", Content = "اكتب اسمًا", Duration = 2}) end end })
WaypointDropdown = WaypointsTab:CreateDropdown({ Name = "قائمة الأماكن", Options = getWaypointNames(), CurrentOption = {""}, MultipleOptions = false, Flag = "WaypointsDropdownList", Callback = function(Options) if Options[1] and Options[1] ~= "لا يوجد مواقع محفوظة" then SelectedWaypointName = Options[1] end end })
WaypointsTab:CreateButton({ Name = "تنقل إلى المكان المحدد", Callback = function() if SelectedWaypointName and SavedWaypoints[SelectedWaypointName] and lp.Character and lp.Character:FindFirstChild("HumanoidRootPart") then lp.Character.HumanoidRootPart.CFrame = SavedWaypoints[SelectedWaypointName] end end })
WaypointsTab:CreateButton({ Name = "حذف المكان المحدد", Callback = function() if SelectedWaypointName and SavedWaypoints[SelectedWaypointName] then SavedWaypoints[SelectedWaypointName] = nil; saveData(); SelectedWaypointName = nil; if WaypointDropdown then WaypointDropdown:Refresh(getWaypointNames()) end end end })

-- ESP
EspTab:CreateToggle({ Name = "تفعيل ESP", CurrentValue = false, Flag = "EspMainToggle", Callback = function(Value) EspEnabled = Value; refreshAllEsp() end })
EspTab:CreateToggle({ Name = "تظليل (Highlight)", CurrentValue = true, Flag = "EspBoxesToggle", Callback = function(Value) EspBoxes = Value; refreshAllEsp() end })
EspTab:CreateToggle({ Name = "أسماء ومسافة", CurrentValue = true, Flag = "EspNamesToggle", Callback = function(Value) EspNames = Value; refreshAllEsp() end })

-- Names
NameTab:CreateToggle({ Name = "تفعيل التأثيرات", CurrentValue = false, Flag

```

```

= "NameEffectToggle", Callback = function(Value) BWNameActive = Value
end })
NameTab:CreateDropdown({ Name = "النوع", Options = {"BW", "Rainbow",
"Pulse", "Strobe", "Police"}, CurrentOption = {"Rainbow"},
MultipleOptions = false, Flag = "NameEffectModeDropdown", Callback =
function(Options) currentNameMode = Options[1] end })
NameTab:CreateSlider({ Name = "السرعة", Range = {0.1, 3.0}, Increment =
0.1, Suffix = "x", CurrentValue = 0.7, Flag = "NameSpeedSlider",
Callback = function(Value) rnSpeed = Value end })

-- Settings
SettingsTab:CreateSection("إدارة الحفظ (Settings)")
SettingsTab:CreateButton({
    Name = "حفظ إعدادات الواجهة (الكل)",
    Callback = function()
        pcall(function() Rayfield:SaveConfiguration() end)
        Rayfield:Notify({Title = "تم الحفظ!", Content = "تم حفظ جميع أزرار
وتفعيلات الواجهة", Duration = 3})
    end
})

SettingsTab:CreateSection("قائمة اللاعبين الآمنين (SAFE)")
local SafeDropdown1, SafeDropdown2, SafeDropdown3, SafeDropdown4,
SafeDropdown5
SafeDropdown1 = SettingsTab:CreateDropdown({ Name = "SAFE 1", Options
= getPlayerNames(false), CurrentOption = {SAVE.safe1 ~= "" and
SAVE.safe1 or ""}, MultipleOptions = false, Flag = "SafeDropdown1",
Callback = function(Options) if Options[1] then SAVE.safe1 =
Options[1]; saveData(); refreshAllEsp() end end })
SafeDropdown2 = SettingsTab:CreateDropdown({ Name = "SAFE 2", Options
= getPlayerNames(false), CurrentOption = {SAVE.safe2 ~= "" and
SAVE.safe2 or ""}, MultipleOptions = false, Flag = "SafeDropdown2",
Callback = function(Options) if Options[1] then SAVE.safe2 =
Options[1]; saveData(); refreshAllEsp() end end })
SafeDropdown3 = SettingsTab:CreateDropdown({ Name = "SAFE 3", Options
= getPlayerNames(false), CurrentOption = {SAVE.safe3 ~= "" and
SAVE.safe3 or ""}, MultipleOptions = false, Flag = "SafeDropdown3",
Callback = function(Options) if Options[1] then SAVE.safe3 =
Options[1]; saveData(); refreshAllEsp() end end })
SafeDropdown4 = SettingsTab:CreateDropdown({ Name = "SAFE 4", Options
= getPlayerNames(false), CurrentOption = {SAVE.safe4 ~= "" and
SAVE.safe4 or ""}, MultipleOptions = false, Flag = "SafeDropdown4",
Callback = function(Options) if Options[1] then SAVE.safe4 =
Options[1]; saveData(); refreshAllEsp() end end })
SafeDropdown5 = SettingsTab:CreateDropdown({ Name = "SAFE 5", Options
= getPlayerNames(false), CurrentOption = {SAVE.safe5 ~= "" and
SAVE.safe5 or ""}, MultipleOptions = false, Flag = "SafeDropdown5",
Callback = function(Options) if Options[1] then SAVE.safe5 =

```

```

Options[1]; saveData(); refreshAllEsp() end end })

SettingsTab:CreateButton({
    Name = "تحديث قائمة اللاعبين الآمنين",
    Callback = function()
        local names = getPlayerNames(false)
        SafeDropdown1:Refresh(names); SafeDropdown2:Refresh(names);
        SafeDropdown3:Refresh(names); SafeDropdown4:Refresh(names);
        SafeDropdown5:Refresh(names)
    end
})

-- =====
-- [ 5 ] (المحرك الأساسي) يعمل لكل شيء
-- =====
RunService.Heartbeat:Connect(function(dt)
    if IsInvisible and lp.Character then
        local rootPart = lp.Character:FindFirstChild("HumanoidRootPart")
        local humanoid = lp.Character:FindFirstChild("Humanoid")
        if rootPart and humanoid then
            local cf = rootPart.CFrame
            local camOffset = humanoid.CameraOffset
            local hidden = cf * CFrame.new(0, -200000, 0)
            rootPart.CFrame = hidden
            humanoid.CameraOffset =
hidden:ToObjectSpace(CFrame.new(cf.Position)).Position
            RunService.RenderStepped:Wait()
            if rootPart.Parent then
                rootPart.CFrame = cf
                humanoid.CameraOffset = camOffset
            end
        end
    end
end

if isSpeedEnabled and lp.Character then
    local hum = lp.Character:FindFirstChildOfClass("Humanoid")
    if hum and hum.WalkSpeed ~= currentWalkSpeed then hum.WalkSpeed =
currentWalkSpeed end
end

if AuraEnabled then
    local currentTick = tick()
    if currentTick - lastHitTick >= (1 / apsVal) then
        lastHitTick = currentTick
        local ch = lp.Character
        if ch then
            local myhrp = ch:FindFirstChild("HumanoidRootPart")
            if myhrp then

```

```

        local nearest, nearDist = nil, math.huge
        for _, p in ipairs(Players:GetPlayers()) do
            if p ~= lp and p.Character and not isSafe(p.Name)
and isTarget(p.Name) then
                local hrp =
p.Character:FindFirstChild("HumanoidRootPart")
                local hum =
p.Character:FindFirstChildOfClass("Humanoid")
                if hrp and hum and hum.Health > 0 then
                    local dist = (hrp.Position -
myhrp.Position).Magnitude
                    if dist <= rangeVal and dist < nearDist
then
                        nearDist = dist; nearest = {hum =
hum, pos = hrp.Position + hrp.CFrame.LookVector * 2}
                    end
                end
            end
        end
        if nearest then task.spawn(function()
doHit(nearest.hum, nearest.pos) end) end
    end
end
end

local shouldGrab = AutoGrab
local activeTargetHRP = nil

if AutoTargetEnabled then
    local myChar = lp.Character
    if myChar and myChar:FindFirstChild("HumanoidRootPart") then
        for _, player in ipairs(Players:GetPlayers()) do
            if player ~= lp and player.Character and
player.Character:FindFirstChild("HumanoidRootPart") then
                if (myChar.HumanoidRootPart.Position -
player.Character.HumanoidRootPart.Position).Magnitude <=
TriggerDistance then
                    shouldGrab = true
                    activeTargetHRP =
player.Character.HumanoidRootPart
                    break
                end
            end
        end
    end
end
end
end
end

```

```

if SpecificTargetEnabled then
    local myChar = lp.Character
    if myChar and myChar:FindFirstChild("HumanoidRootPart") then

        local function checkTarget(targetName)
            if targetName ~= "" and targetName ~= "لا أحد" then
                local p = Players:FindFirstChild(targetName)
                if p and p.Character and
p.Character:FindFirstChild("HumanoidRootPart") then
                    if (myChar.HumanoidRootPart.Position -
p.Character.HumanoidRootPart.Position).Magnitude <= TriggerDistance
then
                        return p.Character.HumanoidRootPart
                    end
                end
            end
            return nil
        end

        activeTargetHRP = checkTarget(ChosenTargetName1)
        if not activeTargetHRP then activeTargetHRP =
checkTarget(ChosenTargetName2) end
        if not activeTargetHRP then activeTargetHRP =
checkTarget(ChosenTargetName3) end

        if activeTargetHRP then shouldGrab = true end
    end
end

if lp.Character and lp.Character:FindFirstChild("HumanoidRootPart")
then
    local myRoot = lp.Character.HumanoidRootPart
    local currentGrabPower = lp:GetAttribute("GrabPower") or 0
    local isFighting = lp:GetAttribute("Fighting")

    if activeTargetHRP then
        if not isFighting then
            if AutoLookEnabled then
                local targetPos =
Vector3.new(activeTargetHRP.Position.X, myRoot.Position.Y,
activeTargetHRP.Position.Z)
                if (targetPos - myRoot.Position).Magnitude > 0.5 then
                    local bg = myRoot:FindFirstChild("AutoLookGyro")
                    if not bg then
                        bg = Instance.new("BodyGyro")
                        bg.Name = "AutoLookGyro"
                        bg.MaxTorque = Vector3.new(0, 400000, 0)
                        bg.P = 30000
                    end
                end
            end
        end
    end
end

```

```

        bg.D = 100
        bg.Parent = myRoot
    end
    bg.CFrame = CFrame.lookAt(myRoot.Position,
targetPos)
        else
            removeLookGyro()
        end
    else
        removeLookGyro()
    end

    if AutoMagnetEnabled and currentGrabPower >= 100 then
        local targetVelocity =
activeTargetHRP.AssemblyLinearVelocity
        local pingPrediction = targetVelocity * 0.05
        myRoot.CFrame = (activeTargetHRP.CFrame +
pingPrediction) * CFrame.new(0, 0, 2.5)

        if firetouchinterest then
            firetouchinterest(myRoot, activeTargetHRP, 0)
            task.wait()
            firetouchinterest(myRoot, activeTargetHRP, 1)
        end
    end
    else
        removeLookGyro()
    end

    if IsHoldingMagnet and currentGrabPower >= 100 then
        local targetVelocity =
activeTargetHRP.AssemblyLinearVelocity
        local pingPrediction = targetVelocity * 0.05
        myRoot.CFrame = (activeTargetHRP.CFrame + pingPrediction)
* CFrame.new(0, 0, 2.5)

        if firetouchinterest then
            firetouchinterest(myRoot, activeTargetHRP, 0)
            task.wait()
            firetouchinterest(myRoot, activeTargetHRP, 1)
        end
    end
    else
        removeLookGyro()
    end
end

if shouldGrab and GrabRF then

```

```

    for i = 1, grabRepeatVal do
        task.spawn(function()
            pcall(function() GrabRF:InvokeServer() end)
        end)
    end
end

if rainbowNameRemote and BWNameActive then
    local now = os.clock()
    rnHue = (rnHue + (dt * rnSpeed)) % 1
    if now - bwLastUpdate >= (currentNameMode == "Police" and 0.12 or
rnUpdateRate) then
        local targetColor
        if currentNameMode == "BW" then local intensity =
(math.sin(rnHue * math.pi * 2) + 1) / 2; targetColor =
Color3.new(intensity, intensity, intensity)
        elseif currentNameMode == "Rainbow" then targetColor =
Color3.fromHSV(rnHue, 1, 1)
        elseif currentNameMode == "Pulse" then targetColor =
Color3.fromHSV(rnHue, 0.8, 1)
        elseif currentNameMode == "Strobe" then targetColor =
Color3.fromRGB(math.random(50,255), math.random(50,255),
math.random(50,255))
        elseif currentNameMode == "Police" then policeToggle = not
policeToggle; targetColor = policeToggle and Color3.fromRGB(0, 100,
255) or Color3.fromRGB(255, 0, 0) end
        if targetColor then pcall(function()
rainbowNameRemote:FireServer(targetColor) end) end
        bwLastUpdate = now
    end
end
end)

pcall(function()
    Rayfield:LoadConfiguration()
end)

```