

Minimum Difference Element (medium)

We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
 - Time complexity
 - Space complexity

Problem Statement

Given an array of numbers sorted in ascending order, find the element in the array that has the minimum difference with the given 'key'.

Example 1:

```
Input: [4, 6, 10], key = 7
Output: 6
Explanation: The difference between the key '7' and '6' is minimum than any other number in the array
```

Example 2:

```
Input: [4, 6, 10], key = 4
Output: 4
```

Example 3:

```
Input: [1, 3, 8, 10, 15], key = 12
Output: 10
```

Example 4:

```
Input: [4, 6, 10], key = 17
Output: 10
```

Try it yourself

Try solving this question here:

JavaPython3JS C++

```
1 class MinimumDifference {
2
3     public static int searchMinDiffElement(int[] arr, int key) {
4         // TODO: Write your code here
5         return -1;
6     }
7
8     public static void main(String[] args) {
9         System.out.println(MinimumDifference.searchMinDiffElement(new int[] { 4, 6, 10 }, 7));
10        System.out.println(MinimumDifference.searchMinDiffElement(new int[] { 4, 6, 10 }, 4));
11        System.out.println(MinimumDifference.searchMinDiffElement(new int[] { 1, 3, 8, 10, 15 }, 12));
12        System.out.println(MinimumDifference.searchMinDiffElement(new int[] { 4, 6, 10 }, 17));
13    }
14 }
```

RunSaveReset

Solution

The problem follows the **Binary Search** pattern. Since Binary Search helps us find a number in a sorted array efficiently, we can use a modified version of the Binary Search to find the number that has the minimum difference with the given 'key'.

We can use a similar approach as discussed in [Order-agnostic Binary Search](#). We will try to search for the

'key' in the given array. If we find the 'key' we will return it as the minimum difference number. If we can't find the 'key', (at the end of the loop) we can find the differences between the 'key' and the numbers pointed out by indices **start** and **end**, as these two numbers will be closest to the 'key'. The number that gives minimum difference will be our required number.

Code

Here is what our algorithm will look like:

Java Python3 C++ JS

```
1 class MinimumDifference {
2
3     public static int searchMinDiffElement(int[] arr, int key) {
4         if (key < arr[0])
5             return arr[0];
6         if (key > arr[arr.length - 1])
7             return arr[arr.length - 1];
8
9         int start = 0, end = arr.length - 1;
10        while (start <= end) {
11            int mid = start + (end - start) / 2;
12            if (key < arr[mid]) {
13                end = mid - 1;
14            } else if (key > arr[mid]) {
15                start = mid + 1;
16            } else {
17                return arr[mid];
18            }
19        }
20
21        // at the end of the while loop, 'start == end+1'
22        // we are not able to find the element in the given array
23        // return the element which is closest to the 'key'
24        if ((arr[start] - key) < (key - arr[end]))
25            return arr[start];
26        return arr[end];
27    }
28}
```

Run Save Reset

Time complexity

Since, we are reducing the search range by half at every step, this means the time complexity of our algorithm will be $O(\log N)$ where 'N' is the total elements in the given array.

Space complexity

The algorithm runs in constant space $O(1)$.

← Back

Search in a Sorted Infinite Array (medi...

Next →

Bitonic Array Maximum (easy)

✓ Mark as Completed

! Report an Issue ? Ask a Question