Solution Review: Problem Challenge 2

Right View of a Binary Tree (easy)

Given a binary tree, return an array containing nodes in its right view. The right view of a binary tree is the set of **nodes visible when the tree is seen from the right side**.

Example 1

Right View: [1, 3, 7]

Exampe 2

Right View: [12, 1, 5, 3]

Solution

This problem follows the [Binary Tree Level Order Traversal](#) pattern. We can follow the same **BFS** approach. The only additional thing we will be do is to append the last node of each level to the result array.

Code

Here is what our algorithm will look like; only the highlighted lines have changed:

```
Java      Python3      C++      JS

 1  import java.util.*;
 2
 3  class TreeNode {
 4    int val;
 5    TreeNode left;
 6    TreeNode right;
 7
 8    TreeNode(int x) {
 9      val = x;
10    }
11  };
12
13  class RightViewTree {
14    public static List<TreeNode> traverse(TreeNode root) {
15      List<TreeNode> result = new ArrayList<>();
16      if (root == null)
```

```
17        return result;
18
19      Queue<TreeNode> queue = new LinkedList<>();
20      queue.offer(root);
21      while (!queue.isEmpty()) {
22        int levelSize = queue.size();
23        for (int i = 0; i < levelSize; i++) {
24          TreeNode currentNode = queue.poll();
25          // if it is the last node of this level, add it to the result
26          if (i == levelSize - 1)
27            result.add(currentNode);
28          // insert the children of current node in the queue
```

Run   Save   Reset   ⛶

Time complexity

The time complexity of the above algorithm is $O(N)$, where 'N' is the total number of nodes in the tree. This is due to the fact that we traverse each node once.

Space complexity

The space complexity of the above algorithm will be $O(N)$ as we need to return a list containing the level order traversal. We will also need $O(N)$ space for the queue. Since we can have a maximum of $N/2$ nodes at any level (this could happen only at the lowest level), therefore we will need $O(N)$ space to store them in the queue.

Similar Questions

Problem 1: Given a binary tree, return an array containing nodes in its left view. The left view of a binary tree is the set of nodes visible when the tree is seen from the left side.

Solution: We will be following a similar approach, but instead of appending the last element of each level we will be appending the first element of each level to the output array.

✔ Mark as Completed

⊘ Report an Issue   ? Ask a Question