

Fruits into Baskets (medium)

We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
 - Time Complexity
 - Space Complexity
- Similar Problems

Problem Statement

Given an array of characters where each character represents a fruit tree, you are given **two baskets**, and your goal is to put **maximum number of fruits in each basket**. The only restriction is that **each basket can have only one type of fruit**.

You can start with any tree, but you can't skip a tree once you have started. You will pick one fruit from each tree until you cannot, i.e., you will stop when you have to pick from a third fruit type.

Write a function to return the maximum number of fruits in both the baskets.

Example 1:

```
Input: Fruit=['A', 'B', 'C', 'A', 'C']
Output: 3
Explanation: We can put 2 'C' in one basket and one 'A' in the other from the subarray ['C', 'A', 'C']
```


Example 2:


```
Input: Fruit=['A', 'B', 'C', 'B', 'B', 'C']
Output: 5
Explanation: We can put 3 'B' in one basket and two 'C' in the other basket.
This can be done if we start with the second letter: ['B', 'C', 'B', 'B', 'C']
```

Try it yourself

Try solving this question here:

 Java

 Python3

 JS

 C++

```
1 import java.util.*;
2
3 class MaxFruitCountOf2Types {
4     public static int findLength(char[] arr) {
5         // TODO: Write your code here
6         return -1;
7     }
8 }
9
```

Test

Save Reset ↺

Solution

This problem follows the **Sliding Window** pattern and is quite similar to [Longest Substring with K Distinct Characters](#). In this problem, we need to find the length of the longest subarray with no more than two distinct characters (or fruit types!). This transforms the current problem into **Longest Substring with K Distinct Characters** where $K=2$.

Code

Here is what our algorithm will look like, only the highlighted lines are different from [Longest Substring with K Distinct Characters](#):

```
1 import java.util.*;
2
3 class MaxFruitCountOf2Types {
4     public static int findLength(char[] arr) {
5         int windowStart = 0, maxLength = 0;
6         Map<Character, Integer> fruitFrequencyMap = new HashMap<>();
7         // try to extend the range [windowStart, windowEnd]
8         for (int windowEnd = 0; windowEnd < arr.length; windowEnd++) {
9             fruitFrequencyMap.put(arr[windowEnd], fruitFrequencyMap.getOrDefault(arr[windowEnd], 0) + 1);
10            // shrink the sliding window, until we are left with '2' fruits in the frequency map
11            while (fruitFrequencyMap.size() > 2) {
12                fruitFrequencyMap.put(arr[windowStart], fruitFrequencyMap.get(arr[windowStart]) - 1);
13                if (fruitFrequencyMap.get(arr[windowStart]) == 0) {
14                    fruitFrequencyMap.remove(arr[windowStart]);
15                }
16                windowStart++; // shrink the window
17            }
18            maxLength = Math.max(maxLength, windowEnd - windowStart + 1);
19        }
20
21        return maxLength;
22    }
23
24    public static void main(String[] args) {
25        System.out.println("Maximum number of fruits: " +
26                           MaxFruitCountOf2Types.findLength(new char[] { 'A', 'B', 'C', 'A', 'C' }));
27        System.out.println("Maximum number of fruits: " +
28                           MaxFruitCountOf2Types.findLength(new char[] { 'A', 'B', 'C', 'B', 'B', 'C' }));
29    }
30 }
```

Run Save Reset

Time Complexity

The above algorithm's time complexity will be $O(N)$, where 'N' is the number of characters in the input array. The outer **for** loop runs for all characters, and the inner **while** loop processes each character only once; therefore, the time complexity of the algorithm will be $O(N + N)$, which is asymptotically equivalent to $O(N)$.

Space Complexity

The algorithm runs in constant space $O(1)$ as there can be a maximum of three types of fruits stored in the frequency map.

Similar Problems

Problem 1: Longest Substring with at most 2 distinct characters

Given a string, find the length of the longest substring in it with at most two distinct characters.

Solution: This problem is exactly similar to our parent problem.

← Back

Longest Substring with K Distinct Cha...

Next →

No-repeat Substring (hard)

✓ Completed

Report an Issue Ask a Question