

## Longest Subarray with Ones after Replacement (hard)

### We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
  - Time Complexity
  - Space Complexity

### Problem Statement #

Given an array containing 0s and 1s, if you are allowed to **replace no more than 'k' 0s with 1s**, find the length of the **longest contiguous subarray having all 1s**.

#### Example 1:

```
Input: Array=[0, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1], k=2
Output: 6
Explanation: Replace the '0' at index 5 and 8 to have the longest contiguous subarray of 1s having length 6.
```

#### Example 2:


```
Input: Array=[0, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 1], k=3
Output: 9
Explanation: Replace the '0' at index 6, 9, and 10 to have the longest contiguous subarray of 1s having length 9.
```


### Try it yourself #

Try solving this question here:

 Java

 Python3

 JS

 C++

```
1 def length_of_longest_substring(arr, k):
2     # TODO: Write your code here
3     return -1
4
```

Test

Save

Reset



### Solution #

This problem follows the **Sliding Window** pattern and is quite similar to [Longest Substring with same Letters after Replacement](#). The only difference is that, in the problem, we only have two characters (1s and 0s) in the input arrays.

Following a similar approach, we'll iterate through the array to add one number at a time in the window. We'll also keep track of the maximum number of repeating 1s in the current window (let's call it `maxOnesCount`). So at any time, we know that we can have a window with 1s repeating `maxOnesCount` time, so we should try to replace the remaining 0s. If we have more than 'k' remaining 0s, we should shrink the window as we are not allowed to replace more than 'k' 0s.

## Code #

Here is how our algorithm will look like:

```
1 def length_of_longest_substring(arr, k):
2     window_start, max_length, max_ones_count = 0, 0, 0
3
4     # Try to extend the range [window_start, window_end]
5     for window_end in range(len(arr)):
6         if arr[window_end] == 1:
7             max_ones_count += 1
8
9         # Current window size is from window_start to window_end, overall we have a maximum of 1s
10        # repeating 'max_ones_count' times, this means we can have a window with 'max_ones_count' 1s
11        # and the remaining are 0s which should replace with 1s.
12        # now, if the remaining 0s are more than 'k', it is the time to shrink the window as we
13        # are not allowed to replace more than 'k' 0s
14        if (window_end - window_start + 1 - max_ones_count) > k:
15            if arr[window_start] == 1:
16                max_ones_count -= 1
17            window_start += 1
18
19        max_length = max(max_length, window_end - window_start + 1)
20    return max_length
21
22
23 def main():
24     print(length_of_longest_substring([0, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1], 2))
25     print(length_of_longest_substring(
26         [0, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 1], 3))
27
28
29 main()
30
```

Run Save Reset

## Time Complexity #

The above algorithm's time complexity will be  $O(N)$ , where 'N' is the count of numbers in the input array.

## Space Complexity #

The algorithm runs in constant space  $O(1)$ .

← Back

Next →

Longest Substring with Same Letters ...

Problem Challenge 1

✓ Completed

Report an Issue Ask a Question