

## Middle of the LinkedList (easy)

### We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
  - Code
  - Time complexity
  - Space complexity

## Problem Statement #

Given the head of a **Singly LinkedList**, write a method to return the **middle node** of the LinkedList.

If the total number of nodes in the LinkedList is even, return the second middle node.

**Example 1:**

```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> null
Output: 3
```

**Example 2:**





```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> 6 -> null
Output: 4
```

**Example 3:**

```
Input: 1 -> 2 -> 3 -> 4 -> 5 -> 6 -> 7 -> null
Output: 4
```

## Try it yourself #

Try solving this question here:

 Java	 Python3	 JS	 C++
--	---	--	---

```
1 class Node:
2     def __init__(self, value, next=None):
3         self.value = value
4         self.next = next
5
6
7 def find_middle_of_linked_list(head):
8     # TODO: Write your code here
9     return head
10
11
12 def main():
13     head = Node(1)
14     head.next = Node(2)
15     head.next.next = Node(3)
16     head.next.next.next = Node(4)
17     head.next.next.next.next = Node(5)
18
19     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
20
21     head.next.next.next.next.next = Node(6)
22     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
23
24     head.next.next.next.next.next.next = Node(7)
25     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
```

```
26
27
28 main()
29
```

Run

Save

Reset



## Solution #

One brute force strategy could be to first count the number of nodes in the LinkedList and then find the middle node in the second iteration. Can we do this in one iteration?

We can use the **Fast & Slow pointers** method such that the fast pointer is always twice the nodes ahead of the slow pointer. This way, when the fast pointer reaches the end of the LinkedList, the slow pointer will be pointing at the middle node.

## Code #

Here is what our algorithm will look like:

Java Python3 C++ JS

```
1 class Node:
2     def __init__(self, value, next=None):
3         self.value = value
4         self.next = next
5
6
7 def find_middle_of_linked_list(head):
8     slow = head
9     fast = head
10    while (fast is not None and fast.next is not None):
11        slow = slow.next
12        fast = fast.next.next
13    return slow
14
15
16 def main():
17     head = Node(1)
18     head.next = Node(2)
19     head.next.next = Node(3)
20     head.next.next.next = Node(4)
21     head.next.next.next.next = Node(5)
22
23     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
24
25     head.next.next.next.next.next = Node(6)
26     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
27
28     head.next.next.next.next.next.next = Node(7)
29     print("Middle Node: " + str(find_middle_of_linked_list(head).value))
30
31
32 main()
33
```

Run Save Reset Copy

## Time complexity #

The above algorithm will have a time complexity of  $O(N)$  where 'N' is the number of nodes in the LinkedList.

## Space complexity #

The algorithm runs in constant space  $O(1)$ .

← Back

Next →

