




Rearrange String (hard)



Problem Statement

Given a string, find if its letters can be rearranged in such a way that no two same characters come next to each other.

Example 1:

```
Input: "aappp"
Output: "papap"
Explanation: In "papap", none of the repeating characters come next to each other.
```

Example 2:

```
Input: "Programming"
Output: "rgmrgmPiano" or "gmringmrPoa" or "gmrPagimnor", etc.
Explanation: None of the repeating characters come next to each other.
```

Example 3:

```
Input: "aapa"
Output: ""
Explanation: In all arrangements of "aapa", atleast two 'a' will come together e.g., "apaa", "pa aa".
```

Try it yourself

Try solving this question here:

```
from heapq import *

def rearrange_string(str):
    # TODO: Write your code here
    return ""

def main():
    print("Rearranged string: " + rearrange_string("aappp"))
    print("Rearranged string: " + rearrange_string("Programming"))
    print("Rearranged string: " + rearrange_string("aappp"))
    print("Rearranged string: " + rearrange_string("aappp"))

main()

main()
```

Solution

This problem follows the Top 'K' Numbers pattern. We can follow a greedy approach to find an arrangement of the given string where no two same characters come next to each other.

We can work in a stepwise fashion to create a string with all characters from the input string. Following a greedy approach, we should first append the most frequent characters to the output strings, for which we can use a **Max Heap**. By appending the most frequent character first, we have the best chance to find a string where no two same characters come next to each other.

So in each step, we should append one occurrence of the highest frequency character to the output string. We will not put this character back in the heap to ensure that no two same characters are adjacent to each other. In the next step, we should process the next most frequent character from the heap in the same way and then, at the end of this step, insert the character from the previous step back to the heap after decrementing its frequency.

Following this algorithm, if we can append all the characters from the input string to the output string, we would have successfully found an arrangement of the given string where no two same characters appeared adjacent to each other.

Code

Here is what our algorithm will look like:

```
👙 Java
            Python3
                          ⓒ C++
                                       Js JS
      rom heapq impor
    def rearrange string(str):
      charFrequencyMap = {}
      for char in str:
        charFrequencyMap[char] = charFrequencyMap.get(char, 0) + 1
      maxHeap = []
      for char, frequency in charFrequencyMap.items():
       heappush(maxHeap, (-frequency, char))
      previousChar, previousFrequency = None, 0
      resultString = []
      while maxHeap:
        frequency, char = heappop(maxHeap)
        if previousChar and -previousFrequency > 0:
          heappush(maxHeap, (previousFrequency, previousChar))
        resultString.append(char)
        previousChar = char
        previousFrequency = frequency+1 # decrement the frequency
      return ''.join(resultString) if len(resultString) == len(str) else ""
    def main():
      print("Rearranged string: " + rearrange_string("aappp"))
print("Rearranged string: " + rearrange_string("Programming"))
      print("Rearranged string: " + rearrange_string("aapa"))
Run
                                                                                                                 ::3
```

Time complexity

input string.

Space complexity

The space complexity will be O(N), as in the worst case, we need to store all the 'N' characters in the **HashMap**.

