

Merkblatt – Installation der MySQL Datenbank auf Ubuntu

Installation des mysql-Servers

Starten Sie das Terminal. Geben Sie folgende Befehle ein:

- 1) `sudo apt update`
- 2) `sudo apt install mysql-server`

Dies installiert den mysql-Server. Starten Sie nun die Konfiguration:

```
Processing triggers for libc-bin (2.31-0ubuntu9.2) ...  
test@test-VirtualBox:~$ sudo mysql_secure_installation  
  
Securing the MySQL server deployment.  
  
Connecting to MySQL using a blank password.  
  
VALIDATE PASSWORD COMPONENT can be used to test passwords  
and improve security. It checks the strength of password  
and allows the users to set only those passwords which are  
secure enough. Would you like to setup VALIDATE PASSWORD component?  
  
Press y|Y for Yes, any other key for No: y
```

3) `sudo mysql_secure_installation`

Entscheiden Sie, ob Sie mit Passwortvalidierung arbeiten möchten.

Setzen Sie dann das Root-Passwort.

Akzeptieren Sie danach die Standardeinstellungen für die nachfolgenden Fragen (Entfernen anonymer Nutzer, Testdatenbank, Remote-Root-Logins und das Neuladen der neuen eingegebenen Regeln).

```
New password:
Re-enter new password:

Estimated strength of the password: 0
Do you wish to continue with the password provided?(Press y|Y for Yes, any other key for No) : y
By default, a MySQL installation has an anonymous user,
allowing anyone to log into MySQL without having to have
a user account created for them. This is intended only for
testing, and to make the installation go a bit smoother.
You should remove them before moving into a production
environment.

Remove anonymous users? (Press y|Y for Yes, any other key for No) : y
Success.

Normally, root should only be allowed to connect from
'localhost'. This ensures that someone cannot guess at
the root password from the network.

Disallow root login remotely? (Press y|Y for Yes, any other key for No) : y
Success.

By default, MySQL comes with a database named 'test' that
anyone can access. This is also intended only for testing,
and should be removed before moving into a production
environment.

Remove test database and access to it? (Press y|Y for Yes, any other key for No) : y
- Dropping test database...
Success.

- Removing privileges on test database...
Success.

Reloading the privilege tables will ensure that all changes
made so far will take effect immediately.

Reload privilege tables now? (Press y|Y for Yes, any other key for No) : y
Success.

All done!
```

Installation der MySQL-Workbench

Geben Sie im Terminal ein:

```
sudo apt install mysql-workbench
```