

# 00ex\_introduction

March 14, 2020

## 1. The MickeyMouse problem

- a) Write a program that prints the numbers from 1 to 100. But for multiples of three print Mickey instead of the number and for the multiples of five print Mouse. For numbers which are multiples of both three and five print MickeyMouse
- b) Put the result in a tuple and substitute Mickey with Donald and Mouse with Duck

```
In [1]: """
        for i in range (1,100):
            if i%3==0 and i%5!=0:
                print("Myckey")
            if i%5==0 and i%3!=0:
                print("Muose")
            if i%3==0 and i%5==0:
                print("MickeyMuose")
            if i%3!=0 and i%5!=0:
                print(i)
        """

a=[]

for i in range(1,100):
    if i%3==0 or i%5==0:
        if i%5==0:
            if i%3==0:
                a.append("MickeyMouse")
            else:
                a.append("Mouse")
        else:
            a.append("Mickey")
    else:
        a.append(i)

for i in a: print (i)

b=a
```

```

for i in range (0,99):
    if b[i]=="MickeyMouse":
        b[i]="DonaldDuck"
    if b[i]=="Mouse":
        b[i]="Duck"
    if b[i]=="Mickey":
        b[i]="Donald"
at=tuple(x for x in b)
print(at)

```

```

1
2
Mickey
4
Mouse
Mickey
7
8
Mickey
Mouse
11
Mickey
13
14
MickeyMouse
16
17
Mickey
19
Mouse
Mickey
22
23
Mickey
Mouse
26
Mickey
28
29
MickeyMouse
31
32
Mickey
34
Mouse
Mickey
37

```

38  
Mickey  
Mouse  
41  
Mickey  
43  
44  
MickeyMouse  
46  
47  
Mickey  
49  
Mouse  
Mickey  
52  
53  
Mickey  
Mouse  
56  
Mickey  
58  
59  
MickeyMouse  
61  
62  
Mickey  
64  
Mouse  
Mickey  
67  
68  
Mickey  
Mouse  
71  
Mickey  
73  
74  
MickeyMouse  
76  
77  
Mickey  
79  
Mouse  
Mickey  
82  
83  
Mickey  
Mouse

```

86
Mickey
88
89
MickeyMouse
91
92
Mickey
94
Mouse
Mickey
97
98
Mickey
(1, 2, 'Donald', 4, 'Duck', 'Donald', 7, 8, 'Donald', 'Duck', 11, 'Donald', 13, 14, 'DonaldDuck')

```

## 2. The swap function

Write a function that swap the values of two input variables x and y (whatever the type). Try to do that also without a temporary variable

```

In [2]: def canonic_swap (x,y):
        t=x
        x=y
        y=t
        return x,y

def python_swap (x,y):
    return y,x

x=input("input x")
y=input("input y")
print (x,y)
x, y = canonic_swap(x,y)
print(x,y)
x, y = python_swap(x,y)
print (x,y)

```

```

input x 5
input y 6

```

```

5 6
6 5
5 6

```

## 3. Computing the distance

Write a function that calculates and returns the euclidean distance between two points  $u$  and  $v$ , where  $u$  and  $v$  are both 2-tuples  $(x,y)$ . For example, if  $u=(3,0)$  and  $v=(0,4)$ , the function should return 5

```
In [3]: import math
def dist (a, b):
    return math.sqrt(pow(a[0]-b[0],2) + pow(a[1]-b[1],2))
a= (3,0)
b=(0,4)
print (dist(a,b))
```

5.0

#### 4. Counting letters

Write a program to calculate the number of times each character occurs in a given string  $s$ . Ignore differences in capitalization

```
In [4]: s="Write a program that prints the numbers from 1 to 100. \
But for multiples of three print Mickey instead of the number and for the multiples of
For numbers which are multiples of both three and five print MickeyMouse"
```

```
a={}
for letter in s:
    f = False
    for i in a:
        if i==letter:
            f=True
    if f==False:
        a[letter]=1
    else:
        a[letter]+=1
print(a)
```

```
{'W': 1, 'r': 17, 'i': 14, 't': 19, 'e': 22, ' ': 41, 'a': 7, 'p': 8, 'o': 13, 'g': 1, 'm': 8,
```

#### 5. Isolating the unique

Write a function that determines and count the unique numbers in the list  $l$

```
In [5]: #as unique i intended number that appears only one time
```

```
l = [157, 157, 36, 45, 58, 3, 74, 96, 64, 45, 31, 10, 24, 19, 33, 86, 99, 18, 63, 70, 8
85, 63, 47, 56, 42, 70, 84, 88, 55, 20, 54, 8, 56, 51, 79, 81, 57, 37, 91,
1, 84, 84, 36, 66, 9, 89, 50, 42, 91, 50, 95, 90, 98, 39, 16, 82, 31, 92, 41,
45, 30, 66, 70, 34, 85, 94, 5, 3, 36, 72, 91, 84, 34, 87, 75, 53, 51, 20, 89, 51, 20]

u=0
for x in l:
```

```

f=0
for y in l:
    if x==y:
        f+=1
if f<2:
    #print(x, "is unique")
    u+=1
print("total uniques: ", u)

```

total uniques: 37

## 6. Combination of functions

Write two functions - one that returns the square of a number, and one that returns the cube. Now write a third function that returns the number raised to the 6th power using the two previous functions.

```

In [6]: def square (x):
        return x*x
        def cube (x):
            return x*x*x
        def sixth (x):
            return square(x)*cube(x)

```

```

x=5
print (x)
x=square(x)
print (x)

```

```

y=5
print (y)
y=cube(y)
print (y)

```

```

z=5
print (z)
z=sixth(z)
print (z)

```

5  
25  
5  
125  
5  
3125

## 7. Cubes

Create a list of the cubes of x for x in [0, 10] using:

- a) a for loop
- b) a list comprehension

```
In [7]: a=[]
        for i in range (0,10):
            a.append(cube(i))
        print (a)

        b=[cube(x) for x in range (0,10)]
        print (b)

[0, 1, 8, 27, 64, 125, 216, 343, 512, 729]
[0, 1, 8, 27, 64, 125, 216, 343, 512, 729]
```

## 8. Nested list comprehension

A Pythagorean triple is an integer solution to the Pythagorean theorem  $a^2 + b^2 = c^2$ . The first Pythagorean triple is (3,4,5). Find and put in a tuple all unique Pythagorean triples for the positive integers a, b and c less than 100.

```
In [8]: a=tuple([(x,y,z) for x in range (1,100) for y in range (x,100) for z in range (y,100) ])
        print (a)

((3, 4, 5), (5, 12, 13), (6, 8, 10), (7, 24, 25), (8, 15, 17), (9, 12, 15), (9, 40, 41), (10, 2
```

## 9. Normalization

Write a function that takes a tuple of numbers and returns it with the entries normalized to one

```
In [9]: import math

#questa funzione è intesa come norma del vettore 1
def norm(a):
    t=0
    for n in a:
        t+=n*n
    b=[x/math.sqrt(t) for x in a]
    c=tuple(b)
    return c

#questa è intesa come valore massimo del vettore 1
def norm2(a):
    t=max(a)
    b=[x/t for x in a]
    c=tuple(b)
    return c

a=(3,5,8)
print(a)
```

```
a=norm (a)
print (a)
a=norm2 (a)
print (a)
```

```
(3, 5, 8)
(0.30304576336566325, 0.5050762722761054, 0.8081220356417685)
(0.37500000000000006, 0.6250000000000001, 1.0)
```

```
In [ ]:
```