TECHNICAL BULLETIN

CulinaPro OV-660 Rear Clearance Requirement Update

Field	Value	Field	Value
Document ID	TB-001	Revision	1
Effective Date	15 July 2026	Status	Current
Document Type	Technical Bulletin	Authority Class	Manufacturer Technical
Product Family	CulinaPro OV Series	Supersedes	None

1. Purpose

Introduces a revised minimum rear-clearance requirement for a defined OV-660 production population. It does not change unaffected OV-660 units or other OV Series models.

2. Affected Equipment

Model: OV-660. Affected production batch range: OV660-B260701 through OV660-B260930.

3. Revised Requirement

Requirement	PT-009 Baseline	TB-001 Affected Units
Minimum rear clearance	150 mm	200 mm

4. Applicability

OV-660 + affected batch -> minimum rear clearance = 200 mm.

Confirmed unaffected OV-660 units remain governed by the current PT-009 baseline unless another controlled bulletin applies.

5. Unknown Batch

If the production batch cannot be confirmed, bulletin applicability is UNKNOWN. Where site fit depends on the difference between 150 mm and 200 mm, obtain the batch before confirming installation feasibility.

6. Scope of Override

TB-001 overrides PT-009 only for the affected OV-660 rear-clearance claim. Side clearance, top clearance, utilities, service access, ventilation, and other installation requirements remain governed by applicable documentation.

7. Decision Rules

• Identify exact model.

• Obtain production batch.

• Retrieve PT-009 and TB-001.

• Apply 200 mm only when the batch is affected.

• Keep applicability UNKNOWN when the batch is missing and the distinction is material.

• Do not transfer the requirement to other OV models.

8. Related Documentation

• PT-008 - CulinaPro OV Series Product Guide

• PT-009 - CulinaPro OV Series Installation Guide

Controlled technical knowledge. Apply only to the documented product population, relationship, and conditions.