POLARIX IC SERIES

Commercial Ice Systems - Installation Guide

Field	Value	Field	Value
Document ID	PT-002	Revision	4
Effective Date	1 January 2026	Status	Current
Document Type	Installation Guide	Product Family	Polarix IC Series

1. Purpose and Scope

Defines general site, utility, clearance, drainage, positioning, and commissioning requirements for IC-280, IC-380, IC-420, IC-500, and IC-650.

2. Environmental and Electrical Requirements

Requirement	Value
Ambient	5-40 degrees C
Inlet water	5-35 degrees C
Relative humidity	<=85%, non-condensing

Model	Supply	Rated Power
IC-280	220-240 V, 1 phase, 50 Hz	0.65 kW
IC-380	220-240 V, 1 phase, 50 Hz	0.85 kW
IC-420	220-240 V, 1 phase, 50 Hz	1.30 kW
IC-500	220-240 V, 1 phase, 50 Hz	1.75 kW
IC-650	220-240 V, 1 phase, 50 Hz	2.40 kW

3. Water Supply

• Potable water required

• Dynamic inlet pressure: 0.1-0.8 MPa

• Dedicated shut-off valve required

• Water treatment must not reduce pressure below the machine requirement

Compatibility between Polarix equipment and external treatment systems must be confirmed using the applicable compatibility documentation.

4. Drainage

• Dedicated approved sanitary drain

• Continuous downward fall

• No kinks, restrictions, or backflow

• Air gap where required by local regulation

5. Ventilation and Clearance

Location	Minimum
Rear	150 mm
Left	100 mm

Location	Minimum
Right	100 mm
Top	300 mm

Front service access must remain unobstructed. Additional maintenance working space may be required.

6. Modular Configuration

IC-420, IC-500, and IC-650 require a compatible storage-bin system. Physical fit alone does not establish compatibility. Confirm approved combinations using CP-003.

7. Pre-Commissioning and Commissioning

• Verify model and configuration

• Verify clearances and electrical supply

• Verify dynamic water pressure

• Verify drainage and treatment configuration

• Review applicable technical bulletins

• Complete initial fill, startup, leakage, drainage, and production checks

8. Installation Limitations

Technical suitability, installation feasibility, and inventory availability are separate decisions.

Do not assume accessory compatibility, substitute unapproved adapters, bypass required treatment, reduce clearance without authorization, or commit to performance outside documented conditions.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.