BREWCORE BC SERIES

Professional Espresso Systems - Installation Guide

Field	Value	Field	Value
Document ID	PT-004	Revision	3
Effective Date	1 January 2026	Status	Current
Document Type	Installation Guide	Product Family	BrewCore BC Series

1. Purpose and Scope

Defines site, electrical, water, drainage, positioning, and commissioning requirements for BC-820, BC-920, BC-980, and BC-1100.

2. Electrical Requirements

Model	Supply	Rated Power
BC-820	220-240 V, 1 phase, 50 Hz	3.2 kW
BC-920	220-240 V, 1 phase, 50 Hz	4.8 kW
BC-980	380-415 V, 3 phase, 50 Hz	5.6 kW
BC-1100	380-415 V, 3 phase, 50 Hz	6.8 kW

3. Water Requirements

• Inlet-water temperature: 5-30 degrees C

• Dynamic pressure: 0.15-0.60 MPa

• Potable water

• Dedicated shut-off valve

• Approved treatment configuration required

Measure dynamic pressure under flow where stability is uncertain.

4. BC-920 Installation Note

BC-920 production configurations have been subject to a controlled water-connection update. For certain earlier production units, additional requirements may apply. Verify serial number or production range against current technical bulletins before finalizing the connection.

5. Drainage and Clearance

Location	Minimum
Rear	100 mm
Left	75 mm
Right	75 mm
Top	200 mm

Dedicated drainage must maintain downward fall and prevent backflow.

6. Legacy Upgrades

When replacing legacy BrewCore equipment, record the existing machine, filtration, accessories, electrical supply, plumbing, drainage, and counter dimensions. Reuse must be validated through current compatibility documentation.

7. Pre-Commissioning

• Verify machine and clearances

• Verify electrical supply and grounding

• Verify approved treatment and dynamic pressure

• Verify drainage

• Review applicable technical bulletins

• Complete fill, heating, brewing, steam, hot-water, and drainage checks

8. Limitations

Installation feasibility and product suitability are separate decisions.

Do not assume filtration or accessory compatibility, bypass treatment, use unapproved conversion components, or commit to reuse before compatibility is confirmed.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.