FROSTLINE COMMERCIAL REFRIGERATION

Commercial Refrigeration Systems - Product Catalog

Field	Value	Field	Value
Document ID	PT-005	Revision	4
Effective Date	1 January 2026	Status	Current
Document Type	Product Catalog	Product Family	Frostline Commercial Refrigeration

1. Range Overview

Current portfolio includes UC undercounter, UR upright, and PC preparation-counter refrigeration. Detailed canonical model facts in this corpus focus on the UC family.

2. UC Model Selection

Model	Usable Capacity	Temp Range	Rated Power	Dimensions	Energy
UC-180	180 L	+1 to +8 degrees C	300 W	1,200 x 600 x 850 mm	Standard
UC-220	280 L	+1 to +8 degrees C	390 W	1,500 x 700 x 850 mm	Standard
UC-240E	300 L	+1 to +8 degrees C	310 W	1,360 x 650 x 850 mm	High efficiency
UC-300	450 L	+1 to +8 degrees C	480 W	1,800 x 700 x 850 mm	Standard

3. UC-220 vs UC-240E

Both may be technically suitable around the 280-300 L requirement range. UC-240E provides 20 L more usable capacity, 140 mm less width, 50 mm less depth, and lower rated power. These differences do not make it universally preferable; selection remains requirement-driven.

4. Operating Performance

• Ambient temperature

• Door-opening frequency

• Product loading

• Airflow obstruction

• Warm product loading

• Condenser cleanliness

• Installation ventilation

Published cabinet temperature range does not mean every stored product remains at an identical temperature at all times.

5. Capacity, Footprint, and Energy

Usable capacity should be evaluated with replenishment frequency and workflow. Equipment dimensions are not the complete operational footprint. Rated power is not equivalent to annual energy consumption.

6. Selection Limitations

> **Where multiple models meet the minimum technical requirement, identify the trade-offs rather than treating one model as universally superior.**

This catalog does not establish installation feasibility, inventory, delivery timing, pricing, discounts, warranty, or customer-specific commercial terms.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.