AQUAPURE WF SERIES

Commercial Water Treatment Systems - Product Guide

Field	Value	Field	Value
Document ID	PT-006	Revision	3
Effective Date	1 January 2026	Status	Current
Document Type	Product Guide	Product Family	AquaPure WF Series

1. WF Series Overview

Current commercial water-treatment systems supporting foodservice equipment. WF-250 and WF-300 may remain in the installed base but are legacy products.

2. Model Selection

Model	Service Flow	Nominal Capacity	Pressure	Connection	Position
WF-400	5.5 L/min	25,000 L	0.15-0.60 MPa	1/2"	Current standard
WF-500	7.5 L/min	40,000 L	0.15-0.60 MPa	1/2"	Current high-flow
WF-600	10.0 L/min	55,000 L	0.15-0.60 MPa	1/2"	Multi-equipment

3. Legacy Systems

Model	Service Flow	Nominal Capacity	Connection
WF-250	3.5 L/min	12,000 L	3/8"
WF-300	5.0 L/min	20,000 L	3/8"

Installed legacy equipment must not be assumed compatible with current equipment. Refer to CP-001.

4. Treatment Capacity

25,000 L treatment capacity does not mean a guaranteed cartridge life of 12 months.

Actual service life depends on inlet-water quality, contaminant loading, consumption, operating conditions, and maintenance requirements.

5. Service Flow and Pressure

Peak flow and downstream pressure matter, especially in multi-equipment applications. Average consumption alone can hide short-duration flow limitations.

6. Compatibility

Matching pressure, flow, or connection size does not establish approved equipment compatibility. Relationships may be direct, conditional on an adapter, unsupported, or not established by available evidence.

7. Limitations

This guide does not establish specific equipment compatibility, adapter requirements, guaranteed cartridge life in months, exact replacement dates, inventory, pricing, discounts, warranty, or customer-specific terms.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.