CULINAPRO CT SERIES

Commercial Cooking Systems - Product Guide

Field	Value	Field	Value
Document ID	PT-007	Revision	2
Effective Date	1 January 2026	Status	Current
Document Type	Product Guide	Product Family	CulinaPro CT Series

1. CT Series Overview

Commercial batch-cooking systems for soups, sauces, stocks, curries, braised products, and other liquid or semi-liquid production. Selection should consider batch size, daily volume, peak schedule, operating hours, utilities, space, workflow, and growth.

2. Model Selection

Model	Working Capacity	Rated Power	Electrical Supply	Dimensions	Position
CT-60	60 L	18 kW	380-415 V, 3 phase	900 x 850 x 950 mm	Compact production
CT-80	80 L	24 kW	380-415 V, 3 phase	1,050 x 900 x 1,000 mm	Standard production
CT-110	110 L	32 kW	380-415 V, 3 phase	1,200 x 950 x 1,050 mm	High utilization
CT-140	140 L	40 kW	380-415 V, 3 phase	1,350 x 1,000 x 1,100 mm	Central production

3. Working Capacity

> **Working capacity is the recommended maximum operating volume for normal production; it is not daily throughput.**

A 70 L batch may fit both CT-80 and CT-110, but the models are not operationally equivalent. Batch frequency, production window, variation, cleaning, and future demand also matter.

4. Production Workload

Daily production divided by vessel capacity is only an initial estimate. It does not account for heating, cooking, loading, unloading, cleaning, recipe changes, sequencing, or peak windows.

5. Capacity Headroom

Reasonable headroom can be useful where batch volume varies, demand grows, peaks are concentrated, or delays matter. Headroom is a selection consideration, not a fixed manufacturer requirement. There is no universal required percentage.

6. CT-80 vs CT-110

• CT-80 may suit workloads comfortably within 80 L with distributed production and tighter space.

• CT-110 may suit workloads approaching the CT-80 limit, variable demand, concentrated production, or where additional scheduling flexibility has value.

7. Requirement Qualification

• Required batch size

• Normal and peak daily production

• Available production hours

- Number of cycles
- Product/menu type
- Demand variation
- Available utilities
- Installation space

If missing information could change the recommended model, keep the recommendation conditional.

8. Limitations

Working capacity is not guaranteed operational throughput. This guide does not establish exact cooking time, installation feasibility, inventory, delivery timing, pricing, discounts, warranty, or customer-specific terms.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.