WASHPRO WAREWASHING

Commercial Warewashing Systems - Product Guide

Field	Value	Field	Value
Document ID	PT-010	Revision	3
Effective Date	1 January 2026	Status	Current
Document Type	Product Guide	Product Family	WashPro Warewashing

1. Range Overview

Current portfolio includes UW undercounter warewashers, HT hood-type warewashers, and GW dedicated glasswashers. Selection should consider workload type, peak throughput, rack/item volume, utilities, workflow, space, and operating pattern.

2. Current Models

Model	Family	Rated Throughput	Cycle Options	Rated Power
UW-50	Undercounter	up to 30 racks/hour	120 / 180 sec	5.5 kW
UW-70	Undercounter	up to 40 racks/hour	90 / 120 / 180 sec	6.5 kW
HT-100	Hood-type	up to 60 racks/hour	60 / 90 / 120 sec	9.5 kW
HT-140	Hood-type	up to 80 racks/hour	45 / 60 / 90 sec	12.0 kW
GW-40	Glasswasher	up to 40 racks/hour	90 / 120 sec	4.5 kW
GW-60	Glasswasher	up to 60 racks/hour	60 / 90 / 120 sec	5.8 kW

3. Rated Throughput

> **Rated throughput is machine capability under defined conditions, not guaranteed real-world wash-area throughput.**

Loading, unloading, pre-rinsing, rack availability, soil, cycle choice, staffing, utility recovery, and workflow congestion can reduce actual throughput.

4. Peak Workload

Daily totals alone are insufficient. Two sites washing 250 racks/day can need different equipment if one spreads work across ten hours and the other concentrates it into a two-hour peak.

5. Undercounter vs Hood-Type

Undercounter systems suit moderate intermittent workloads and tighter spaces. Hood-type systems suit sustained higher rack volume where pass-through loading and unloading workflow is available.

6. Glasswashing

Dedicated glasswashing may be useful where glass volume and turnaround justify a separate workflow. Some operations may require both general warewashing and dedicated glasswashing.

7. Utility Overview

WashPro equipment requires potable water, drainage, suitable electrical supply, ventilation, treatment where applicable, chemicals, and adequate clearance. Detailed requirements are in PT-011.

8. Limitations

This guide does not establish guaranteed operational racks/hour, exact results for every soil condition, installation feasibility, treatment compatibility, inventory, delivery timing, pricing, discounts, warranty, or customer-specific terms.

Specifications and requirements are subject to controlled technical revision. Always verify the current applicable documentation before a final customer-facing or installation commitment.