

# Compiler Design Lab Report

## University of Chittagong

Compiler Design Lab, 2023

*Group 8*

### ***Authors:***

Md. Masud Mazumder  
Tonmoy Chandro Das  
Tareq Rahman Likhon Khan  
Md. Siam  
Rabbi Hasan  
Imtiaz Ahamad Imon  
Md. Mustak Ahmed  
Abdullah Al Faruque  
Hasan Mia  
Arif Hasan  
Abu Noman Shawn Shikdar

### ***Instructor:***

Nasrin Sultana  
Assistant Professor  
Dept. of Computer Science & Engineering  
University of Chittagong, Chittagong - 4331

***Date: September 5, 2023***

# Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Phases of Compiler . . . . .	3
<b>2</b>	<b>Task Description</b>	<b>5</b>
2.1	Task Overview . . . . .	5
2.2	Motivation . . . . .	5
2.3	Project Goals . . . . .	5
<b>3</b>	<b>Context Free Grammar (CFG)</b>	<b>6</b>
<b>4</b>	<b>Lexical Analysis</b>	<b>7</b>
4.1	Overview . . . . .	7
4.2	Role of Lexical Analysis . . . . .	7
4.3	Lexical Analysis Code . . . . .	8
4.4	Lexical Analysis Result . . . . .	9
4.5	Conclusion . . . . .	10
<b>5</b>	<b>Syntax Analysis</b>	<b>11</b>
5.1	Overview . . . . .	11
5.2	Role of Syntax Analysis . . . . .	11
5.3	Parsing Techniques . . . . .	11
5.4	Syntax Analysis Code . . . . .	11
5.5	Parsing Result . . . . .	14
5.6	Conclusion . . . . .	14
<b>6</b>	<b>Semantic Analysis</b>	<b>16</b>
<b>A</b>	<b>Appendix</b>	<b>17</b>
A.1	Full Code . . . . .	17

# 1 Introduction

Compiler design is a fundamental aspect of computer science and software engineering. It plays a pivotal role in the software development process by translating high-level programming languages into low-level machine code that can be executed by a computer's central processing unit (CPU). The development of compilers is essential to bridge the gap between human-readable code and machine-executable instructions, enabling programmers to express complex algorithms and logic in a more abstract and understandable manner.

The primary objective of this lab report is to explore the key concepts and components involved in the design and construction of a compiler. We will delve into the various phases of compilation, including **lexical analysis**, **syntax analysis**, **semantic analysis**, **intermediate code generation**, **code optimization**, and **code generation**. Understanding these phases is crucial for anyone involved in compiler development or interested in gaining a deeper insight into how programming languages are processed and executed.

In this lab, we will also examine specific topics and tasks related to compiler design, such as regular expressions and finite automata for lexical analysis, context-free grammars and parsing techniques for syntax analysis, and symbol tables for managing program identifiers and their attributes. Moreover, we will discuss how compilers can optimize code for better execution performance.

The knowledge and skills gained from this lab are not only valuable for compiler developers but also for software engineers, as they provide a deeper understanding of the internal workings of programming languages and their translation into machine code. A well-designed and efficient compiler can significantly impact the performance of software systems, making compiler design an integral part of software engineering education.

As our lab task is to design a parser for **Complex Bengali Sentences**, this lab report will document our exploration of concepts of compiler design based on a sentence parser for the assigned kind of sentences, providing insights into the intricate world of compiler design and its importance in the realm of computer science.

## 1.1 Phases of Compiler

A compiler is a complex software tool that translates high-level programming code into low-level machine code or an intermediate representation. To achieve this transformation, compilers are typically divided into several well-defined phases (Figure 1), each responsible for a specific aspect of the compilation process. These phases work together systematically to ensure that the source code is analyzed, transformed, and generated into an executable form. In this section, we will explore the key phases of a compiler.

- **Lexical Analysis:** The first phase of a compiler is lexical analysis, also known as scanning. This phase reads the source code and breaks it into a stream of tokens, which are the basic units of the programming language. The tokens are then passed on to the next phase for further processing.
- **Syntax Analysis:** The second phase of a compiler is syntax analysis, also known as parsing. This phase takes the stream of tokens generated by the lexical analysis phase and checks whether they conform to the grammar of the programming language. The output of this phase is usually an Abstract Syntax Tree (AST).
- **Semantic Analysis:** The third phase of a compiler is semantic analysis. This phase checks whether the code is semantically correct, i.e., whether it conforms to the language's type system and other semantic rules.
- **Intermediate Code Generation:** The fourth phase of a compiler is intermediate code generation. This phase generates an intermediate representation of the source code that can be easily translated into machine code.
- **Code Optimization:** The fifth phase of a compiler is optimization. This phase applies various optimization techniques to the intermediate code to improve the performance of the generated machine code.
- **Code Generation:** The final phase of a compiler is code generation. This phase takes the optimized intermediate code and generates the actual machine code that can be executed by the target hardware.




Figure 1: Phases of a compiler

## 2 Task Description

### 2.1 Task Overview

The task at hand involves the design and implementation of a sentence parser and compiler for handling complex Bengali sentences. Natural language processing (NLP) and compiler design are two distinct but interconnected fields. Combining them presents a unique challenge, as it requires us to bridge the gap between the rich and often intricate linguistic structures of Bengali and the formalized, executable code of a compiler.

### 2.2 Motivation

The motivation behind this task is twofold. First, Bengali is a language of immense depth and complexity, with a rich syntax and extensive vocabulary. Developing tools that can analyze and process Bengali sentences is of significant linguistic and practical value. Second, the integration of compiler design principles into NLP opens up opportunities for automating linguistic analysis, which can be applied to various fields, including machine translation, sentiment analysis, and information retrieval.

### 2.3 Project Goals

- Develop a CFG for Complex Sentences in Bengali that accurately models complex sentence structures.
- Implement a parser that can analyze Complex Sentences in Bengali sentences based on the CFG.

### 3 Context Free Grammar (CFG)

A crucial step in this project is the development of a CFG that accurately captures the syntax and structure of complex Bengali sentences. The CFG will include rules for sentence formation, noun phrases, verb phrases, adjectives, and various sentence connectors. It must consider both grammatical correctness and semantic meaning.

For our task, we first chose 10 Bengali Complex sentences. These are as follows:

1. যদি তুমি আসো, তবে আমি যাবো।
2. যে পড়োশানা করবে, সে গিড়েত চড়বে।
3. যত পড়েব, তত জানবে।
4. যেমনটা আমি চেয়েছিলাম, তেমনটা পাইনি।
5. যারা দেশপ্রেমিক, তারা দেশকে ভালোবাসে।
6. যদিও লোকটি গরিব, তথাপি সে অতিথিপরায়ণ।
7. যতই পরিশ্রম করবে, ততই ফল পাবে।
8. যে অপরাধ করেছে, সে শাস্তি পেয়েছে।
9. যখন বিপদ আসে, তখন দুঃখও আসে।
10. যে অন্ধ, তাকে আলো দাও।

To satisfy this sentence structure we then define a Context Free Grammar (CFG) as follows:

বাক্য --> সাপেক্ষ-সর্বনাম-শুরু + খন্ড-বাক্য + , + সাপেক্ষ-সর্বনাম-শেষ + খন্ড-বাক্য  
খন্ড-বাক্য --> বিশেষ্য + খন্ড-বাক্য-শেষ | সর্বনাম + খন্ড-বাক্য-শেষ  
খন্ড-বাক্য-শেষ --> ক্রিয়া | বিশেষণ  
সাপেক্ষ-সর্বনাম-শুরু --> যদি | যে | যত | যেমনটা | যারা | যদিও | যতই | যখন  
সাপেক্ষ-সর্বনাম-শেষ --> তবে | সে | তত | তেমনটা | তারা | তথাপি | ততই | তখন  
বিশেষ্য --> বিপদ | দুঃখও | অপরাধ | শাস্তি | আলো | পড়োশানা | গিড়েতে | e  
বিশেষণ --> গরিব | অন্ধ | দেশপ্রেমিক | অতিথিপরায়ণ  
সর্বনাম --> তুমি | আমি | আমার ভাই | লোকটি | সে | e  
ক্রিয়া --> আসো | দাও | আসে | করেছে | পেয়েছে | করবে | পাবে | চড়বে | ভালোবাসে  
যাবো | জানবে | পড়বে | এসেছিলো | চেয়েছিলাম | পাইনি | e

## 4 Lexical Analysis

### 4.1 Overview

Lexical analysis, also known as scanning or tokenization, is the first phase in the process of parsing and compiling complex Bengali sentences. It converts the High-level input program into a sequence of Tokens. In this phase, the raw input sentence, composed of characters, is broken down into meaningful units known as tokens. These tokens serve as the basic building blocks for subsequent phases of parsing and analysis.

**Tokens:** Lexemes are said to be a sequence of characters (alphanumeric) in a token. There are some predefined rules for every lexeme to be identified as a valid token. These rules are defined by grammar rules, by means of a pattern. A pattern explains what can be a token, and these patterns are defined by means of regular expressions.

In the case of our task, Noun, Pronoun, Verb, Adjective, etc. can be considered as tokens. For example, the sentence “যত পড়বে, তত জানবে।” contains the tokens: “যত”, “পড়বে”, “তত”, “জানবে”.

### 4.2 Role of Lexical Analysis

The primary goals of lexical analysis in the context of Bengali sentence parsing and compilation are as follows:

- **Tokenization:** Identify and tokenize the input sentence into discrete elements, such as words, punctuation, and special symbols, that are relevant for linguistic analysis.
- **Normalization:** Normalize the tokens to a consistent format to facilitate further processing. This includes handling variations in case, removing diacritics, and ensuring consistent spacing.
- **Error Detection:** Detect and report lexical errors in the input sentence, such as unrecognized characters or syntax errors at the token level.
- **Token Classification:** Categorize tokens into different classes, such as nouns, verbs, adjectives, pronouns, and connectors, based on their linguistic roles.



### 4.3 Lexical Analysis Code

In the context of the project focused on designing a sentence parser and compiler for complex Bengali sentences, the lexical analysis phase plays a crucial role in processing raw input sentences. The Python code below demonstrates the lexical analysis process, which tokenizes Bengali sentences into meaningful units while handling common delimiters.

Listing 1: Code for Lexical analysis

```
1 def lexical_analysis(self, sentence):
2     print("Lexical analysis started...")
3
4     # Initialize an empty token
5     token = ""
6
7     # Iterate through each character in the input sentence
8     for c in sentence:
9         # Check for common delimiters: comma and Bengali full
10        stop
11        if c == "," or c == " ":
12            # If the token is not empty, append it to the list of
13            tokens
14            if len(token) > 0:
15                self.tokens.append(token)
16            # Append the delimiter as a separate token
17            self.tokens.append(c)
18            # Reset the token
19            token = ""
20        # Check for whitespace or newline characters
21        elif c == " " or c == "\n":
22            # If the token is not empty, append it to the list of
23            tokens
24            if len(token) > 0:
25                self.tokens.append(token)
26            # Reset the token
27            token = ""
28        else:
29            # Add the character to the current token and remove
30            leading/trailing whitespace
31            token += c
32            token = token.strip()
33
34    print("Lexical analysis successful...")
```

#### Explanation:

- The `lexical_analysis` function takes an input sentence in Bengali as its parameter.

- It initializes an empty token to capture segments of the sentence.
- The function iterates through each character in the input sentence, checking for common delimiters like commas and Bengali full stops ( ).
- When a delimiter is encountered, the current token is appended to the list of tokens, and the delimiter is added as a separate token.
- Whitespace and newline characters are used to determine the boundaries between tokens. When encountered, they trigger the addition of the current token to the list of tokens.
- Characters are accumulated in the current token, stripping leading and trailing whitespace.
- Finally, the function prints messages to indicate the start and successful completion of the lexical analysis process.

This code snippet represents the initial step in processing Bengali sentences, breaking them down into tokens that can be further analyzed and compiled. It demonstrates the essential functionality required for the lexical analysis phase of the project.

## 4.4 Lexical Analysis Result

The result of lexical analysis is the tokenization of the input sentence. In your code, after performing lexical analysis, the tokens are stored in the **self.tokens** list. These tokens represent the individual elements of the input sentence, separated based on the lexical rules you defined.

For example, if we pass the sentence "যে অন্ধ, তাকে আলো দাও ।" to the **Complex\_sentence\_parser**, the lexical analysis will break it down into tokens as follows:

[ "যে", "অন্ধ", ",", "তাকে", "আলো", "দাও", "।" ] Here's a breakdown of these tokens:

- "যে" (Bengali word)
- "অন্ধ" (Bengali word)
- "," (Comma punctuation)
- "তাকে" (Bengali word)
- "আলো" (Bengali word)
- "দাও" (Bengali word)
- "।" (full stop (dari) punctuation)

These tokens represent the individual elements of the input sentence, where Bengali words are separated by commas and spaces, and punctuation marks (the comma in this case) are treated as separate tokens. These tokens are the result of the lexical analysis and serve as the input for the subsequent syntax analysis phase of your parser.

## 4.5 Conclusion

The lexical analysis phase serves as the foundational step in the complex task of parsing and compiling Bengali sentences. By breaking down sentences into manageable tokens, normalizing them, and classifying them based on their linguistic roles, we pave the way for subsequent phases of syntactic and semantic analysis. The success of this phase greatly influences the overall accuracy and effectiveness of the sentence parser and compiler for complex Bengali sentences.

## 5 Syntax Analysis

### 5.1 Overview

The syntax analysis phase in the context of our project plays a pivotal role in dissecting and understanding the structural arrangement of Bengali sentences. It is the second crucial step after lexical analysis and focuses on examining how words and phrases are structured to convey meaning.

### 5.2 Role of Syntax Analysis

The primary objectives of the syntax analysis phase are as follows:

1. **Parse Tree Generation:** Construct a parse tree or syntax tree that represents the hierarchical structure of the input sentence. This tree illustrates how words and phrases relate to one another in terms of syntactic rules.
2. **Grammar Compliance:** Validate the input sentence against a predefined Context-Free Grammar (CFG) for Bengali. Detect and report any syntax errors or violations of grammatical rules.
3. **Semantic Analysis Preparation:** Prepare the groundwork for semantic analysis by providing a structured representation of the sentence's syntactic elements. This paves the way for the subsequent phase of semantic analysis.

### 5.3 Parsing Techniques

In the context of our project, parsing Bengali sentences involves the use of context-free grammars and parsing techniques. Some of the commonly used parsing techniques include:

- **Top-Down Parsing:** Starting from the root of the parse tree and working down to the leaves, this technique is often used for LL(k) grammars.
- **Bottom-Up Parsing:** Beginning with the leaves and working upwards to construct the parse tree, this approach is suitable for LR(k) grammars.
- **Chart Parsing:** Chart parsing is employed for grammars with potentially ambiguous structures. It generates multiple parse trees, allowing for the exploration of various interpretations of the same sentence.

### 5.4 Syntax Analysis Code

In the context of our project, the syntax analysis phase is responsible for validating the structural correctness of Bengali complex sentences based on predefined syntactic rules. The Python code provided below implements the syntax analysis process using a top-down parsing approach known as **Recursive Descent** parsing. Recursive

descent parsing involves creating a set of recursive functions, each corresponding to a non-terminal in the grammar, to recursively parse the input sentence to verify the sentence's grammatical structure.

Listing 2: Code for Syntax analysis

```
1 def get_next_token(self):
2     # Move to the next token in the list
3     self.index += 1
4
5     # Check if the end of the token list is reached
6     if self.index == len(self.tokens):
7         return '#'
8
9     return self.tokens[self.index]
10
11 def Noun(self, token):
12     # Check if the token is a noun
13     if token not in noun:
14         return self.SS2(token)
15     else:
16         return self.SS2(self.get_next_token())
17
18 def Pronoun(self, token):
19     # Check if the token is a pronoun
20     if token not in pronoun:
21         return self.SS2(token)
22     else:
23         return self.SS2(self.get_next_token())
24
25 def Verb(self, token):
26     # Check if the token is a verb
27     if token not in verb:
28         return False
29     else:
30         return True
31
32 def Adjective(self, token):
33     # Check if the token is an adjective
34     if token not in adjective:
35         return False
36     else:
37         return True
38
39 def PS(self, token):
40     # Check if the token is a pronoun start
41     if token not in pronoun_start:
42         raise Exception('Pronoun start does not exist.')
43     else:
```

```

44         return True
45
46 def PE(self, token):
47     # Check if the token is a pronoun end
48     if token not in pronoun_end:
49         raise Exception('Pronoun end does not exist.')
50     else:
51         return True
52
53 def SS(self, token):
54     # Check if the token represents a valid sentence segment
55     if self.Noun(token) or self.Pronoun(token):
56         return True
57     else:
58         raise Exception('Invalid sentence segment.')
59
60 def SS2(self, token):
61     # Check if the token represents a valid secondary sentence
62     # segment
63     if self.Verb(token) or self.Adjective(token):
64         return True
65     else:
66         return False
67
68 def Has_comma(self, token):
69     # Check if the token is a comma
70     if token == ',':
71         return True
72     else:
73         raise Exception('Comma does not exist.')
74
75 def Has_dari(self, token):
76     # Check if the token is a Bengali full stop (dari)
77     if token == '.':
78         return True
79     else:
80         raise Exception('Dari (full stop) does not exist.')
81
82 def parse(self):
83     try:
84         # Start the parsing process
85         self.PS(self.get_next_token())
86         self.SS(self.get_next_token())
87         self.Has_comma(self.get_next_token())
88         self.PE(self.get_next_token())
89         self.SS(self.get_next_token())
90         self.Has_dari(self.get_next_token())

```

```

90
91     # Check if there are additional tokens remaining
92     if self.index + 1 < len(self.tokens):
93         raise Exception('This parser cannot handle this
94             sentence parsing.')
95
96     # Reset the index for future parsing
97     self.index = -1
98
99     print('Parsing successful.')
100 except Exception as e:
    print('Parsing Error: ', str(e))

```

#### Explanation:

- The provided Python code outlines a syntax analysis process that verifies the structural correctness of Bengali complex sentences based on a set of predefined grammatical rules.
- The code employs a series of functions, each dedicated to checking specific aspects of sentence structure, including nouns, pronouns, verbs, adjectives, and more.
- The **parse** function serves as the main entry point, orchestrating the sequence of checks required for valid sentence parsing. It raises exceptions when encountering structural inconsistencies.
- The code is designed to handle Bengali complex sentence structures that conform to the defined rules, and it provides detailed error messages for any deviations.

This code represents a critical component of the syntax analysis phase in our project. It ensures that Bengali sentences adhere to grammatical rules before proceeding to further stages of analysis and compilation.

## 5.5 Parsing Result

Successful syntax analysis results in the generation of a parse tree or syntax tree that visually represents the sentence's syntactic structure. This tree can be instrumental in subsequent stages of semantic analysis and code generation.

The code included in the above notifies about the error or success result of parsing a sentence.

## 5.6 Conclusion

The syntax analysis phase is a critical component of our project's goal to design a sentence parser and compiler for complex Bengali sentences. By generating parse trees and validating sentences against a CFG, we gain insights into the structural

composition of sentences. This phase prepares the groundwork for subsequent stages, including semantic analysis and code generation, bringing us closer to achieving our project's objectives.



## 6 Semantic Analysis

To be added...

# A Appendix

## A.1 Full Code

Listing 3: Your Code Title

```
1
2 class Complex_sentence_parser:
3     def __init__(self, sentence):
4         # Initialize the index for token retrieval
5         self.index = -1
6         # Initialize a list to store tokens
7         self.tokens = []
8         # Perform lexical analysis on the input sentence
9         self.lexical_analysis(sentence)
10
11    def lexical_analysis(self, sentence):
12        print("Lexical analysis started...")
13        # Initialize an empty token
14        token = ""
15        # Iterate through each character in the sentence
16        for c in sentence:
17            # Check for common delimiters: comma and Bengali full
18            # stop (dari)
19            if(c == "," or c == " "):
20                # If the token is not empty, append it to the
21                # list of tokens
22                if len(token) > 0:
23                    self.tokens.append(token)
24                # Append the delimiter as a separate token
25                self.tokens.append(c)
26                # Reset the token
27                token = ""
28            # Check for whitespace or newline characters
29            elif(c == " " or c == "\n"):
30                # If the token is not empty, append it to the
31                # list of tokens
32                if len(token) > 0:
33                    self.tokens.append(token)
34                # Reset the token
35                token = ""
36            else:
37                # Add the character to the current token and
38                # remove leading/trailing whitespace
39                token += c
40                token = token.strip()
41        print("Lexical analysis successful...")
42
```

```

39 def get_next_token(self):
40     # Move to the next token in the list
41     self.index += 1
42     # Check if the end of the token list is reached
43     if(self.index == len(self.tokens)):
44         return '#'
45     # Return the next token
46     return self.tokens[self.index]
47
48 def Noun(self, token):
49     # Check if the token is not in the set of known nouns
50     if token not in noun:
51         return self.SS2(token)
52     else:
53         return self.SS2(self.get_next_token())
54
55 def Pronoun(self, token):
56     # Check if the token is not in the set of known pronouns
57     if token not in pronoun:
58         return self.SS2(token)
59     else:
60         return self.SS2(self.get_next_token())
61
62 def Verb(self, token):
63     # Check if the token is in the set of known verbs
64     if token not in verb:
65         return False
66     else:
67         return True
68
69 def Adjective(self, token):
70     # Check if the token is in the set of known adjectives
71     if token not in adjective:
72         return False
73     else:
74         return True
75
76 def PS(self, token):
77     # Check if the token is not in the set of known pronoun
78     # starts
79     if token not in pronoun_start:
80         raise Exception('Pronoun start does not exist.')
81     else:
82         return True
83
84 def PE(self, token):

```

```

84         # Check if the token is not in the set of known pronoun
           ends
85     if token not in pronoun_end:
86         raise Exception('Pronoun end does not exist.')
87     else:
88         return True
89
90     def SS(self, token):
91         # Check if the token is a valid noun or pronoun
92         if self.Noun(token) or self.Pronoun(token):
93             return True
94         else:
95             raise Exception('Invalid sentence segment.')
96
97     def SS2(self, token):
98         # Check if the token is a valid verb or adjective
99         if self.Verb(token) or self.Adjective(token):
100             return True
101         else:
102             return False
103
104     def Has_comma(self, token):
105         # Check if the token is a comma
106         if token == ',':
107             return True
108         else:
109             raise Exception('Comma does not exist.')
110
111     def Has_dari(self, token):
112         # Check if the token is a Bengali full stop (dari)
113         if token == '.':
114             return True
115         else:
116             raise Exception('Dari (full stop) does not exist.')
117
118     def parse(self):
119         try:
120             # Start parsing with a pronoun start
121             self.PS(self.get_next_token())
122             # Expect a valid sentence segment
123             self.SS(self.get_next_token())
124             # Expect a comma
125             self.Has_comma(self.get_next_token())
126             # Expect a pronoun end
127             self.PE(self.get_next_token())
128             # Expect another valid sentence segment
129             self.SS(self.get_next_token())

```

```
130         # Expect a Bengali full stop (dari)
131         self.Has_dari(self.get_next_token())
132
133         # If there are more tokens, raise an exception
134         if self.index + 1 < len(self.tokens):
135             raise Exception('This parser cannot handle this
136                             sentence parsing.')
136
137         # Reset the index for future parsing
138         self.index = -1
139         print('Parsing successful.')
140     except Exception as e:
141         print('Parsing Error: ', str(e))
```