

## Table of Contents

CSS Specificity	2
CSS !important Property	15

link: [https://www.w3schools.com/css/css\\_important.asp](https://www.w3schools.com/css/css_important.asp)

link: [https://www.w3schools.com/css/css\\_specificity.asp](https://www.w3schools.com/css/css_specificity.asp)

## Specificity Hierarchy

Every CSS selector has its place in the specificity hierarchy.

There are four categories which define the specificity level of a selector:

- **Inline styles** - Example: `<h1 style="color: pink;">`
- **IDs** - Example: `#navbar`
- **Classes, pseudo-classes, attribute selectors** - Example: `.test, :hover, [href]`
- **Elements and pseudo-elements** - Example: `h1, :before`



Menu ▼



HTML

CSS



# CSS Specificity

[< Previous](#)[Next >](#)

## What is Specificity?

If there are two or more CSS rules that point to the same element, the selector with the highest specificity value will "win", and its style declaration will be applied to that HTML element.

Think of specificity as a score/rank that determines which style declaration is ultimately applied to an element.

Look at the following examples:

### Example 1

In this example, we have used the "p" element as selector, and specified a red color for this element. The text will be red:

```
<html>
<head>
  <style>
    p {color: red;}
  </style>
</head>
<body>
```

```
<p>Hello World!</p>

</body>
</html>
```

Try it Yourself »

Now, look at example 2:

## Example 2

In this example, we have added a class selector (named "test"), and specified a green color for this class. The text will now be green (even though we have specified a red color for the element selector "p"). This is because the class selector is given higher priority:

```
<html>
<head>
  <style>
    .test {color: green;}
    p {color: red;}
  </style>
</head>
<body>

<p class="test">Hello World!</p>

</body>
</html>
```

Try it Yourself »

Now, look at example 3:

## Example 3

In this example, we have added the id selector (named "demo"). The text will now be blue, because the id selector is given higher priority:

```
<html>
<head>
  <style>
    #demo {color: blue;}
    .test {color: green;}
    p {color: red;}
  </style>
</head>
<body>

<p id="demo" class="test">Hello World!</p>

</body>
</html>
```

Try it Yourself »

Now, look at example 4:

## Example 4

In this example, we have added an inline style for the "p" element. The text will now be pink, because the inline style is given the highest priority:

```
<html>
<head>
  <style>
    #demo {color: blue;}
    .test {color: green;}
    p {color: red;}
  </style>
</head>
<body>

<p id="demo" class="test" style="color: pink;">Hello World!</p>
```

```
</body>  
</html>
```

Try it Yourself »

## Specificity Hierarchy

Every CSS selector has its place in the specificity hierarchy.

There are four categories which define the specificity level of a selector:

- **Inline styles** - Example: `<h1 style="color: pink;">`
- **IDs** - Example: `#navbar`
- **Classes, pseudo-classes, attribute selectors** - Example: `.test`, `:hover`, `[href]`
- **Elements and pseudo-elements** - Example: `h1`, `:before`

## How to Calculate Specificity?

Memorize how to calculate specificity!

Start at 0, add 100 for each ID value, add 10 for each class value (or pseudo-class or attribute selector), add 1 for each element selector or pseudo-element.

**Note:** Inline style gets a specificity value of 1000, and is always given the highest priority!

**Note 2:** There is one exception to this rule: if you use the !important rule, it will even override inline styles!

The table below shows some examples on how to calculate specificity values:

Selector	Specificity Value	Calculation
p	1	1

p.test	11	1 + 10
p#demo	101	1 + 100
<p style="color: pink;">	1000	1000
#demo	100	100
.test	10	10
p.test1.test2	21	1 + 10 + 10
#navbar p#demo	201	100 + 1 + 100
*	0	0 (the universal selector is ignored)

**The selector with the highest specificity value will win and take effect!**

Consider these three code fragments:

## Example

A: h1

B: h1#content

C: <h1 id="content" style="color: pink;">Heading</h1>

The specificity of A is 1 (one element selector)

The specificity of B is 101 (one ID reference + one element selector)

The specificity of C is 1000 (inline styling)

Since the third rule (C) has the highest specificity value (1000), this style declaration will be applied.

ADVERTISEMENT



## More Specificity Rules Examples

**Equal specificity: the latest rule wins** - If the same rule is written twice into the external style sheet, then the latest rule wins:

### Example

```
h1 {background-color: yellow;}  
h1 {background-color: red;}
```

Try it Yourself »

---

**ID selectors have a higher specificity than attribute selectors** - Look at the following three code lines:

### Example

```
div#a {background-color: green;}  
#a {background-color: yellow;}  
div[id=a] {background-color: blue;}
```

Try it Yourself »

the first rule is more specific than the other two, and will therefore be applied.

---

**Contextual selectors are more specific than a single element selector** - The embedded style sheet is closer to the element to be styled. So in the following situation

## Example

From external CSS file:

```
#content h1 {background-color: red;}
```

In HTML file:

```
<style>  
#content h1 {background-color: yellow;}  
</style>
```

the latter rule will be applied.

---

**A class selector beats any number of element selectors** - a class selector such as .intro beats h1, p, div, etc:

## Example

```
.intro {background-color: yellow;}  
h1 {background-color: red;}
```

Try it Yourself »

---

**The universal selector (\*) and inherited values have a specificity of 0** - The universal selector (\*) and inherited values are ignored!



[< Previous](#)[Next >](#)

ADVERTISEMENT




COLOR PICKER




Get certified  
by completing  
a CSS  
course today!



Get started



ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT

---

[Report Error](#)

[Spaces](#)

[Upgrade](#)

[Newsletter](#)

[Get Certified](#)

---

## Top Tutorials

[HTML Tutorial](#)  
[CSS Tutorial](#)  
[JavaScript Tutorial](#)  
[How To Tutorial](#)  
[SQL Tutorial](#)  
[Python Tutorial](#)  
[W3.CSS Tutorial](#)  
[Bootstrap Tutorial](#)  
[PHP Tutorial](#)  
[Java Tutorial](#)  
[C++ Tutorial](#)  
[jQuery Tutorial](#)

## Top References

[HTML Reference](#)  
[CSS Reference](#)  
[JavaScript Reference](#)  
[SQL Reference](#)  
[Python Reference](#)

[W3.CSS Reference](#)[Bootstrap Reference](#)[PHP Reference](#)[HTML Colors](#)[Java Reference](#)[Angular Reference](#)[jQuery Reference](#)

## Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[Java Examples](#)[XML Examples](#)[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[Front End Certificate](#)[SQL Certificate](#)[Python Certificate](#)[PHP Certificate](#)[jQuery Certificate](#)[Java Certificate](#)[C++ Certificate](#)[C# Certificate](#)[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.







# CSS The !important Rule

[< Previous](#)[Next >](#)

## What is !important?

The **!important** rule in CSS is used to add more importance to a property/value than normal.

In fact, if you use the **!important** rule, it will override ALL previous styling rules for that specific property on that element!

Let us look at an example:

### Example

```
#myid {  
  background-color: blue;  
}  
  
.myclass {  
  background-color: gray;  
}  
  
p {  
  background-color: red !important;  
}
```

[Try it Yourself »](#)

## Example Explained

In the example above, all three paragraphs will get a red background color, even though the ID selector and the class selector have a higher specificity. The `!important` rule overrides the `background-color` property in both cases.

## Important About !important

The only way to override an `!important` rule is to include another `!important` rule on a declaration with the same (or higher) specificity in the source code - and here the problem starts! This makes the CSS code confusing and the debugging will be hard, especially if you have a large style sheet!

Here we have created a simple example. It is not very clear, when you look at the CSS source code, which color is considered most important:

### Example

```
#myid {  
  background-color: blue !important;  
}  
  
.myclass {  
  background-color: gray !important;  
}  
  
p {  
  background-color: red !important;  
}
```

[Try it Yourself »](#)

**Tip:** It is good to know about the `!important` rule. You might see it in some CSS source code. However, do not use it unless you absolutely have to.



## ADVERTISEMENT



## Maybe One or Two Fair Uses of !important

One way to use `!important` is if you have to override a style that cannot be overridden in any other way. This could be if you are working on a Content Management System (CMS) and cannot edit the CSS code. Then you can set some custom styles to override some of the CMS styles.

Another way to use `!important` is: Assume you want a special look for all buttons on a page. Here, buttons are styled with a gray background color, white text, and some padding and border:

### Example

```
.button {  
  background-color: #8c8c8c;  
  color: white;  
  padding: 5px;  
  border: 1px solid black;  
}
```

Try it Yourself »

The look of a button can sometimes change if we put it inside another element with higher specificity, and the properties get in conflict. Here is an example of this:

## Example

```
.button {  
  background-color: #8c8c8c;  
  color: white;  
  padding: 5px;  
  border: 1px solid black;  
}  
  
#myDiv a {  
  color: red;  
  background-color: yellow;  
}
```

Try it Yourself »

To "force" all buttons to have the same look, no matter what, we can add the **!important** rule to the properties of the button, like this:

## Example

```
.button {  
  background-color: #8c8c8c !important;  
  color: white !important;  
  padding: 5px !important;  
  border: 1px solid black !important;  
}  
  
#myDiv a {  
  color: red;  
  background-color: yellow;  
}
```


Try it Yourself »

◀ Previous

Next ▶



ADVERTISEMENT




## COLOR PICKER



Get certified  
by completing  
a CSS  
course today!



Get started



ADVERTISEMENT

ADVERTISEMENT

ADVERTISEMENT

---

[Report Error](#)

[Spaces](#)

[Upgrade](#)

[Newsletter](#)

[Get Certified](#)

---

## Top Tutorials

[HTML Tutorial](#)  
[CSS Tutorial](#)  
[JavaScript Tutorial](#)  
[How To Tutorial](#)  
[SQL Tutorial](#)  
[Python Tutorial](#)  
[W3.CSS Tutorial](#)  
[Bootstrap Tutorial](#)  
[PHP Tutorial](#)  
[Java Tutorial](#)  
[C++ Tutorial](#)  
[jQuery Tutorial](#)

## Top References

[HTML Reference](#)  
[CSS Reference](#)  
[JavaScript Reference](#)  
[SQL Reference](#)  
[Python Reference](#)  
[W3.CSS Reference](#)

[Bootstrap Reference](#)[PHP Reference](#)[HTML Colors](#)[Java Reference](#)[Angular Reference](#)[jQuery Reference](#)

## Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[Java Examples](#)[XML Examples](#)[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[Front End Certificate](#)[SQL Certificate](#)[Python Certificate](#)[PHP Certificate](#)[jQuery Certificate](#)[Java Certificate](#)[C++ Certificate](#)[C# Certificate](#)[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

