

Executive Proposal: Media Player Fleet Migration

1. Problem: Functional Obsolescence

The legacy fleet of 360+ media players equipped with 60GB SSDs has reached a state of **functional obsolescence**. The current storage architecture acts as a critical bottleneck, preventing mandatory security updates and causing systemic instability.

2. Evidence: Storage & Update Mechanics

Technical analysis confirms a fundamental mismatch between legacy hardware capacity and modern OS requirements:

- **Baseline Consumption:** A clean Windows install occupies 50%–66% (30-40GB) of the drive immediately.
 - **Update Friction:** Windows updates require large temporary allocations that the remaining 20–30GB cannot provide.
 - **Data Accrual:** Residual update data and file corruption eventually render the drive too full to function, despite manual "disk cleanup" efforts.
-

3. Risk: Security & Compliance Exposure

The storage bottleneck has created a state of "**Update Stagnation**," where 85% of the 60GB fleet is currently running OS versions that are 12+ months out of date.

- **Vulnerability Gap:** Legacy units are susceptible to known exploits (e.g., PrintNightmare) because they lack the 20GB of free space required to stage "Patch Tuesday" security bundles.
 - **Regulatory Non-Compliance:** Under standard **SOC2** and **HIPAA** frameworks, hardware must be patched within 30 days of a critical release. Our current "manual clear" workflow results in a 90+ day lag, risking audit failure and fines.
 - **Data Integrity:** Failed update cycles have led to a 15% increase in filesystem corruption, necessitating manual re-imaging and increasing client downtime.
-

4. Financial Model: 3-Year TCO Comparison

This model monetizes the "Support Burden" to demonstrate that the **Cost of Inaction** exceeds the **Cost of Change**.

Metric	Legacy Fleet (60GB SSD)	Current-Gen Standard (256GB+)
Annual Support Labor	6.5 Hours/Unit (Manual Disk Clearing)	0.5 Hours/Unit (Automated Patching)
Hourly Burdened Labor	\$75.00/hr. (Estimated)	\$75.00/hr. (Estimated)
Annual OpEx per Unit	\$487.50 (Manual maintenance)	\$37.50 (Routine monitoring)
Hardware Cost	\$0.00 (Existing)	\$550.00 (Standardized Unit)
3-Year TCO Projection	\$1,462.50	\$662.50 (CapEx + 3yrs OpEx)

Financial Outcome: Migrating to the Current-Gen platform yields a **\$800.00 per-unit saving** over 36 months, with a projected **break-even point at 14 months** post-deployment.

5. Migration Roadmap & Strategic Implementation

To manage Capital Expenditure (CapEx) flow, the migration follows a phased rollout:

- **Phase 1: Reactive "Replace-on-Failure" (Months 1–6):** Immediately cease 60GB hardware repairs. Units experiencing OS corruption are decommissioned rather than wiped, optimizing asset depreciation.
 - **Phase 2: Strategic Migration (Months 6–18):** Proactively replace 60GB units at "High-Touch" accounts (averaging >3 storage tickets per year) to maximize ROI by targeting the highest labor-cost centers.
 - **Phase 3: Standardized Baseline (Months 18+):** Mandate Current-Gen hardware for all new 1:1 installation to prevent technical debt regression and achieve 100% security parity.
-

6. Strategic Outcome & Recommendation

The transition represents a shift from reactive "firefighting" to proactive asset management.

- **Financial Health:** The \$800+ savings per unit significantly offset the initial \$550 investment.
- **Security Posture:** 100% update compatibility ensures protection against unpatched vulnerabilities.
- **Operational Maturity:** This plan addresses systemic technical debt, future-proofing the fleet for upcoming software pivots.

Recommendation: It is recommended that the organization immediately adopt the **Phased Migration Plan** to achieve 100% compliance and realize the projected \$800.00 per-unit savings.

Prepared by: Stephanie R. Wilder — Technical Support Specialist II *This case study was developed based on real-world technical data and field experience. I utilized AI as a collaborative editor to refine the financial modeling and ensure the formatting met executive communication standards.*