Sourcing and Validating High-Fidelity GeoJSON Administrative Boundaries for Cebu Province and its Archipelagic Municipalities

Introduction to Archipelagic Spatial Data Infrastructures

The accurate geospatial delineation of archipelagic administrative boundaries represents one of the most complex ontological and technical challenges in modern Geographic Information Systems (GIS). The Republic of the Philippines, officially comprising approximately 7,641 distinct islands categorized within the macro-regional divisions of Luzon, Visayas, and Mindanao, requires highly specialized and mathematically rigorous topological models to accurately represent its political sub-divisions.[1] Within the Central Visayas region (Region VII), the province of Cebu serves as an archetypal example of this profound geospatial complexity.[2] Cebu is not merely a single contiguous landmass; rather, it is a sophisticated archipelagic province consisting of a long, narrow mainland surrounded by over 160 smaller islands, islets, and atolls. This includes the highly populated Mactan Island, the northern Bantayan Island group, and the eastern Camotes Islands.[4]

For spatial data scientists, urban planners, humanitarian logistics coordinators, and web developers, acquiring legitimate, officially recognized, and topologically precise boundary data formatted as GeoJSON is a non-negotiable prerequisite for advanced spatial analysis. GeoJSON, an open standard format designed for representing simple geographical features along with their non-spatial attributes based on JavaScript Object Notation, has firmly established itself as the industry standard for web-based mapping applications.[4] Its lightweight, text-based nature ensures native compatibility with modern web frameworks and visualization libraries such as MapLibre GL JS, Leaflet, and D3.js.[4] However, sourcing official and geometrically accurate GeoJSON files for Cebu's constituent municipalities and scattered islands requires navigating an incredibly fragmented landscape. This landscape consists of restrictive official government portals, heavily vetted humanitarian data exchanges, dynamic volunteer geographic information systems, and globally aggregated administrative boundary databases.[4]

This comprehensive analysis provides an exhaustive review of the available repositories for Cebu's administrative boundaries. It rigorously evaluates their institutional provenance, underlying technical specifications, topological fidelity, coordinate projection systems, and integration with the official Philippine Standard Geographic Code (PSGC). By systematically

cross-referencing national cartographic data with open-source geometric distributions, this report establishes a definitive, actionable framework for acquiring, validating, and deploying municipal-level GeoJSON data for the province of Cebu.

The Institutional and Legal Architecture of Philippine Geospatial Data

The production, maintenance, and distribution of official administrative boundaries in the Philippines involve a multi-layered ecosystem of national agencies. Each agency operates with distinct legal mandates that collectively form the nation's overarching spatial data infrastructure. Understanding this rigid institutional hierarchy is essential for evaluating the legal legitimacy and geometric accuracy of any GeoJSON dataset purporting to represent Cebu and its municipalities.

The National Mapping and Resource Information Authority (NAMRIA)

The National Mapping and Resource Information Authority (NAMRIA), an attached agency operating under the Department of Environment and Natural Resources (DENR), serves as the central mapping agency and absolute cartographic authority of the Philippine government.[11] NAMRIA bears the primary statutory responsibility for producing base topographic maps, nautical charts, satellite imagery processing, and the official Administrative Map of the Philippines.[11] The agency fundamentally manages the Philippine Geoportal (www.geoportal.gov.ph), a sophisticated web-based spatial data infrastructure designed to share, integrate, and synchronize geospatial data across various government entities and the public sector.[11]

NAMRIA's cartographic outputs are the foundational layers upon which thematic mapping is built. For example, their topographic databases serve as the base for mapping coastal resources, including the highly vulnerable mangrove forests, seagrass beds, and coral reefs that heavily populate the coastlines of Cebu's municipal waters.[13] Furthermore, NAMRIA is heavily involved in national security and maritime delineations, regularly issuing navigational warnings for activities such as dredging operations, submarine cable surveys off the coast of Cebu and Bohol, and offshore sand extraction.[11]

However, from the perspective of a data scientist or web developer seeking ready-to-use vector geometries, accessing raw, high-resolution vector data—such as Shapefiles or GeoJSON—directly from NAMRIA's public-facing portals presents significant friction. Publicly downloadable boundary files are frequently provided in static, visually oriented formats, such as PDF documents, low-resolution JPG images suitable only for letter-size printing, or compressed ZIP files containing proprietary map project formats.[11] While high-resolution 1:50,000 scale topographic maps and hazard maps are available, they often require extensive manual digitization and georeferencing to be utilized programmatically in modern GIS software architectures.[11] Furthermore, while the Geoportal Philippines publishes extensive analytical data—such as flood extent maps generated following Typhoon Ulysses (Vamco) in 2020 or

sea-level rise vulnerability mapping for Cebu—direct, unencumbered downloads of sub-municipal GeoJSON boundaries often necessitate navigating bureaucratic layers, purchasing data at Map Sales Offices, or submitting formal requests under the Freedom of Information (FOI) Executive Order No. 02.[11]

The Land Management Bureau and the Indicative Boundary Framework

While NAMRIA handles the cartographic representation of the physical earth, the official legal and cadastral delineation of political administrative boundaries is the exclusive statutory mandate of the Land Management Bureau (LMB).[8] However, due to ongoing historical cadastral disputes, the continuous legislative evolution of local government units, and the complexities of maritime municipal water boundaries, a complete, legally undisputed, and universally accepted seamless vector dataset is rarely published in real-time by the LMB.[8]

In the functional absence of universally available official cadastral administrative boundaries from the LMB, the Information Management Technical Working Group (IMTWG) of the Philippines—which coordinates data across government and humanitarian sectors—relies heavily on the administrative boundaries utilized by the Philippine Statistics Authority (PSA).[8] It is critical for geospatial analysts to understand that these PSA-aligned boundaries are explicitly classified as "indicative boundaries" rather than legally binding territorial delineations.[8] These indicative boundaries are meticulously crafted to facilitate the spatial aggregation of census data, demographic profiling, and national household surveys.[8] For virtually all civilian, commercial, academic, and humanitarian applications involving Cebu's municipal geometries, these indicative boundaries serve as the functional, accepted standard, mitigating the legal paralysis that would otherwise halt spatial analysis.

Philippine Standard Geographic Code (PSGC) Integration

The absolute cornerstone of any accurate, relational geospatial dataset in the Philippines is its strict compliance with the Philippine Standard Geographic Code (PSGC), a system managed and updated continuously by the PSA.[2] The PSGC is a systematic, hierarchical classification system that assigns highly specific, unique numeric codes to every recognized administrative unit in the country.[2] This system meticulously tracks the creation of new barangays, the merging of municipalities, or the renaming and reclassification of regions and provinces.[2]

Recently, to accommodate the growing number of administrative subdivisions and ensure database future-proofing, the PSA transitioned to a new 10-digit coding structure, entirely replacing the legacy coding formats.[2] In this modern architecture, the province of Cebu operates under specific numerical identifiers that define its topological relationships. A GeoJSON dataset lacking strict alignment with the 2023 or 2024 PSGC updates cannot be considered structurally accurate, as it may fail to reflect recent municipal reclassifications or the creation of new administrative barangays within Cebu's rapidly urbanizing economic corridors.

Administrative Level	Geographic Designation	PSGC Prefix Code	Example Application within the Archipelago
Level 1 (ADM1)	Region	07	Region VII (Central Visayas)
Level 2 (ADM2)	Province	0722	Cebu
Level 3 (ADM3)	Municipality / City	072201 to 072253	Alcantara (072201), Alcoy (072202), Cebu City, Lapu-Lapu
Level 4 (ADM4)	Barangay (Village)	0722xxxxxx	Cabadiangan, Cabil-isan

Table 1: The hierarchical structure of the Philippine Standard Geographic Code (PSGC) as applied specifically to Cebu Province. This cascading numerical architecture is essential for linking tabular data, such as census demographics or epidemiological statistics, to GeoJSON geometric features within relational database mapping systems.[16]

The utility of these codes is demonstrated by programmatic libraries such as the addresspinas npm package, which utilizes this exact hierarchical structure.[17] Developers can programmatically fetch all municipalities linked to Cebu's prov_code "0722", returning array objects containing names like Alcantara and their corresponding mun_code "072201".[17] Consequently, any high-fidelity GeoJSON file must encode these PSGC values within the properties object of each geometric feature to allow for seamless automated data joining.

Humanitarian Data Exchange (HDX) and Operational Delineations

When official government web portals restrict direct, unauthenticated access to machine-readable GeoJSON files, the global humanitarian and non-governmental community steps in to standardize, clean, and distribute this vital data. The most reliable and internationally

recognized repository for national-scale administrative boundaries is the Humanitarian Data Exchange (HDX), a platform managed by the United Nations Office for the Coordination of Humanitarian Affairs (UN OCHA).[8]

Common Operational Datasets for Administrative Boundaries (COD-AB)

Within the HDX ecosystem, the Common Operational Datasets for Administrative Boundaries (COD-AB) represent the undeniable gold standard for verified, indicative geospatial data used in crisis response and strategic planning.[8] The specific Philippines COD-AB dataset provides unbroken, topologically checked boundaries spanning Administrative Levels 0 through 4.[8] This dataset does not simply mirror raw government data; it is continuously and rigorously vetted by Information Technology Outreach Services (ITOS), operating with funding and oversight from USAID.[8]

The COD-AB dataset categorizes the Philippine administrative hierarchy with extreme precision. As of its latest structural review in April 2024, the dataset comprises:

- Administrative Level 1: 17 Features (Regions).[8]
- Administrative Level 2: 88 Features (Provinces, including Cebu).[8]
- Administrative Level 3: 1,642 Features (Municipalities and Cities, encompassing all 53 local government units of Cebu).[8]
- Administrative Level 4: 42,048 Features (Barangays).[8]

A critical aspect of the COD-AB's accuracy is its responsiveness to macroeconomic and political restructuring. For example, the dataset successfully propagated the complex dissolution of the 'Negros Island Region' (which existed briefly from 2015 to 2017), properly restoring the adjacent administrative level 2 features back to Region 6 and Region 7 (Central Visayas), ensuring that Cebu's regional context remains accurate and structurally sound.[8] Furthermore, because the Philippines is an archipelagic, island nation entirely surrounded by maritime borders, the COD-AB notes that no edge-matched (COD-EM) version—typically required for countries sharing contiguous terrestrial borders with neighboring nation-states—is necessary.[8]

The recommended cartographic projection for the Philippine COD-AB dataset is the Asia South Albers Equal Area Conic projection.[8] This specific conic projection is mathematically engineered to minimize severe areal distortion across the vast, longitudinal spread of the Philippine archipelago, ensuring that spatial calculations regarding land area or population density in Cebu remain statistically valid.[8] While the primary open distributions on the HDX platform are often packaged in Esri Shapefile (SHP), file Geodatabase (GDB), and Enhanced Metafile (EMF) formats, these are easily and losslessly translatable to GeoJSON using standard open-source GIS libraries like GDAL/OGR.[8] The rigorous validation processes applied to the COD-AB make it the most reliable source for high-stakes spatial analysis, particularly in disaster risk reduction and post-calamity response scenarios that frequently impact Cebu's municipalities.[18]

High-Fidelity Open-Source GeoJSON Ecosystems: GitHub Repositories

For full-stack developers, software engineers, and spatial analysts seeking immediate, frictionless access to native GeoJSON files—without the intermediate, often cumbersome step of manually converting Shapefiles via desktop GIS software—a highly robust ecosystem of GitHub repositories exists. These repositories are maintained by dedicated civic technologists and bridge the critical gap between heavy, proprietary GIS formats and lightweight, web-ready mapping requirements.

The Faeldon and Altcoder Geospatial Pipelines

The most comprehensive, technically sound, and PSGC-compliant open-source repository for Philippine administrative boundaries directly in GeoJSON format is maintained by the developer community on GitHub. Specifically, the faeldon/philippines-json-maps project and its upstream source data provider, the altcoder/philippines-psgc-shapefiles repository, serve as the definitive sources for web developers.[2]

These interconnected repositories represent a masterclass in open-source geospatial data processing and continuous integration. The raw source shapefiles from the altcoder repository are actively maintained and continuously updated to reflect the exact, line-by-line PSGC Summary of Changes published by the PSA.[2] As of their latest major iterations, the administrative level boundaries encoded in these repositories utilize PSGC data strictly updated as of December 31, 2023.[4] The raw source shapefiles, which originally stem from legacy OCHA data distributions from 2011 and 2015, have been meticulously cleaned, topologically corrected, and definitively matched with the new 10-digit PSGC numeric formats.[2] Because these datasets are massive, the repository utilizes git-lfs (Large File Storage) to manage the spatial geometry payloads.[2]

The downstream faeldon repository processes these pristine shapefiles directly into both GeoJSON and TopoJSON formats.[4] TopoJSON is an extension of GeoJSON that encodes topology, eliminating redundancy by sharing line segments (arcs) between adjacent polygons, thereby significantly reducing file sizes.[4] To accommodate drastically varying performance requirements in web mapping—where rendering highly complex, highly verticied archipelagic coastlines can instantly bottleneck browser memory and crash mobile applications—the conversion pipeline generates files at three distinct, mathematically controlled resolutions [4]:

Resolution Designation	Processing Tool	Simplification Parameter	Primary Use Case and Application
High Resolution	ogr2ogr	0% (Full geometric	Localized

(hires)		fidelity)	geospatial analysis, cadastral overlays, exact boundary calculations where the true geometry of Cebu's intricate coastlines and municipal borders must be preserved exactly as surveyed.[4]
Medium Resolution (medres)	mapshaper	-simplify 1%	Optimal for standard web dashboards and regional visualizations, providing an excellent balance between recognizable boundary fidelity and reduced payload size.[4]
Low Resolution (lowres)	mapshaper	-simplify 0.1%	Highly optimized for resource-constraine d environments, mobile devices, or dynamic national-level maps over slow network connections where only the macroscopic shape of Cebu is necessary.[4]

Table 2: Algorithmic resolution and simplification parameters utilized in the faeldon/philippines-json-maps repository to optimize GeoJSON payloads for archipelagic rendering.[4]

The geometric mapping projection utilized uniformly across these GeoJSON datasets is

EPSG:32651, a projection combining the WGS 84 datum with UTM zone 51N.[4] This is a highly suitable projected coordinate system for the longitudinal positioning of the central and eastern Philippines, allowing for highly accurate, localized area and Cartesian distance calculations.[4] For an analyst requiring specifically Cebu's data, navigating to the 2023/geojson/hires directory within this GitHub repository provides direct access to Level 2 (Provincial) and Level 3 (Municipal) GeoJSON objects that are topologically verified and perfectly synchronized with PSGC 0722.[4] Automated shell scripts within the repository, such as topojson-provdists.sh and topojson-municities.sh, transparently document the exact geometric transformation parameters applied to the source files.[21]

Global Boundary Databases and Programmatic API Access

Beyond localized, country-specific repositories, Cebu's administrative boundaries are comprehensively indexed within massive, globally aggregated geospatial databases. These sophisticated platforms harmonize boundary geometries from hundreds of disparate national agencies into a single, standardized global schema. This makes them ideal for comparative international research, multi-national application development, and large-scale econometric modeling.

The geoBoundaries Global Database Ecosystem

The geoBoundaries Global Database of Political Administrative Boundaries, meticulously maintained by the William & Mary geoLab in close collaboration with UN OCHA, UN SALB, and GRID3, is a premier open-license (Creative Commons CC BY 4.0) resource.[9] Since its inception in 2016, the geoBoundaries project has tracked, cleaned, and version-controlled over one million boundaries within over 200 sovereign entities and territories worldwide, supported by major institutions including the National Science Foundation and the Bill & Melinda Gates Foundation.[22]

The fundamental, paradigm-shifting advantage of the geoBoundaries architecture is its programmatic accessibility. Rather than manually downloading static zip files, developers can interface directly with the geoBoundaries API for deterministic data retrieval.[24] For the Philippines, geoBoundaries provides seamless boundary definitions extending down to Administrative Level 3 (ADM3 - Municipalities) and Level 4 (ADM4 - Barangays).[25]

To programmatically extract the specific GeoJSON geometries for Cebu's municipalities, users construct a standard API request taking the form of https://www.geoboundaries.org/api/current////.[24]

The `` parameter offers distinct licensing and verification tiers:

- **gbOpen:** CC-BY 4.0 compliant, openly sourced, and suitable for commercial, academic, and general-purpose deployments.[24]

- **gbHumanitarian:** Geometries strictly mirrored from UN OCHA's COD-AB datasets.[24]
- **gbAuthoritative:** Geometries explicitly verified and endorsed through direct in-country processes and recognized national authorities.[24]

To acquire the municipal boundaries (ADM3) for the Philippines under the universally accessible open license, utilizing the ISO-3166-1 Alpha-3 code for the Philippines (PHL), the exact API endpoint is constructed as: https://www.geoboundaries.org/api/current/gbOpen/PHL/ADM3/.[24]

Executing an HTTP GET request to this endpoint returns a structured JSON payload containing explicit, version-controlled paths to gjDownloadURL (the static download link for the full-fidelity GeoJSON) and simplifiedGeometryGeoJSON (a link for a mathematically simplified variant optimized for rapid rendering).[24] By ingesting this GeoJSON into a spatial analysis environment (such as Python's GeoPandas or PostGIS) and filtering the resulting FeatureCollection for properties matching "Cebu" or the corresponding ADM2 identifier, analysts can instantly isolate the precise multi-polygons for the province's local government units. The CC BY 4.0 licensing model of geoBoundaries allows for extensive commercial and academic use, provided that proper attribution—such as citing their primary PLoS ONE publication or prominently displaying the geoBoundaries name and URL—is maintained.[22]

Global Administrative Areas (GADM)

A prominent alternative global repository is the Global Administrative Areas (GADM) database. Currently operating on its mature version 4.1 release (with a highly anticipated version 5 scheduled for release in January 2026), GADM delimits a staggering 400,276 administrative areas globally.[28] The database provides explicit, high-resolution spatial data for all Philippine sub-divisions.[28] The structural hierarchy encoded within GADM closely mirrors standard ADM levels, with Level 2 accurately representing provinces like Cebu, and Level 3 capturing its internal municipalities.[2]

While GADM offers exceptionally high-quality geospatial vectors that are frequently utilized in high-level academic literature, its restrictive licensing model presents a significant hurdle for enterprise deployments. GADM data is explicitly and strictly available solely for academic use and other non-commercial purposes.[28] Redistribution or commercial deployment in proprietary software, commercial web mapping applications, or corporate risk modeling is strictly prohibited without obtaining prior, express permission.[28] Consequently, while GADM serves as an excellent, independent verification mechanism to cross-reference and audit the topology of other datasets, the geoBoundaries or HDX datasets remain the unequivocally preferred options for unrestricted, scalable deployments.

Crowdsourced Geographic Information and the OpenStreetMap (OSM) Ecosystem

While institutional, top-down datasets from NAMRIA and aggregated databases rely on slow-moving bureaucratic data propagation, crowdsourced Volunteered Geographic Information

(VGI) provides a highly dynamic, bottom-up approach to boundary delineation. OpenStreetMap (OSM) serves as an unprecedented, living repository of community-validated spatial data.[10] The mapping conventions utilized by the dedicated OSM community in the Philippines specifically document the exact metadata tagging structures for regions, provinces, cities, municipalities, and barangays, ensuring a highly standardized approach to local government mapping.[31]

Because OSM is an ontological database rather than a simple collection of shapes, extracting specific GeoJSON administrative boundaries requires specialized middleware tools capable of querying the underlying relational data structures (nodes, ways, and relations). Platforms such as OSM-Boundaries are specifically engineered to extract these administrative borders by recursively querying the OSM database and outputting topologically clean GeoJSON files for specific administrative levels.[10] Similarly, infrastructure providers like Geofabrik provide routine, daily extracts of raw OSM data for the entire Philippines in Protocolbuffer Binary Format (.osm.pbf), which can be efficiently converted using command-line tools like Osmium into distinct municipal polygons.[32]

Furthermore, advanced spatial services like NextGIS continuously ingest and process the OSM database to output daily updated vector layers. Their pipelines generate over 30 distinct data categories—including administrative boundaries, road networks, building footprints, and water features—in ready-to-go formats such as GeoJSON, GeoPackage, and Esri Shapefile.[33] Crucially, NextGIS applies processing and enhancement algorithms that automatically fix inherent geometry errors (such as self-intersecting polygons or unclosed rings), clip administrative boundaries cleanly to the physical land/coastline boundary, and inject hierarchical IDs linking upper-level features to ensure relational database integrity.[33]

The overwhelming advantage of the OSM ecosystem is its hyper-dynamic nature. When catastrophic natural disasters dramatically alter coastlines, or when new municipal infrastructure (such as massive land reclamation projects in Manila Bay or Cebu) is built, local mappers update the OSM database within hours or days, long before official shapefiles are published by central agencies.[11] However, analysts deploying OSM data in production must remain continually vigilant regarding vandalism or inadvertent topological errors introduced by amateur contributors, necessitating rigorous programmatic cross-validation with PSA/NAMRIA-aligned baseline datasets.

Deep Topological Nuances: Mapping Cebu and its Archipelagic Municipalities

Cebu province is characterized by a uniquely challenging geographic topology that continuously tests the absolute mathematical limits of spatial data structures and rendering algorithms. A standard, landlocked province might be easily represented in GeoJSON as a single, contiguous Polygon geometry. Cebu, however, must fundamentally be represented as a highly complex MultiPolygon within any valid GeoJSON schema to account for its sprawling archipelagic nature.[1] The geometric accuracy of any GeoJSON dataset claiming to legitimately represent

Cebu can be rapidly audited by examining how it topologically handles three specific, highly complex offshore island groups that constitute distinct local government units.

Mactan Island and the Metro Cebu Coastal Periphery

Separated from the densely populated Cebu mainland by the extremely narrow Mactan Channel, Mactan Island is a critical global economic hub, housing the Mactan-Cebu International Airport (PSGC/IATA code CEB) and extensive export processing zones.[34] Administratively, Mactan Island is not a single, unified entity. It is sharply divided between the highly urbanized city of Lapu-Lapu to the north and west, and the municipality of Cordova to the south.[5]

High-fidelity GeoJSON data must flawlessly and accurately trace the incredibly sinuous coastal boundaries of Lapu-Lapu and Cordova. This is particularly vital for the expansive tidal flats, shallow reefs, and fragile mangrove ecosystems that define Cordova's southern perimeter, where land and sea boundaries are highly ambiguous. Furthermore, Cordova is now physically connected to the Cebu mainland via the monumental Cebu-Cordova Link Expressway (CCLEX). Precise, legally sound boundary data must definitively demarcate the exact maritime jurisdictions extending into the Mactan Channel, ensuring that Cordova's municipal waters do not topologically overlap with the mainland jurisdictions of Cebu City or Mandaue City.[12]

The Bantayan Island Group Topography

Located off the northernmost tip of the Cebu mainland, navigating the treacherous waters of the Visayan Sea, the Bantayan Island group represents another critical, high-level test of geospatial and topological accuracy. This distinct island group is structurally subdivided into three completely separate municipalities: Bantayan, Madridejos, and Santa Fe.[5]

- **Bantayan:** Occupies the central and western portions of the main island and exercises jurisdiction over numerous smaller, uninhabited offshore islets.
- **Madridejos:** Commands the northern peninsula of the main island.
- **Santa Fe:** Covers the southeastern portion of the main island but crucially extends its administrative jurisdiction far offshore over adjacent, highly populated smaller islands such as Kinatarcan (Guintacan) and Hilantagaan.[5]

A mathematically rigorous, legitimately accurate GeoJSON file will model the municipality of Santa Fe not merely as a terrestrial boundary inscribed on the main island of Bantayan, but absolutely must encode it as a massive MultiPolygon encompassing its distant maritime territorial islets. Failure to include these remote islets within the municipal boundary geometry results in catastrophic spatial exclusion errors during demographic spatial joins or localized disaster risk assessment algorithms.

The Camotes Islands Delineation

To the east of the Cebu mainland, deep within the Camotes Sea, lies the Camotes Islands group. This unique archipelago consists of four primary islands—Pacijan, Tulang, Poro, and

Ponson—which are politically organized into four distinct municipalities: San Francisco, Poro, Tudela, and Pilar.[5]

- **San Francisco:** Exercises full jurisdiction over the entire island of Pacijan and the smaller adjacent islet of Tulang.
- **Poro and Tudela:** These two separate municipalities share the single landmass of the island of Poro, requiring a highly precise terrestrial boundary line that bisects the island's rugged, mountainous interior.
- **Pilar:** Occupies the entirely distinct, solitary island of Ponson.

The spatial relationship and topological connection between the municipalities of San Francisco and Poro is particularly complex and frequently mapped incorrectly. The two islands (Pacijan and Poro) are physically connected by a narrow, artificial causeway crossing a dense mangrove forest. Lower-resolution, overly simplified GeoJSON files (such as those subjected to aggressive Douglas-Peucker simplification algorithms) will often erroneously fuse these two islands into a single, undifferentiated polygon, obliterating the distinct administrative boundaries of the municipalities entirely. Only high-fidelity, meticulously verified datasets derived directly from NAMRIA baseline data or unsimplified HDX source files correctly maintain the spatial distinction and the precise municipal demarcation line running exactly across the connecting isthmus.

Furthermore, integrating elevation data provides an additional dimension of accuracy. Topographic mapping systems reveal significant elevation variance within Cebu, ranging from sea level at coastal features like the Mananga River in Talisay (17m) or Lindogon (52m), to interior elevated barangays such as Labangon (132m), Tonggo (142m), Alambijud (434m), and highly mountainous terrains like Butong (612m).[5] When 2D GeoJSON boundary data is draped over 3D Digital Elevation Models (DEM), ensuring the horizontal vertices perfectly match the vertical topological features (like ridgelines that form natural municipal borders between coastal and interior towns) is the ultimate test of boundary accuracy.

Applied Spatial Analytics: Second and Third-Order Real-World Imperatives

The strict requirement for legitimate, highly accurate, and mathematically valid GeoJSON data for Cebu extends far beyond simple cartographic aesthetics or web design. The absolute precision of these municipal boundaries definitively dictates the operational efficacy of massive systems across public health, electoral governance, disaster risk management, and the macro-economic allocation of utility resources.

Disaster Risk Management and Climate Resilience Engineering

The Philippine archipelago is precariously situated along the hyper-active Pacific Ring of Fire and lies directly in the path of the primary global typhoon belt. Consequently, precise spatial data is fundamentally a matter of national security and sheer physical survival.[11] The Philippine government recognized this through sweeping legislation, including the Climate Change Act of

2009 (Republic Act No. 9729) and the Philippine Disaster Risk Reduction and Management Act of 2010 (Republic Act No. 10121).[38]

In the chaotic aftermath of catastrophic meteorological events, such as the unprecedented devastation of Typhoon Haiyan (Yolanda) in 2013 or Typhoon Rai (Odette) in 2021, international humanitarian agencies rely instantly on high-resolution satellite imagery cleanly overlaid with municipal boundary GeoJSONs to conduct rapid, automated damage assessments.[18] For instance, datasets analyzing severe structural damage in the highly populated municipalities of Talisay, Carcar, and San Fernando in southern Cebu required exact, undisputed spatial delineations to accurately calculate the percentage of housing stock destroyed within specific jurisdictions.[18]

Furthermore, NAMRIA's collaborative READY Project—executed in partnership with AusAID, UNDP, the Office of Civil Defense (OCD), MGB, PHIVOLCS, and PAGASA—relies explicitly on these verified administrative boundaries to map a comprehensive matrix of ten distinct hazard types:

1. Earthquake-induced Landslide
2. Ground Rupture
3. Ground Shaking
4. Liquefaction
5. Storm Surge
6. Tsunami
7. Rain-induced Landslide
8. Flood (Above 1:10,000 scale)
9. Flood (1:10,000 scale)
10. Volcanic hazards.[11]

If a GeoJSON boundary for a vulnerable, low-lying coastal municipality like Daanbantayan or Bogo is offset by even a few hundred meters due to an incorrect coordinate reference system reprojection or overly aggressive polygon simplification, the overlay of a simulated 3-meter storm surge model will wildly and inaccurately predict the number of inundated households.[5] This geometric failure leads directly to deeply flawed evacuation protocols, the misplacement of emergency staging areas, and the fatal misallocation of critical relief funds.

Electoral Governance and Democratic Infrastructure Delineation

Spatial data plays an increasingly critical, visible role in the mechanics of democratic processes. Independent civic technology initiatives aiming to map the Commission on Elections (COMELEC) offices require the complex integration of raw, often unstructured address data with highly precise geospatial boundaries.[14] Because most government data in the Philippines is not easily accessible without navigating the bureaucracy of the FOI Executive Order No. 02, civic groups like Sakay.ph have been forced to synthesize their own datasets.[14]

By successfully combining sophisticated public transport routing data with verified, accurate

municipal polygons derived from OSM and cross-referenced against official limits, developers can construct applications that guide unregistered voters to the correct municipal hall or precinct based on their precise geolocation within a specific barangay.[14] In highly contested municipal borders—where the line between two jurisdictions may determine the outcome of a local election—the topological accuracy of the GeoJSON ensures that populations are mathematically allocated to the correct voting districts, preserving the unquestionable integrity of the electoral map.

Epidemiological Surveillance and Spatial Health Interventions

In the realm of advanced public health, epidemiological modeling relies entirely on the concept of spatial granularity and accurate areal calculation.[40] The complex transmission dynamics of vector-borne diseases, such as Dengue fever, which heavily impacts the Visayas region, are inextricably linked to highly localized micro-climates and exact human population densities.[40] The Philippine Department of Health (DOH) mandates that health facilities report incidence cases aggregated strictly by barangay, municipality, and province via systems like the National Health Facility Registry (NHFR).[40]

When epidemiological researchers map these disease incidence rates to generate predictive spatial risk indices, they utilize the municipal boundary polygons to calculate spatial incidence densities (cases per square kilometer).[40] An inaccurate, malformed GeoJSON polygon that structurally misrepresents the true land area of a municipality will artificially inflate or deflate the calculated disease incidence rate. This geometric error propagates upward, potentially causing public health officials to misdirect critical, life-saving interventions, such as vector control spraying or the deployment of emergency medical personnel, to the wrong geographic sectors.

Macroeconomic Utility Modeling and Electrification

The accuracy of geospatial boundaries is also paramount for macroeconomic modeling and the logistical expansion of national utility grids. Organizations like the World Bank utilize spatial data to track infrastructure development, mapping vast census data against administrative polygons.[41] For example, when analyzing the electrification rate of Cebu—which data models have calculated at a rate of 0.855 against a massive household baseline of 1,055,646 units—the spatial distribution of these households must be accurately binned into their respective municipal containers.[38] If the GeoJSON geometries fail to accurately capture the remote, mountainous barangays or the distant island municipalities of the Camotes or Bantayan groups, the resulting electrification heatmaps will exhibit severe spatial bias, falsely suggesting total grid coverage while masking deep pockets of energy poverty in topologically isolated areas.

Synthesis and Strategic GeoJSON Procurement Directives

The complex acquisition of legitimate, mathematically accurate, and legally indicative GeoJSON

boundary data for Cebu Province and its uniquely challenging archipelagic municipalities is a multi-layered, highly technical procurement process. The Philippine government, functioning primarily through the Philippine Statistics Authority (PSA) and the National Mapping and Resource Information Authority (NAMRIA), actively maintains the authoritative, PSGC-compliant frameworks essential for state operations.[2] However, frictionless, programmatic direct access to web-ready GeoJSON formats from these state portals is significantly hindered by institutional protocols, legacy data formats, and technical distribution bottlenecks.[14]

To successfully bridge this critical infrastructure gap, spatial analysts, data scientists, and web developers must rely on a highly curated matrix of verified secondary and tertiary repositories. Based on the exhaustive, rigorous analysis of the available spatial data infrastructure, the following strategic procurement framework is definitively established:

1. **For Web Development, Mobile Applications, and Dynamic Dashboards:** The faeldon/philippines-json-maps GitHub repository, powered by altcoder shapefiles, represents the absolute optimal source.[2] Utilizing the robust EPSG:32651 projection and strictly based on the latest December 2023 PSGC updates, this repository provides multi-resolution GeoJSON files that perfectly balance cartographic fidelity with browser memory performance limits.[4] Analysts must specifically utilize the Level 2 (Province) and Level 3 (Municipality) geometries from the hires directory to successfully capture the highly nuanced, structurally complex MultiPolygon geometries of Cebu's offshore islands, including Mactan, the Bantayan group, and the Camotes Islands.[4]
2. **For Humanitarian Operations, Disaster Response, and Official Audits:** The Humanitarian Data Exchange (HDX) Common Operational Datasets (COD-AB) provide the most rigorously vetted, internationally recognized indicative boundaries.[8] While requiring an initial software conversion from Shapefile or Geodatabase formats to GeoJSON, the ITOS-validated alignment with the PSA and NAMRIA standards ensures that disaster risk assessments, demographic aggregations, and casualty estimations maintain undeniable operational and statistical validity.[8]
3. **For Programmatic Pipeline Integration and Academic Research:** The geoBoundaries API provides a highly structured, version-controlled mechanism for extracting Philippine ADM2 and ADM3 GeoJSON geometries directly into automated analytical pipelines via simple RESTful HTTP requests.[24] Its permissive CC BY 4.0 license ensures unencumbered, rapid deployment in both proprietary corporate environments and high-level academic research scenarios.[22]
4. **For Real-Time Infrastructure Validation and Hyper-Local Delineation:** OpenStreetMap (OSM) derivatives, efficiently extracted via OSM-Boundaries or NextGIS, should be utilized continuously as an active, living validation layer.[10] This dynamic, crowdsourced topology captures highly localized changes in land reclamation, infrastructure development, and shifting coastal boundaries that official decadal cadastral surveys may lag significantly in reporting.[14]

In absolute conclusion, accurately mapping the archipelagic province of Cebu demands a

rigorous, uncompromising approach to geographic data science. By fully comprehending the deep hierarchical nature of the PSGC, the immense topological complexities of multi-polygon island delineations, and the highly specific strengths and licensing parameters of the open-source spatial repositories currently available, geospatial professionals can ensure that their analytical models are built upon a bedrock foundation of absolute mathematical accuracy and undeniable institutional legitimacy.

Works cited

1. Download Philippines Administrative Boundary Shapefiles - Regions Provinces, Municipalities and more - - igismap, accessed April 10, 2026, https://www.igismap.com/download-philippines-barangay-shapefile-free-country-boundary-polygon-shapefile/
2. Philippines PSGC Administrative Boundaries Shapefiles - GitHub, accessed April 10, 2026, https://github.com/altcoder/philippines-psgc-shapefiles
3. philippines/provinces.json at master · darklight721/philippines - GitHub, accessed April 10, 2026, https://github.com/darklight721/philippines/blob/master/provinces.json
4. faeldon/philippines-json-maps: Philippine administrative ... - GitHub, accessed April 10, 2026, https://github.com/faeldon/philippines-json-maps
5. Cebu topographic maps, elevation, terrain, accessed April 10, 2026, https://en-ph.topographic-map.com/place-x1h/Cebu/
6. Santicon topographic map, elevation, terrain, accessed April 10, 2026, https://en-nz.topographic-map.com/map-snzx18/Santicon/
7. Free GIS Maps of Philippines - Resources - Simplemaps.com, accessed April 10, 2026, https://simplemaps.com/gis/country/ph
8. Philippines - Subnational Administrative Boundaries | Humanitarian ..., accessed April 10, 2026, https://data.humdata.org/dataset/cod-ab-phl
9. geoBoundaries | HDX - Humanitarian Data Exchange, accessed April 10, 2026, https://data.humdata.org/organization/geoboundaries
10. OSM-Boundaries, accessed April 10, 2026, https://osm-boundaries.com/
11. national mapping and resource information authority - NAMRIA, accessed April 10, 2026, https://www.namria.gov.ph/downloads.aspx
12. NAMRIA | National Mapping and Resource Information Authority, accessed April 10, 2026, https://www.namria.gov.ph/
13. 1 Infomapper 2020 - NAMRIA, accessed April 10, 2026, https://www.namria.gov.ph/jdownloads/Info_Mapper/Map_101_Oct26.pdf
14. Building A Geospatial Dataset of COMELEC Offices in The Philippines - The Sakay Blog, accessed April 10, 2026, https://blog.sakay.ph/building-a-geospatial-dataset-of-comelec-offices-in-the-philippines/
15. https://geoserver.poc.geoportal.gov.ph/geoserver/ows?service=wms&version=1.1.1&request=GetCapabilities, accessed April 10, 2026, https://geoserver.poc.geoportal.gov.ph/geoserver/ows?service=wms&version=1.1.1&request=GetCapabilities

16. accessed April 10, 2026, https://huggingface.co/datasets/shivangibithel/SATO/resolve/main/msato_cv_1.csv?download=true
17. GitHub - edcranger/addresspinas: his is a simple package for getting a complete list of Regions, Provinces, Cities/Muninicapals and Barangays of the Philippines that could be useful for registration forms or other app functionality., accessed April 10, 2026, https://github.com/edcranger/addresspinas
18. Damage assessment in City of Carcar and San Fernando municipalities, Cebu Province, Region VII, Philippines - Humanitarian Data Exchange, accessed April 10, 2026, https://data.humdata.org/dataset/damage-assessment-in-city-of-carcar-and-san-fernando-municipalities-cebu-province-region-v
19. Humanitarian Datasets | Find Crisis Data | HDX, accessed April 10, 2026, https://data.humdata.org/m/dataset/?ext_archived=1&q=Nepal+OpenStreetMap+Extracts%2C+Buildings&page=38
20. Improving Post-Disaster Damage Data Collection to - Global Earthquake Model Foundation, accessed April 10, 2026, https://cloud-storage.globalquakemodel.org/public/wix-new-website/pdf-collections-wix/publications/GEM-2018-Damage_Loss_Collection_Protocols-Technical_Report.pdf
21. philippines-json-maps/README.md at master · faeldon/philippines ..., accessed April 10, 2026, https://github.com/faeldon/philippines-json-maps/blob/master/README.md
22. geoBoundaries, accessed April 10, 2026, https://www.geoboundaries.org/
23. geoBoundaries, accessed April 10, 2026, https://www.geoboundaries.org/index.html
24. geoBoundaries, accessed April 10, 2026, https://www.geoboundaries.org/api.html
25. Shp Administrative boundaries divisions Geodata Humanitarian, accessed April 10, 2026, https://data.humdata.org/dataset/?ext_geodata=1&vocab_Topics=administrative+boundaries-divisions&q=Airports+in+United+States+of+America&res_format=SHP&page=5
26. Geoboundaries Administrative boundaries divisions Humanitarian Datasets | Find Crisis Data | HDX, accessed April 10, 2026, https://data.humdata.org/dataset/?vocab_Topics=administrative+boundaries-divisions&organization=geoboundaries&page=3
27. Geoboundaries Administrative boundaries divisions Humanitarian Datasets | Find Crisis Data | HDX, accessed April 10, 2026, https://data.humdata.org/dataset/?vocab_Topics=administrative+boundaries-divisions&organization=geoboundaries&force_layout=desktop&page=12
28. GADM data, accessed April 10, 2026, https://gadm.org/data.html
29. GADM, accessed April 10, 2026, https://gadm.org/
30. Download GADM data (version 4.1), accessed April 10, 2026, https://gadm.org/download_country.html
31. Philippines/Mapping conventions/Local government - OpenStreetMap Wiki,

accessed April 10, 2026, https://wiki.openstreetmap.org/wiki/Philippines/Mapping_conventions/Local_government
32. Download OpenStreetMap for Philippines | Geofabrik Download Server, accessed April 10, 2026, https://download.geofabrik.de/asia/philippines.html
33. Cebu City: OpenStreetMap basemap — download vector layers and GIS project for QGIS, ArcGIS Pro, ArcMap, MapInfo - NextGIS Data, accessed April 10, 2026, https://data.nextgis.com/en/region/PH-CITY-006/base/
34. doc-onboarding/datasets/geo.json at master - GitHub, accessed April 10, 2026, https://github.com/algolia/doc-onboarding/blob/master/datasets/geo.json
35. FreeGeoDB/Distribution/JSON/airports.json at master - GitHub, accessed April 10, 2026, https://github.com/delight-im/FreeGeoDB/blob/master/Distribution/JSON/airports.json
36. accessed April 10, 2026, https://fgis.bfar.da.gov.ph/server/rest/services/Hosted/BFAR_Facilities_Layer/FeatureServer/layers?f=pjson
37. philippines/cities.json at master · darklight721/philippines - GitHub, accessed April 10, 2026, https://github.com/darklight721/philippines/blob/master/cities.json
38. An Impact-Based Flood Forecasting System for Citizen Empowerment - AgEcon Search, accessed April 10, 2026, https://ageconsearch.umn.edu/record/348355/files/00_Lagmay%20et%20al_AJAD%2020th%20special.pdf
39. Philippines - Census of Population 2015 - Catalog.ihsn.org., accessed April 10, 2026, https://catalog.ihsn.org/catalog/7186
40. Constructing and validating a transferable epidemic risk index in data scarce environments using open data: A case study for dengue in the Philippines - PMC, accessed April 10, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8849499/
41. Mainstreaming Disruptive Technologies in Energy (P166854) - Documents & Reports, accessed April 10, 2026, https://documents1.worldbank.org/curated/en/305771562750007469/pdf/Mainstreaming-Disruptive-Technologies-in-Energy.pdf